Date:

Question 4

```
Function days() // Take input and validate it
    int days // Take input number of days
    validate it
    return days
END Function
Function sales() // Calculate daily sales and return total
    int a, i, amount = 0
    float amount, total = 0, max = 0
    Input n // Taking input number of orders
    Input amount // Taking amount of orders as input
        validate amount
        total = total + amount
        if (amount > max) Then max = amount
    print (total, total/n, max) // printing total sale,
    // average amount and maximum amount of an order
    return total
END Function
Function highestsale (dailysale[ ], days)
    int best
    for (int i=0 ; i< days ; i++)
        if (dailysale[i] > the dailysale[best]) Then best = i
    //END For
    return best+1
END Function
Function of Barchart (dailysale[ ], n days)
    for (int i=0 ; i< days ; i++) {
        print (i+1) // printing day number
        for (int s=0 ; s< dailysale[i]/100 ; s++)
```

Date:

```
        Print ("*") //Printing bar
        //END FOR
    Print (daily sale[i]) //printing sale on that day
    //END for
END Function
Main
    float daily sale[7], Total = 0
    int day, s, best
    days = days()
    for (int i=0 ; i < day ; i++) {
        daily sale[i] = sales(i+1);
        Total = Total + daily sale[i]} //END FOR
    best = highest Sale (daily sales, day)
    print (Total, best, daily sale(best-1))
    // printing total sale, day with the highest sa
        and highest daily sales
    print bar chart (daily sales, day) // printing bar chart.
```