

```

<?xml version="1.0" encoding="UTF-8" ?>
<scenario name="UAC MSD Transfer Scenario">
  <send>
    <![CDATA[
      INVITE sip:[service]@[remote_ip]:[remote_port] SIP/2.0
      Via: SIP/2.0/[transport] [local_ip]:[local_port]
      From: sipp <sip:sipp@[local_ip]:[local_port]>;tag=[call_number]
      To: sut <sip:[service]@[remote_ip]:[remote_port]>
      Call-ID: [call_id]
      Cseq: 1 INVITE
      Contact: sip:sipp@[local_ip]:[local_port]
      Content-Type: application/sdp, application/pidf+xml, application/EmergencyCallData.Control+xml
      CSeq: 31862 INVITE
      Recv-Info: EmergencyCallData.eCall.MSD
      Allow: INVITE, ACK, PRACK, INFO, OPTIONS, CANCEL, REFER, BYE, SUBSCRIBE, NOTIFY, UPDATE
      Content-Type: multipart/mixed; boundary=boundary1
      P-Preferred-Service: urn:urn-7:3gpp-service.ims.icsi.mmtel
      a: *;+g.3gpp.icsi-ref="urn%3Aurn-7%3A3gpp-service.ims.icsi.mmtel"
      P-Early-Media: supported
      l: 1431
      x: 300
      Content-Length: [len]

      --boundary1
        Content-Type: application/sdp
          v=0
          o=user1 53655765 2353687637 IN IP[local_ip_type] [local_ip]
          s=-
          t=0 0
          c=IN IP[media_ip_type] [media_ip]
          m=audio [media_port] RTP/AVP 0
          a=rtpmap:0 PCMU/8000

      --boundary1
        Content-Type: application/EmergencyCallData.eCall.MSD
        Content-ID: <123456789@vzims.com>
        Content-Disposition: by-reference;handling=optional
        [file name=EmergencyCallData.eCall.MSD]
      --boundary1--

    ]]>
  </send>

  <recv response="100" optional="true">
  </recv>

  <recv response="180" optional="true">
  </recv>

  <recv response="200">
  </recv>

  <send>
    <![CDATA[
      ACK sip:[service]@[remote_ip]:[remote_port] SIP/2.0
      Via: SIP/2.0/[transport] [local_ip]:[local_port]
      From: sipp <sip:sipp@[local_ip]:[local_port]>;tag=[call_number]
      To: sut <sip:[service]@[remote_ip]:[remote_port]>[peer_tag_param]
      Call-ID: [call_id]
      Cseq: 1 ACK
      Contact: sip:sipp@[local_ip]:[local_port]
    ]]>
  </send>

```

```
Content-Length: 0
]]>
</send>

<pause milliseconds="2000"/>

<send retrans="500">
  <![CDATA[
    BYE sip:[service]@[remote_ip]:[remote_port] SIP/2.0
    Via: SIP/2.0/[transport] [local_ip]:[local_port]
    From: sipp <sip:sipp@[local_ip]:[local_port]>;tag=[call_number]
    To: sut <sip:[service]@[remote_ip]:[remote_port]>[peer_tag_param]
    Call-ID: [call_id]
    Cseq: 2 BYE
    Contact: sip:sipp@[local_ip]:[local_port]
    Content-Length: 0
  ]]>
</send>

<recv response="200">
</recv>

</scenario>
```