

Construction/Operation of Two Hexacopters for Autonomous Landing

Joshua Springer

Reykjavík University



Overview

Two Tarot 680 Hexacopters enable real world testing of autonomous navigation techniques developed in simulation. This project tests an autonomous landing algorithm based on computer vision and fiducial markers.^[1] A landing pad is marked with fiducial markers which are recognized by the drone's onboard camera. The gimbal automatically aims the camera at the landing pad to track it during descent. The landing software then directs the drone to descend towards the landing pad.


Components

Standard Drone Components


All drone electronics (e.g. motors, speed controllers, propellers, power electronics, RC Receiver, telemetry radio) are mounted on the Tarot 680 Pro hexacopter body.

Computational Components

- **Raspberry Pi 3 B+:** runs the ArduPilot flight software and ROS.
- **Navio2 Hat:** provides IMU data and control signal interfaces.
- **Companion board:** image processing, fiducial marker systems, coordinate system transforms. One drone uses a Google Coral Dev board and the other uses an NVIDIA Jetson Nano.




Custom 3D-Printed Components




Power and Data Flow

The drones have two power systems to isolate the computational electronics from voltage spikes/drops caused by the motors and gimbal.



Data Flow


- **Camera module:** provides a high-quality video image.
- **gscam:** pre-processes the image (lowering resolution, flipping).
- **landing_controller:** generates a target position for the drone.
- **gimbal_controller:** tracks the landing pad by aiming the camera.
- **MAVROS:** translates ROS messages to ArduPilot messages.
- **ArduPilot:** controls the drone based on MAVROS commands.



Landing Pad

Fiducial markers (top: April Tag^[2], bottom: WhyCon^[3]) allow the drone to determine its position relative to the landing pad using only a normal RGB camera.

- **April Tag:** provides accurate pose estimation at close range, when the WhyCon marker is too big for the camera to fully see. Eventually it was abandoned for consuming excessive CPU time.
- **WhyCon:** provide easier/faster recognition at long range. The center of the WhyCon marker is the target landing site.



A block containing some math

Nullam non est elit. In eu ornare justo. Maecenas porttitor sodales lacus, ut cursus augue sodales ac.

$$\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$$

Interdum et malesuada fames {1, 4, 9, ...} ac ante ipsum primis in faucibus. Cras eleifend dolor eu nulla suscipit suscipit. Sed lobortis non felis id vulputate.

A heading inside a block

Praesent consectetur mi $x^2 + y^2$ metus, nec vestibulum justo viverra nec. Proin eget nulla pretium, egestas magna aliquam, mollis neque. Vivamus dictum **ut** sagittis odio, vel porta erat congue sed. Maecenas ut dolor quis arcu auctor porttitor.

Another heading inside a block

Sed augue erat, scelerisque a purus ultricies, placerat porttitor neque. Donec $P(y | x)$ fermentum consectetur $\nabla_x P(y | x)$ sapien sagittis egestas. Duis eget leo euismod nunc viverra imperdiet nec id justo.

Nullam vel erat at velit convallis laoreet

Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos himenaeos. Phasellus libero enim, gravida sed erat sit amet, scelerisque congue diam. Fusce dapibus dui ut augue pulvinar iaculis.

First column	Second column	Third column	Fourth
Foo	13.37	384,394	α
Bar	2.17	1,392	β
Baz	3.14	83,742	δ
Qux	7.59	974	γ

Table: A table caption.

References

- [1] Joshua Springer, ``Autonomous landing of a multicopter using computer vision," Master's thesis, Reykjavík University, Department of Computer Science, 2020.
- [2] E. Olson, ``Apriltag: A robust and flexible visual fiducial system," in 2011 IEEE International Conference on Robotics and Automation, pp. 3400-3407, 2011.
- [3] M. Nitsche, T. Krajiník, P. Čížek, M. Mejail, and T. Duckett, ``Whycon: An efficient, marker-based localization system," in IROS Workshop on Open Source Aerial Robotics, 2015.