

EVIDENCIAS

Infraestructura 2

Estudiante	Jennifer López
Matrícula	20240860
Asignatura	TSI-203 Seguridad de Redes

Evidencias de la Infraestructura 2

A continuación se presentan evidencias breves obtenidas durante la configuración, validación y troubleshooting de esta infraestructura.

```

Oct 1 19:10:14.011: %SYS-5-CONFIG-I: Configured from console by console
R-USER#show crypto map
Crypto Map IPv4 "VPN-MAP" 10 ipsec-isakmp
  Peer = 200.20.86.1
  Extended IP access list VPN-TRAFFIC
    access-list VPN-TRAFFIC permit ip 10.86.0.0 0.0.0.127 10.86.1.0 0.0.
0.15
  Current peer: 200.20.86.1
  Security association lifetime: 4608000 kilobytes/3600 seconds
  Responder-Only (Y/N): N
  PFS (Y/N): N
  Transform sets={
    VPN-SET:  { esp-des esp-sha-hmac  } ,
  }
  Interfaces using crypto map VPN-MAP:
    FastEthernet0/0

```

Configuración IPsec del router Cisco: ISAKMP, peer, transform-set, ACL y crypto map.

```

R-USER#
*Oct 1 19:37:39.959: ISAKMP:(0): retransmitting phase 1 MM_NO_STATE...
*Oct 1 19:37:39.959: ISAKMP (0): incrementing error counter on sa, attempt 1 of
5: retransmit phase 1
*Oct 1 19:37:39.963: ISAKMP:(0): retransmitting phase 1 MM_NO_STATE
*Oct 1 19:37:39.963: ISAKMP:(0): sending packet to 200.20.86.1 my_port 500 peer
_port 500 (I) MM_NO_STATE
*Oct 1 19:37:39.967: ISAKMP:(0):Sending an IKE IPv4 Packet.
R-USER#
*Oct 1 19:37:49.967: ISAKMP:(0): retransmitting phase 1 MM_NO_STATE...
*Oct 1 19:37:49.967: ISAKMP (0): incrementing error counter on sa, attempt 2 of
5: retransmit phase 1
*Oct 1 19:37:49.971: ISAKMP:(0): retransmitting phase 1 MM_NO_STATE
*Oct 1 19:37:49.971: ISAKMP:(0): sending packet to 200.20.86.1 my_port 500 peer
_port 500 (I) MM_NO_STATE
*Oct 1 19:37:49.971: ISAKMP:(0):Sending an IKE IPv4 Packet.
R-USER#

```

Debug de IKE/IPsec durante las pruebas de negociación.

error while starting R-USER: Could not
send Dynamips command 'vm
set_ghost_status "R-USER" 2' to
localhost:57722: [WinError 64] The
specified network name is no longer
available, process running: False

Evidencia de la incidencia de ejecución de R-USER en GNS3 durante el troubleshooting.