


Miniature stuck light V5M4-B series



Highlights

- Maintenance-free LED technology
- Adjustable colors through RGB LEDs
- 1 to 3 signal levels
- Intense light colors thanks to innovative light guide technology
- Variants with IO link communication system
- Versions with acoustic signal generator
- Robust aluminium housing
- Prevents accumulation of dirt
- Direct connection to machine voltage
- Built in buzzer

Dimension



Applications



Gas detection panel warning light




Wall mount M30 size

Product parameters

TECHNICAL PARAMETERS AND DRAWING

Current	Red: 31mA Green: 45mA	Yellow: 42mA Buzzer: 15mA
Flash frequency	63-65 times/min	
Buzzer volume	> 75 db	
IP rating	IP54 / IP65	
Working temperature	- 20 ~ 45° C	
Lifetime	50,000H	
Housing color	Black	
Installation	For M30 standard hall, fixed by screw	
Material	Aluminum anodized body with PC bulb cover	



1	Model	V5M4-B
2	Layer	1 - One layer bulb (3 Colors LEDs)
3	Mounting	Fixed by thread
4	Voltage	A. DC12V B. DC24V
5	Function	B. Steady F. Steady with buzzer S. Red flash C. Red flash with buzzer D. All flash E. All flash with buzzer
6	Connect type	T. PNP&NPN C. Contact type
7	Color	R. Red Y. Yellow G. Green B. Blue
8	Diameter	50. Ø50mm
9	Connection	M12 (note: 5 pin male connector) / 30cm (note: Short wire connection)
10	Protection	IP54(note: with buzzer / IP65 (note: without buzzer)

Input/Output circuit

