

Common inductive proximity sensors series - Q40 size DC 2 wire



■ Highlights

Inductive sensor
When the metal conductive objects close to the magnetic field and reach the induction area, high-frequency alternating magnetic field generated by a LC oscillation circuit, which is composed of a coil wound on a ferrite, through the eddy current effect generated by internal of metal objects to achieve non-contact detection.

Standards
All inductive proximity sensors conform to IEC 60947-5-2.

Housing material
The housing material of sensor including nickel plated copper, also stainless steel and plastic with resistance of compression and temperature rapid change. Most of square sensor is plastic housing. These materials can also be used to produce square sensors with adjustable sensing surface or compact (small square) sensors. Such sensors can be used in the occasions of limited installation space or required large detection range.

■ Application

Inductive proximity switch is a low cost method for non-contact detection of metal objects, which is widely used in the following sectors, such as:

- Automotive Industry
- Metallurgical sector
- Machine tool sector
- Robot industry
- Conveyor system
- Paper and printing industry
- Mechanical Engineering




■ P/N table

Sensing distance	Sn: 15mm		
2 Wire , NO	VL1B-FQ40-15NO-LM12		
2 Wire , NC	VL1B-FQ40-15NC-LM12		

■ Installation



■ Product parameters

<div>Features:</div> <ul style="list-style-type: none">• Diameter Q40• Sensing distance: P/N table• Body material: Nickel plated brass• Built-in electric protection• Output: See P/N table• Connection: M12, 4 pins connector Power supply: 24V DC, 3 wires	<div></div> <div>CE</div>	<div></div> <div>CE</div>	<div></div>																	
	TECHNICAL INFORMATION																			
INDUCTIVE SPECIFICATION																				
	Sensing Distance	See P/N table																		
	Correction Factor	<table><tr><th>Nav-ferrous metal</th><th>Factor</th></tr><tr><td>Fe360</td><td>1</td></tr><tr><td>Aluminum</td><td>0.35 ~ 0.45</td></tr><tr><td>Brass</td><td>0.35 ~ 0.5</td></tr><tr><td>Copper</td><td>0.35 ~ 0.45</td></tr><tr><td>Stainless Steel</td><td>0.35 ~ 0.45</td></tr><tr><td>Cast Iron</td><td>0.93 ~ 1.05</td></tr><tr><td>Nickel</td><td>0.65 ~ 0.75</td></tr></table>	Nav-ferrous metal	Factor	Fe360	1	Aluminum	0.35 ~ 0.45	Brass	0.35 ~ 0.5	Copper	0.35 ~ 0.45	Stainless Steel	0.35 ~ 0.45	Cast Iron	0.93 ~ 1.05	Nickel	0.65 ~ 0.75		
	Nav-ferrous metal	Factor																		
	Fe360	1																		
Aluminum	0.35 ~ 0.45																			
Brass	0.35 ~ 0.5																			
Copper	0.35 ~ 0.45																			
Stainless Steel	0.35 ~ 0.45																			
Cast Iron	0.93 ~ 1.05																			
Nickel	0.65 ~ 0.75																			
Mounting	Flush type installation																			
Switching Histeresis	< 10%																			
ELECTRICAL DATA																				
	Operating Voltage	10~60V DC																		
	Switching Frequency	500Hz																		
	Voltage Drop	≤ 2.0 V																		
	Leakage Current	< 0.01mA																		
	Load Current	200 mA																		
	No Load Current	≤ 10 mA (24V DC)																		
	Hysteresis	< 15% (Sr)																		
	Repeatability	< 1.0% (Sr)																		
	Temperature Drift	< 1.0% (Sr)																		
	Short Circuit Protection	Yes																		
	Overload Protection	Yes																		
	Polarity Reversal Protection	Yes																		
ENVIRONMENT DATA																				
	Ambient Temperature	-25.....70 ℃																		
	Ingress Protection	IP67																		
MECHANICAL DATA																				
	Housing Material	PBT																		
	Face Material	PBT																		
ELECTRICAL CONNECTION DATA																				
	Connector	M12, 4 pins connector																		
ACCESORIES																				
	Cable	Two meter angled cable (P/N: V5PN-AM12402OF) (available)																		
	Cable	Ten meter angled cable (P/N: V5PN-AM12410OF) (available)																		
	Connector	M12, 4 PIN, Male type, IP67, Straight, Female, Screw connection (P/N: EAM12MC4001A) (available)																		

■ Input/Output circuit

