

# *Data Structures*

## Level Order Traversal 1

**Mostafa S. Ibrahim**

*Teaching, Training and Coaching since more than a decade!*

*Artificial Intelligence & Computer Vision Researcher*

*PhD from Simon Fraser University - Canada*


*Bachelor / Msc from Cairo University - Egypt*

*Ex-(Software Engineer / ICPC World Finalist)*




# Level Order Traversal

- We learned 3 recursive traversal methods that each go as deep as possible
  - We call them depth first (go deeper)
  - Inorder here is: 8 4 2 6 3 5
- In level order traversal, we print the tree level by level
  - Level 0: 2
  - Level 1: 4 3
  - Level 2: 8 6 5
  - We call it: breadth first
- Depth vs Breadth




# Traversing level by level

- Although we can use recursion to find the levels one by one, it will be very impractical
- One of the great applications of the **queue** is to iterate on a tree level by level
- Start a queue with the root.
- Pop the root node, then immediately push the root node's children - and then repeat this process with each child node!
- Can you finish this idea, and implement it by yourself?



# Traversing level by level


- Add the root node to the queue
- While not empty
  - Get node
  - Print it
  - Add its available children



2				
---	--	--	--	--

# Traversing level by level


- Pop: Tree(2)
- Add children: 4, 3
- **Printed so far: 2**



4	3			
---	---	--	--	--

# Traversing level by level


- Pop: Tree(4)
- Add children: 8
- **Printed so far: 2 4**



3	8			
---	---	--	--	--

# Traversing level by level


- Pop: Tree(3)
- Add children: 6, 5
- **Printed so far:** 2 4 3



8	6	5		
---	---	---	--	--

# Traversing level by level

- Pop: Tree(8)
- Add children: None
- **Printed so far:** 2 4 3 8




6	5			
---	---	--	--	--



# Traversing level by level


- Pop: Tree(6)
- Add children: None
- **Printed so far:** 2 4 3 8 6



5				
---	--	--	--	--

# Traversing level by level


- Pop: Tree(5)
- Add children: None
- Empty: queue: stop
- **Printed so far:** 2 4 3 8 6 5



--	--	--	--	--

# The queue content


- What is happening? We iterate through the nodes one by one, adding each node's child/children to the current queue
- The queue will be in 1 of 2 cases
  - Either all current nodes are at 1 specific level
  - OR it will contain nodes from 2 consecutive levels



3	8			
8	6	5		

# Let's check the queue

- A1 : remove A1, add B2, B3
- B2, B3 : remove B2, add C4
- B3, C4 : remove B3, add C5, C6
- **C4, C5, C6** : remove C4, add D7
- **C5, C6, D7** : remove C5, add nothing
- C6, D7 : remove C6, add D8
- D7, D8 : remove D7, add E9
- D8, E9 : remove D8, add E10, E11
- E9, E10, E11 : remove E9, add F12
- E10, E11, F12
- F12
- G13



*“Acquire knowledge and impart it to the people.”*

*“Seek knowledge from the Cradle to the Grave.”*