Data Structures DLL Insertion

Mostafa S. Ibrahim Teaching, Training and Coaching for more than a decade!


Artificial Intelligence & Computer Vision Researcher PhD from Simon Fraser University - Canada Bachelor / Msc from Cairo University - Egypt Ex-(Software Engineer / ICPC World Finalist)




Insert end

```
def insert_end(self, value):
    node = Node(value)
    self._add_node(node)

    if not self.head:
        self.head = self.tail = node
    else:
        self._link(self.tail, node)
        self.tail = node
```






Insert front


- Also, exactly the same
- Just link properly

```
def insert_front(self, value):
    item = Node(value)
    self._add_node(item)

self._link(item, self.head)
    self.head = item

if self.length == 1:
    self.tail = self.head
```





Insert Sorted

- This same homework code.
- Can you rewrite the _embed_after()?

```
def insert sorted(self, value):
    # 3 special cases for simplicity
    if not self.length or value <= self.head.data:</pre>
        self.insert front(value)
    elif self.tail.data <= value:</pre>
        self.insert end(value)
    else:
        prev, cur = None, self.head
        while cur:
             if value <= cur.data:</pre>
                 self. embed after(prev, value)
                 break
             prev, cur = cur, cur.next
```

Insert Sorted

- Again, the same logic, but instead of next linking, we link the 2 directions
 - We have 3 nodes: A, B, C \Rightarrow link (B, C), then link (A, B)
 - Tip: the link function makes our life easier (code and logic)

```
def _embed_after(self, node, value):
    # Add a node with value between node and its next
    new_node = Node(value)
    self._add_node(new_node)
    self._link(new_node, node.next)
    self._link(node, new_node)
```

"Acquire knowledge and impart it to the people."

"Seek knowledge from the Cradle to the Grave."