

CENTRAL INTELLIGENCE

Developer Handoff Document

Database Architecture & System Overview

Version 1.0 — March 2026

1. System Overview

Central Intelligence is a marketing intelligence engine that transforms raw conversation transcripts (sales calls, coaching calls, discovery calls, accountability calls) into structured Voice of Customer (VOC) data. This data powers a content calendar, email writing system, and marketing strategy layer.

The system is built to serve multiple clients, with each client operating against the same schema. It is designed for Claude Code (AI-assisted development environment) to read from and write to via the Supabase JavaScript client.

Tech Stack

Backend: Node.js + Express | Database: Supabase (PostgreSQL) | AI Layer: Claude Code (Anthropic) | Transcript Source: Cockatoo (manual upload), Fireflies (future automation)

1.1 The Data Pipeline

Data flows through the system in this order:

```
Transcripts → Transcript Processor Skill
  → calls, insights, insight_tags, content_ideas
  → Market Signal Aggregation (market_signals)
  → Content Calendar Skill
  → monthly_preferences, content_ideas (scheduled)
  → Email Writer Skill
  → Drafted emails written to content_ideas (status: Written)
```

1.2 Skills Built So Far

- Transcript Processor — ingests TXT/PDF/DOCX transcripts, runs 2-pass extraction, writes all records to Supabase
- Content Calendar Skill — in design phase
- Email Writer Skill — planned
- Performance Tracker — planned

2. Database Architecture

The database lives on Supabase (PostgreSQL). There are 9 tables organized into two layers.

Connection

Client: @supabase/supabase-js | Credentials stored in .env as SUPABASE_URL, SUPABASE_PUBLISHABLE_KEY, SUPABASE_SECRET_KEY | Client file: /supabase.js

2.1 Table Map

Table	Layer	Purpose
calls	Intelligence	One record per processed transcript
insights	Intelligence	Extracted signals from each call (pains, goals, objections, etc.)
insight_tags	Intelligence	Tags assigned to each insight for filtering
tag_dictionary	Intelligence	Canonical tag reference to prevent duplicates
content_ideas	Intelligence	Marketing content ideas generated from strong insights
market_signals	Intelligence	Aggregated trend reporting across all insights
offers	Marketing	Products, services, webinars, VSLs available to promote
business_profile	Marketing	Business context read by all skills at runtime
monthly_preferences	Marketing	Per-month calendar settings: cadence, email types, goals

3. Table Schemas

3.1 calls

Root table. One row per transcript processed. All insights connect back to a call record.

Field	Type	Description	Notes
call_id	TEXT (PK)	Deterministic ID: CALL_<TranscriptUID>	Primary key
date	DATE	Date the call took place	Parsed from filename
call_type	TEXT	Sales, Discovery, Coaching, Accountability, Support	Inferred by AI, validated against business_profile
call_result	TEXT	Closed, No Decision, Lost, Qualified, N/A, etc.	Blank if unclear
call_owner	TEXT	Who ran the call	Optional
transcript_source	TEXT	Cockatoo, Otter, Fireflies, Manual	Detected from file header
transcript_uid	TEXT	Unique transcript ID	From filename or auto-generated
transcript_quality	TEXT	Clean / Moderate / Messy	Assessed by AI during processing
processed_date	DATE	When extraction ran	Set at processing time
call_duration_minutes	INTEGER	Length of call in minutes	Optional
transcript_link	TEXT	URL to source transcript	Optional
notes	TEXT	Free text notes	Optional
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.2 insights

Core VOC table. Each row is one meaningful signal extracted from a transcript. This is the primary dataset for all marketing intelligence.

Field	Type	Description	Notes
insight_id	TEXT (PK)	INS_<CallID>_01, INS_<CallID>_02...	Deterministic
call_id	TEXT (FK)	References calls.call_id	CASCADE delete
speaker_name	TEXT	Prospect or client name if available	Parsed from filename
insight_type	TEXT	Pain, Goal, Objection, False Belief, Win, Breakthrough, Product Issue, Feature Request	Assigned by AI
signal_family	TEXT	Broad category: Income & Leverage, Time Freedom, etc.	Normalized against existing DB values
signal	TEXT	Specific signal: Income tied to effort, Fear of posting, etc.	Normalized against existing DB values
signal_strength	TEXT	Strong / Moderate / Weak	Required
pain_layer	TEXT	Surface / Emotional / Existential	For Pain type insights only

Field	Type	Description	Notes
raw_quote	TEXT	Exact or near-exact quote from transcript	Preserve customer language
what_they_say	TEXT	Surface interpretation of the quote	
the_real_problem	TEXT	Underlying issue beneath the surface	
emotional_driver	TEXT	Emotion powering the statement	
core_fear_revealed	TEXT	Deep fear beneath the problem	
false_belief_revealed	TEXT	Limiting belief if applicable	
structural_obstacle	TEXT	Operational or logistical barrier	
identity_signal	TEXT	Identity or self-concept statement	
buying_trigger	TEXT	Event or realization that drives action	
objection_created	TEXT	Objection arising from this problem	
marketing_translation	TEXT	How to frame this in marketing copy	
hook_angle_example	TEXT	Suggested hook based on this insight	
best_use_case	TEXT	Email, Webinar, VSL, Ads, etc.	
quote_confidence	TEXT	High / Medium / Low	Low = do not use in marketing directly
frequency_score	INTEGER	How often this signal appears across calls	Updated by aggregation queries
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.3 insight_tags

Junction table linking insights to canonical tags. Each insight can have 1-3 tags. Tags are validated against the tag_dictionary before insertion.

Field	Type	Description	Notes
id	SERIAL (PK)	Auto-incrementing ID	
insight_id	TEXT (FK)	References insights.insight_id	CASCADE delete
tag	TEXT	Canonical tag name from tag_dictionary	e.g. Time Freedom, Burnout, Offer Clarity
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.4 tag_dictionary

Reference table that controls the tag vocabulary. Prevents fragmentation (e.g. Time Freedom vs Time-Freedom vs Freedom of Time). All tags must exist here before being used in insight_tags.

Field	Type	Description	Notes
tag	TEXT (PK)	Canonical tag name	Primary key
tag_type	TEXT	Theme, Pain, Goal, Objection, Identity, Other	
synonyms	TEXT	Alternate phrasings that map to this tag	Comma-separated
notes	TEXT	Usage guidance for AI tagging	
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.5 content_ideas

Stores marketing content ideas generated from strong insights. Also used by the Content Calendar skill to schedule emails. Status field tracks lifecycle from idea through to sent.

Field	Type	Description	Notes
content_id	TEXT (PK)	CONT_<CallID>_01, CONT_<CallID>_02...	Deterministic
insight_id	TEXT (FK)	Source insight	SET NULL on delete
call_id	TEXT (FK)	Source call	SET NULL on delete
source	TEXT	Call type that generated this idea	
market_audience	TEXT	Target market or audience segment	
content_format	TEXT	Email, Reel, YouTube, Webinar, Ad, VSL, Post, Other	
content_angle	TEXT	Narrative framing for this content	
trigger_insight	TEXT	The signal that inspired this idea	
raw_quote	TEXT	Customer quote used as foundation	
content_premise	TEXT	Main concept or argument	
hook_opening_line	TEXT	Suggested opening hook	
teaching_point	TEXT	Key lesson or takeaway	
cta_idea	TEXT	Call to action direction	
priority_level	TEXT	High / Medium / Low	
best_platform	TEXT	Primary platform recommendation	

Field	Type	Description	Notes
repurpose_opportunities	TEXT	Cross-platform use notes	
idea_score	INTEGER	Internal ranking score	0-10
status	TEXT	Idea, Scheduled, Written, Sent, Archived	Default: Idea
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.6 market_signals

Aggregation and reporting layer. Populated by queries against the insights table, not by direct insertion. Powers trend dashboards: top pains, dominant objections, emerging messaging angles.

Field	Type	Description	Notes
id	SERIAL (PK)	Auto-incrementing ID	
signal_family	TEXT	Aggregation bucket matching insights.signal_family	
signal	TEXT	Specific signal matching insights.signal	
insight_type	TEXT	Pain, Goal, Objection, etc.	
total_mentions	INTEGER	All-time count across all calls	Updated by aggregation job
last_30_days	INTEGER	Mentions in last 30 days	Updated by aggregation job
last_7_days	INTEGER	Mentions in last 7 days	Updated by aggregation job
example_quote	TEXT	Representative customer quote	
example_call_id	TEXT (FK)	Source call for example quote	SET NULL on delete
best_marketing_angle	TEXT	Observed best messaging for this signal	
notes	TEXT	Strategic notes	
updated_at	TIMESTAMPTZ	Last aggregation run timestamp	

3.7 offers

Catalog of all products, services, webinars, and VSLs available to promote. Referenced by the Content Calendar skill when planning promotional email campaigns.

Field	Type	Description	Notes
offer_id	TEXT (PK)	Manually assigned or system-generated	e.g. OFFER_001
name	TEXT	Offer name	Required
offer_type	TEXT	Product, Service, Webinar, VSL, Course, Coaching, Other	
description	TEXT	Brief description of the offer	
price	NUMERIC(10,2)	Price point	
status	TEXT	Active, Inactive, Coming Soon	Default: Active
url	TEXT	Sales page or registration URL	
notes	TEXT	Internal notes	
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

3.8 business_profile

Loaded by every skill at runtime to provide business context. Acts as the system's source of truth for brand voice, audience, and operational settings. Typically one row per client.

Field	Type	Description	Notes
id	SERIAL (PK)	Auto-incrementing ID	
business_name	TEXT	Client business name	Required
mission	TEXT	Business mission statement	
target_audience	TEXT	Primary audience description	
brand_voice	TEXT	Tone, style, and voice guidelines	Used by Email Writer skill
core_values	TEXT	Business values	
key_differentiators	TEXT	What sets this business apart	
primary_market	TEXT	Primary market or niche	
notes	TEXT	Additional context for AI skills	
updated_at	TIMESTAMPTZ	Last update timestamp	Auto-set

Note for Developer

The `call_types` and `email_types` fields will be added to this table in a future update as part of the client onboarding flow. These will be `TEXT[]` (array) fields storing each client's custom call type and email type lists.

3.9 monthly_preferences

Stores the email calendar configuration for each month. The Content Calendar skill reads this at the start of each session and asks if settings should carry over from the previous month.

Field	Type	Description	Notes
id	SERIAL (PK)	Auto-incrementing ID	
month	INTEGER	Month number (1-12)	Combined with year for unique constraint
year	INTEGER	Four-digit year	
sending_days	TEXT[]	Array of days: [Monday, Wednesday, Friday]	
emails_per_week	INTEGER	Target send frequency	
email_types	TEXT[]	Array of email types active this month	e.g. [Newsletter, Promotional, Story-based]
primary_goal	TEXT	Main goal: Nurture, Book Calls, Drive Sales, etc.	
secondary_goal	TEXT	Supporting goal for the month	
active_offers	TEXT[]	Array of offer_ids being promoted this month	FK references to offers table
notes	TEXT	Additional context for this month	
created_at	TIMESTAMPTZ	Record creation timestamp	Auto-set

Unique constraint on (month, year) prevents duplicate monthly records.

4. Table Relationships

From	To	Relationship
calls	insights	One call has many insights (CASCADE delete)
insights	insight_tags	One insight has many tags (CASCADE delete)
insights	content_ideas	One insight may produce many content ideas (SET NULL on delete)
calls	content_ideas	One call may produce many content ideas (SET NULL on delete)
calls	market_signals	One call referenced as example source (SET NULL on delete)
tag_dictionary	insight_tags	Tag vocabulary controls what tags can be used
offers	monthly_preferences	Offers referenced by ID in active_offers array

5. Indexes

The following indexes are already applied and should be preserved in any migrations:

idx_insights_call_id	- insights.call_id
idx_insights_signal_family	- insights.signal_family
idx_insights_signal	- insights.signal
idx_insights_insight_type	- insights.insight_type
idx_insights_created_at	- insights.created_at
idx_insight_tags_insight_id	- insight_tags.insight_id
idx_insight_tags_tag	- insight_tags.tag
idx_content_ideas_insight_id	- content_ideas.insight_id
idx_content_ideas_status	- content_ideas.status
idx_content_ideas_format	- content_ideas.content_format
idx_market_signals_family	- market_signals.signal_family
idx_calls_date	- calls.date
idx_calls_call_type	- calls.call_type

6. ID Strategy

IDs are deterministic and do not require live database lookups before insertion. This supports batch processing and stable reruns without collision risk.

Record Type	Format	Example
Call	CALL_<TranscriptUID>	CALL_AMY_TURNER_20260203
Insight	INS_<CallID>_01	INS_CALL_AMY_TURNER_20260203_01
Content Idea	CONT_<CallID>_01	CONT_CALL_AMY_TURNER_20260203_01
Offer	OFFER_<Name>	OFFER_MENTORSHIP_10K

If no Transcript UID is available, fall back to: CALL_<YYYYMMDD>_<HHMMSS>

7. Planned Future Tables

The following tables are planned but not yet built. They should be designed to integrate cleanly with the existing schema.

Table	Phase	Purpose
email_stats	Phase 2	Open rates, click rates, revenue per email from ActiveCampaign
funnel_stats	Phase 2	Conversion rates, opt-ins, funnel step performance
ads_stats	Phase 2	Meta ads performance: CPL, ROAS, spend, impressions
funnels	Phase 2	Funnel definitions, stages, and mapped offers
traffic_sources	Phase 2	Organic, paid, referral channel definitions and performance
written_emails	Phase 2	Full email copy written by the Email Writer skill, linked to content_ideas

8. Skills Architecture Overview

The system is powered by Claude Code skills — markdown-based instruction files that tell the AI how to interact with the database. Each skill is self-contained and reads business_profile at startup.

Skill	Status	What It Does
Transcript Processor	Built	Ingests transcripts, runs 2-pass extraction, writes to calls/insights/tags/content_ideas
Content Calendar	In Design	Builds monthly email calendar structure from goals, offers, and content ideas
Email Marketing Specialist	Planned	Designs email strategy for the month, assigns email types to calendar dates
Email Writer	Planned	Writes full email copy using VOC language from insights database
Performance Tracker	Planned	Ingests email/funnel/ads stats and writes to stats tables
Market Signal Analyzer	Planned	Aggregates insights into market_signals, surfaces trends and messaging angles

9. Developer Notes

Multi-Client Architecture

The system is being built to serve multiple clients. The current schema does not yet have a `client_id` foreign key across tables. This should be added in Phase 2 before the system is deployed for more than one client. Each client will need their own `business_profile` row at minimum, with `client_id` propagated to `calls`, `insights`, and `monthly_preferences`.

ActiveCampaign Integration

Email delivery is via ActiveCampaign. API credentials will need to be stored per client (likely in `business_profile` or a future `clients` table). The Email Writer skill will eventually push drafted emails to ActiveCampaign campaigns via their API.

Fireflies Automation (Future)

Transcripts are currently uploaded manually from Cockatoo. The future automation path is: Fireflies webhook → transcript ingestion endpoint → Transcript Processor skill triggered automatically. The `calls` table `transcript_source` field already supports Fireflies as a value.

signal_family and signal are not hardcoded

These fields are dynamically inferred by the AI from transcript content and normalized against existing values in the database. Do not add enum constraints to these fields. They grow organically as more transcripts are processed.

Central Intelligence — Confidential Developer Document

Questions? Contact the project owner before making schema changes.