



Free Questions for MTCNA

Shared by Beard on 06-03-2026

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)



Question 1

Question Type: MultipleChoice

What command will display the line, protocol, DLCI, and LMI information of an interface?

Options:

- A- sh pvc
- B- show interface
- C- show frame-relay pvc
- D- show run

Answer:

B

Question 2

Question Type: MultipleChoice



A PC with IP 192.168.1.2 can access internet, and static ARP has been set for that IP address on gateway. When the PC Ethernet card failed, the user change it with a new card and set the same IP for it. What else

should be done? [multiple answers]

Options:

- A- Old static ARP entry on gateway has to be updated for the new card
- B- Nothing -- it will work as before
- C- MAC-address of the new card has to be changed to MAC address of old card
- D- Another IP has to be added for Internet access

Answer:

A, C

Question 3

Question Type: MultipleChoice

How many usable IP addresses are there in a 23-bit (255.255.254.0) subnet?

Options:

- A- 512
- B- 510
- C- 508
- D- 254

Answer:

B

Question 4

Question Type: MultipleChoice



DHCP server is configured on a router's ether1 interface. IP address 192.168.0.100/24 is assigned to

the interface. Possible IP pools, that can be used by this DHCP server, are:

Options:

- A- 192.168.0.1-192.168.0.255
- B- 192.169.0.1-192.169.0.254
- C- 192.168.0.1-192.168.0.99 , 192.168.0.101-192.168.0.254
- D- 192.168.0.1-192.168.0.14

Answer:

C

Question 5

Question Type: MultipleChoice

What is the correct action to be specified in the NAT rule to hide a private network when communicating to the outside world?

Options:

- A- masquerade
- B- allow
- C- passthrough
- D- tarpit

Answer:

A

Question 6

Question Type: MultipleChoice

Choose minimal set of software packages in RouteOS required to configuring a wireless AP



Options:

- A- Wireless
- B- advanced-tools
- C- dhcp
- D- routing
- E- System

Answer:

A, E

Question 7

Question Type: MultipleChoice

A network ready device is directly connected to a MikroTik RouterBOARD 750 with a correct U.T.P. RJ45 functioning cable. The device is configured with an IPv4 address of 192.168.100.70 using a subnet mask of 255.255.255.252. What will be a valid IPv4 address for the RouterBOARD 750 for a successful connection to the device?

Options:

- A- 192.168.100.69/255.255.255.252
- B- 192.168.100.70/255.255.255.252
- C- 192.168.100.71/255.255.255.252
- D- 192.168.100.68/255.255.255.252

Answer:

A

Question 8

Question Type: MultipleChoice

If a packet comes to a router and starts a new, previously unseen connection, which connection state would be applied to it?

Options:



- A- no connection state would be applied to such packet
- B- new
- C- unknown
- D- invalid
- E- established

Answer:

B

Question 9

Question Type: MultipleChoice

Which command is used to determine if an IP access list is enabled on a particular interface?

Options:

- A- show access-lists

- B- show interface
- C- show ip interface
- D- show interface access-lists

Answer:

B

Question 10

Question Type: MultipleChoice

Evaluate the following information:

Access Point configuration:

- wlan1 is in 'AP-Bridge' mode
- Bridge1 has wlan1 and ether1 as ports

CPE configuration:

- wlan1 is in 'Station-Bridge' mode
- Bridge1 has wlan1 and ether1 as ports



Select protocols that will pass from ether1 on the CPE to ether1 on the Access Point.

Options:

- A- IPv4
- B- ARP
- C- USB
- D- BGP
- E- Firewire
- F- IPv6
- G- DHCP
- H- PPPoE

Answer:

A, B, F, G, H

Question 11

Question Type: MultipleChoice

Which one of the following is true regarding VLANs?

Options:

- A- Two VLANs are configured by default on all Cisco switches.
- B- VLANs only work if you have a complete Cisco switched internetwork. No off-brand switches are allowed.
- C- You should not have more than 10 switches in the same VTP domain.
- D- VTP is used to send VLAN information to switches in a configured VTP domain.

Answer:

D

Question 12

Question Type: MultipleChoice



There are two routes in the routing table:

0 dst-addr=10.1.1.0/24 gateway=5.5.5.5

1 dst-addr=10.1.1.4/30 gateway=5.6.6.6

Which gateway will be used to get to the IP address 10.1.1.6?

Options:

- A- both - half of the traffic will be routed through one gateway, half through the other
- B- 5.5.5.5
- C- the required route is not in the routing table
- D- 5.6.6.6

Answer:

D

To Get Premium Files for MTCNA Visit

<https://www.p2pexams.com/products/mtcna>

For More Free Questions Visit

<https://www.p2pexams.com/mikrotik/pdf/mtcna>

20%
DISCOUNT

