Field Application Engineer

Adaptive and Embedded Computing Group (AECG)



Revision History

Date	Version	Description
02/16/24	1.0	Initial version for flow introduction.

© Copyright 2021 Xilinx, Inc. Xilinx, the Xilinx logo, Artix, ISE, Kintex, Spartan, Virtex, Vivado, Zynq, and other designated brands included herein are trademarks of Xilinx in the United States and other countries. All other trademarks are the property of their respective owners.

NOTICE OF DISCLAIMER: The information disclosed to you hereunder (the "Information") is provided "AS-IS" with no warranty of any kind, express or implied. Xilinx does not assume any liability arising from your use of the Information. You are responsible for obtaining any rights you may require for your use of this Information. Xilinx reserves the right to make changes, at any time, to the Information without notice and at its sole discretion. Xilinx assumes no obligation to correct any errors contained in the Information or to advise you of any corrections or updates. Xilinx expressly disclaims any liability in connection with technical support or assistance that may be provided to you in connection with the Information. XILINX MAKES NO OTHER WARRANTIES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, REGARDING THE INFORMATION, INCLUDING ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT OF THIRD-PARTY RIGHTS.



1. 先從以下網站安裝 KD240 的 Ubuntu 22.04

Install Ubuntu on AMD | Ubuntu

CHOOSE A BOARD

Kria™ K24 SOMs

Kria™ K26 SOMs

Zynq™ UltraScale+™ MPSoC Development Boards

Versal™ Adaptive SoC Evaluation Kit

Kria™ K24 SOMs (KD240)



Ubuntu Server 22.04

The version of optimised Ubuntu Server 22.04 is beta for now, the certified version is coming soon.

Works on:

- ① Please check the AMD Kria™ Wiki for the platform's latest boot firmware, technical documentation, and the Ubuntu for AMD-Xilinx Devices Wiki for known issues and limitations.


Download 22.04



2. 使用 balenaEtcher 燒錄到 SD Card 內




Setting up the SD Card Image (xilinx.com)







3. 依照下面方式插入到 KD240 的 SD Card 槽中



4. 上電並透過 MobaXtern 與 KD240 透過 UART 溝通





- 6. 登入帳號與密碼皆為 ubuntu,第一次輸入密碼後會叫你改成自己的密碼
- 7. 登入後一定要先進行以下指令

```
sudo snap install xlnx-config --classic --channel=2.x
sudo xlnx-config.sysinit
這條指令相當於作了以下的事情:
sudo add-apt-repository ppa:xilinx-apps
sudo add-apt-repository ppa:ubuntu-xilinx/sdk
sudo apt update
sudo apt upgrade
sudo apt search xlnx-firmware-kd240 ---> 尋找 BIST 的 firmware
也可以用 sudo apt search bist 尋找
sudo apt install xlnx-firmware-kd240-bist
sudo xmutil unloadapp
sudo xmutil loadapp kd240-bist
sudo apt-get install docker.io
docker pull xilinx/kria-bist:2023.1
```

```
Docker 啟動!
sudo docker run \
--env=DISPLAY \
--env=XDG_SESSION_TYPE \
--net=host \
--privileged \
--volume=/home/ubuntu/.Xauthority:/root/.Xauthority:rw \
-v /tmp:/tmp \
-v /dev:/dev \
-v /sys:/sys \
-v /etc/vart.conf:/etc/vart.conf \
-v /lib/firmware/xilinx:/lib/firmware/xilinx \
-v /run:/run \
-it xilinx/kria-bist:2023.1 bash
```

- cd /opt/xilinx/kria-bist/tests
- 10. pytest-3 --board kd240
- 11. Result 如下:

測試成功項

```
Start of test
Operation Mode: MotorOpMode.kModeOff
Measuring motor ADC voltage feedback for ElectricalData.kDCLink...
Average measured motor voltage: 24.11V
Motor voltage ADC feedback test successful in 'OFF' mode
Test passed
End of test
PASSED
motor/test_bist_motor.py::test_motor[dc_link_curr_adc_fb_test]
```

測試失敗項

```
Start of test
Please set the BIST_REMOTE_HOST_IP environment variable.
Test failed
End of test
FAILED
eth/test_bist_eth.py::test_eth[ethernet3_perf]
```

====== short test summary info =======

測試總結

```
FAILED can/test_bist_can.py::test_can[can_bus_send] - assert False
FAILED can/test_bist_can.py::test_can[can_bus_receive] - assert False
FAILED disk/test_bist_disk.py::test_disk[usb1_read_performance] - assert False
FAILED disk/test_bist_disk.py::test_disk[usb1_write_performance] - assert False
FAILED disk/test bist disk.py::test disk[usb2 read performance] - assert False
FAILED disk/test bist disk.py::test disk[usb2 write performance] - assert False
FAILED eth/test_bist_eth.py::test_eth[ethernet1_ping] - assert False
FAILED eth/test_bist_eth.py::test_eth[ethernet1_perf] - assert False
FAILED eth/test_bist_eth.py::test_eth[ethernet2_ping] - assert False
FAILED eth/test bist eth.py::test eth[ethernet2 perf] - assert False
FAILED eth/test_bist_eth.py::test_eth[ethernet3_ping] - assert False
FAILED eth/test bist eth.py::test eth[ethernet3 perf] - assert False
FAILED pwm/test bist pwm.py::test pwm[fan] - assert False
FAILED tty/test bist tty.py::test tty[rs485 temp humidity sensor_read] - AssertionError: assert False
                                                                                                                    failed, 26 passed, 2 skipped in 145.11s (0:02:25) ==
                                                                                                                                                       together we advance
```

AMDI