

Lecture 1 - Assignment

Vanda Derzsi

24/02/2022

This introduction is essentially Chapter 2 from Kieran Healy's book Data Visualization, which you should read as part of Assignment 2 and to find your way around RStudio. The reason I start with this (and continue for one or two more weeks) is that visualization is one of the more fun parts of data analysis making it a great starting point.

We will use exclusively R Markdown files. In this case, you should simply open the file 'lecture1-to-fill.Rmd' from the repository and you are set. Whenever you create a new file, you should choose to make an R Markdown file.

Things to Know about R

There are 4 things to bear in mind about R:

1. Everything has a name
2. Everything is an object
3. You do things using functions
4. Functions come in packages

Everything has a name Everything that you use in R has a name: variables (including datasets), functions, or special reserved words. That is the way you talk about them. Here are some examples:

```
# Numbers are called by their number, arithmetic operations by their usual symbol
3
3+3
# There are some pre-defined variables
pi
# There are also pre-defined functions
mean(c(0, 78))
```

Some Notes:

- '#' is the *commenting* (EXERCISE) sign. It tells R that everything that follows is a comment and R should ignore it. Comments are there to help explain parts of the code that need additional documentation. We will overuse them initially, but reduce this as the course proceeds.
- c, "c", and "C" are not the same things
- Naming conventions: When you name variables and functions, you should use snake case.

Exercise: For each of the lines in the following code chunk, write in a comment next to it what it returns. I completed the first example for you.

```

3          # -> 3
7 %% 3     # -> 1
False      # -> Error: object 'False' not found
'pi'       # -> "pi"
FALSE      # -> FALSE

```

Exercise: Look up what ‘snake case’ is and add your answer here.

Answer: In general programming, snake case is a convention to fill up spaces in written text by using underscores instead of space - e.g., “this_is_my_answer”. In R environment, snakecase is a name of a package that has been created for similar purposes - from The Comprehensive R Archive Network’s website, snakecase (package) is “a consistent, flexible and easy to use tool to parse and convert strings into cases like snake or camel among others”.

Exercise: What types of names are allowed in R? Look it up and write your answer here as you understand it. Then provide 3 examples of things that are not valid names in R for different reasons.

Answer: Basic functions and arithmetical elements (e.g., constants, other mathematical notations, logical operators, etc.) are pre-defined in R by default and are strongly advised not to be overwritten because they can lead to loss of precision (e.g., if we re-define the variable ‘pi’, we can no longer use it as the value what pi really stands for). Three examples: - mean: pre-defined function to calculate the arithmetic mean of n numbers - pi: pre-defined constant - FALSE: logical operator/ Boolean

Everything is an object There are built-in objects and objects you import or create. Most importantly, you assign values to objects you create with the ‘<-’ operator: a ‘<’ (‘less than’) followed by a ‘-’ (‘minus’ or ‘dash’).

```

marcs_new_object <- 12
marcs_new_object

```

One important function to create objects is the `c()` function, which combines several items into one object:

```

marcs_new_combined_object <- c(1, 2, 3, 4, 5, 6)
marcs_new_combined_object

```

In principle, you can use ‘=’ to assign values, but this is very non-idiomatic R. I discourage that you use ‘=’.

Class Exercise: Let’s start doing something with data. How many of the following programming languages have you *heard* of?

```

# Indent the list
list_of_programming_languages <- c(
  "R",
  "SQL",
  "Racket",
  "Lisp",
  "JavaScript",
  "ECMAScript",
  "bash",
  "C",
  "Perl",
  "Logo",
  "Scratch"
)

```

```
languages_heard_of <- c(11)
```

You do things using functions

A function is a thing that does things to things.

Me, paraphrasing Cosma Shalizi

A function is a special object that you can call, such as the function *mean*. It is an object:

```
mean
```

```
## function (x, ...)
## UseMethod("mean")
## <bytecode: 0x7fbf746bdb58>
## <environment: namespace:base>
```

When we *call* it, we put parentheses at the end, and we tell it what to perform its action on:

Exercise: What happens if you call the function *mean* without any arguments, i.e. *mean()*?

Answer: An error message pops up: “Error in mean.default() : argument”x” is missing, with no default”. There are no arguments (values) to calculate the mean of.

Functions come in packages As you may start to realize, lots of functions already exist, such as *mean()* and *sd()* and *c()*. There are many more functions that were written by other people and bundled into packages so that you can use them. Many packages come bundled with R from the start (base R), while you can install others on your system via ‘install.packages()’ and use via ‘library()’. We will soon use the ‘ggplot()’ function. Try using it now:

```
ggplot
```

You will get an error. We first need to import the library:

```
# install.packages("ggplot2")
# library(ggplot2)
```

This tells R to go and get all the objects defined in the library called ggplot2, which includes *ggplot*. This gives us our first data (non-)visualization: a beautifully empty plot.

Think of it as the equivalent of recipe books: you can either experiment and concoct your own recipes, which is fine if you are a cook. Alternatively, you get recipe books from great chefs and follow their instructions. Depending on the type of recipe, you still need a lot of background knowledge – what does it mean to boil, fry, blanch, roast – but you don’t have to figure out everything.

How to figure out what is what

Suppose you have an object *x* that you don’t know what it is. You can do a few things to find out:

```
x <- c(1, 3.0, 2.9)
```

For built-in functions, you can also ask for help or bring up the documentation with ‘help()’ or ‘?’ or ‘??’:

Exercise: What do ‘class()’ and ‘str()’ do? Use ‘help’ (or ‘?’). Don’t spend too much time reading the docs. Which description do you find more helpful?

```
help(class)
# R possesses a simple generic function mechanism which can be used for an object-oriented style of programming
help(str)
# Compactly display the internal structure of an R object, a diagnostic function and an alternative to class()
```

Make Your First Figure

```
# install.packages("gapminder")
# library(gapminder)
# gapminder
```

As you can see, some datasets are conveniently bundled for you as libraries.

Assignment 2

This assignment is due before the start of class 2. Commit your knitted assignment2.html to your git and push it to your repository regularly as you make progress.

- Only your work until 1:30 PM 24/02/2022 (EXERCISE) will be considered. # I am not sure if this is the right answer as we have learned much of these techniques on the 2nd class. In the other document (in Lecture 2 folder) it says that we should submit this and the assignment for Lecture 2 together. Therefore, the correct answer here might be 1:30 PM 01/03/2022.
- If you know that you might miss the deadline, you have to email me in advance and I will tell you whether you can get an extension. No extension will be granted less than 24 hours prior to the deadline – you should have started working on it.
- If you miss the deadline (even by 1 minute) you lose 25% irrespective of technical issues such as ‘the internet went down’. It wasn’t down the whole week, and you knew a deadline was coming. In a business setting, you would probably lose more than 25%. Repeat offenders will face an increasingly large penalty.
- If you struggle *answering* the assignment, you should submit what you tried, and send me a message that you struggled. Much of the grade initially is on trying out things, even if it doesn’t work out, so you should submit.

Part 1

Read chapter 2 of Data Visualization. Make sure you know where the console is, the editor, and what code chunks are in RStudio.

Part 2

Complete all the exercises and fill all the holes in the notes of lecture 1. Put your answer to an exercise right after the question of the exercise in the R Markdown file. When done, knit the document, commit the changes with the commit message “Part 1 of assignment 2” and push them to your GitHub repository.

Knit the slides for class 1 to html and/or pdf, commit the .Rmd and .html files – but not the pdf – and push.

Note: To get pdf generation working, the easiest is to install the package `tinytex`. See <https://www.rdocumentation.org/packages/tinytex> for installation instructions, it is specifically geared towards use in R Markdown files. Pdf and Latex issues can be... interesting shall we say, so ask for help.

Note: If you can't figure out how to use git, ask a question on Slack.

Part 3

You have to get in the habit of reading and making sense of error messages, even though initially they might be written in a language you don't understand. Track as many error messages as possible that you received during this week (but stop at 4). Put the code that caused the error in the chunk below, and copy the error message as a comment below it. I provide an example.

```
# Example: "4" - "3" leads to the error 'Error in "4" - "3" : non-numeric argument to binary operator'  
# Thus you write:  
"4" - "3"  
# -> Error in "4" - "3" : non-numeric argument to binary operator  
  
# Your examples below  
  
# Example_1: install.packages(tinytex) leads to the error 'Error in install.packages : object 'tinytex'  
# I forgot to put the name of the package in quote marks  
  
# Example_2: typing "False" leads to the error 'Error: object 'False' not found'  
# The word False as a string is not defined  
  
# Example_3: typing 4 = 3 leads to the error 'Error in 4 = 3 : invalid (do_set) left-hand side to assign'  
# If one would like to evaluate the equivalency of two floats, == should be used, not =  
  
# Example_4: typing `{r, eval=FALSE}` results in 'Error: attempt to use zero-length variable name'  
# One more backtick is needed in order to have an executable block for pieces of code in R markdown files
```

Post one of these 4 errors in Slack.