

## Appendix A

### Block Diagrams

---

#### APPENDIX CONTENTS

##### Power Distribution

24V Power Supply Wiring Diagram	A - 3
Multi-Output Power Supply Wiring Diagram	A - 5
AC Power Distribution Overview	A - 7

##### Card Cage

Main Block Diagram	A - 9
Master Card Cage	A - 10
Slave Card Cage	A - 11

##### Robotics

Reagent Arm	A - 12
Sample Arm	A - 13
Syringes (Reagent and Sample)	A - 14
Sample Carousel Drive	A - 15

##### Incubator Optics

Optics	A - 16
Lamp Drive	A - 17
Incubator Optics Interface Board	A - 18
Mixer Drive	A - 19

##### Reagent Cooler

Reagent Cooler	A - 20
Reagent Bar Code Reader Assembly Interconnect	A - 21

##### I/O Devices

CRT and Touchscreen	A - 23
I/O Peripherals	A - 24

##### Pumps and Valves


Pumps and Valves	A - 25
------------------	--------

##### Water System

Water System	A - 26
--------------	--------



24V POWER SUPPLY WIRING DIAGRAM




NOTE: On the old style Pump & Valve Bd,  
P494 goes to the Home/Station Interface Bd.

On both boards (old style and new style),  
24 VDC is supplied to the Sample Carousel  
Assy through P494.

NOTE: Motor Controller #6  
drives the Shutter Assy.


24VFOLD.VSD

MULTI-OUTPUT POWER SUPPLY WIRING DIAGRAM




MULTFOLD.VSD

AC POWER DISTRIBUTION OVERVIEW




ACDISTOV.VSD


**MAIN BLOCK DIAGRAM**



MAINBLD.VSD

### MASTER CARD CAGE




**SLAVE CARD CAGE**

SLCARDG.VSD




### REAGENT ARM




RGTARMFN.VSD

SAMPLE ARM




### SYRINGES (REAGENT AND SAMPLE)




SYRINGES.VSD


**SAMPLE CAROUSEL DRIVE**



SMPCRS�.VSD


### OPTICS




**LAMP DRIVE**

LAMPDRIV.VSD

### INCUBATOR OPTICS INTERFACE BOARD




MIXER DRIVE






### REAGENT COOLER



## REAGENT BAR CODE READER ASSEMBLY INTERCONNECT




**NOTE:** P576V connected to J576S only when Welch Allyn Interface and Welch Allyn reader head is used.

**NOTE:** Voltage between pins 1 and 2 of P576V will be 24 VDC only when reader head is driving clockwise.


**NOTE:** J576S and P576D are used only with the InterMec board and Bar Code Reader Head.


Bar Code Reader Bd	Bar Code Reader Head	Interface Bd Needed	576S	576D	576V
InterMec	InterMec	No	Yes	Yes or Yes	
InterMec	Welch Allyn	No	Yes	Yes or Yes	
Welch Allyn	Intermec				
<i>This combination will not work.</i>					
Welch Allyn	Welch Allyn	No	Yes		Yes

BARCODE.VSD

**CRT AND TOUCHSCREEN**

### I/O PERIPHERALS



**PUMPS AND VALVES**

### WATER SYSTEM

