

The screenshot displays the Cisco Packet Tracer software interface. The main workspace shows a network topology with a central 2911 Router0 connected to two 2950 Switches (Switch0 and Switch1). Each switch is connected to two PCs (PC0, PC1 on Switch0; PC2, PC3 on Switch1). The interface includes a top menu bar, a toolbar, and a bottom status bar. On the right, the Simulation Panel is open, showing an Event List with a table of events and Play Controls. The Event List table is as follows:

Vis.	Time(sec)	Last Device
	0.006	Switch0
	0.007	Router0
	0.008	Switch0

Below the table, the Play Controls section includes buttons for 'Reset Simulation', 'Constant Delay', and 'Captured to: 0.008 s'. There are also play/pause and step buttons. The bottom status bar shows the time as 00:10:48.551 and includes a 'PLAY CONTROLS' section with a play button and a 'Copper Straight-Through' section with various cable types.

The screenshot displays the Cisco Packet Tracer software interface. The main workspace shows a network topology with a central 2911 Router0 connected to two 2950 Layer 2 switches (Switch0 and Switch1). Switch0 is connected to two PCs (PC0 and PC1), and Switch1 is connected to two PCs (PC2 and PC3). The interface includes a top menu bar (File, Edit, Options, View, Tools, Extensions, Window, Help), a toolbar with various icons, and a status bar at the bottom. On the right side, there is a Simulation Panel with an Event List, Play Controls, and Event List Filters. The Event List shows three events related to Switch1. The Play Controls include buttons for Play, Stop, and Step. The Event List Filters section lists various protocols and services. The bottom status bar shows the time (00:10:50.536) and the current simulation mode (Simulation).