

tcp

No.	Time	Source	Destination	Protocol	Length	Info
62	2.149353200	35.186.224.35	172.25.32.150	TLSv1.2	94	Application Data
68	2.268193400	172.25.32.150	35.186.224.35	TCP	54	38539 → 443 [ACK] Seq=44 Ack=41 Win=507 Len=0
88	3.368712200	172.25.32.150	57.144.209.32	TCP	55	38575 → 443 [ACK] Seq=1 Ack=1 Win=515 Len=1
89	3.376109800	57.144.209.32	172.25.32.150	TCP	60	443 → 38575 [RST] Seq=1 Win=0 Len=0
99	3.768516300	172.25.32.150	35.186.224.22	TCP	55	38501 → 443 [ACK] Seq=1 Ack=1 Win=512 Len=1
100	3.792675300	35.186.224.22	172.25.32.150	TCP	66	443 → 38501 [ACK] Seq=1 Ack=2 Win=829 Len=0 SLE=1 SRE=2
132	5.502492800	172.25.32.150	184.28.109.61	TCP	54	38573 → 443 [FIN, ACK] Seq=1 Ack=1 Win=511 Len=0
133	5.515315500	184.28.109.61	172.25.32.150	TLSv1.2	85	Encrypted Alert
134	5.515316700	184.28.109.61	172.25.32.150	TCP	60	443 → 38573 [FIN, ACK] Seq=32 Ack=2 Win=501 Len=0
135	5.515490200	172.25.32.150	184.28.109.61	TCP	54	38573 → 443 [RST, ACK] Seq=2 Ack=32 Win=0 Len=0
136	5.515630100	172.25.32.150	184.28.109.61	TCP	54	38573 → 443 [RST] Seq=2 Win=0 Len=0
561	16.181646100	95.100.153.135	172.25.32.150	TLSv1.2	85	Encrypted Alert
562	16.181646700	95.100.153.135	172.25.32.150	TCP	60	443 → 38577 [FIN, ACK] Seq=32 Ack=1 Win=650 Len=0
563	16.182818300	172.25.32.150	95.100.153.135	TCP	54	38577 → 443 [ACK] Seq=1 Ack=33 Win=1022 Len=0
673	20.272134300	172.25.32.150	199.232.214.248	TCP	55	38542 → 443 [ACK] Seq=1 Ack=1 Win=516 Len=1
674	20.272291500	172.25.32.150	199.232.214.248	TCP	55	38541 → 443 [ACK] Seq=1 Ack=1 Win=516 Len=1
685	20.482702900	199.232.214.248	172.25.32.150	TCP	66	443 → 38542 [ACK] Seq=1 Ack=2 Win=277 Len=0 SLE=1 SRE=2

Ethernet II, Src: Cisco 6d:c0:e7 (24:d5:e4:6d:c0:e7), Dst: Intel 05:c2:bf (c8:cb:9e:05:c2:bf)

Internet Protocol Version 4, Src: 57.144.209.32, Dst: 172.25.32.150

Transmission Control Protocol, Src Port: 443, Dst Port: 38575, Seq: 1, Len: 0

Source Port: 443
Destination Port: 38575
[Stream Index: 3]
[Stream Packet Number: 2]
[Conversation completeness: Incomplete (40)]
[TCP Segment Len: 0]
Sequence Number: 1 (relative sequence number)
Sequence Number (raw): 751962419
[Next Sequence Number: 1 (relative sequence number)]
Acknowledgment Number: 0
Acknowledgment number (raw): 0
0101 = Header Length: 20 bytes (5)
Flags: 0x004 (RST)
Window: 0
[Calculated window size: 0]
[Window size scaling factor: -1 (unknown)]

Packets: 924 · Displayed: 28 (3.0%) · Dropped: 0 (0.0%) Profile: Default

*Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

udp

No.	Time	Source	Destination	Protocol	Length	Info
33	1.024791000	172.25.34.126	172.25.47.255	UDP	86	57621 → 57621 Len=44
35	1.024791500	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
36	1.024791700	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
62	1.240368600	0.0.0.0	255.255.255.255	DHCP	347	DHCP Request - Transaction ID 0x3f116228
65	1.240369500	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
66	1.240369800	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
67	1.240370200	172.25.39.182	255.255.255.255	UDP	72	49619 → 30000 Len=30
69	1.434457800	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
70	1.434458000	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
75	1.638526900	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
76	1.638527200	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
82	1.846128100	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
83	1.846128400	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
120	2.051523800	172.25.39.65	255.255.255.255	UDP	82	59999 → 1947 Len=40
129	2.051524300	172.25.39.65	172.25.47.255	UDP	82	59998 → 1947 Len=40
133	2.260998500	172.25.39.182	255.255.255.255	UDP	72	49619 → 30000 Len=30
200	3.281033700	172.25.34.204	172.25.47.255	NBNS	92	Name query NB WPAD(00)

Frame 70: Packet, 82 bytes on wire (656 bits), 82 bytes captured (656 bits) on interface \Device\NPF{...}

Ethernet II, Src: AzureWaveTec 7d:fc:59 (94:bb:43:7d:fc:59), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

Internet Protocol Version 4, Src: 172.25.39.65, Dst: 172.25.47.255

0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 68
Identification: 0xc1b7 (49591)
000. = Flags: 0x0
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 128
Protocol: UDP (17)
Header Checksum: 0xc97e [validation disabled]
[Header checksum status: Unverified]
Source Address: 172.25.39.65
Destination Address: 172.25.47.255
[Stream Index: 1]

User Datagram Protocol, Src Port: 59998, Dst Port: 1947
Source Port: 59998

Header length in 32-bit words (ip_hdr_len), 4 bits

Packets: 422 · Displayed: 74 (17.5%) · Dropped: 0 (0.0%) Profile: Default