

Wireshark interface showing a packet capture of HTTP traffic. The packet list displays two packets: a GET request (No. 575) and a 200 OK response (No. 576). The packet details pane for packet 576 shows the Ethernet II, Internet Protocol Version 4, and Transmission Control Protocol (TCP) layers. The packet bytes pane shows the raw data of the HTTP response.

No.	Time	Source	Destination	Protocol	Length	Info
575	16.451422100	172.25.32.150	23.201.53.170	HTTP	136	GET /ncc.txt HTTP/1.1
576	16.465426700	23.201.53.170	172.25.32.150	HTTP	205	HTTP/1.1 200 OK (text/html)

Frame Number: 576
Frame Length: 205 bytes (1640 bits)
Capture Length: 205 bytes (1640 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp:http:data-text-lines]
Character encoding: ASCII (0)
[Coloring Rule Name: HTTP]
[Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: Cisco_6d:c0:e7 (24:d5:e4:6d:c0:e7), Dst: Intel_05:c2:bf (c8:cb:9e:05:c2:bf)
Internet Protocol Version 4, Src: 23.201.53.170, Dst: 172.25.32.150
Transmission Control Protocol, Src Port: 80, Dst Port: 23618, Seq: 1, Ack: 83, Len: 151
Source Port: 80
Destination Port: 23618
[Stream index: 11]
[Stream Packet Number: 5]
[Conversation completeness: Complete, WITH_DATA (31)]
[TCP Segment Len: 151]
Sequence Number: 1 (relative sequence number)

Destination Port (tcp.dstport), 2 bytes

Packets: 1721 - Displayed: 2 (0.1%) - Dropped: 0 (0.0%) Profile: Default

Wireshark interface showing a packet capture of ARP traffic. The packet list displays multiple ARP requests and probes. The packet details pane for packet 107 shows the Ethernet II, Internet Protocol Version 4, and Address Resolution Protocol (ARP) layers. The packet bytes pane shows the raw data of the ARP request.

No.	Time	Source	Destination	Protocol	Length	Info
38	0.825361400	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.35.242? Tell 172.25.32.1
39	0.825363800	Intel_3a:06:3d	Broadcast	ARP	60	ARP Announcement for 172.25.33.45
40	0.825963400	AzureWaveTec_ab:32:...	Broadcast	ARP	60	Who has 172.25.32.1? Tell 172.25.39.109
41	0.827139900	AzureWaveTec_ab:32:...	Broadcast	ARP	60	Who has 172.25.32.1? Tell 172.25.39.109
46	1.023947800	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.179.85? Tell 172.25.176.1
47	1.023947800	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.34.58? Tell 172.25.32.1
48	1.023948100	ASUSTekCOMPU_d1:eb:...	Broadcast	ARP	60	Who has 172.25.180.48? Tell 172.25.180.75
81	1.225558000	Intel_3c:6a:09	Broadcast	ARP	60	Who has 172.25.34.98? Tell 172.25.36.107
82	1.226921500	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.34.120? Tell 172.25.32.1
83	1.226924500	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.34.51? Tell 172.25.32.1
84	1.226925200	HifocusElect_0b:5a:...	Broadcast	ARP	60	Who has 172.25.176.130? (ARP Probe)
99	1.439493000	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.179.83? Tell 172.25.176.1
101	1.439493700	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.180.113? Tell 172.25.176.1
102	1.439494000	HifocusElect_0b:63:...	Broadcast	ARP	60	Who has 172.25.176.136? (ARP Probe)
107	1.439495500	MKC_7d:8a:d8	Broadcast	ARP	60	Who has 172.25.36.54? Tell 172.25.32.143
108	1.439495800	Cisco_6d:c0:e7	Broadcast	ARP	60	Who has 172.25.180.4? Tell 172.25.176.1
109	1.439496000	HifocusElect_0b:62:...	Broadcast	ARP	60	Who has 169.254.112.113? (ARP Probe)

Frame 107: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface V...
Section Number: 1
Interface id: 0 (\Device\NPF_{7729FA76-5F8E-4D08-939B-E10A099F51A5})
Encapsulation type: Ethernet (1)
Arrival Time: Aug 7, 2026 14:35:20.330652500 India Standard Time
UTC Arrival Time: Aug 7, 2026 09:05:20.330652500 UTC
Epoch Arrival Time: 1786093520.330652500
[Time shift for this packet: 0.000000000 seconds]
[Time delta from previous captured frame: 200 nanoseconds]
[Time delta from previous displayed frame: 1.500 microseconds]
[Time since reference or first frame: 1.439495500 seconds]
Frame Number: 107
Frame Length: 60 bytes (480 bits)
Capture Length: 60 bytes (480 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:arp]
Character encoding: ASCII (0)
[Coloring Rule Name: ARP]

Address Resolution Protocol: Protocol

Packets: 425 - Displayed: 189 (44.5%) - Dropped: 0 (0.0%) Profile: Default