

LOT SIGNAL

Quick Start Manual

LOT Systems Corporation · Los Angeles, CA · 2026
brand.lot-systems.com

1. WHAT'S IN THE BOX

- LOT SIGNAL device – two-piece stainless steel puck, ~40 x 40 x 14mm
- Wireless charging puck
- USB-C cable (service & fallback charge only)

2. FIRST CHARGE

Place the device, screen-side up, on the charging puck. The screen shows a charging indicator. Allow 2 hours for a full first charge before pairing.

3. PAIRING

On first boot the device broadcasts a WiFi network named LOT-SIGNAL-XXXX. From your phone, connect to that network and open the setup page. Enter your home WiFi credentials and the pairing code shown in your account settings at lot-systems.com. The device joins your network and syncs.

4. USING LOT SIGNAL

The screen shows short notifications sent by the LOT AI from lot-systems.com – for example, “Coffee time!”

Press the single button to copy whatever is on screen into your Log tab on lot-systems.com. If the screen is idle when you press the button, the device takes a snapshot and logs that instead.

One button. One action: Copy.

5. WEATHER SENSING

The device quietly reports ambient temperature, humidity, and pressure back to your LOT profile. No action needed.

6. CHARGING

Wireless only – no exposed contacts on the device. Battery lasts roughly 1.5–2 days between charges under typical use.

7. CARE

Front face is polished stainless steel – wipe with a soft, dry cloth.

Rear face has a camera lens window – avoid abrasive cleaners near it.

8. PRIVACY

The camera activates only on a deliberate button press when the screen is idle. No continuous recording. No data sold to third parties.

Full detail at brand.lot-systems.com.