Raspberry Pi Pico-series C/C++ SDK

Libraries and tools for C/C++ development on Raspberry Pi microcontrollers

Colophon

Copyright © 2020-2024 Raspberry Pi Ltd (formerly Raspberry Pi (Trading) Ltd.)

The documentation of the RP2350 microcontroller is licensed under a Creative Commons Attribution-NoDerivatives 4.0 International (CC BY-ND).

build-date: 2024-08-09 build-version: c274ff8-clean

About the SDK

Throughout the text "the SDK" refers to our Raspberry Pi Pico SDK. More details about the SDK can be found throughout this book. Source code included in the documentation is Copyright © 2023-2024 Raspberry Pi Ltd (formerly Raspberry Pi (Trading) Ltd.) and licensed under the 3-Clause BSD license.

Legal disclaimer notice

TECHNICAL AND RELIABILITY DATA FOR RASPBERRY PI PRODUCTS (INCLUDING DATASHEETS) AS MODIFIED FROM TIME TO TIME ("RESOURCES") ARE PROVIDED BY RASPBERRY PI LTD ("RPL") "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW IN NO EVENT SHALL RPL BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THE RESOURCES, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

RPL reserves the right to make any enhancements, improvements, corrections or any other modifications to the RESOURCES or any products described in them at any time and without further notice.

The RESOURCES are intended for skilled users with suitable levels of design knowledge. Users are solely responsible for their selection and use of the RESOURCES and any application of the products described in them. User agrees to indemnify and hold RPL harmless against all liabilities, costs, damages or other losses arising out of their use of the RESOURCES.

RPL grants users permission to use the RESOURCES solely in conjunction with the Raspberry Pi products. All other use of the RESOURCES is prohibited. No licence is granted to any other RPL or other third party intellectual property right.

HIGH RISK ACTIVITIES. Raspberry Pi products are not designed, manufactured or intended for use in hazardous environments requiring fail safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, weapons systems or safety-critical applications (including life support systems and other medical devices), in which the failure of the products could lead directly to death, personal injury or severe physical or environmental damage ("High Risk Activities"). RPL specifically disclaims any express or implied warranty of fitness for High Risk Activities and accepts no liability for use or inclusions of Raspberry Pi products in High Risk Activities.

Raspberry Pi products are provided subject to RPL's Standard Terms. RPL's provision of the RESOURCES does not expand or otherwise modify RPL's Standard Terms including but not limited to the disclaimers and warranties expressed in them.

Legal disclaimer notice

Colophon	
Legal disclaimer notice	
1. About the SDK.	
1.1. Introduction	
1.2. Anatomy of a SDK Application	
2. SDK architecture	
2.1. The Build System	
2.2. Every Library is an INTERFACE Library	
2.3. SDK Library Structure	
2.3.1. Higher-level Libraries	
2.3.2. Runtime Support Libraries	. 13
2.3.3. Hardware Support Libraries	. 14
2.3.4. Hardware Structs Library	. 15
2.3.5. Hardware Registers Library	. 16
2.3.6. TinyUSB Port	. 17
2.3.7. FreeRTOS Ports	. 17
2.3.8. Wi-Fi on Pico W	. 18
2.3.9. Bluetooth on Pico W	. 18
2.4. Directory Structure	. 19
2.4.1. Locations of Files	. 19
2.5. Conventions for Library Functions	. 21
2.5.1. Function Naming Conventions	. 21
2.5.2. Return Codes and Error Handling	
2.5.3. Use of Inline Functions	
2.5.4. Builder Pattern for Hardware Configuration APIs	
2.6. Customisation and Configuration Using Preprocessor variables	
2.6.1. Preprocessor Variables via Board Configuration File	
2.6.2. Preprocessor Variables Per Binary or Library via CMake	
2.7. SDK Runtime	
2.7.1. Standard Input/Output (stdio) Support	
2.7.2. Printf Support	
2.7.3. Runtime Initialization and Linking	
2.7.4. C-Library Integration	
2.7.5. Floating-point Support	
2.7.6. Hardware Divider	
2.8. Multi-core support	
2.9. Using C++	
2.10. Supporting both RP2040 and RP2350	
2.11. Next Steps	
3. Using programmable I/O (PIO)	
3.1. What is Programmable I/O (PIO)?	
3.1.1. Background	
3.1.2. I/O Using dedicated hardware on your PC	
3.1.3. I/O Using dedicated hardware on your Raspberry Pi or microcontroller	
3.1.4. I/O Using software control of GPIOs ("bit-banging")	
3.1.5. Programmable I/O Hardware using FPGAs and CPLDs	
3.1.6. Programmable I/O Hardware using PIO	
3.2. Getting started with PIO	
3.2.1. A First PIO Application	
3.2.2. A Real Example: WS2812 LEDs	
3.2.3. PIO and DMA (A Logic Analyser)	
3.2.4. Further examples	
3.3. Using PIOASM, the PIO Assembler	
3.3.1. Usage	
3.3.2. Directives	. 52

3.3.3. Values	54
3.3.4. Expressions	54
3.3.5. Comments	54
3.3.6. Labels	55
3.3.7. Instructions	55
3.3.8. Pseudoinstructions	56
3.3.9. Output pass through	
3.3.10. Language generators	
3.4. PIO Instruction Set Reference	
3.4.1. Encoding (version 0, RP2040)	
3.4.2. Encoding (version 1, RP2350)	
3.4.3. Summary	
3.4.4. JMP	
3.4.5. WAIT	
3.4.6. IN	
3.4.7. OUT	
3.4.8. PUSH	
3.4.9. PULL	
3.4.10. MOV (to RX)	
3.4.11. MOV (from RX)	
3.4.12. MOV	
3.4.13. IRQ	
3.4.14. SET	
4. Library documentation	
4.1. Hardware APIs.	76
4.1.1. hardware_adc	
4.1.2. hardware_base.	82
4.1.3. hardware_claim	84
4.1.4. hardware_clocks	86
4.1.5. hardware_divider	100
4.1.6. hardware_dcp RP2350	109
4.1.7. hardware_dma	110
4.1.8. hardware_exception	131
4.1.9. hardware_flash.	135
4.1.10. hardware_gpio	138
4.1.11. hardware_hazard3 (RP2350)	
4.1.12. hardware_i2c	
4.1.13. hardware_interp	
4.1.14. hardware_irq	
4.1.15. hardware_pio	
4.1.16. hardware_pll.	
4.1.17. hardware_powman RP2350	
4.1.18. hardware_pwm	
4.1.19. hardware_resets	
4.1.20. hardware_riscv (RP2350)	
4.1.21. hardware_riscv_platform_timer RP2350	
4.1.22. hardware_rtc RP2040	
4.1.23. hardware_rcp	
4.1.24. hardware_spi	
·	
4.1.25. hardware_sha256 RP2350	
4.1.26. hardware_sync	
4.1.27. hardware_ticks	
4.1.28. hardware_timer	
4.1.29. hardware_uart	
4.1.30. hardware_vreg	
4.1.31. hardware_watchdog	
4.1.32. hardware_xosc.	
4.2. High Level APIs	
4.2.1. pico_aon_timer.	
4.2.2. pico_async_context	328

5.

6.

7.

8.

4.2.3. pico_bootsel_via_double_reset	
4.2.4. pico_flash	
4.2.5. pico_i2c_slave	
4.2.6. pico_multicore	
4.2.7. pico_rand	
4.2.8. pico_sha256 RP2350	
4.2.9. pico_stdlib	
4.2.10. pico_sync	
4.2.11. pico_time	
4.2.12. pico_unique_id	
4.2.13. pico_util	
4.3. Third-party Libraries	
4.3.1. tinyusb_device	
4.3.2. tinyusb_host	
4.4. Networking Libraries	
4.4.1. pico_btstack 4.4.2. pico_lwip	
4.4.3. pico_cyw43_driver	
4.4.4. pico_cyw43_arch	
4.5. Runtime Infrastructure	
4.5.1. boot_stage2	
4.5.2. pico_atomic	
4.5.3. pico_base	
4.5.4. pico_binary_info	
4.5.5. pico_bootrom	
4.5.6. pico_bit_ops	
4.5.7. pico_cxx_options	
4.5.8. pico_clib_interface	
4.5.9. pico_crt0	
4.5.10. pico_divider	
4.5.11. pico_double	
4.5.12. pico_float	
4.5.13. pico_int64_ops.	
4.5.14. pico_malloc	
4.5.15. pico_mem_ops.	. 466
4.5.16. pico_platform.	. 467
4.5.17. pico_printf.	. 475
4.5.18. pico_runtime	. 475
4.5.19. pico_runtime_init	. 476
4.5.20. pico_stdio	. 477
4.5.21. pico_standard_binary_info	. 486
4.5.22. pico_standard_link.	
4.6. External API Headers	
4.6.1. boot_picobin_headers	
4.6.2. boot_picoboot_headers	
4.6.3. boot_uf2_headers	
4.6.4. pico_usb_reset_interface_headers	
SDK configuration	
5.1. Full List of SDK Configuration Defines	
CMake build configuration	
6.1. Full List of SDK Configuration Variables	
6.2. Platform and Board Configuration	
6.3. Compiler and Toolchain configuration.	
6.4. Binary Type configuration	
CMake build functions 7.1. Control of picotool post-processing (not available on RP2040)	
7.1. Control of picotool post-processing (not available on RP2040)	
8.1. The Configuration files	
8.2. Building applications with a custom board configuration	
8.3. Available configuration parameters	
The state of the s	

9. Embedded Binary Information	512
9.1. Basic information	512
9.2. Pins	512
9.3. Full Information	513
9.4. Including Binary Information	513
9.5. Setting Common Information from CMake	515
Appendix A: App Notes	517
Attaching a 7 segment LED via GPIO	517
Wiring information	517
List of Files	
Bill of Materials	
DHT-11, DHT-22, and AM2302 Sensors	
Wiring information	520
List of Files	
Bill of Materials	
Attaching a 16x2 LCD via TTL	
Wiring information	
List of Files	524
Bill of Materials	
Attaching a microphone using the ADC.	528
Wiring information	528
List of Files	
Bill of Materials	
Attaching a BME280 temperature/humidity/pressure sensor via SPI	531
Wiring information	531
List of Files	
Bill of Materials	536
Attaching a MPU9250 accelerometer/gyroscope via SPI	536
Wiring information	536
List of Files	537
Bill of Materials	540
Attaching a MPU6050 accelerometer/gyroscope via I2C	540
Wiring information	540
List of Files	541
Bill of Materials	543
Attaching a 16x2 LCD via I2C	543
Wiring information	544
List of Files	544
Bill of Materials	547
Attaching a BMP280 temp/pressure sensor via I2C	548
Wiring information	548
List of Files	548
Bill of Materials	553
Attaching a LIS3DH Nano Accelerometer via i2c.	553
Wiring information	554
List of Files	554
Bill of Materials	557
Attaching a MCP9808 digital temperature sensor via I2C	557
Wiring information	557
List of Files	558
Bill of Materials	560
Attaching a MMA8451 3-axis digital accelerometer via I2C	561
Wiring information	561
List of Files	561
Bill of Materials	564
Attaching an MPL3115A2 altimeter via I2C	564
Wiring information	
List of Files	565
Bill of Materials	569
Attaching an OLED display via I2C	569

Wiring information	570
List of Files	
Bill of Materials	
Attaching a PA1010D Mini GPS module via I2C	
Wiring information	
List of Files	 . 582
Bill of Materials	 . 585
Attaching a PCF8523 Real Time Clock via I2C	 . 585
Wiring information	 . 585
List of Files	
Bill of Materials	
Interfacing 1-Wire devices to the Pico	
· · · · · · · · · · · · · · · · · · ·	
Wiring information	
Bill of materials.	
List of files	
Communicating as master and slave via SPI	
Wiring information	 . 598
Outputs	 . 598
List of Files	 600
Bill of Materials	 604
Appendix B: Building the SDK API documentation	605
Appendix C: SDK release history	
Release 1.0.0 (20/Jan/2021)	
Release 1.0.1 (01/Feb/2021)	
Boot Stage 2	
Release 1.1.0 (05/Mar/2021)	
Backwards incompatibility	
Release 1.1.1 (01/Apr/2021)	
Release 1.1.2 (07/Apr/2021)	 . 608
Release 1.2.0 (03/Jun/2021)	 . 608
New/improved Board headers	 608
Updated TinyUSB to 0.10.1	 608
Added CMSIS core headers	
API improvements	
General code improvements	
SVD	
pioasm	
RTOS interoperability	
CMake build changes.	
Boot Stage 2	 . 611
Release 1.3.0 (02/Nov/2021)	 . 611
Updated TinyUSB to 0.12.0	 . 611
New Board Support	 . 612
Updated SVD, hardware_regs, hardware_structs	 612
Behavioural Changes	 613
Other Notable Improvements	
CMake build	
pioasm	
·	
elf2uf2	
Release 1.3.1 (18/May/2022)	
New Board Support	
Notable Library Changes/Improvements	 . 616
Build	 . 617
pioasm	 . 617
elf2uf2	 617
Release 1.4.0 (30/Jun/2022)	
New Board Support	
Wireless Support	
Notable Library Changes/Improvements	
Build	
Duliu	 . 020

Release 1.5.0 (11/Feb/2023) 620
New Board Support 620
Library Changes/Improvements 620
New Libraries
Build
Bluetooth Support for Pico W (BETA)
Release 1.5.1 (14/Jun/2023) 625
Board Support 625
Library Changes/Improvements 625
New Libraries
Miscellaneous. 627
Build
Bluetooth Support for Pico W
Release 2.0.0 (08/Aug/2024)
Notices
Major New Features 628
Security and Code Signing
Board Support 629
New Libraries
Library Changes / Improvements 633
pico_bt_stack
FreeRTOS integration 643
Backwards Incompatibilities
Build
Building Documentation
Fixed Issues
Appendix D: Documentation release history