
## **Problem 3 (6 Points)**

Let's revisit the initial speed vs. launch angle data from the logistic regression module. This time, you will train a decision tree classifier to predict whether a projectile launched with a given speed and angle will hit a target.

Run this cell to load the data and decision tree tools:

```
In [1]: import numpy as np
       import matplotlib.pyplot as plt
       from sklearn.tree import DecisionTreeClassifier, plot_tree
       from matplotlib.colors import ListedColormap
       x1 = np.array([0.02693745, 0.41186575, 0.10363585, 0.08489663, 0.09512868, 0.31121109,
       x2 = np.array([0.3501823, 0.10349458, 0.20137442, 0.37973165, 0.71062143, 0.25377085]
       X = np.vstack([x1, x2]).T
       def plot_data(X,y):
           colors=["blue","red"]
           labels = ["0 - Misses target", "1 - Hits target"]
           for i in range(2):
               plt.scatter(X[y==i,0],X[y==i,1],s=20,c=colors[i],edgecolors="black",linewidths
               plt.xlabel("Initial Speed")
               plt.ylabel("Launch Angle")
               plt.legend(loc="upper right",prop={'size':8})
               ax = plt.gca()
               ax.set_xticklabels([])
               ax.set_yticklabels([])
               plt.xlim([-0.55,.55])
               plt.ylim([-0.55,.55])
       plt.figure(figsize=(4,4),dpi=120)
       plot data(X,y)
       plt.show()
```




# Training a decision tree classifier.

Below, a decision tree of max depth 4 is trained, and the tree is visualized with plot\_tree().

```
In [2]: dt = DecisionTreeClassifier(max_depth=4)
    dt.fit(X,y)

plt.figure(figsize=(4,3),dpi=250)
    plot_tree(dt)
    plt.show()
```



#### Accuracy on training data

Compute the accuracy on the training data with the provided function <code>get\_dt\_accuracy(dt, X, y)</code> . Print the result.

```
In [3]: def get_dt_accuracy(dt, X, y):
    pred = dt.predict(X)
    return 100*np.sum(pred == y)/len(y)

# YOUR CODE GOES HERE
accuracy = get_dt_accuracy(dt,X,y)
print("Accuracy on the training data with the provided function is: ",accuracy,"%")
```

Accuracy on the training data with the provided function is: 87.6923076923077 %


#### Visualizing tree predictions

By evaluating the model on a meshgrid of results, we can look at how our model performs on the input space:

```
In [4]: vals = np.linspace(-.5,.5,100)
    x1grid, x2grid = np.meshgrid(vals, vals)
    X_test = np.vstack([x1grid.flatten(), x2grid.flatten()]).T

    pred = dt.predict(X_test)
```

```
plt.figure(figsize=(4,4),dpi=120)
bgcolors = ListedColormap(["powderblue","pink"])
plt.pcolormesh(x1grid, x2grid, pred.reshape(x1grid.shape), shading="nearest",cmap=bgcoplot_data(X,y)
plt.show()
```



### **Expanded feature set**

Now, we will add a third feature that (for this problem) happens to be very useful. That feature is  $x_1^2 + x_2^2$ . A new training input  $X_ex$  is generated below containing this additional feature.

Train a new decision tree, max depth 4, on this data. Then visualize the tree with plot\_tree().

```
In [5]:


def feature_expand(X):
    x1 = X[:,0].reshape(-1, 1)
    x2 = X[:,1].reshape(-1, 1)
    columns = [x1, x2, x1*x1 + x2*x2]
    return np.concatenate(columns, axis=1)

X_ex = feature_expand(X)

# YOUR CODE GOES HERE
# Train a new decision tree on X_ex, y
# Plot the tree

dt_new = DecisionTreeClassifier(max_depth = 4)
dt_new.fit(X_ex,y)
plt.figure(figsize=(4,3),dpi=250)
```

```
plot_tree(dt_new)
plt.show()
```



### Accuracy on training data: expanded features

Compute the accuracy of this new model its training data. It should have increased. Note that the useful features to expand will vary significantly from problem to problem.

```
In [6]: # YOUR CODE GOES HERE
accuracy = get_dt_accuracy(dt_new,X_ex,y)
print("Accuracy on the training data with the provided function is: ",accuracy,"%")
```


Accuracy on the training data with the provided function is: 94.61538461538461 %

## Visualizing expanded feature results

Use your model to make a prediction called <code>pred</code> on the data <code>X\_test\_ex</code>, an expanded meshgrid of points, as indicated. This code will plot the class decisions. Note the difference between this and the previous model, which only had speed and angle as features.

```
In [7]: X_test_ex = feature_expand(X_test)
# YOUR CODE GOES HERE
# Have your model make a prediction, `pred` on X_test_ex
pred = dt_new.predict(X_test_ex)
```

```
plt.figure(figsize=(4,4),dpi=120)
bgcolors = ListedColormap(["powderblue","pink"])
plt.pcolormesh(x1grid, x2grid, pred.reshape(x1grid.shape), shading="nearest",cmap=bgcoplot_data(X,y)
plt.show()
```



In [ ]: