Comprehensive Component List and Analysis of the 40KG Turbojet Engine

Date: September 11, 2025

Introduction

This document provides a full component list for the 40KG Turbojet Engine, compiled from provided documentation including price lists, manuals, and functional analyses. The list includes mechanical, structural, and auxiliary components.

The components are first presented in a tabular format mirroring the price list, with inferences for unnamed items based on labels and descriptions. Following the list is a detailed functional analysis of each component, grouped by engine stage, drawn from the anatomy documents.

Component List Table

The following table lists all identified components with their model (all 40KG) and unit (pc for piece). Unnamed items from the price list have been inferred based on image labels and descriptions.

NO.	Items	Model	Unit
1	Inlet runner	40KG	рс
2	Transit ring	40KG	рс
3	Cowling	40KG	рс
4	Bearing Pad	40KG	рс
5	Screw nut CW	40KG	рс
6	Screw nut TW	40KG	рс
7	Diffuser	40KG	рс
8	Billet wheel	40KG	рс
9	Turbine shaft	40KG	рс
10	Turbine wheel	40KG	рс
11	Turbine shaft Sleeve	40KG	рс
12	NGV+ Evaporator	40KG	рс
13	NGV with Protecting Layer (inferred)	40KG	рс
14	Starter Connector	40KG	рс
15	Evaporator Component (inferred)	40KG	рс
16	Cartridge receiver	40KG	рс
17	Combustion Chamber in	40KG	рс
18	Combustion Chamber out	40KG	рс
19	Oil ring	40KG	рс
20	Oil pipe	40KG	рс
21	Clamp	40KG	рс

Additional components identified from manuals and guides:

- **ECU (Engine Control Unit):** Controls startup, monitoring, and fuel delivery. It manages the engine's operation from start to shutdown, ensuring optimal performance and safety. This advanced control system is built around a sophisticated 32-bit microprocessor architecture.
- **GSU (Ground Support Unit):** Interface for monitoring and configuring the ECU. It provides real-time data and access to configuration menus for engine parameters. The GSU features a ruggedized color LCD display for visibility in direct sunlight.
- **Starter Motor:** Spins the shaft during startup. This electric motor initiates engine rotation until self-sustaining combustion is achieved. It safely and reliably transmits electrical power to the engine's internal mechanism.
- **Glow Plug:** Ignites the fuel-air mixture during startup. It heats up to provide the initial ignition for combustion. This ensures a continuous and stable flame within the combustion chamber.
- **Fuel Pump:** Delivers fuel based on ECU commands. It precisely controls fuel flow to the combustion chamber. This ensures optimal air-fuel ratios across all power settings.
- **Fuel Injectors:** Spray a fine, atomized mist of fuel into the combustion chamber, allowing it to mix thoroughly with compressed air. This process promotes efficient and stable combustion. They are crucial for the engine's heat-addition process.
- **Sensors (e.g., RPM, EGT):** Monitor RPM, EGT, etc., for safe operation. They provide critical real-time data to the ECU for engine protection. These sensors are vital for continuous analysis of engine parameters.
- **LiPo Battery:** Provides power to the engine's systems and the receiver. It is essential for the operation of the ECU and other electrical components. This battery ensures the engine's electrical systems function correctly.
- Radio Receiver: Receives throttle commands from the radio control system. It translates user input into signals for the ECU. This component enables remote control of the engine's thrust.
- **Fuel Shut-off Valve:** Controls the flow of fuel to the engine. It is a safety mechanism to cut off fuel supply when needed. This valve ensures immediate fuel cut-off in emergency situations.

- **Fuel Lines:** Transport fuel from the tank to the engine components. They ensure a continuous and clean supply of fuel. These lines are designed to withstand various operational conditions.
- **Exhaust Nozzle:** Accelerates exhaust gases to produce thrust. It is the final stage where hot gases are expelled at high velocity. This high-velocity jet of gas creates the forward push for the engine.

Functional Analysis of Components

The following sections provide a detailed functional analysis of the key components, organized by engine stage. This is based on the provided anatomy documents.

Air Intake and Compression Stage Components

The strategic importance of the intake and compression stage cannot be overstated. This initial phase of the Brayton cycle is where the engine captures ambient air and dramatically increases its pressure, preparing it for a combustion process that will generate exhaust gas temperatures of up to 1000°C. The efficiency of this stage directly impacts the overall performance and thrust output of the entire engine.

Inlet Runner

The Inlet Runner serves as the engine's primary interface with the surrounding atmosphere, functioning as a carefully designed subsonic diffuser. Its critical role is to capture ambient air and guide it smoothly into the compressor section. The component's aerodynamic design is crucial for slowing the incoming airflow and converting its kinetic energy into static pressure with minimal turbulence. This action maximizes pressure recovery and ensures a stable, uniform flow of air enters the compressor, which is a foundational requirement for the engine's efficient operation.

Billet Wheel

The Billet Wheel is the main impeller of the engine's centrifugal compressor. The term "billet" signifies that it is machined from a solid block of high-strength material, a manufacturing process that ensures exceptional precision, strength, and durability against immense rotational forces. Driven by the turbine shaft at extremely high speeds, the impeller's blades accelerate the incoming air and fling it radially outwards.

This action imparts significant kinetic energy to the air, preparing it for the final step of the compression process.

Diffuser

Working in tandem with the Billet Wheel, the Diffuser is a stationary component that receives the high-velocity air exiting the impeller. Its function is to slow this airflow down in a controlled manner. As the air decelerates within the Diffuser's carefully shaped passages, its kinetic energy is converted into high static pressure. This action completes the compression stage, delivering a stable supply of high-pressure air to the next section of the engine. This pressurized air is now ready to be mixed with fuel for combustion.

Combustion Stage Components

Following compression, the high-pressure air enters the combustion stage. This is the heart of the engine's heat-addition process, where the chemical potential energy of fuel is converted into immense thermal energy. By mixing atomized fuel with the compressed air and igniting it, this stage dramatically increases the temperature and volume of the gas flow, creating the high-energy stream needed to power the turbine.

Combustion Chamber (In/Out)

The Combustion Chamber is the contained space where the thermodynamic magic happens. It is designed to mix compressed air with atomized fuel and sustain a continuous, stable flame. The "Combustion Chamber In" and "Combustion Chamber Out" designations refer to the inlet and outlet sections of this critical assembly. The entire structure must be engineered to withstand extreme temperatures while ensuring complete and efficient combustion, providing a uniform flow of hot gas to the turbine section.

NGV + Evaporator

The NGV + Evaporator is a sophisticated, dual-function assembly located immediately downstream of the combustion chamber.

• NGV (Nozzle Guide Vanes): The NGVs are a set of stationary, airfoil-shaped blades that direct the hot, high-pressure gas exiting the combustor. Their primary function is to guide this energetic gas stream onto the blades of the rotating

Turbine Wheel at the optimal angle and velocity. This precise guidance is essential for efficiently extracting energy from the gas flow in the next stage.

• **Evaporator:** Based on its nomenclature and common design practices in smaller turbines, the Evaporator's function is inferred to be part of the fuel delivery system, likely a series of tubes or passages that use heat from the NGV assembly to vaporize fuel prior to injection, promoting more efficient and stable combustion.

This high-energy gas, now properly conditioned by the NGVs, flows directly into the turbine section, where its power is harnessed to sustain the engine's operation.

Turbine and Power Extraction Stage Components

The turbine stage is where the engine becomes a self-sustaining system. This section is designed to extract a portion of the energy from the hot, high-velocity gas stream flowing from the combustor. It expertly converts the gas's thermal and kinetic energy into the mechanical power required to spin the compressor at the front of the engine, thus perpetuating the entire cycle.

Turbine Wheel

The Turbine Wheel is the rotating assembly of blades that is struck by the high-velocity gas exiting the Nozzle Guide Vanes. Its sole purpose is to extract kinetic and thermal energy from this gas stream, converting it into rotational energy. This component operates under the most extreme temperature and stress conditions found anywhere in the engine and must be manufactured from advanced superalloys to survive. The power it generates is the engine's lifeblood, driving all other rotating components.

Turbine Shaft

The Turbine Shaft is the critical mechanical link that connects the Turbine Wheel at the hot end of the engine to the Billet Wheel (compressor) at the cold end. Its singular function is to transmit the immense rotational power generated by the turbine to drive the compressor. This direct power transmission is what sustains the engine's operating cycle, allowing it to continuously draw in and compress air.

Turbine Shaft Sleeve

The Turbine Shaft Sleeve is a precision component that fits over the main Turbine Shaft. It serves as a protective covering, a precision bearing surface, or an additional structural support. Its importance lies in ensuring the main shaft can rotate smoothly and stably at extreme speeds, reducing wear, maintaining critical alignment, and contributing to the overall longevity and reliability of the engine's core rotating assembly. While this rotating group forms the thermodynamic heart of the engine, its stability and integrity depend entirely on the static structural components that house and align it.

Core Structural and Assembly Components

While the rotating and thermodynamic components perform the engine's primary work, the structural framework and fasteners provide the physical integrity, precise alignment, and resilience necessary for operation. These parts are the skeleton and connective tissue that must withstand immense operational forces, vibrations, and thermal expansion to ensure the engine functions as a cohesive unit.

Cowling

The Cowling is the outer casing of the engine. It serves a dual purpose: first, it provides a protective enclosure for the delicate internal components, shielding them from external elements. Second, and just as importantly, it forms the aerodynamic flow path for the air passing through the engine, ensuring a smooth and efficient transit from the inlet to the exhaust nozzle.

Transit Ring

The Transit Ring is a structural component designed to connect two major sections of the engine, such as the compressor section and the combustion section. Its role is to ensure a rigid, secure, and perfectly aligned transition between these critical modules, maintaining the structural integrity of the engine assembly under all operating loads.

Cartridge Receiver

The Cartridge Receiver is a precision-machined housing designed to accept a major sub-assembly or "cartridge." This cartridge is likely the entire balanced rotating group, consisting of the compressor, shaft, turbine, and bearing assembly. The receiver's critical function is to hold this core assembly in perfect alignment within the engine's outer casings, which is paramount for smooth, vibration-free operation at high RPMs.

Bearing Pad

The Bearing Pad is a key element of the bearing system that supports the main rotating shaft. Its detailed role is to absorb and manage the immense axial and radial loads generated by the rotating assembly. By reducing friction and ensuring the shaft can spin with stability at tens of thousands of RPMs, the bearing pad is essential for the engine's reliability and long service life.

Fasteners

Specialized fasteners are used to secure the most critical components, designed to resist loosening under extreme vibration and rotational forces.

- **Screw Nut CW / TW:** Secures the Billet Wheel and Turbine Wheel to the shaft. The specific threading direction (e.g., Clockwise) is engineered to oppose the engine's rotational forces, creating a self-tightening effect that is vital for preventing the nut from loosening at extreme RPMs.
- **Clamp:** Provides a secure fastening mechanism for hoses (e.g., oil and fuel pipes) or engine casing joints, preventing leaks and ensuring structural integrity under vibration and pressure.

Auxiliary and Support System Components

The components of the auxiliary systems are not part of the engine's primary airflow path, yet they are indispensable. These systems are responsible for initiating the engine cycle, managing lubrication for high-speed moving parts, and ensuring the long-term health and reliability of the entire machine.

Starter Connector

The Starter Connector is the electrical interface that connects the external starter motor to the engine's internal mechanism. Its purpose is to safely and reliably transmit the electrical power needed to spin the engine's main shaft during the startup sequence. The starter motor rotates the engine until it reaches a self-sustaining speed, at which point the combustion process can take over and the starter disengages.

Lubrication System Components

The lubrication system is vital for reducing friction and dissipating heat in the engine's bearings, which support the main shaft spinning at extreme speeds.

- Oil Pipe: This is the conduit responsible for transporting specialized turbine oil
 from a reservoir to the engine's high-speed bearings and other critical moving
 parts. It ensures a constant supply of lubricant to prevent wear and thermal
 damage.
- **Oil Ring:** This component functions as a seal within the bearing and lubrication system. It is precisely designed to direct the flow of lubricating oil onto critical surfaces while simultaneously preventing that oil from leaking into the main airflow path, which could compromise combustion and engine performance.

Additional Components from Manuals

The following components are mentioned in operational manuals and guides as essential for engine operation:

- **ECU (Engine Control Unit):** Controls startup, monitoring, and fuel delivery. It manages the engine's operation from start to shutdown, ensuring optimal performance and safety. This advanced control system is built around a sophisticated 32-bit microprocessor architecture.
- **GSU (Ground Support Unit):** Interface for monitoring and configuring the ECU. It provides real-time data and access to configuration menus for engine parameters. The GSU features a ruggedized color LCD display for visibility in direct sunlight.
- **Starter Motor:** Spins the shaft during startup. This electric motor initiates engine rotation until self-sustaining combustion is achieved. It safely and reliably transmits electrical power to the engine's internal mechanism.
- **Glow Plug:** Ignites the fuel-air mixture during startup. It heats up to provide the initial ignition for combustion. This ensures a continuous and stable flame within the combustion chamber.
- **Fuel Pump:** Delivers fuel based on ECU commands. It precisely controls fuel flow to the combustion chamber. This ensures optimal air-fuel ratios across all power settings.

- **Fuel Injectors:** Spray a fine, atomized mist of fuel into the combustion chamber, allowing it to mix thoroughly with compressed air. This process promotes efficient and stable combustion. They are crucial for the engine's heat-addition process.
- **Sensors (e.g., RPM, EGT):** Monitor RPM, EGT, etc., for safe operation. They provide critical real-time data to the ECU for engine protection. These sensors are vital for continuous analysis of engine parameters.
- **LiPo Battery:** Provides power to the engine's systems and the receiver. It is essential for the operation of the ECU and other electrical components. This battery ensures the engine's electrical systems function correctly.
- Radio Receiver: Receives throttle commands from the radio control system. It translates user input into signals for the ECU. This component enables remote control of the engine's thrust.
- **Fuel Shut-off Valve:** Controls the flow of fuel to the engine. It is a safety mechanism to cut off fuel supply when needed. This valve ensures immediate fuel cut-off in emergency situations.
- **Fuel Lines:** Transport fuel from the tank to the engine components. They ensure a continuous and clean supply of fuel. These lines are designed to withstand various operational conditions.
- **Exhaust Nozzle:** Accelerates exhaust gases to produce thrust. It is the final stage where hot gases are expelled at high velocity. This high-velocity jet of gas creates the forward push for the engine.