

⇒ Condition based on a list (IN)

- If a list of values are specified, the IN operator is used to select a value that matches any values in the list.
- Select name, rollno from studentv where name IN (55, 75, 67);
- Select name, rollno from studentv where place IN ("Delhi", "Goa", "Mumbai");
- Select * from employee where state not in ("Delhi", "Mumbai", "UP");

NULL

28/8/26 - 28/8/26

- Null means a value that is unavailable, unassigned, unknown or inapplicable.
- It is searched for by using the keyword IS NULL.
- NULL is not the same as zero or a space or any other character.
- In a table null is searched for using IS NULL keyword.
- If any column value involved in an arithmetic expression is NULL, the result of the expression is also Null.

Example:-

- select * from student where name is NULL;
- select * from employee where Commission is NOT NULL;

Update Statement

- It is used to modify the existing data in the table.
- The syntax is:
UPDATE table name Set field 1 = value 1, field 2 = value 2
Where Condition

Eg: - 1. Update table stu set S.NO = 10, Name = Anju where
marker = 78;

2. update student SET marker = 90 where name = "abc";

DELETE STATEMENT

- Used to DELETE one or more rows from a table.
- It removes the entire row.
- The syntax is

DELETE FROM tablename WHERE Condition;

Example:

- Delete from Emp where Empno = 100;
 - To remove all the rows of the table use, DELETE from Emp;
- Delete from Emp;

SORTING THE RESULTS - "ORDER BY"

- ORDER BY is used to display the results of the Select Statement in ascending or descending values.
- The syntax is:
- select < column > where < Condition list > order by < column >

eg: Select * from student order by name;

To Display in descending order;

Select * from student order by name DESC;