

Script: backup.sh

How the script works

- Creates a **backup/** directory if it doesn't exist.
- Finds all **.txt** files in the current folder.
- Copies each **.txt** file into **backup/**, appending a timestamp to the filename.

Example Run

```
$ echo "Hello" > file1.txt
$ echo "World" > file2.txt
$ ./backup.sh
$ ls backup/
file1_20250913_162530.txt  file2_20250913_162530.txt
```

```
[vaibhavkumar@VAIBHAVs-MacBook-Air scripts % nano backup1.sh
[vaibhavkumar@VAIBHAVs-MacBook-Air scripts % chmod 777 backup1.sh
[vaibhavkumar@VAIBHAVs-MacBook-Air scripts % echo "Test file A" > file1.txt
[vaibhavkumar@VAIBHAVs-MacBook-Air scripts % echo "Test file B" > file2.txt
[vaibhavkumar@VAIBHAVs-MacBook-Air scripts % ./backup1.sh
✅ Backup complete. Files saved in 'backup/' with timestamp.
vaibhavkumar@VAIBHAVs-MacBook-Air scripts % █
```

Extra Questions

1. What is the difference between **cp**, **mv**, and **rsync**?

- **cp**: Copies files or directories.
- **mv**: Moves (renames) files or directories.
- **rsync**: Synchronizes files/directories, efficient for backups and remote transfers.

2. How can you schedule scripts to run automatically?

- Use **cron** jobs (with **crontab -e**) to schedule scripts at specific times.