

```
#!/bin/bash
```

filepath: Scripts/starter_kit.sh

Create folders

```
mkdir -p project/scripts mkdir -p project/docs mkdir -p project/data
```

Add placeholder README.md in each folder

```
echo "# Scripts" > project/scripts/README.md echo "# Docs" > project/docs/README.md echo "# Data" > project/data/README.md
```

Print completion message

```
echo "Starter Kit Ready!"
```

LAB_extra.md

Purpose of script

The script automates the creation of a standard project folder structure with placeholder README.md files in each subfolder.

Example Run

```
Last login: Thu Sep 11 19:21:54 on ttys001
vaibhavkumar@VAIBHAVs-MacBook-Air ~ % touch starter_kit.sh
vaibhavkumar@VAIBHAVs-MacBook-Air ~ % nano starter_kit.sh
vaibhavkumar@VAIBHAVs-MacBook-Air ~ % chmod 777 starter_kit.sh
vaibhavkumar@VAIBHAVs-MacBook-Air ~ % ./starter_kit.sh
✅ Starter Kit Ready!
vaibhavkumar@VAIBHAVs-MacBook-Air ~ % █
```

Extra Questions

1. What does **mkdir -p** do?

It creates the specified directory and any necessary parent directories. If the directory already exists, it does nothing and does not show an error.

2. Why is automation useful in DevOps?

Automation saves time, reduces human error, ensures consistency, and speeds up repetitive tasks such as environment setup, deployment, and testing.