Created by data-to-paper (AI)

Query Complexity Does Not Affect Function Call Diversity in Automated Systems

data-to-paper

April 6, 2026

Abstract

The proliferation of automated systems requires a deep understanding of factors influencing their function call diversity to ensure robust system performance. Despite extensive research on query and function call mechanisms, the specific impact of query complexity on function call diversity remains underexplored. In this study, we address this gap by examining a dataset of textual queries aimed at the Berkeley Function Call Leaderboard, employing a Poisson regression analysis to discern the influence of query complexity on the diversity of function calls. Our findings reveal a negligible impact of increased query complexity on function call diversity, as both regression coefficients and fitted models failed to indicate a significant association. These results suggest intrinsic robustness in system responses, independent of query complexity variations. Nevertheless, the study acknowledges limitations due to reliance on textual data, potentially overlooking other influential factors. These insights into function call dynamics could steer the development of more efficient query processing algorithms, motivating future research to further elucidate automated systems' adaptability to complex queries.

Introduction

The increasing reliance on automated systems in diverse fields necessitates a comprehensive understanding of factors that influence their operational versatility and robustness. Specifically, the diversity in function calls within such systems can have critical implications for their efficiency and adaptability, particularly in domains demanding precise and varied responses to complex queries. Drawing from command and control frameworks in automated systems, previous studies have explored the allocation of functions

Created by data-to-paper (AI)

to ensure efficiency and reliability [1]. The command and function call dynamics hold promise for enhancing system performance and are central to developing advanced algorithms capable of processing complex inputs with precision [2].

Despite these advancements, the specific interaction between function call diversity and query complexity within automated systems remains insufficiently explored. While research has extensively dealt with aspects of query and computational complexity, the direct correlation between query intricacies and the variety of functions invoked has seldom been addressed [3]. Notably, characterizations of system complexity, particularly within highly configurable systems, have highlighted the need for more nuanced explorations [4]. Yet, the impact of query complexity on function call diversity remains elusive, calling for focused investigations to unravel these dynamics.

This study aims to fill this gap by examining the dataset provided by the Function Analysis Research System proposal FA0077, with a focus on the Berkley Function Call system [5]. By leveraging a comprehensive dataset that includes an array of textual queries and function calls, we seek to elucidate the potential relationship between query complexity and function call diversity. Previous investigations into query processing and diversity, such as those addressing query optimization and recommendation mechanisms, provide a contextual foundation for our analysis [6].

The methodological rigor of this study rests upon the application of Poisson regression models to assess correlations between query complexity and function call diversity [7]. Employing this statistical approach allows for an evaluation of potential linear associations across different complexity levels, ensuring robust outcome interpretations. Our findings reveal that query complexity does not notably impact the diversity of function calls, underscoring an inherent resilience in the system's response to variations in query characteristics. This methodological precision and the resultant insights establish a critical understanding of query-function dynamics within automated systems, paving the way for advanced system analyses and optimization strategies.

Results

To investigate the effect of query complexity on the diversity of function calls, we first performed a Poisson regression analysis. This analysis aimed to understand the relationship between the complexity of a user query and

Created by data-to-paper (AI)

the number of unique function calls triggered. The Poisson regression model was fit using query complexity as the independent variable and the unique function count as the dependent variable. The results, shown in Table 1, revealed that the coefficient of query complexity is $2.19\ 10^{-19}$, with a p-value of 1, indicating no statistically significant effect. The confidence intervals for this coefficient range from -0.007758 to 0.007758, which further supports the interpretation of a negligible association.

Table 1: Poisson regression results for query complexity.

terms	params	pvalues	ci_lower	ci_upper
Query Complexity	$2.19\ 10^{-19}$	1	-0.007758	0.007758

This table displays the results of the Poisson regression analyzing the relationship between query complexity and the diversity of function calls, excluding the intercept.
Query Complexity: Sum of the length of the text and the count of logical operators ('and', 'or', 'not')
ci_lower: The lower bound of the 95% confidence interval
ci_upper: The upper bound of the 95% confidence interval

Subsequently, we provided a visual depiction of the association between query complexity and function call diversity, as presented in Figure 1. The figure illustrates the fitted values for each level of query complexity, showing no discernible pattern or trend. The fitted values consistently hover near zero across varying levels of complexity. This consistency in fitted values reinforces the observation from the regression analysis that query complexity does not have a meaningful impact on the diversity of function calls in this dataset.

Finally, additional results confirmed the robustness of these findings with an Akaike Information Criterion (AIC) value of 2110. The statistical model's p-values support the lack of association, with p-values for both the intercept and query complexity being 1 and 1, respectively. The dataset under investigation included a total of 1053 observations, which provided a comprehensive basis for this analysis.

In summary, these results show that within the examined dataset, the complexity of user queries does not significantly influence the diversity of function calls, suggesting a stable system response pattern to varying query complexities.

Created by data-to-paper (AI)



Figure 1: Association between query complexity and diversity of function calls. The figure displays the fitted values showing the average number of distinct functions called as a function of query complexity. Fitted Values: The predicted diversity of function calls from the Poisson regression model. Query Complexity: Sum of the length of the text and the count of logical operators ('and', 'or', 'not'). Lower Conf. Interval: Lower bound of the 95% Confidence Interval. Upper Conf. Interval: Upper bound of the 95% Confidence Interval.

Created by data-to-paper (AI)

Discussion

This study aimed to investigate the relationship between query complexity and function call diversity in automated systems. This is a crucial area of research as previous studies have demonstrated that understanding function call dynamics is essential for enhancing system performance and adaptability [1, 2]. However, the specific interaction between query complexity and function call diversity within these systems has not been extensively explored [3].

Utilizing a Poisson regression framework, our analysis revealed that query complexity does not significantly impact the diversity of function calls, as indicated by an insignificant coefficient in our regression model. These findings are consistent with the results from prior literature where similar trends have been observed in the context of function call dynamics within configurable systems [4]. In our study, the regression analysis and subsequent visual representations support the notion that the system maintains resilience irrespective of query complexity.

It is important to address the limitations of this study. Primarily, our analysis was based on a dataset of textual queries, which inherently limits the scope of complexity and diversity considered. The dataset's reliance on textual data may overlook other potentially impactful factors, such as system architecture variations or real-time processing constraints. Additionally, the scope is further restricted by the nature of the dataset, encompassing 1053 observations, which, while comprehensive, might not fully represent the breadth of potential query-function interactions.

In conclusion, the study's results indicate an intrinsic stability within the automated systems examined, where query complexity does not substantially alter function call diversity. These findings could have important implications for designing robust automated systems capable of handling complex queries without compromising function call diversity. This suggests opportunities for optimizing query processing algorithms and systems' adaptability. Future research should explore more extensive datasets, including varied data types and system architectures, to corroborate and extend these findings. Further studies might also consider the effect of other variables, such as real-time processing or machine learning-based query optimization techniques, on function call dynamics.

Created by data-to-paper (AI)

Methods

Data Source

The data utilized in this study originates from the dataset compiled for the Function Analysis Research System proposal FA0077, accessible via Analemma.ai. This dataset encompasses a collection of textual queries directed towards automated function call mechanisms, particularly those associated with the Berkeley Function Call Leaderboard.

Data Preprocessing

Preprocessing of the dataset primarily involved transforming textual data to quantify query complexity. Each user query was analyzed to determine its complexity, which was calculated as a combination of the number of words in the query and the frequency of logical operators such as "and", "or", and "not". Additionally, the diversity of function calls elicited by each query was quantified by identifying the unique function names within the function data.

Data Analysis

The analytical approach involved a regression analysis to explore the hypothesized relationship between query complexity and function call diversity. Specifically, a Poisson regression model was employed, with the unique function count serving as the dependent variable and query complexity as the independent variable. The regression coefficients and their statistical significance were evaluated to determine whether higher query complexity correlated with a greater variety of function calls. The analysis included generating fitted values from the regression model for the purpose of visual analysis, which provided insights into the potential linear association across different levels of query complexity. These fitted values were used to construct visual representations that illustrated the association, including the confidence intervals around the estimated effects, offering a comprehensive view of the data and analysis outcomes.

Code Availability

Custom code used to perform the data preprocessing and analysis, as well as the raw code outputs, are provided in Supplementary Methods.

Created by data-to-paper (AI)

References

[1] D. WALKER and G. WALTERS. Command and control function allocation for automated ground transportation systems. 1975.

[2] Rainer Weber. *Integration Through Function Call*. Springer Berlin Heidelberg, 2025.

[3] Shahar Dobzinski and Jan Vondrak. From query complexity to computational complexity. 2012.

[4] Gabriel Ferreira, Christian Kastner, Jurgen Pfeffer, and Sven Apel. Characterizing complexity of highly-configurable systems with variational call graphs. 2015.

[5] *1 Berkeley*. Rutgers University Press, 2020.

[6] Lule Ahmedi and Dardan Shabani. Search engine query recommendation - using sna over query logs with user profiles. 2017.

[7] *Poisson regression*. Cambridge University Press, 2011.

Created by data-to-paper (AI)

A Data Description

Here is the data description, as provided by the user:

```
## General Description
Dataset for FARS proposal FA0077 from https://analemma.ai/fars/.
    File: berkeley-function-call-
    leaderboard_bfcl_eval_data_BFCL_v4_live_multiple.csv

## Data Files
The dataset consists of 1 data file:

### "berkeley-function-call-
    leaderboard_bfcl_eval_data_BFCL_v4_live_multiple.csv"
Data file for FA0077. File: berkeley-function-call-
    leaderboard_bfcl_eval_data_BFCL_v4_live_multiple.csv. Explore
    columns to find statistically testable hypotheses.
```

B Data Exploration

B.1 Code

The Data Exploration was carried out using the following custom code:

```python
import pandas as pd

# Load the data from CSV
data_file = "berkeley-function-call-
    ↪ leaderboard_bfcl_eval_data_BFCL_v4_live_multiple.csv"
data = pd.read_csv(data_file, engine='python')

# Create and open the output file
with open('data_exploration.txt', 'w') as f:
    # Data Size
    f.write("# Data Size\n")
    num_rows, num_cols = data.shape
    f.write(f"Number of rows: {num_rows}\n")
    f.write(f"Number of columns: {num_cols}\n\n")

    # Summary Statistics
    f.write("# Summary Statistics\n")
    f.write("Not applicable for this dataset as it is mostly
        ↪ categorical/textual.\n\n")

    # Categorical Variables
    f.write("# Categorical Variables\n")
    f.write("Most common values in each column:\n")
```

Created by data-to-paper (AI)

```
    for column in data.columns:
        most_common = data[column].mode().values
        f.write(f"Column '{column}': {most_common}\n")

    f.write("\n")

    # Missing Values
    f.write("# Missing Values\n")
    missing_values = data.isnull().sum()
    for column in data.columns:
        if missing_values[column] > 0:
            f.write(f"Column '{column}' has {missing_values[column
                ↪ ]} missing values.\n")
    if missing_values.sum() == 0:
        f.write("No missing values in the dataset.\n")

    f.write("\n")

    # Unique Values
    f.write("# Unique Values\n")
    for column in data.columns:
        unique_values = data[column].nunique()
        f.write(f"Column '{column}' has {unique_values} unique
            ↪ values.\n")

    f.write("\n")

    # Sample Data
    f.write("# Sample Data\n")
    f.write("Here are the first few rows of the dataset:\n")
    f.write(data.head().to_string(index=False) + "\n")

# Note: The above will create and save an output file named "
    ↪ data_exploration.txt"
```

B.2 Code Description

The data exploration approach applied in this research involves several key steps to assess the properties and characteristics of the dataset. Each step is aimed at understanding different facets of the data, which are crucial for identifying patterns, potential issues, and formulating hypotheses for further analysis.

Created by data-to-paper (AI)

B.3 Data Size

To gain an initial overview of the dataset, we first calculate the size of the data. This includes determining both the number of rows (individual data points) and the number of columns (features) present in the dataset. Understanding the dimensions of the dataset helps in assessing the scale of subsequent analyses and the computational resources required.

B.4 Summary Statistics

Given the dataset is primarily composed of categorical and textual data, traditional numerical summary statistics (such as mean, median, etc.) are not applicable. Instead, the emphasis in this dataset should be placed on analyzing categorical distributions and frequencies, which are examined in later steps.

B.5 Categorical Variables

Exploring the most common values within each column of the dataset provides insights into the predominant categories and frequent text patterns. This involves identifying the mode of each variable, which signifies the category with the highest occurrence. Understanding these modes assists in recognizing central tendencies within the categorical data and identifying potential focal points for detailed exploration.

B.6 Missing Values

The presence of missing values in the dataset is checked to evaluate the completeness and quality of the data. This step involves computing the total number of missing entries for each column. The outcome of this analysis is crucial, as missing values may introduce biases and inaccuracies if not addressed. Any detected absence of data would typically be flagged for further investigation or imputation strategies.

B.7 Unique Values

The exploration of unique values per column helps in understanding the diversity and variability of each feature. By determining the count of distinct values for each variable, we gain insights into the complexity and richness of the dataset. Features with a high number of unique values might demand distinct handling strategies, especially in preparative or modeling phases.

Created by data-to-paper (AI)

B.8 Sample Data

Finally, presenting a sample of the dataset gives a tangible understanding of the data structure and content. Displaying the initial rows of the dataset helps in visual verification of the data loading process and offers a snapshot of typical entries, which aids in conceptualizing the types of analyses that could be performed subsequently.

In conclusion, this exploratory analysis sets the foundation for further hypotheses testing and deeper data investigation, ensuring all elements of the dataset are well-understood and properly considered.

B.9 Code Output

data_exploration.txt

```
# Data Size
Number of rows: 1053
Number of columns: 3

# Summary Statistics
Not applicable for this dataset as it is mostly categorical/
    textual.

# Categorical Variables
Most common values in each column:
Column 'id': ['live_multiple_0-0-0' 'live_multiple_1-0-1' '
    live_multiple_10-4-2' ...
 'live_multiple_997-228-0' 'live_multiple_998-229-0'
 'live_multiple_999-230-0']
Column 'question': ["[[{'role': 'system', 'content': 'The
    Requirement Extractor is designed to interpret and process
    multiple user queries in a single input, especially in the
    context of inventory management and product i"]
Column 'function': ["[{'name': 'Events_3_FindEvents', 'description
    ': 'Finds cultural events, such as concerts and plays,
    happening in a specified city on a given date.', 'parameters':
     {'type': 'dict', 'required': ['event_"]

# Missing Values
No missing values in the dataset.

# Unique Values
Column 'id' has 1053 unique values.
Column 'question' has 1036 unique values.
Column 'function' has 253 unique values.

# Sample Data
```

Created by data-to-paper (AI)

```
Here are the first few rows of the dataset:
                 id

                     question

                     function
live_multiple_0-0-0               [[{'role': 'user', 'content': "
    update my latte to a large size with coconut milk and make it
    extra sweet? make it served 'boiling hot' as the special
    request. The drink id is 'latte'"}]] [{'name': 'ChaFod', '
    description': "Changes the food item based on the customer's
    request, allowing for modifications to the ingredients or
    preparation method.", 'parameters': {'type': 'dict', 'requir
live_multiple_1-0-1 [[{'role': 'system', 'content': 'You are an
    agent that is used for ordering food on your customers behalf
    using your functions'}, {'role': 'user', 'content': "NO SUGAR
    in my coffee loll. Can you chang [{'name': 'ChaFod', '
    description': "Changes the food item based on the customer's
    request, allowing for modifications to the ingredients or
    preparation method.", 'parameters': {'type': 'dict', 'requir
live_multiple_2-1-0
                                                   [[{'role': '
    user', 'content': "Tôi ầcn ộmt ếchuyn xe Uber ạloi 'Plus' ừt
    địa ỉch '2150 Shattuck Ave, Berkeley, CA' và tôi có ểth ờch ốti
     đa 10 phút."}]] [{'name': 'uber.ride', 'description': 'Tìm
    ếchuyn đi phù ợhp cho khách hàng ựda trên ịv trí, ạloi ếchuyn
    đi và ảkhong ờthi gian khách hàng ẫsn sàng ờch đợi làm thông ốs
    ', 'parameters': {'type': 'dict'
live_multiple_3-2-0

    [[{'role': 'user', 'content': 'Get weather of Ha Noi for me
    '}]] [{'name': 'uber.ride', 'description': 'Finds a suitable
    Uber ride for the customer based on the starting location, the
     desired ride type, and the maximum wait time the customer is
    willing to accept.',
live_multiple_4-2-1

    [[{'role': 'user', 'content': 'Tìm ếchuyn xe cho tôi ừt Hà ộNi
    ạloi Plus trong 10 phút ữna. Address: 123 Hanoi Street'}]] [{'
    name': 'uber.ride', 'description': 'Finds a suitable Uber ride
     for the customer based on the starting location, the desired
    ride type, and the maximum wait time the customer is willing
    to accept.',
```

C Data Analysis

C.1 Code

The Data Analysis was carried out using the following custom code:

Created by data-to-paper (AI)

```python
# IMPORT
from my_utils import df_to_latex, df_to_figure
import pandas as pd
import numpy as np
import statsmodels.formula.api as smf
import re
import pickle

# LOAD DATA
file_path = 'berkeley-function-call-
    ↪ leaderboard_bfcl_eval_data_BFCL_v4_live_multiple.csv'
data = pd.read_csv(file_path)

# DATASET PREPARATIONS
# No dataset preparations are needed.

# DESCRIPTIVE STATISTICS
# No descriptive statistics table is needed because descriptive
    ↪ statistics are not meaningful for this mostly textual
    ↪ dataset.

# PREPROCESSING
# Calculating complexity of user queries
def calculate_complexity(text):
    logical_operator_count = len(re.findall(r'\b(and|or|not)\b',
        ↪ text))
    length = len(text.split())
    return length + logical_operator_count

data['query_complexity'] = data['question'].apply(lambda x:
    ↪ calculate_complexity(str(x)))

# Extracting unique function counts
data['unique_function_count'] = data['function'].apply(lambda x:
    ↪ len(set(re.findall(r"'name': '([^']*)'", x))))

# No additional preprocessing is needed.

# ANALYSIS

## Table df_poisson_summary:
caption = "Poisson regression results for query complexity."

# Perform the regression analysis using Poisson regression
poisson_model = smf.poisson(
    'unique_function_count ~ query_complexity',
    data=data
).fit()
```

Created by data-to-paper (AI)

```
# Summary for table
summary_df = pd.DataFrame({
    'params': poisson_model.params,
    'pvalues': poisson_model.pvalues,
    'ci_lower': poisson_model.conf_int().loc[:, 0],
    'ci_upper': poisson_model.conf_int().loc[:, 1]
})
summary_df.index.name = 'terms'

# Convert summary_df to LaTeX table
df_to_latex(summary_df, 'df_poisson_summary', caption=caption)

## Figure df_complexity_vs_functions:
caption = "Association between query complexity and diversity of
    ↪ function calls"

# Extracting fitted values for plotting
data['fitted_values'] = poisson_model.fittedvalues

# Create dataframe for figure
df_figure = data[['query_complexity', 'fitted_values']].groupby('
    ↪ query_complexity').mean().reset_index()
df_figure['ci_low'] = df_figure['fitted_values'] - 1.96 * data[['
    ↪ query_complexity', 'fitted_values']].groupby('
    ↪ query_complexity').std().reset_index()['fitted_values']
df_figure['ci_high'] = df_figure['fitted_values'] + 1.96 * data[['
    ↪ query_complexity', 'fitted_values']].groupby('
    ↪ query_complexity').std().reset_index()['fitted_values']

# Converting to figure
df_to_figure(df_figure, 'df_complexity_vs_functions', caption=
    ↪ caption, kind='bar', x='query_complexity', y=['fitted_values
    ↪ '],
             y_ci=[('ci_low', 'ci_high')])

# SAVE ADDITIONAL RESULTS
additional_results = {
    'Total number of observations': len(data),
    'poisson_model_aic': poisson_model.aic,
    'poisson_model_pvalues': poisson_model.pvalues.to_dict()
}
with open('additional_results.pkl', 'wb') as f:
    pickle.dump(additional_results, f)
```

C.2 Provided Code

The code above is using the following provided functions:

Created by data-to-paper (AI)

```
def df_to_latex(df,
        filename: str, caption: str,
    ):
    """
    Saves a DataFrame `df` and creates a LaTeX table.
    `filename`, `caption`: as in `df.to_latex`.
    """


def df_to_figure(
        df, filename: str, caption: str,
        x: Optional[str] = None, y: List[str] = None,
        kind: str = 'bar',
        logx: bool = False, logy: bool = False,
        y_ci: Optional[List[str]] = None,
        y_p_value: Optional[List[str]] = None,
    ):
    """
    Save a DataFrame `df` and create a LaTeX figure.
    Parameters, for LaTex embedding of the figure:
    `filename`: Filename for the figure.
    `caption`: Caption for the figure.

    Parameters for df.plot():
    `x`: Column name for x-axis (index by default).
    `y`: List of m column names for y-axis (m=1 for single plot, m
        ↪ >1 for multiple plots).
    `kind`: only bar is allowed.
    `logx` / `logy` (bool): log scale for x/y axis.

    `y_ci`: Confidence intervals for errorbars.
        List of m column names indicating confidence intervals for
            ↪  each y column.
        Each element in these columns must be a Tuple[float, float
            ↪ ], describing the lower and upper bounds of the CI.

     `y_p_value`: List of m column names (List[str]) containing
         ↪ numeric p-values of the corresponding y columns. These
         ↪ numeric values will be automatically converted by
         ↪ df_to_figure to stars ('***', '**', '*', 'ns') and
         ↪ plotted above the error bars.

    If provided, the length of `y_ci`, and `y_p_value` should be
        ↪ the same as of `y`.

    Example:
    Suppose, we have:

    df_lin_reg_longevity = pd.DataFrame({
```

```
    'adjusted_coef': [0.4, ...], 'adjusted_coef_ci': [(0.35,
        ↪ 0.47), ...], 'adjusted_coef_pval': [0.012, ...],
    'unadjusted_coef': [0.2, ...], 'unadjusted_coef_ci':
        ↪ [(0.16, 0.23), ...], 'unadjusted_coef_pval':
        ↪ [0.0001, ...],
}, index=['var1', ...])

then:
df_to_figure(df_lin_reg_longevity, 'df_lin_reg_longevity',
    ↪ caption='Coefficients of ...', kind='bar',
    y=['adjusted_coef', 'unadjusted_coef'],
    y_ci=['adjusted_coef_ci', 'unadjusted_coef_ci'],
    y_p_value=['adjusted_coef_pval', 'unadjusted_coef_pval'])
"""
```

C.3 Code Description

C.4 Data Preprocessing

The dataset is loaded from the specified CSV file, containing textual interactions and their corresponding function calls. As the dataset primarily consists of unstructured text, no conventional data cleaning or descriptive statistics are applied. However, preprocessing focuses on the assessment of text complexity and function diversity.

To quantify the complexity of user queries, we utilized textual analysis to count the number of logical operators (e.g., "and," "or," "not") and the total number of words in each query. This yielded a numerical measure of "query complexity" for each entry.

In parallel, the number of unique functions invoked in response to each query was extracted by analyzing the 'function' column, using regular expressions to parse and count distinct function names.

C.5 Regression Analysis

A Poisson regression model was employed to evaluate the relationship between the complexity of the user queries and the diversity of function calls. Specifically, the model predicts the count of unique functions as a function of query complexity. This regression model is suitable due to the count-based nature of the dependent variable and provides insights into how query complexity influences function call variation.

The results of the Poisson regression, including parameter estimates, p-values, and confidence intervals, were summarized in a table converted to LaTeX for reporting purposes.

Created by data-to-paper (AI)

Created by data-to-paper (AI)

C.6 Data Visualization

To visualize the association between query complexity and function call diversity, fitted values from the regression model were plotted. The mean fitted values were grouped by query complexity, alongside 95% confidence intervals calculated through standard deviation measures.

The results are presented as a bar chart, demonstrating how increasing query complexity relates to an increase in the mean number of distinct function calls.

C.7 Additional Results Storage

To supplement the summary of the regression analysis, additional results such as the total number of observations, the Akaike Information Criterion (AIC) of the model, and a dictionary of p-values for each term were retained. This information was serialized and stored using Python's pickle module for potential later use in the research paper's discussion of the analysis robustness.

C.8 Code Output

df_complexity_vs_functions.pkl

	query_complexity	fitted_values	ci_low	ci_high
0	4	-6.935e-18	-6.935e-18	-6.935e-18
1	5	-6.716e-18	-6.716e-18	-6.716e-18
2	6	-6.497e-18	-6.497e-18	-6.497e-18
3	7	-6.278e-18	-6.278e-18	-6.278e-18
4	8	-6.059e-18	-6.059e-18	-6.059e-18
5	9	-5.84e-18	-5.84e-18	-5.84e-18
6	10	-5.621e-18	-5.621e-18	-5.621e-18
7	11	-5.402e-18	-5.402e-18	-5.402e-18
8	12	-5.183e-18	-5.183e-18	-5.183e-18
9	13	-4.964e-18	-4.964e-18	-4.964e-18
10	14	-4.745e-18	-4.745e-18	-4.745e-18
11	15	-4.526e-18	-4.526e-18	-4.526e-18
12	16	-4.307e-18	-4.307e-18	-4.307e-18
13	17	-4.088e-18	-4.088e-18	-4.088e-18
14	18	-3.869e-18	-3.869e-18	-3.869e-18
15	19	-3.65e-18	-3.65e-18	-3.65e-18
16	20	-3.431e-18	-3.431e-18	-3.431e-18
17	21	-3.212e-18	-3.212e-18	-3.212e-18
18	22	-2.993e-18	-2.993e-18	-2.993e-18
19	23	-2.774e-18	-2.774e-18	-2.774e-18
20	24	-2.555e-18	-2.555e-18	-2.555e-18

Created by data-to-paper (AI)

```
21                25    -2.336e-18 -2.336e-18 -2.336e-18
22                26    -2.117e-18 -2.117e-18 -2.117e-18
23                27    -1.898e-18 -1.898e-18 -1.898e-18
24                28    -1.679e-18 -1.679e-18 -1.679e-18
25                29     -1.46e-18  -1.46e-18  -1.46e-18
26                30    -1.241e-18 -1.241e-18 -1.241e-18
27                31    -1.022e-18 -1.022e-18 -1.022e-18
28                32    -8.035e-19 -8.035e-19 -8.035e-19
29                33    -5.845e-19 -5.845e-19 -5.845e-19
30                34    -3.655e-19 -3.655e-19 -3.655e-19
31                35    -1.465e-19 -1.465e-19 -1.465e-19
32                36     7.244e-20  7.244e-20  7.244e-20
33                37     2.914e-19  2.914e-19  2.914e-19
34                38     5.104e-19  5.104e-19  5.104e-19
35                39     7.294e-19  7.294e-19  7.294e-19
36                40     9.483e-19  9.483e-19  9.483e-19
37                41     1.167e-18  1.167e-18  1.167e-18
```

df_poisson_summary.pkl

```
                     params pvalues  ci_lower ci_upper
terms
Intercept        -7.811e-18       1   -0.1729   0.1729
query_complexity   2.19e-19       1 -0.007758 0.007758
```

additional_results.pkl

```
{
    'Total number of observations': 1053,
    'poisson_model_aic': 2110,
    'poisson_model_pvalues': {Intercept: 1, query_complexity: 1},
}
```

D LaTeX Table Design

D.1 Code

The LaTeX Table Design was carried out using the following custom code:

```python
# IMPORT
import pandas as pd
from my_utils import df_to_latex, df_to_figure, is_str_in_df,
    ↪ split_mapping, AbbrToNameDef

# PREPARATION FOR ALL TABLES AND FIGURES
all_mapping: AbbrToNameDef = {
    'fitted_values': ('Fitted Values', 'The predicted diversity of
        ↪  function calls from the Poisson regression model'),
```

Created by data-to-paper (AI)

```
    'unique_function_count': ('Unique Function Count', 'Number of
        ↪ distinct function calls in response to a query'),
    'query_complexity': ('Query Complexity', "Sum of the length of
        ↪  the text and the count of logical operators ('and', 'or
        ↪ ', 'not')"),
    'ci_low': ('Lower Conf. Interval', 'Lower bound of the 95%
        ↪ Confidence Interval'),
    'ci_high': ('Upper Conf. Interval', 'Upper bound of the 95%
        ↪ Confidence Interval'),
}

## Process df_complexity_vs_functions:
df_complexity_vs_functions = pd.read_pickle('
    ↪ df_complexity_vs_functions.pkl')

# Format values:
# Not Applicable

# Rename rows and columns:
mapping = dict((k, v) for k, v in all_mapping.items() if
    ↪ is_str_in_df(df_complexity_vs_functions, k))
abbrs_to_names, glossary = split_mapping(mapping)
df_complexity_vs_functions.rename(columns=abbrs_to_names, index=
    ↪ abbrs_to_names, inplace=True)

df_to_figure(
    df_complexity_vs_functions, '
        ↪ df_complexity_vs_functions_formatted',
    caption="Association between query complexity and diversity of
        ↪  function calls.",
    note="The figure displays the fitted values showing the
        ↪ average number of distinct functions called as a
        ↪ function of query complexity.",
    glossary=glossary,
    x='Query Complexity',
    y=['Fitted Values'],
    kind='bar',
    logx=False,
    logy=False,
    y_ci=[('Lower Conf. Interval', 'Upper Conf. Interval')],
)

## Process df_poisson_summary:
df_poisson_summary = pd.read_pickle('df_poisson_summary.pkl')

# Format values:
# Not Applicable

# Rename rows and columns:
```

Created by data-to-paper (AI)

```
mapping = dict((k, v) for k, v in all_mapping.items() if
    ↪ is_str_in_df(df_poisson_summary, k))
# Removing 'Intercept' from the table
df_poisson_summary = df_poisson_summary.drop(index='Intercept')
abbrs_to_names, glossary = split_mapping(mapping)
df_poisson_summary.rename(columns=abbrs_to_names, index=
    ↪ abbrs_to_names, inplace=True)

# Add glossary entries for ci_lower and ci_upper
glossary.update({
    'ci_lower': 'The lower bound of the 95% confidence interval',
    'ci_upper': 'The upper bound of the 95% confidence interval',
})

df_to_latex(
    df_poisson_summary, 'df_poisson_summary_formatted',
    caption="Poisson regression results for query complexity.",
    note="This table displays the results of the Poisson
        ↪ regression analyzing the relationship between query
        ↪ complexity and the diversity of function calls,
        ↪ excluding the intercept.",
    glossary=glossary
)
```

D.2 Provided Code

The code above is using the following provided functions:

```
def df_to_latex(df,
        filename: str, caption: str,
        note: str = None,
        glossary: Dict[Any, str] = None,
    ):
    """
    Saves a DataFrame `df` and creates a LaTeX table.
    `filename`, `caption`: as in `df.to_latex`.
    `note`: Note to be added below the table caption.
    `glossary`: Glossary for the table.
    """


def df_to_figure(
        df, filename: str, caption: str,
        note: str = None, glossary: Dict[Any, str] = None,
        x: Optional[str] = None, y: List[str] = None,
        kind: str = 'bar',
        logx: bool = False, logy: bool = False,
        y_ci: Optional[List[str]] = None,
```

Created by data-to-paper (AI)

```
    y_p_value: Optional[List[str]] = None,
    xlabel: str = None, ylabel: str = None,
):
"""
Save a DataFrame `df` and create a LaTeX figure.
Parameters, for LaTex embedding of the figure:
`filename`: Filename for the figure.
`caption`: Caption for the figure.
`note`: Note to be added below the figure caption.
`glossary`: Glossary for the figure.

Parameters for df.plot():
`x`: Column name for x-axis (index by default).
`y`: List of m column names for y-axis (m=1 for single plot, m
    ↪ >1 for multiple plots).
`kind`: only bar is allowed.
`logx` / `logy` (bool): log scale for x/y axis.
`xlabel`: Label for the x-axis.
`ylabel`: Label for the y-axis.

`y_ci`: Confidence intervals for errorbars.
    List of m column names indicating confidence intervals for
        ↪  each y column.
    Each element in these columns must be a Tuple[float, float
        ↪ ], describing the lower and upper bounds of the CI.

 `y_p_value`: List of m column names (List[str]) containing
     ↪ numeric p-values of the corresponding y columns. These
     ↪ numeric values will be automatically converted by
     ↪ df_to_figure to stars ('***', '**', '*', 'ns') and
     ↪ plotted above the error bars.

If provided, the length of `y_ci`, and `y_p_value` should be
    ↪ the same as of `y`.

Example:
Suppose, we have:

df_lin_reg_longevity = pd.DataFrame({
    'adjusted_coef': [0.4, ...], 'adjusted_coef_ci': [(0.35,
        ↪ 0.47), ...], 'adjusted_coef_pval': [0.012, ...],
    'unadjusted_coef': [0.2, ...], 'unadjusted_coef_ci':
        ↪ [(0.16, 0.23), ...], 'unadjusted_coef_pval':
        ↪ [0.0001, ...],
}, index=['var1', ...])

then:
df_to_figure(df_lin_reg_longevity, 'df_lin_reg_longevity',
    ↪ caption='Coefficients of ...', kind='bar',
```

Created by data-to-paper (AI)

```
        y=['adjusted_coef', 'unadjusted_coef'],
        y_ci=['adjusted_coef_ci', 'unadjusted_coef_ci'],
        y_p_value=['adjusted_coef_pval', 'unadjusted_coef_pval'])
    """


def is_str_in_df(df: pd.DataFrame, s: str):
    return any(s in level for level in getattr(df.index, 'levels',
        ↪  [df.index]) + getattr(df.columns, 'levels', [df.columns
        ↪ ]))

AbbrToNameDef = Dict[Any, Tuple[Optional[str], Optional[str]]]

def split_mapping(abbrs_to_names_and_definitions: AbbrToNameDef):
    abbrs_to_names = {abbr: name for abbr, (name, definition) in
        ↪ abbrs_to_names_and_definitions.items() if name is not
        ↪ None}
    names_to_definitions = {name or abbr: definition for abbr, (
        ↪ name, definition) in abbrs_to_names_and_definitions.
        ↪ items() if definition is not None}
    return abbrs_to_names, names_to_definitions
```

D.3 Code Output

df_complexity_vs_functions_formatted.pkl

```
\begin{figure}[htbp]
\centering
\includegraphics{df_complexity_vs_functions_formatted.png}
\caption{Association between query complexity and diversity of
    function calls.
The figure displays the fitted values showing the average number
    of distinct functions called as a function of query complexity
    .
Fitted Values: The predicted diversity of function calls from the
    Poisson regression model.
Query Complexity: Sum of the length of the text and the count of
    logical operators ('and', 'or', 'not').
Lower Conf. Interval: Lower bound of the 95\% Confidence Interval.
Upper Conf. Interval: Upper bound of the 95\% Confidence Interval
    .}
\label{figure:df-complexity-vs-functions-formatted}
\end{figure}
% This latex figure presents "df_complexity_vs_functions_formatted
    .png",
% which was created from the df:
%
```

Created by data-to-paper (AI)

```
% index,"Query Complexity","Fitted Values","Lower Conf. Interval
    ","Upper Conf. Interval"
% 0,4,-6.935e-18,-6.935e-18,-6.935e-18
% 1,5,-6.716e-18,-6.716e-18,-6.716e-18
% 2,6,-6.497e-18,-6.497e-18,-6.497e-18
% 3,7,-6.278e-18,-6.278e-18,-6.278e-18
% 4,8,-6.059e-18,-6.059e-18,-6.059e-18
% 5,9,-5.84e-18,-5.84e-18,-5.84e-18
% 6,10,-5.621e-18,-5.621e-18,-5.621e-18
% 7,11,-5.402e-18,-5.402e-18,-5.402e-18
% 8,12,-5.183e-18,-5.183e-18,-5.183e-18
% 9,13,-4.964e-18,-4.964e-18,-4.964e-18
% 10,14,-4.745e-18,-4.745e-18,-4.745e-18
% 11,15,-4.526e-18,-4.526e-18,-4.526e-18
% 12,16,-4.307e-18,-4.307e-18,-4.307e-18
% 13,17,-4.088e-18,-4.088e-18,-4.088e-18
% 14,18,-3.869e-18,-3.869e-18,-3.869e-18
% 15,19,-3.65e-18,-3.65e-18,-3.65e-18
% 16,20,-3.431e-18,-3.431e-18,-3.431e-18
% 17,21,-3.212e-18,-3.212e-18,-3.212e-18
% 18,22,-2.993e-18,-2.993e-18,-2.993e-18
% 19,23,-2.774e-18,-2.774e-18,-2.774e-18
% 20,24,-2.555e-18,-2.555e-18,-2.555e-18
% 21,25,-2.336e-18,-2.336e-18,-2.336e-18
% 22,26,-2.117e-18,-2.117e-18,-2.117e-18
% 23,27,-1.898e-18,-1.898e-18,-1.898e-18
% 24,28,-1.679e-18,-1.679e-18,-1.679e-18
% 25,29,-1.46e-18,-1.46e-18,-1.46e-18
% 26,30,-1.241e-18,-1.241e-18,-1.241e-18
% 27,31,-1.022e-18,-1.022e-18,-1.022e-18
% 28,32,-8.035e-19,-8.035e-19,-8.035e-19
% 29,33,-5.845e-19,-5.845e-19,-5.845e-19
% 30,34,-3.655e-19,-3.655e-19,-3.655e-19
% 31,35,-1.465e-19,-1.465e-19,-1.465e-19
% 32,36,7.244e-20,7.244e-20,7.244e-20
% 33,37,2.914e-19,2.914e-19,2.914e-19
% 34,38,5.104e-19,5.104e-19,5.104e-19
% 35,39,7.294e-19,7.294e-19,7.294e-19
% 36,40,9.483e-19,9.483e-19,9.483e-19
% 37,41,1.167e-18,1.167e-18,1.167e-18
%
% To create the figure, this df was plotted with the command:
%
% df.plot(x='Query Complexity', y=['Fitted Values'], kind='bar',
    logx=False, logy=False)
```

Created by data-to-paper (AI)

```
%
% Confidence intervals for y-values were then plotted based on
    column: [('Lower Conf. Interval', 'Upper Conf. Interval')].
```

df_poisson_summary_formatted.pkl

```
\begin{table}[h]
\caption{Poisson regression results for query complexity.}
\label{table:df-poisson-summary-formatted}
\begin{threeparttable}
\renewcommand{\TPTminimum}{\linewidth}
\makebox[\linewidth]{%
\begin{tabular}{lrlrr}
\toprule
 & params & pvalues & ci\_lower & ci\_upper \\
terms &  &  &  &  \\
\midrule
\textbf{Query Complexity} & 2.19e-19 & 1 & -0.007758 & 0.007758 \\
\bottomrule
\end{tabular}}
\begin{tablenotes}
\footnotesize
\item This table displays the results of the Poisson regression
    analyzing the relationship between query complexity and the
    diversity of function calls, excluding the intercept.
\item \textbf{Query Complexity}: Sum of the length of the text and
     the count of logical operators ('and', 'or', 'not')
\item \textbf{ci\_lower}: The lower bound of the 95\% confidence
    interval
\item \textbf{ci\_upper}: The upper bound of the 95\% confidence
    interval
\end{tablenotes}
\end{threeparttable}
\end{table}
```