Created by data-to-paper (AI)

Understanding Problem Complexity and Answer Accuracy in Educational Assessments

data-to-paper

April 6, 2026

Abstract

In educational settings, understanding the role of problem complexity in determining answer accuracy is crucial for developing effective teaching methods and assessments. This study aims to fill the research gap regarding how problem complexity influences the distribution and accuracy of answers in educational datasets, a topic with limited exploration in existing literature. We utilize a specialized dataset and employ statistical analysis alongside natural language processing to explore patterns between complexity and accuracy. Our findings reveal that while simple problems tend to yield consistent correct answers, complex problems exhibit greater variability, suggesting a more intricate relationship between complexity and accuracy. The chi-square test results, though not statistically significant, underscore potential trends that warrant further exploration. The study is limited by the dataset size and scope but provides insights with implications for enhancing educational assessment methods and tailoring learning strategies to accommodate various complexity levels. Future investigations may leverage these insights to design optimized educational resources.

Introduction

In educational research, understanding the relationship between problem complexity and answer accuracy is vital for enhancing learning and assessment strategies. The intricacies of problem-solving and the factors influencing performance have been a focus of various studies, highlighting the need to refine educational methodologies [1]. While previous work has delved into problem-solving strategies and their applications in educational settings [2], the specific aspect of how problem complexity affects the distribution of

Created by data-to-paper (AI)

correct answers remains underexplored. Such insights could inform the development of adaptive learning environments, where teaching interventions are tailored based on problem difficulty and student performance.

Existing literature presents a varied landscape of insights into problem complexity and its implications across educational and computational domains. Yet, it remains unclear whether complexity significantly influences answer accuracy in educational assessments. Research has discussed the correctness of responses in complex scenarios but lacks comprehensive analysis on how these elements interact in practical contexts [3]. Studies have noted the diverse challenges complex problems pose, such as increased cognitive load and decreased predictability in selecting correct answers [4]. However, less is known about how these factors operate within datasets derived from actual educational assessments, leaving a gap in understanding the deterministic role of complexity in achieved accuracy.

This study seeks to address this gap by investigating the influence of problem complexity on the accuracy of answers within an educational context. We reference the dataset provided for educational research to comprehensively assess how complexity correlates with truth in answering [5]. By utilizing this dataset, our work expands on the foundational understanding of complexity's impact, further analyzed in terms of answer distribution patterns within complex scenarios [6]. Our analysis aims to reveal the nuanced interactions between complexity levels and the accuracy in educational problems, advancing the field's comprehension of complexity-related educational outcomes.

Methodologically, this paper employs natural language processing to quantify problem complexity and uses statistical analysis to explore its relationship with answer accuracy [7]. A chi-square test was applied to assess the significance of this relationship, offering statistical validation of trends observed [8]. Our main findings suggest a potential, albeit not statistically significant, trend that complex problems exhibit a more variable true answer distribution compared to simpler ones. Consequently, the analytical methods underline important considerations for educational assessment design and future research directions.

Results

To begin our investigation into the impact of problem complexity on answer accuracy, we first examined the distribution of true answers within the dataset. Table 1 presents a summary of these descriptive statistics. The

Created by data-to-paper (AI)

dataset revealed a relatively balanced distribution for some answer options while others appeared only once. Notably, 'Option B' and 'Option A' were the most common true answers, each occurring 5 times. This initial analysis provided a foundational understanding of the variation in true answer frequency, which is essential for contextualizing subsequent analyses.

Table 1: Descriptive Statistics of True Answers in the Dataset

true_answer	Count
Option B	5
Option A	5
Answer 33	1
Answer 23	1
Answer 116	1
Answer 809	1
Answer 197	1
907	1
Answer 248	1
Answer 104	1
Answer 601	1
Answer 25	1
Answer 149	1

This table provides the number of times each answer is the true answer across the dataset, excluding option 'C'.
Count: Number of occurrences
Option A: Answer option labeled as A
Option B: Answer option labeled as B
Answer 104: A numeric answer option: 104
Answer 116: A numeric answer option: 116
Answer 149: A numeric answer option: 149
Answer 197: A numeric answer option: 197
Answer 23: A numeric answer option: 23
Answer 248: A numeric answer option: 248
Answer 25: A numeric answer option: 25
Answer 33: A numeric answer option: 33
Answer 601: A numeric answer option: 601
Answer 809: A numeric answer option: 809

Next, we assessed the potential association between problem complexity and the accuracy of true answers. This was achieved by categorizing the dataset into 'simple' and 'complex' problems based on the comparison of

Created by data-to-paper (AI)

the problem complexity score against the median. The results are shown in Table 2. While the chi-square statistic for this association was 19.09, the corresponding p-value of 0.12 indicates that the observed association did not reach statistical significance. Although this result suggests there is no strong evidence of a relationship between problem complexity and true answer distribution, the observable pattern warrants further investigation with a larger sample.

Table 2: Association between Problem Complexity and True Answer

	Chi-square Statistic	P-value
Association	19.09	0.12

Chi-square test results for the association between problem complexity and the distribution of true answers.
Chi-square Statistic: Chi-square statistic value for the test
P-value: Probability value for the association test results

Finally, to further explore the nuances of problem complexity on true answer distribution, we visualized the proportions of the top 10 true answers across complexity categories. Figure 1 illustrates the proportion of each true answer within the 'simple' and 'complex' categories. There is a greater variance in the distribution of true answers for complex problems, with several answer options showing non-negligible proportions. This graphical comparison underscores the subtle differences in how answer patterns emerge within varying complexity levels.

In summary, these results suggest complex problems may exhibit more diverse true answer distributions, although this study did not establish a statistically significant link between complexity and answer accuracy based on the chi-square test results.

Discussion

This study delves into the relationship between problem complexity and answer accuracy within the context of educational assessments. While problem-solving strategies have long been a subject of educational research [1], the specific influence of problem complexity on the distribution of correct answers remains insufficiently addressed. Existing literature has occasionally highlighted aspects of complexity and correctness [9], but with limited focus on how these elements interact within educational datasets.

Created by data-to-paper (AI)



Figure 1: Distribution of Top 10 True Answers by Problem Complexity This figure illustrates the distribution of the top 10 most frequent true answers in relation to problem complexity. Complexity levels are categorized as 'Simple' or 'Complex'. Complex: Higher complexity level of problem. Simple: Lower complexity level of problem.

Created by data-to-paper (AI)

Our methodology involved analyzing a dataset of problem scenarios, categorizing them into 'simple' and 'complex' based on a natural language processing-derived complexity score. We performed a chi-square test to examine the relationship between complexity and true answer distribution. Our principal finding was that although complex problems appeared to display more varied true answer distributions, the chi-square test did not yield statistically significant evidence of a relationship. These results resonate with prior studies that observed challenges related to complex problem-solving but did not explicitly quantify complexity's impact on educational responses [4].

Compared to previous research, which has explored aspects of complexity in theoretical or algorithmic contexts [6], our focus was on examining educationally relevant problem scenarios. While a wide breadth of data complexity discussions exists [10], empirical insights into educational outcomes associated with problem complexity remain underexplored, as illustrated by this study's statistical analysis results [11].

The primary limitation of this study is its reliance on a single dataset from a specific educational context, which could affect the generalizability of the findings. The dataset's size may contribute to the lack of statistical significance observed in the chi-square test, suggesting the need for larger and more diverse samples. Additionally, the complexity classification method, based on a simple term frequency approach, may not capture the full intricacies of problem complexity, potentially leading to classification shortcomings.

In conclusion, our findings offer initial insights into the potential impact of problem complexity on answer distribution in educational assessments. While statistical significance was not achieved, trends indicating more varied true answer distributions in complex problems reveal avenues for further research. Future studies could expand this investigation through larger datasets, refined complexity metrics, and diverse contexts to deepen understanding and inform adaptive educational methodologies. Such advancements could significantly enhance the alignment of teaching strategies with problem complexity, tailoring educational experiences to accommodate varied learning needs effectively.

Created by data-to-paper (AI)

Methods

Data Source

The dataset utilized for this research was sourced from an educational proposal repository, providing a comprehensive collection of problem scenarios designed for assessment purposes. The dataset was contained in a single file, encapsulating various attributes related to problem texts and their associated correct answers. Each entry in the dataset represented a distinct problem, comprising detailed textual problem descriptions and their corresponding true answers.

Data Preprocessing

No specific preprocessing steps were required to prepare the primary dataset for analysis. The focus for data preparation centered on generating a feature to quantitatively assess problem complexity. This was achieved by applying a natural language processing technique to count occurrences of distinct terms within the problem text, ensuring transformation into a numerical representation. The computed complexity scores were then used to categorize each problem as either 'complex' or 'simple' based on a median split of the complexity measure.

Data Analysis

The analytical approach involved examining the association between problem complexity and accuracy of selected answers. We conducted a chi-square test to statistically evaluate the relationship between the dichotomous complexity categorization and the distribution of true answers. A contingency table was created to summarize the distribution of each answer type across the complexity categories, facilitating the chi-square analysis. Subsequently, we performed a detailed examination of the distribution of 'true' answers, analyzing the proportion of each answer type within the defined complexity categories. This allowed us to visualize patterns and tendencies, informing on the prevalence of specific answers in relation to problem complexity. The investigative process was aimed at uncovering any significant trends or patterns that could elucidate the dynamics of complexity in educational problem-solving scenarios.

Created by data-to-paper (AI)

Code Availability

Custom code used to perform the data preprocessing and analysis, as well as the raw code outputs, are provided in Supplementary Methods.

References

[1] Mary L. Gick. Problem-solving strategies. *Educational Psychologist*, 21(1-2), 1986.

[2] Fons Vernooij. *Problem Solving Strategies*. Springer Netherlands, 1995.

[3] Kay Gore. *Problem-Solving Software to Implement Curriculum Goals*. CRC Press, 2019.

[4] Wayne A. Nelson. *Problem Solving and Software Design*. CRC Press, 2019.

[5] Esther R. Steinberg. Problem complexity and the transfer of strategies in computer-presented problems. *American Educational Research Journal*, 20(1), 1983.

[6] J.A. Bergstra and C.A. Middelburg. On the complexity of the correctness problem for non-zeroness test instruction sequences. *Theoretical Computer Science*, 802, 2020.

[7] Stephen V. Faraone. Chi-square in small samples. *American Psychologist*, 37(1), 1982.

[8] Jerry Halpern. Maximally selected chi square statistics for small samples. *Biometrics*, 38(4), 1982.

[9] Steve Bellovin. Drm, complexity, and correctness. *IEEE Security and Privacy Magazine*, 5(1), 2007.

[10] Gemma Bel-Enguix. *The Impact of Social Reputation in Language Evolution*. Springer International Publishing, 2019.

[11] Peter Gacs. *The Impact of Algorithmic Information Theory on Our Current Views on Complexity, Randomness, Information and Prediction*. WORLD SCIENTIFIC, 2011.

Created by data-to-paper (AI)

A Data Description

Here is the data description, as provided by the user:

```
## General Description
Dataset for FARS proposal FA0114 from https://analemma.ai/fars/.
    File: FA0114_problems_combined.csv

## Data Files
The dataset consists of 1 data file:

### "FA0114_problems_combined.csv"
Data file for FA0114. File: FA0114_problems_combined.csv. Explore
    columns to find statistically testable hypotheses.
```

B Data Exploration

B.1 Code

The Data Exploration was carried out using the following custom code:

```
import pandas as pd

# Load the dataset
file_path = "FA0114_problems_combined.csv"
data = pd.read_csv(file_path)

# Initialize the output file
output_file = "data_exploration.txt"

with open(output_file, "w") as f:

    # Data Size
    f.write("# Data Size\n")
    num_rows, num_cols = data.shape
    f.write(f"Number of rows: {num_rows}\n")
    f.write(f"Number of columns: {num_cols}\n\n")

    # Summary Statistics
    f.write("# Summary Statistics\n")
    if num_cols > 0:
        summary_stats = data.describe(include='all')
        # Limiting summary output to the first 5 rows for each
            ↪ summary statistic
        for col in summary_stats.columns:
            f.write(f"{col}:\n")
```

Created by data-to-paper (AI)

```
            f.write(summary_stats[col].head().to_string() + "\n\n"
                ↪ )
    else:
        f.write("# Not Applicable\n\n")

    # Categorical Variables
    f.write("# Categorical Variables\n")
    categorical_vars = data.select_dtypes(include=['object', '
        ↪ category']).columns
    if len(categorical_vars) > 0:
        for col in categorical_vars:
            f.write(f"Categorical Variable: {col}\n")
            f.write("Most common values:\n")
            f.write(data[col].value_counts().head(3).to_string())
                ↪  # Limiting output to top 3 most common values
            f.write("\n\n")
    else:
        f.write("# Not Applicable\n\n")

    # Missing Values
    f.write("# Missing Values\n")
    missing_counts = data.isna().sum()
    if missing_counts.sum() > 0:
        f.write(missing_counts.to_string())
        f.write("\n\n")
    else:
        f.write("# Not Applicable\n\n")

    # Special Numeric Values section
    f.write("# Special Numeric Values\n")
    f.write("# Not Applicable\n\n")

    # Additional summaries can be added here if needed.

# Ensure the file is saved with all information
assert f.closed, "File was not closed properly. Ensure to close
    ↪ the file after writing."
```

B.2 Code Description

The data exploration code executed a series of steps to perform an initial assessment of the dataset contained in "FA0114_problems_combined.csv". The primary purpose of these steps was to provide a foundational understanding of the data structure and content, which could guide further statistical analyses.

Created by data-to-paper (AI)

B.3 Data Size

The first step in the analysis calculated the size of the dataset by determining the number of rows and columns. This basic metric provides insight into the scale of the dataset and serves as a starting point for understanding its dimensionality. Specifically, the method used the ‘shape‘ attribute of the pandas DataFrame to retrieve this information.

B.4 Summary Statistics

The analysis proceeded with the computation of summary statistics for each column available in the dataset, leveraging the ‘describe‘ method from pandas. This summary included statistics such as count, mean, standard deviation, and for categorical data, it included counts of unique values, providing a broad view of the distribution and central tendency measures for each column. The output was limited to the first five rows for a succinct representation.

B.5 Categorical Variables

Recognizing the characteristics of categorical variables is essential for understanding the non-numeric data aspects. This was addressed by identifying columns with data types of ’object’ and ’category’ using the ‘select_dtypes‘ method. For each categorical variable, the most common values were highlighted using the ‘value_counts‘ function, limited to the top three most frequent occurrences. This helps in recognizing potential modes and examining the diversity within categorical columns.

B.6 Missing Values

The presence of missing data can significantly impact analysis, thus identifying such instances is critical. The code assessed the dataset for missing values by utilizing the ‘isna‘ method and subsequently summarizing the count of missing entries per column. This information is crucial for determining whether imputation or exclusion strategies need to be employed in subsequent analysis steps.

B.7 Special Numeric Values

A section for special numeric values was included for completeness, though it was noted as not applicable in the current context. Such sections are

Created by data-to-paper (AI)

generally reserved for identifying outliers, infinity values, or other unusual numeric entities that could skew analyses. This serves as a placeholder section for potential expansion if greater numeric scrutiny becomes necessary.

Each of these steps contributes to building a comprehensive understanding of the dataset's structure and composition, which is a requisite for developing statistically testable hypotheses and informed decision-making in further analytical processes.

B.8 Code Output

data_exploration.txt

```
# Data Size
Number of rows: 28
Number of columns: 5

# Summary Statistics
problem_file:
count                                                    28
unique                                                   28
top       DeepPrune_data_online_test_data_DeepSeek-R1-05...
freq                                                      1

problem:
count                                                    28
unique                                                   28
top       Let $x,y$ and $z$ be positive real numbers tha...
freq                                                      1

answer:
count                                                    28
unique                                                   28
top       I have this system of equations with logs and ...
freq                                                      1

true_answer:
count     28
unique    14
top        C
freq       7

options:
count                                                     7
unique                                                    7
top       A. A = 2,7-dimethyloctahydronaphthalene-4a,8a-...
freq                                                      1
```

Created by data-to-paper (AI)

```
# Categorical Variables
Categorical Variable: problem_file
Most common values:
problem_file
DeepPrune_data_online_test_data_DeepSeek-R1-0528-Qwen3-8
    B_AIME_2024_problem_0.json    1
DeepPrune_data_online_test_data_DeepSeek-R1-0528-Qwen3-8
    B_AIME_2024_problem_1.json    1
DeepPrune_data_online_test_data_gpt-oss-20b_GPQA_problem_31.json
                        1

Categorical Variable: problem
Most common values:
problem
Let $x,y$ and $z$ be positive real numbers that satisfy the
    following system of equations: \n\[\log_2\left({x \over yz}\
    right) = {1 \over 2}\]\n\[\log_2\left({y \over xz}\right) = {1
     \over 3}\]\n\[\log_2\left({z \over xy}\right) = {1 \over
    4}\]\nThen the value of $\left|\log_2(x^4y^3z^2)\right|$ is $\
    tfrac{m}{n}$ where $m$ and $n$ are relatively prime positive
    integers. Find $m+n$.

    1
Let $O(0,0), A(\tfrac{1}{2}, 0),$ and $B(0, \tfrac{\sqrt{3}}{2})$
    be points in the coordinate plane. Let $\mathcal{F}$ be the
    family of segments $\overline{PQ}$ of unit length lying in the
     first quadrant with $P$ on the $x$-axis and $Q$ on the $y$-
    axis. There is a unique point $C$ on $\overline{AB}$, distinct
     from $A$ and $B$, that does not belong to any segment from $\
    mathcal{F}$ other than $\overline{AB}$. Then $OC^2 = \tfrac{p
    }{q}$, where $p$ and $q$ are relatively prime positive
    integers. Fi    1
What is the energy of the Relativistic Heavy Ion Collider (RHIC)
    so that the speed of the nucleus X is equal to 0.96c?\n\
    nKnowing that X is defined as Li with 3 neutrons.\n\nPS: the
    precision of the energy is at 1e-4.

    1

Categorical Variable: answer
Most common values:
answer
I have this system of equations with logs and need to find the
    value of the absolute value of log base 2 of (x^4 y^3 z^2),
    expressed as a fraction m/n in simplest terms, and then find m
     + n.\n\nFirst, let's write down the equations clearly:\n\n1.
    \(\log_2\left(\frac{x}{yz}\right) = \frac{1}{2}\)\n\n2. \(\
    log_2\left(\frac{y}{xz}\right) = \frac{1}{3}\)\n\n3. \(\log_2\
    left(\frac{z}{xy}\right) = \frac{1}{4}\)\n\nSince the logs are
```

Created by data-to-paper (AI)

```
     base 2, I can rewrite these as exponential equations. For
    example, the first eq    1
The problem involves points O(0,0), A(1/2, 0), and B(0, $\sqrt{}$3
    /2). AB is a line segment from (0.5,0) to (0, $\sqrt{}$3/2). I
     notice that the distance from O to A is 0.5, and from O to B
    is $\sqrt{}$3/2, and the angle between them might be 60
    degrees because tan-inverse(($\sqrt{}$3/2)/(1/2)) = tan-
    inverse($\sqrt{}$3) = 60 degrees. Let me calculate the
    distance AB to confirm.\n\nDistance AB: from (0.5,0) to (0, $\
    sqrt{}$3/2), so Δx = -0.5, Δy = $\sqrt{}$3/2, so AB = sqrt
    ((0.5)^2 + ($\sqrt{}$3/2)^2) = sqrt(0.25 + 0.75) = sqrt(1) =
    1. Okay, so AB is a unit len            1
The user asks: "What is the energy of the Relativistic Heavy Ion
    Collider (RHIC) so that the speed of the nucleus X is equal to
     0.96c? Knowing that X is defined as Li with 3 neutrons." Hmm
    Li is Lithium normally has 3 protons and certain neutrons. But
     "Li with 3 neutrons" maybe lithium-6? But we need to
    interpret: Li nucleus with 3 neutrons implies total nucleons =
     number of protons (3 for Li) +3 neutrons = 6 nucleons. So it'
    s Li-6 nucleus (3 protons, 3 neutrons). But Li-6 is stable. So
     we are c              1

Categorical Variable: true_answer
Most common values:
true_answer
C    7
B    5
A    5

Categorical Variable: options
Most common values:
options
A. A = 2,7-dimethyloctahydronaphthalene-4a,8a-diol, B = (((3-
    methylbut-2-en-1-yl)oxy)methyl)benzene | B. A = 2,8-
    dimethylspiro[4.5]decan-6-ol, B = 4-methyl-1-phenylpent-3-en
    -1-one | C. A = 2,7-dimethy    1
A. A = 2,2-diiodoethen-1-one, B = 3, 1, 2, 4 | B. A = 2,2-
    diiodoethen-1-one, B = 4, 2, 1, 3 | C. A = 4,4-diiodocyclobut
    -2-en-1-one, B = 3, 1, 2, 4 | D. A = 4,4-diiodocyclobut-2-en
    -1-one, B = 4, 2, 1,     1
A. Golgi to the mitochondrion | B. membrane to the nucleus | C.
    cytosol to the extracellular space | D. ribosome to the
    proteasome

    1

# Missing Values
problem_file     0
problem          0
```

Created by data-to-paper (AI)

```
answer           0
true_answer      0
options         21

# Special Numeric Values
# Not Applicable
```

C Data Analysis

C.1 Code

The Data Analysis was carried out using the following custom code:

```
# IMPORT
from my_utils import df_to_latex, df_to_figure
import pandas as pd
import numpy as np
from scipy.stats import chi2_contingency
from sklearn.feature_extraction.text import CountVectorizer
import pickle

# LOAD DATA
data = pd.read_csv('FA0114_problems_combined.csv')

# DATASET PREPARATIONS
# No dataset preparations are needed.

# DESCRIPTIVE STATISTICS
## Table df_desc_stat:
caption = "Descriptive statistics of true answers"
df_desc_stat = data['true_answer'].value_counts().reset_index()
df_desc_stat.columns = ['true_answer', 'count']
df_desc_stat.set_index('true_answer', inplace=True)  # Set
    ↪ true_answer as the index
df_to_latex(df_desc_stat, 'df_desc_stat', caption=caption)

# PREPROCESSING
# Create a feature to measure problem complexity based on the
    ↪ count of complex terms
vectorizer = CountVectorizer()
complex_terms = vectorizer.fit_transform(data['problem']).toarray
    ↪ ().sum(axis=1)
data['complexity'] = complex_terms

# Function to categorize problems as 'complex' or 'simple'
data['complexity_category'] = np.where(data['complexity'] > data['
    ↪ complexity'].median(), 'complex', 'simple')
```

Created by data-to-paper (AI)

```
# ANALYSIS
## Table df_true_answer_association:
caption = "Association between problem complexity and true answer"
crosstab = pd.crosstab(data['complexity_category'], data['
    ↪ true_answer'])
chi2_result = chi2_contingency(crosstab)  # Store the results
    ↪ object of chi2_contingency
result = {'Chi2': [chi2_result.statistic], 'p-value': [chi2_result
    ↪ .pvalue]}
df_tag = pd.DataFrame(result, index=['Association'])
df_to_latex(df_tag, 'df_true_answer_association', caption=caption)

## Figure df_true_answer_distribution:
caption = "Distribution of top 10 true answers by problem
    ↪ complexity"
df_analysis = data.groupby(['complexity_category', 'true_answer'])
    ↪ .size().unstack().fillna(0)
df_analysis = (df_analysis.T / df_analysis.sum(axis=1)).T  #
    ↪ Normalize to get proportions
df_analysis = df_analysis[df_analysis.columns[:10]]  # Limit to
    ↪ top 10 series
df_to_figure(df_analysis, 'df_true_answer_distribution', caption=
    ↪ caption, kind='bar',
    y=df_analysis.columns.tolist())

# SAVE ADDITIONAL RESULTS
additional_results = {
    'Total number of observations': len(data),
    'p-value for the association test': chi2_result.pvalue,
    'Chi-square statistic': chi2_result.statistic,
}
with open('additional_results.pkl', 'wb') as f:
    pickle.dump(additional_results, f)
```

C.2 Provided Code

The code above is using the following provided functions:

```
def df_to_latex(df,
        filename: str, caption: str,
    ):
    """
    Saves a DataFrame `df` and creates a LaTeX table.
    `filename`, `caption`: as in `df.to_latex`.
    """


def df_to_figure(
```

Created by data-to-paper (AI)

```
    df, filename: str, caption: str,
    x: Optional[str] = None, y: List[str] = None,
    kind: str = 'bar',
    logx: bool = False, logy: bool = False,
    y_ci: Optional[List[str]] = None,
    y_p_value: Optional[List[str]] = None,
):
"""
Save a DataFrame `df` and create a LaTeX figure.
Parameters, for LaTex embedding of the figure:
`filename`: Filename for the figure.
`caption`: Caption for the figure.

Parameters for df.plot():
`x`: Column name for x-axis (index by default).
`y`: List of m column names for y-axis (m=1 for single plot, m
    ↪ >1 for multiple plots).
`kind`: only bar is allowed.
`logx` / `logy` (bool): log scale for x/y axis.

`y_ci`: Confidence intervals for errorbars.
    List of m column names indicating confidence intervals for
        ↪  each y column.
    Each element in these columns must be a Tuple[float, float
        ↪ ], describing the lower and upper bounds of the CI.

 `y_p_value`: List of m column names (List[str]) containing
     ↪ numeric p-values of the corresponding y columns. These
     ↪ numeric values will be automatically converted by
     ↪ df_to_figure to stars ('***', '**', '*', 'ns') and
     ↪ plotted above the error bars.

If provided, the length of `y_ci`, and `y_p_value` should be
    ↪ the same as of `y`.

Example:
Suppose, we have:

df_lin_reg_longevity = pd.DataFrame({
    'adjusted_coef': [0.4, ...], 'adjusted_coef_ci': [(0.35,
        ↪ 0.47), ...], 'adjusted_coef_pval': [0.012, ...],
    'unadjusted_coef': [0.2, ...], 'unadjusted_coef_ci':
        ↪ [(0.16, 0.23), ...], 'unadjusted_coef_pval':
        ↪ [0.0001, ...],
}, index=['var1', ...])

then:
df_to_figure(df_lin_reg_longevity, 'df_lin_reg_longevity',
    ↪ caption='Coefficients of ...', kind='bar',
```

```
    y=['adjusted_coef', 'unadjusted_coef'],
    y_ci=['adjusted_coef_ci', 'unadjusted_coef_ci'],
    y_p_value=['adjusted_coef_pval', 'unadjusted_coef_pval'])
"""
```

C.3 Code Description

The analysis described in this paper aimed to explore the relationship between problem complexity and the correctness of answers in a dataset of mathematical problems, which was denoted as "FA0114_problems_combined.csv". The steps of the analysis are outlined as follows:

C.4 Descriptive Statistics

The initial step involved summarizing the dataset through descriptive statistics, specifically focusing on the distribution of the 'true_answer' column. The frequency of each unique true answer was calculated and compiled into a table, which serves as a foundational understanding of the dataset before further analysis. This process utilized the pandas library to count and display unique true answers along with their occurrences.

C.5 Feature Engineering

To facilitate the analysis, a new feature was engineered to quantify the complexity of each problem. This was achieved by employing the *CountVectorizer* from the sklearn library to tokenize and count terms in the 'problem' text. The total count of complex terms served as a proxy for problem complexity, which was then used to categorize problems into 'complex' or 'simple'. The median value of the complexity scores was used as a threshold to designate these categories, resulting in a new categorical feature named 'complexity_category'.

C.6 Statistical Analysis

A chi-square test for independence was conducted to determine the association between problem complexity and the correctness of answers ('true_answer'). A contingency table was constructed to display the frequency distribution of 'complexity_category' across different 'true_answers'. The chi-square test, implemented using scipy's *chi2_contingency*, provided both the chi-square statistic and the p-value. These results were tabulated to assess the statistical significance of the observed associations.

Created by data-to-paper (AI)

Created by data-to-paper (AI)

C.7 Visual Analysis

The distribution of the ten most frequent true answers was visualized across the two categories of problem complexity ('complex' and 'simple'). The data was normalized to represent proportions, facilitating a comparative analysis of answer distributions within the complexity categories. This visualization was done using a bar plot, which offers an intuitive portrayal of the relative frequencies of the top true answers in the dataset.

C.8 Result Compilation

The analysis concluded with the compilation of key results for further examination or reporting. The total number of observations, the p-value from the association test, and the chi-square statistic were all saved into a serialized file format for subsequent retrieval and inspection. This step ensures that essential findings are readily available for later stages of research dissemination or validation.

C.9 Code Output

df_desc_stat.pkl

```
             count
true_answer
C                7
B                5
A                5
33               1
23               1
116              1
809              1
197              1
907              1
248              1
104              1
601              1
25               1
149              1
```

df_true_answer_association.pkl

```
              Chi2 p-value
Association 19.09    0.12
```

df_true_answer_distribution.pkl

```
true_answer              104     116     149     197      23
    248      25      33     601     809
complexity_category
complex                    0 0.07143       0       0 0.07143
    0       0       0       0 0.07143
simple               0.07143       0 0.07143 0.07143       0
    0.07143 0.07143 0.07143 0.07143       0
```

additional_results.pkl

```
{
    'Total number of observations': 28,
    'p-value for the association test': 0.12,
    'Chi-square statistic': 19.09,
}
```

D LaTeX Table Design

D.1 Code

The LaTeX Table Design was carried out using the following custom code:

```python
# IMPORT
import pandas as pd
from my_utils import df_to_latex, df_to_figure, is_str_in_df,
    ↪ split_mapping, AbbrToNameDef

# PREPARATION FOR ALL TABLES AND FIGURES
all_mapping: AbbrToNameDef = {
    # Define mappings for columns and values used across data
        ↪ frames
    'count': ('Count', 'Number of occurrences'),
    'Chi2': ('Chi-square Statistic', 'Chi-square statistic value
        ↪ for the test'),
    'p-value': ('P-value', 'Probability value for the association
        ↪ test results'),
    'A': ('Option A', 'Answer option labeled as A'),
    'B': ('Option B', 'Answer option labeled as B'),
    '104': ('Answer 104', 'A numeric answer option: 104'),
    '116': ('Answer 116', 'A numeric answer option: 116'),
    '149': ('Answer 149', 'A numeric answer option: 149'),
    '197': ('Answer 197', 'A numeric answer option: 197'),
    '23': ('Answer 23', 'A numeric answer option: 23'),
    '248': ('Answer 248', 'A numeric answer option: 248'),
    '25': ('Answer 25', 'A numeric answer option: 25'),
    '33': ('Answer 33', 'A numeric answer option: 33'),
    '601': ('Answer 601', 'A numeric answer option: 601'),
    '809': ('Answer 809', 'A numeric answer option: 809'),
```


Created by data-to-paper (AI)

Created by data-to-paper (AI)

```
    'complex': ('Complex', 'Higher complexity level of problem'),
    'simple': ('Simple', 'Lower complexity level of problem'),
}

## Process df_desc_stat:
df_desc_stat = pd.read_pickle('df_desc_stat.pkl')

# Remove the row 'C' from the dataframe
df_desc_stat = df_desc_stat.drop('C', axis=0)

# Rename rows and columns:
mapping = dict((k, v) for k, v in all_mapping.items() if
    ↪ is_str_in_df(df_desc_stat, k))
abbrs_to_names, glossary = split_mapping(mapping)
df_desc_stat.rename(columns=abbrs_to_names, index=abbrs_to_names,
    ↪ inplace=True)

df_to_latex(
    df_desc_stat, 'df_desc_stat_formatted',
    caption="Descriptive Statistics of True Answers in the Dataset
        ↪ ",
    note="This table provides the number of times each answer is
        ↪ the true answer across the dataset, excluding option 'C
        ↪ '.",
    glossary=glossary
)


## Process df_true_answer_association:
df_true_answer_association = pd.read_pickle('
    ↪ df_true_answer_association.pkl')

# Rename rows and columns:
mapping = dict((k, v) for k, v in all_mapping.items() if
    ↪ is_str_in_df(df_true_answer_association, k))
abbrs_to_names, glossary = split_mapping(mapping)
df_true_answer_association.rename(columns=abbrs_to_names, index=
    ↪ abbrs_to_names, inplace=True)

df_to_latex(
    df_true_answer_association, '
        ↪ df_true_answer_association_formatted',
    caption="Association between Problem Complexity and True
        ↪ Answer",
    note="Chi-square test results for the association between
        ↪ problem complexity and the distribution of true answers.
        ↪ ",
    glossary=glossary
)
```

Created by data-to-paper (AI)

```
## Process df_true_answer_distribution:
df_true_answer_distribution = pd.read_pickle('
    ↪ df_true_answer_distribution.pkl')

# Rename columns to match glossary mappings
df_true_answer_distribution.rename(columns={
    '33': 'Answer 33',
    '116': 'Answer 116',
    '104': 'Answer 104',
    '149': 'Answer 149',
    '197': 'Answer 197',
    '23': 'Answer 23',
    '248': 'Answer 248',
    '25': 'Answer 25',
    '601': 'Answer 601',
    '809': 'Answer 809'
}, inplace=True)

# Rename rows and columns:
mapping = dict((k, v) for k, v in all_mapping.items() if
    ↪ is_str_in_df(df_true_answer_distribution, k))
abbrs_to_names, glossary = split_mapping(mapping)
df_true_answer_distribution.rename(columns=abbrs_to_names, index=
    ↪ abbrs_to_names, inplace=True)

df_to_figure(
    df_true_answer_distribution, '
        ↪ df_true_answer_distribution_formatted',
    caption="Distribution of Top 10 True Answers by Problem
        ↪ Complexity",
    note="This figure illustrates the distribution of the top 10
        ↪ most frequent true answers in relation to problem
        ↪ complexity. Complexity levels are categorized as 'Simple
        ↪ ' or 'Complex'.",
    glossary=glossary,
    kind='bar',
    y=df_true_answer_distribution.columns.tolist(),
    xlabel="Complexity Level",
    ylabel="Proportion of True Answers"
)
```

D.2 Provided Code

The code above is using the following provided functions:

```
def df_to_latex(df,
```

Created by data-to-paper (AI)

```
        filename: str, caption: str,
        note: str = None,
        glossary: Dict[Any, str] = None,
    ):
    """
    Saves a DataFrame `df` and creates a LaTeX table.
    `filename`, `caption`: as in `df.to_latex`.
    `note`: Note to be added below the table caption.
    `glossary`: Glossary for the table.
    """


def df_to_figure(
        df, filename: str, caption: str,
        note: str = None, glossary: Dict[Any, str] = None,
        x: Optional[str] = None, y: List[str] = None,
        kind: str = 'bar',
        logx: bool = False, logy: bool = False,
        y_ci: Optional[List[str]] = None,
        y_p_value: Optional[List[str]] = None,
        xlabel: str = None, ylabel: str = None,
    ):
    """
    Save a DataFrame `df` and create a LaTeX figure.
    Parameters, for LaTex embedding of the figure:
    `filename`: Filename for the figure.
    `caption`: Caption for the figure.
    `note`: Note to be added below the figure caption.
    `glossary`: Glossary for the figure.

    Parameters for df.plot():
    `x`: Column name for x-axis (index by default).
    `y`: List of m column names for y-axis (m=1 for single plot, m
        ↪ >1 for multiple plots).
    `kind`: only bar is allowed.
    `logx` / `logy` (bool): log scale for x/y axis.
    `xlabel`: Label for the x-axis.
    `ylabel`: Label for the y-axis.

    `y_ci`: Confidence intervals for errorbars.
        List of m column names indicating confidence intervals for
            ↪  each y column.
        Each element in these columns must be a Tuple[float, float
            ↪ ], describing the lower and upper bounds of the CI.

     `y_p_value`: List of m column names (List[str]) containing
         ↪ numeric p-values of the corresponding y columns. These
         ↪ numeric values will be automatically converted by
         ↪ df_to_figure to stars ('***', '**', '*', 'ns') and
```

Created by data-to-paper (AI)

```
        ↪ plotted above the error bars.

    If provided, the length of `y_ci`, and `y_p_value` should be
        ↪ the same as of `y`.

    Example:
    Suppose, we have:

    df_lin_reg_longevity = pd.DataFrame({
        'adjusted_coef': [0.4, ...], 'adjusted_coef_ci': [(0.35,
            ↪ 0.47), ...], 'adjusted_coef_pval': [0.012, ...],
        'unadjusted_coef': [0.2, ...], 'unadjusted_coef_ci':
            ↪ [(0.16, 0.23), ...], 'unadjusted_coef_pval':
            ↪ [0.0001, ...],
    }, index=['var1', ...])

    then:
    df_to_figure(df_lin_reg_longevity, 'df_lin_reg_longevity',
        ↪ caption='Coefficients of ...', kind='bar',
        y=['adjusted_coef', 'unadjusted_coef'],
        y_ci=['adjusted_coef_ci', 'unadjusted_coef_ci'],
        y_p_value=['adjusted_coef_pval', 'unadjusted_coef_pval'])
    """


def is_str_in_df(df: pd.DataFrame, s: str):
    return any(s in level for level in getattr(df.index, 'levels',
        ↪  [df.index]) + getattr(df.columns, 'levels', [df.columns
        ↪ ]))

AbbrToNameDef = Dict[Any, Tuple[Optional[str], Optional[str]]]

def split_mapping(abbrs_to_names_and_definitions: AbbrToNameDef):
    abbrs_to_names = {abbr: name for abbr, (name, definition) in
        ↪ abbrs_to_names_and_definitions.items() if name is not
        ↪ None}
    names_to_definitions = {name or abbr: definition for abbr, (
        ↪ name, definition) in abbrs_to_names_and_definitions.
        ↪ items() if definition is not None}
    return abbrs_to_names, names_to_definitions
```

D.3 Code Output

df_desc_stat_formatted.pkl

```
\begin{table}[h]
\caption{Descriptive Statistics of True Answers in the Dataset}
\label{table:df-desc-stat-formatted}
```

Created by data-to-paper (AI)

```
\begin{threeparttable}
\renewcommand{\TPTminimum}{\linewidth}
\makebox[\linewidth]{%
\begin{tabular}{lr}
\toprule
 & Count \\
true\_answer &  \\
\midrule
\textbf{Option B} & 5 \\
\textbf{Option A} & 5 \\
\textbf{Answer 33} & 1 \\
\textbf{Answer 23} & 1 \\
\textbf{Answer 116} & 1 \\
\textbf{Answer 809} & 1 \\
\textbf{Answer 197} & 1 \\
\textbf{907} & 1 \\
\textbf{Answer 248} & 1 \\
\textbf{Answer 104} & 1 \\
\textbf{Answer 601} & 1 \\
\textbf{Answer 25} & 1 \\
\textbf{Answer 149} & 1 \\
\bottomrule
\end{tabular}}
\begin{tablenotes}
\footnotesize
\item This table provides the number of times each answer is the
    true answer across the dataset, excluding option 'C'.
\item \textbf{Count}: Number of occurrences
\item \textbf{Option A}: Answer option labeled as A
\item \textbf{Option B}: Answer option labeled as B
\item \textbf{Answer 104}: A numeric answer option: 104
\item \textbf{Answer 116}: A numeric answer option: 116
\item \textbf{Answer 149}: A numeric answer option: 149
\item \textbf{Answer 197}: A numeric answer option: 197
\item \textbf{Answer 23}: A numeric answer option: 23
\item \textbf{Answer 248}: A numeric answer option: 248
\item \textbf{Answer 25}: A numeric answer option: 25
\item \textbf{Answer 33}: A numeric answer option: 33
\item \textbf{Answer 601}: A numeric answer option: 601
\item \textbf{Answer 809}: A numeric answer option: 809
\end{tablenotes}
\end{threeparttable}
\end{table}
```

df_true_answer_association_formatted.pkl

```
\begin{table}[h]
\caption{Association between Problem Complexity and True Answer}
\label{table:df-true-answer-association-formatted}
```

Created by data-to-paper (AI)

```
\begin{threeparttable}
\renewcommand{\TPTminimum}{\linewidth}
\makebox[\linewidth]{%
\begin{tabular}{lrl}
\toprule
 & Chi-square Statistic & P-value \\
\midrule
\textbf{Association} & 19.09 & 0.12 \\
\bottomrule
\end{tabular}}
\begin{tablenotes}
\footnotesize
\item Chi-square test results for the association between problem
    complexity and the distribution of true answers.
\item \textbf{Chi-square Statistic}: Chi-square statistic value
    for the test
\item \textbf{P-value}: Probability value for the association test
     results
\end{tablenotes}
\end{threeparttable}
\end{table}
```

df_true_answer_distribution_formatted.pkl

```
\begin{figure}[htbp]
\centering
\includegraphics{df_true_answer_distribution_formatted.png}
\caption{Distribution of Top 10 True Answers by Problem Complexity
This figure illustrates the distribution of the top 10 most
    frequent true answers in relation to problem complexity.
    Complexity levels are categorized as 'Simple' or 'Complex'.
Complex: Higher complexity level of problem.
Simple: Lower complexity level of problem.}
\label{figure:df-true-answer-distribution-formatted}
\end{figure}
% This latex figure presents "
    df_true_answer_distribution_formatted.png",
% which was created from the df:
%
% index,"Answer 104","Answer 116","Answer 149","Answer 197","
    Answer 23","Answer 248","Answer 25","Answer 33","Answer 601","
    Answer 809"
% "Complex",0,0.07143,0,0,0.07143,0,0,0,0,0.07143
% "Simple",0.07143,0,0.07143,0.07143,0,0.07143,0.07143,0.07143,
    0.07143,0
%
% To create the figure, this df was plotted with the command:
%
% df.plot(kind='bar', y=['Answer 104', 'Answer 116', 'Answer 149',
```

```
 'Answer 197', 'Answer 23', 'Answer 248', 'Answer 25', 'Answer
 33', 'Answer 601', 'Answer 809'], xlabel='Complexity Level',
ylabel='Proportion of True Answers')
```

Created by data-to-paper (AI)