

FileEditOptionsViewToolsExtensionsHelp

Logical[Root]

New ClusterMove ObjectSet Tiled BackgroundView

Router-PT
Router0

20.0.0.1
Fa0/0
10.0.0.1

PC-PT
PC0
10.0.0.10
Def gateway 10.0.0.1

Router-PT
Router1

20.0.0.2
Se2/0
30.0.0.1
Se3/0

Router-PT
Router2

30.0.0.2
Se3/0
40.0.0.1
Fa0/0

PC-PT
PC1
40.0.0.10
Def gateway 40.0.0.1

Router2

PhysicalConfigCLI

IOS Command Line Interface

```
Router#config terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#ip address 30.0.0.2 255.0.0.0
Router(config-if)#
% Invalid input detected at '^' marker.

Router(config)#interface serial 3/0
Router(config-if)#ip address 30.0.0.2 255.0.0.0
Router(config-if)#no shut

%LINK-5-CHANGED: Interface Serial3/0, changed state to down
Router(config-if)#exit
Router(config)#interface fastEthernet 1/0
Router(config-if)#ip address 40.0.0.1 255.0.0.0
Router(config-if)#no shut

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet1/0, changed state to up
%LINK-5-CHANGED: Interface Serial3/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Serial3/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet1/0, changed state to up
```

CopyPaste

Time: 00:23:57Power Cycle DevicesFast Forward Time

Scenario 0

FireLast StatusSourceDestinationTypeColorTime(sec)PeriodicNumEditDelete

NewDelete

Toggle PDU List Window

Connections

Console