

Class: CL_JVA_EQUITY_ADJUST

Status: Active

Implemented interfaces

IF_JVA_EQUITY_ADJUST (Interface for Equity Adjustment)

Attributes

Description: Equity Adjustment for JVA

Instantiation: Public

Not final

Not released

Fixed Point Arithmetic

Program status: SAP Standard Production Program

Category: General Object Type

Package: GJVA

Original lang.: EN

Created by: SAP

Created On: 27.12.2018

Last changed on: 09.01.2024

Forward declaration type grps.

ABAP

Forward declaration interfaces

CL_JVA_EQUITY_ADJUST

Attributes

Private attribute

Attrib. Ref.	Cat	Description	Init. value
MV_BELNR_TEST TYPE NUMC06	Inst	Document number for testing	
MV_MESSAGE_TEXT TYPE STRING	Inst	Message Text	
MO_APPLICATION_LOG TYPE REF TO IF_JVA_MESSAGE_OUTPUT	Inst		
MO_CUTBACK TYPE REF TO IF_JVA_CUTBACK	Inst		
MO_MESSAGE_COLLECTOR TYPE REF TO IF_JVA_MESSAGE_COLLECTION	Inst		
MO_MESSAGE_OUTPUT TYPE REF TO IF_JVA_MESSAGE_OUTPUT	Inst		
MO_OUTPUT TYPE REF TO IF_JVA_OUTPUT	Inst		
MS_ALV_CALLBACK_DATA TYPE GTY_S_ALV_CALLBACK_DATA	Inst		
MS_CB_RESULTS TYPE JVA_CB_RESULTS	Inst		

Attrib. Ref. Type	Cat	Description	Init. value
MS_EA_RESULTS TYPE JVA_EA_RESULTS	Inst		
MS_PROGPARS TYPE JVA_EA_PROGPARS	Inst		
MS_SETTINGS TYPE JVA_EA_SETTINGS	Inst		
MO_JVA_POST_ACDOCA TYPE REF TO IF_JVA_POST_ACDOCA	Inst	Post ACDOCA document	
MO_PARTNER_SHARES TYPE REF TO IF_JVA_PARTNER_SHARES	Inst	JVA partner share calculations	
MO_OUTPUT_SPOOL TYPE REF TO IF_JVA_EQUITY_ADJUST_OUTPUT	Inst	Interface for equity adjustment printing	
MV_PROCESS TYPE T8JEV-PROCESS	Inst		
GC_PROCESS_EQAD TYPE T8JEV-PROCESS	Const		'EQAD'
GC_PROCESS_FARM TYPE T8JEV-PROCESS	Const		'FARM'
GC_EVENT_AGGREGATED TYPE T8JEVP-PARAM	Const		'P_AGGREG'

Intern. types

Private types

Cat	Cat	Ref. Type	Description
GTY_S_INTCO_SETTL_ACCT	TYPE		
GTY_S_ACDOCA_CHECK	TYPE		
GTY_T_ACDOCA_CHECK	TYPE		
GTY_S_ACDOCA_AGGREGATED	TYPE		
GTY_T_ACDOCA_AGGREGATED	TYPE		
GTY_S_DISP	TYPE		
GTY_S_BELNR	TYPE		
GTY_S_ALV_INFOS	TYPE		
GTY_S_ALV_CALLBACK_DATA	TYPE		

Methods

Private methods

ADD_ACCIT_LINE_CASHCALL

Description: Add correcrtion line to
Instance mthd

Importing parameter

VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)
VALUE(IV_SELFCLEARING) TYPE ABAP_BOOL (Create the document as self-clearing document)

Changing parameter

CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING

```
method add_accit_line_cashcall.  
  data: lv_fatal_error type abap_bool,  
        lv_error_text  type string.  
  cs_accit-jvactivity = iv_jvactivity.  
  cs_accit-awtyp = 'BKPFF'.      "AW type  
  cs_accit-mandt = sy-mandt.     "Client  
  cs_accit-bukrs = is_acdoca-rbukrs. "Company code  
  cs_accit-posnr = iv_buzei.     "Line number  
*  Venture data  
  cs_accit-vname = is_acdoca-vname. "Venture  
  cs_accit-egrup = is_acdoca-egrup. "Equity group  
  cs_accit-recid = is_acdoca-recid. "Recovery indicator  
  cs_accit-prctr = is_acdoca-prctr. "Profit center  
  cs_accit-segment = is_acdoca-segment. "Segment  
  if not is_acdoca-lifnr is initial.  
    cs_accit-lifnr = is_acdoca-lifnr.  
    "Get the payment terms  
    select single zterm from lfb1 into cs_accit-zterm  
      where bukrs = cs_accit-bukrs  
      and lifnr = cs_accit-lifnr.  
    clear cs_accit-hkont.  
  elseif not is_acdoca-kunnr is initial.  
    cs_accit-kunnr = is_acdoca-kunnr.  
    "Get the payment terms  
    select single zterm from knb1 into cs_accit-zterm  
      where bukrs = cs_accit-bukrs  
      and kunnr = cs_accit-kunnr.  
    clear cs_accit-hkont.  
  else.  
    cs_accit-hkont = is_acdoca-racct.  
  endif.  
  cs_accit-blart = ms_settings-s_t8j0f-doctyped. "Document type  
  set_posting_indicators( exporting  
    iv_jvfunc      = iv_jvfunc  
    iv_jvactivity  = iv_jvactivity  
    is_acdoca      = is_acdoca  
    changing  
    cs_accit       = cs_accit  
    cv_fatal_error = lv_fatal_error  
    cv_error_text  = lv_error_text ).  
  if iv_selfclearing = abap_true.
```

```

    cs_accit-augbl = '*'.
    endif.
    append cs_accit to ct_accit.
    fill_accctr( exporting
                  is_accit      = cs_accit
                  is_acdoca     = is_acdoca
                  iv_rwcur      = is_acdoca-rwcur
                  is_curr_info  = ms_settings-s_curr_info
                  changing
                  ct_accctr     = ct_accctr ).
    if lv_fatal_error = 'X'.
        cv_fatal_error = 'X'.
        if cv_error_text is initial.
            cv_error_text = lv_error_text.
        endif.
    endif.
endmethod.
```

ADD_ACCIT_LINE_CORRECTION

Description: Add correction line to
Instance mthd

Importing parameter

- VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
- VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
- VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
- VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)

Changing parameter

- CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
- CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
- CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
- CV_FATAL_ERROR TYPE C
- CV_ERROR_TEXT TYPE STRING

```

method add_accit_line_correction.
    data: lv_fatal_error type abap_bool,
          lv_error_text  type string.
    cs_accit-jvactivity = iv_jvactivity.
    cs_accit-posnr = iv_buzei.
    cs_accit-egrup = is_acdoca-egrup.
    cs_accit-vptnr = is_acdoca-vptnr.
    if not is_acdoca-lifnr is initial.
        cs_accit-lifnr = is_acdoca-lifnr.
        clear cs_accit-hkont.
    elseif not is_acdoca-kunnr is initial.
        cs_accit-kunnr = is_acdoca-kunnr.
        clear cs_accit-hkont.
    else.
        cs_accit-hkont = is_acdoca-racct.
    endif.
    cs_accit-koart = is_acdoca-koart.
    set_posting_indicators( exporting
                            iv_jvfunc      = iv_jvfunc
                            iv_jvactivity = iv_jvactivity
```

```

        is_acdoca      = is_acdoca
    changing
        cs_accit       = cs_accit
        cv_fatal_error = lv_fatal_error
        cv_error_text  = lv_error_text ).
append cs_accit to ct_accit.
fill_accr( exporting
    is_accit      = cs_accit
    is_acdoca     = is_acdoca
    iv_rwcur      = is_acdoca-rwcur
    is_curr_info  = ms_settings-s_curr_info
    changing
        ct_accr   = ct_accr ).
if lv_fatal_error = 'X'.
    cv_fatal_error = 'X'.
    if cv_error_text is initial.
        cv_error_text = lv_error_text.
    endif.
endif.
endmethod.
```

ADD_ACCIT_LINE_SETTLEMENT

Description: Add settlement line to FI document
Instance mthd

Importing parameter

- VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
- VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
- IV_JVACTIVITY TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
- VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)

Changing parameter

- CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
- CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
- CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
- CV_FATAL_ERROR TYPE C
- CV_ERROR_TEXT TYPE STRING

```

method add_accit_line_settlement.
    cs_accit-jvactivity = iv_jvactivity.
    cs_accit-posnr = iv_buzei.
    cs_accit-egrup = is_acdoca-egrup.
    cs_accit-vptnr = is_acdoca-vptnr.
    cs_accit-hkont = is_acdoca-racct.
    "Clear customer and vendor number
    clear: cs_accit-kunnr,
           cs_accit-lifnr.
    cs_accit-koart = is_acdoca-koart.
    set_posting_indicators( exporting
        iv_jvfunc      = iv_jvfunc
        iv_jvactivity  = iv_jvactivity
        is_acdoca      = is_acdoca
    changing
        cs_accit       = cs_accit
        cv_fatal_error = cv_fatal_error
```

```

                                cv_error_text  = cv_error_text ).
append cs_accit to ct_accit.
fill_accchr( exporting
              is_accit      = cs_accit
              is_acdoca     = is_acdoca
              iv_rwcur      = is_acdoca-rwcur
              is_curr_info  = ms_settings-s_curr_info
              changing
              ct_accchr     = ct_accchr ).

endmethod.
```

ADD_FIDOC_HEADER

Description: Add FI doc header
Instance mthd

Changing parameter

CT_ACCHD TYPE ACCHD_T (Transfer Table: Header Information for FI Documents)

```

method add_fidoc_header.
  data: lv_hd_text(25) type c,
        ls_acchd      type acchd.
  lv_hd_text = 'Cash Call Adjustment'  ##NO_TEXT.
  ls_acchd-mandt = sy-mandt.
  ls_acchd-awtyp = 'BKPFF'.
  ls_acchd-glvor = 'RFBU'.
  ls_acchd-tcode = sy-tcode.
  ls_acchd-usnam = sy-uname.
  ls_acchd-cpudt = sy-datum.
  ls_acchd-cputm = sy-uzeit.
  ls_acchd-bktxt = lv_hd_text.
  append ls_acchd to ct_acchd.
endmethod.
```

ADD_GENERAL_INFORMATION

Description: Add general information for output
Instance mthd

```

method add_general_information.
  data: lv_text type string.
*   Add info about test or real run
  lv_text = text-rty && |:|.
  if ms_progpars-analysis_only = abap_true.
    lv_text = lv_text && text-ano.
  elseif ms_progpars-test = abap_true.
    lv_text = lv_text && text-tst.
  else.
    lv_text = lv_text && text-rru.
  endif.
  add_info( exporting
            iv_info_text = lv_text
            changing
            ct_infos_print = ms_ea_results-t_infos ).
  if ms_ea_results-t_print_ec[] is initial.
    lv_text = text-nod.
```

```
else.
  lv_text = text-ner && |: | && ms_ea_results-no_of_errors.
endif.
add_info( exporting
          iv_info_text = lv_text
          changing
          ct_infos_print = ms_ea_results-t_infos ).
endmethod.
```

ADD_INFO

Description: Add info about errors in the settings

Instance mthd

Importing parameter

IV_INFO_TEXT TYPE ANY

Changing parameter

CT_INFOS_PRINT TYPE JVA_INFO_PRINT_T (Info text to be printed)

```
method add_info.
  data: ls_infos_print type jva_info_print.
  ls_infos_print-text = iv_info_text.
  append ls_infos_print to ct_infos_print.
endmethod.
```

ADD_ITEM_TO_FIELDCATALOG

Description: Add an item to a field catalog for ACDOCA selects

Instance mthd

Importing parameter

IT_DFIES TYPE DFIES_TABLE (DD Interface: Table Fields for DDIF_FIELDINFO_GET)

IV_FIELDNAME TYPE FIELDNAME (Field Name)

Changing parameter

CS_DFIES TYPE DFIES (DD Interface: Table Fields for DDIF_FIELDINFO_GET)

CT_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)

```
method add_item_to_fieldcatalog.
  data: ls_fieldcatalog type lvc_s_fcat,
        lv_tabix       type sy-tabix.
  clear cs_dfies.
*  Check if the item is already in the field catalog
  read table ct_fieldcatalog transporting no fields
                        with key fieldname = iv_fieldname
                        binary search.

  lv_tabix = sy-tabix.
  if sy-subrc > 2.
*  Add the item to the field catalog
  read table it_dfies into cs_dfies
                        with key fieldname = iv_fieldname
                        binary search.

  if sy-subrc = 0.
    move-corresponding cs_dfies to ls_fieldcatalog.
    insert ls_fieldcatalog into ct_fieldcatalog index lv_tabix.
  endif.
endif.
```

endmethod.

ADD_ITEM_TO_SELECT_TABLES

Description: Add item to tables used for database selects

Instance mthd

Importing parameter

IT_DFIES TYPE DFIES_TABLE (Table for dfies entries)

IV_FIELDNAME TYPE FIELDNAME (Field Name)

Changing parameter

CT_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)

CT_SEL_FIELDS TYPE RSDD_T_COMPNAME

CT_GROUP_FIELDS TYPE RSDD_T_COMPNAME

```
method add_item_to_select_tables.  
  data: ls_dfies      type dfies,  
        lv_strlen    type i,  
        ls_sel_fields like line of ct_sel_fields.  
  "Do not add the following fields  
  if iv_fieldname = 'EPRCTR' or  
    iv_fieldname = 'PSEGMENT' or  
    iv_fieldname = 'PS_POSID' or  
    iv_fieldname = 'RFAREA' or  
    iv_fieldname = 'RMVCT' or  
    iv_fieldname = 'AFABE' or  
    iv_fieldname = 'ANLGR' or  
    iv_fieldname = 'ANLGR2' or  
    iv_fieldname = 'BWKEY' or  
    iv_fieldname = 'BWTAR' or  
    iv_fieldname = 'CO_OSL' or  
    iv_fieldname = 'FCSL' or  
    iv_fieldname = 'GLACCOUNT_TYPE' or  
    iv_fieldname = 'HBKID' or  
    iv_fieldname = 'HKTID' or  
    iv_fieldname = 'HVKWRT' or  
    iv_fieldname = 'KALNR' or  
    iv_fieldname = 'KDAUF' or  
    iv_fieldname = 'KDPOS' or  
    iv_fieldname = 'KOART' or  
    iv_fieldname = 'KTOP2' or  
    iv_fieldname = 'KTOPL' or  
    iv_fieldname = 'KZBWS' or  
    iv_fieldname = 'LOKKT' or  
    iv_fieldname = 'MAT_KDAUF' or  
    iv_fieldname = 'MAT_KDPOS' or  
    iv_fieldname = 'MAT_LIFNR' or  
    iv_fieldname = 'MOVCAT' or  
    iv_fieldname = 'PEGRUP' or  
    iv_fieldname = 'PERIV' or  
    iv_fieldname = 'PFSL' or  
    iv_fieldname = 'PKDAUF' or  
    iv_fieldname = 'PKDPOS' or  
    iv_fieldname = 'PPS_POSID' or  
    iv_fieldname = 'PPS_PSP_PNR' or
```

```
iv_fieldname = 'PSL' or
iv_fieldname = 'PS_PRJ_PNR' or
iv_fieldname = 'PS_PSPID' or
iv_fieldname = 'PVNAME' or
iv_fieldname = 'QUANT1' or
iv_fieldname = 'QUANT2' or
iv_fieldname = 'QUANT3' or
iv_fieldname = 'RASSC' or
iv_fieldname = 'RBUNIT' or
iv_fieldname = 'RBUPTR' or
iv_fieldname = 'RCLNT' or
iv_fieldname = 'RCOMP' or
iv_fieldname = 'RCO_OCUR' or
iv_fieldname = 'RFCCUR' or
iv_fieldname = 'RHOART' or
iv_fieldname = 'RISK_CLASS' or
iv_fieldname = 'RITCLG' or
iv_fieldname = 'RITEM' or
iv_fieldname = 'RRCTY' or
iv_fieldname = 'RTCUR' or
iv_fieldname = 'RVUNIT' or
iv_fieldname = 'SBUSA' or
iv_fieldname = 'SCNTR' or
iv_fieldname = 'SITYP' or
iv_fieldname = 'SLALITTYPE' or
iv_fieldname = 'SOBKZ' or
iv_fieldname = 'SUBIT' or
iv_fieldname = 'TSL' or
iv_fieldname = 'VALOBJTYPE' or
iv_fieldname = 'VALOBJ_ID' or
iv_fieldname = 'VALSOBJ_ID' or
iv_fieldname = 'VMSL' or
iv_fieldname = 'VRGNG' or
iv_fieldname = 'XOB EW' or
iv_fieldname = 'PPRCTR'.
return.
endif.
* Do not add the currency fields, except for the document currency
lv_strlen = strlen( iv_fieldname ).
if lv_strlen = 5 and iv_fieldname(1) = 'R' and iv_fieldname+2(3) = 'CUR'.
  if iv_fieldname <> 'RWCUR'.
    return.
  endif.
endif.
try.
  cl_abap_dyn_prg=>check_column_name( iv_fieldname ).
  catch cx_abap_invalid_name.
    return.
endtry.
* Add item to the fieldcatalog
add_item_to_fieldcatalog( exporting
                          it_dfies      = it_dfies
                          iv_fieldname  = iv_fieldname
                          changing
```

```

                                ct_fieldcatalog = ct_fieldcatalog
                                cs_dfies       = ls_dfies ).
if not ls_dfies is initial.
  if ls_dfies-sign = abap_true.
    ls_sel_fields-compname = |SUM( { iv_fieldname } ) AS { iv_fieldname }|.
  else.
    ls_sel_fields-compname = iv_fieldname.
*   Add item to group-by list
    append iv_fieldname to ct_group_fields.
  endif.
*   Add item to list of fields to be selected
    append ls_sel_fields to ct_sel_fields.
  endif.
endmethod.
```

ADJUST_CASHCALL_EG

Description: Adjust the cash call postings for equity group
Instance mthd

Changing parameter

```

CV_NO_DIFFERENCES TYPE ABAP_BOOL

method adjust_cashcall_eg.
  data: lv_bukrs      type bukrs,
        lt_bilind_cutb type jva_bilind_range_t,
        lt_bilind_pay  type jva_bilind_range_t,
        lt_acdoca_cc1  type gty_t_acdoca_check,
        lt_acdoca_cb   type jva_cb_acdoca_t,
        lv_error       type abap_bool.
  check_shares_cc1( changing
                    cv_no_differences = cv_no_differences ).
  if cv_no_differences = abap_true.
    return.
  endif.
*   First get the billing indicators to be EXcluded from ACDOCA select
  get_billind_range_cutback( exporting
                             iv_bukrs = ms_progpars-bukrs
                             iv_sign  = 'E'
                             importing
                             et_bilind = lt_bilind_cutb ).
*   Now get the billing indicator needed for zero balance checking
  get_billind_range_payments( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'I'
                              importing
                              et_bilind = lt_bilind_pay ).
  sort ms_settings-t_diff_share by partn_old.
  loop at ms_settings-t_diff_share into data(ls_diff_share).
    get_data_cc1( exporting
                  it_bilind_cutb = lt_bilind_cutb
                  it_bilind_pay  = lt_bilind_pay
                  is_diff_share  = ls_diff_share
                  changing
                  ct_acdoca_cc1  = lt_acdoca_cc1
```

```

                                cv_error      = lv_error ).
if lv_error <> abap_true and
  lines( lt_acdoca_cc1 ) > 0.
  prepare_equity_change( exporting
                        iv_jvfunc      = 'FACC'
                        iv_vname_new   = ms_progpars-vname
                        iv_egrup_new   = ms_progpars-eqnew
                        changing
                        ct_acdoca_main = lt_acdoca_cc1
                        ct_acdoca_cb  = lt_acdoca_cb ).
endif.
endloop.
endmethod.

```

ADJUST_CASHCALL_EG_INTCO

Description: Adjust the cash call postings for equity group

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method adjust_cashcall_eg_intco.
  data: lv_bukrs      type bukrs,
        lt_bilind_cutb type jva_bilind_range_t,
        lt_bilind_pay  type jva_bilind_range_t,
        lt_acdoca_cc1  type gty_t_acdoca_check,
        lt_acdoca_cb   type jva_cb_acdoca_t,
        lv_error       type abap_bool.
  check_shares_cc1_intco( changing
                        cv_no_differences = cv_no_differences ).
  if cv_no_differences = abap_true.
    return.
  endif.
* First get the billing indicators to be EXcluded from ACDOCA select
  get_billind_range_cutback( exporting
                            iv_bukrs = ms_progpars-bukrs
                            iv_sign  = 'E'
                            importing
                            et_bilind = lt_bilind_cutb ).
* Now get the billing indicator needed for zero balance checking
  get_billind_range_payments( exporting
                             iv_bukrs = ms_progpars-bukrs
                             iv_sign  = 'I'
                             importing
                             et_bilind = lt_bilind_pay ).
  sort ms_settings-t_diff_share by intcocd_old
                                     intrcovent_old
                                     intcompegp_old
                                     partn_old.
  loop at ms_settings-t_diff_share into data(ls_diff_share).
    get_data_cc1_intco( exporting
                      it_bilind_cutb = lt_bilind_cutb
                      it_bilind_pay  = lt_bilind_pay
                      is_diff_share  = ls_diff_share

```

```

        changing
        ct_acdoca_cc1 = lt_acdoca_cc1
        cv_error      = lv_error ).
if lv_error <> abap_true and
  lines( lt_acdoca_cc1 ) > 0.
  prepare_equity_change( exporting
    iv_jvfunc      = 'FACC'
    iv_vname_new   = ls_diff_share-intrcovent_new
    iv_egrup_new    = ls_diff_share-intcompegp_new
    changing
    ct_acdoca_main = lt_acdoca_cc1
    ct_acdoca_cb   = lt_acdoca_cb ).
endif.
endloop.
endmethod.
```

ADJUST_CASHCALL_EQUITY_GROUP

Description: Adjust the cash call postings for equity group

Instance mthd

```

method adjust_cashcall_equity_group.
  data: lv_no_differences type abap_bool,
        lv_no_differences_intco type abap_bool.
  if ms_progpars-test <> abap_true.
*    Commit work and wait must be executed because this step
*    requires the documents of the previous steps to be posted
    mo_output->commit_work_and_wait( ).
    set update task local.
  endif.
  adjust_cashcall_eg( changing
    cv_no_differences = lv_no_differences ).
  adjust_cashcall_eg_intco( changing
    cv_no_differences = lv_no_differences_intco ).
*  If the shares of the partners are identical, issue an information message
  if lv_no_differences = abap_true and
    lv_no_differences_intco = abap_true.
    message i799(g5) with text-ndi
      ms_progpars-eqnew
      ms_progpars-vname
      into mv_message_text.
    save_sy_message( ).
  endif.
endmethod.
```

ADJUST_CASHCALL_PARTNERS

Description: Prepare the adjustment postings for intercompany cash call

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method adjust_cashcall_partners.
  data: lt_acdoca type gty_t_acdoca_check,
        lt_acdoca_posted type gty_t_acdoca_check,
```

```

        lr_acdoca_dyn      type ref to data,
        lr_acdoca_dyn_posted type ref to data.
check_shares_cc2( changing
                    cv_no_differences = cv_no_differences ).
if cv_no_differences = abap_true.
    return.
endif.
get_data_cc2( changing
              ct_acdoca      = lt_acdoca
              ct_acdoca_posted = lt_acdoca_posted
              cr_acdoca_dyn   = lr_acdoca_dyn
              cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).
prepare_cc_adjustments( exporting
                       iv_jvfunc      = 'FAC2'
                       changing
                       ct_acdoca_check = lt_acdoca
                       ct_acdoca_posted = lt_acdoca_posted
                       cr_acdoca_dyn   = lr_acdoca_dyn
                       cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).

endmethod.

```

ADJUST_CASHCALL_PARTNERS_INTCO

Description: Adjust the intercompany partner postings

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method adjust_cashcall_partners_intco.
data: lt_acdoca      type gty_t_acdoca_check,
      lt_acdoca_posted type gty_t_acdoca_check,
      lr_acdoca_dyn   type ref to data,
      lr_acdoca_dyn_posted type ref to data.
check_shares_cc2_intco( changing
                       cv_no_differences = cv_no_differences ).
if cv_no_differences = abap_true.
    return.
endif.
sort ms_settings-t_diff_share_intco by partn_old intcompegp_old.
get_data_cc2_intco( changing
                   ct_acdoca      = lt_acdoca
                   ct_acdoca_posted = lt_acdoca_posted
                   cr_acdoca_dyn   = lr_acdoca_dyn
                   cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).
prepare_cc_adjustments_intco( exporting
                             iv_jvfunc      = 'FAC1'
                             changing
                             ct_acdoca_check = lt_acdoca
                             ct_acdoca_posted = lt_acdoca_posted
                             cr_acdoca_dyn   = lr_acdoca_dyn
                             cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).

endmethod.

```

ADJUST_CASHCALL_PARTNER_SHARES

Description: Adjust the partner shares of cash call postings

Instance mthd

```
method adjust_cashcall_partner_shares.  
  data: lv_no_differences      type abap_bool,  
        lv_no_differences_intco type abap_bool.  
  if ms_progpars-test <> abap_true.  
*    Commit work and wait must be executed because this step  
*    requires the documents of the previous steps to be posted  
    mo_output->commit_work_and_wait( ).  
    set update task local.  
  endif.  
  adjust_cashcall_partners( changing  
                           cv_no_differences = lv_no_differences ).  
  adjust_cashcall_partners_intco( changing  
                                  cv_no_differences = lv_no_differences_intco ).  
*  If the shares of the partners are identical, issue an information message  
  if lv_no_differences      = abap_true and  
    lv_no_differences_intco = abap_true.  
    message i799(g5) with text-ndi  
                        ms_progpars-eqnew  
                        ms_progpars-vname  
                        into mv_message_text.  
    save_sy_message( ).  
  endif.  
endmethod.
```

ADJUST_CUTBACK_RESULTS

Description: Adjust the cutback results

Instance mthd

Importing parameter

```
IT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T
```

```
method adjust_cutback_results.  
  data: ls_venture type jva_cb_venture,  
        lv_cbdctx  type jv_text22.  
  if ms_progpars-test <> abap_true.  
*    Commit work and wait must be executed because cutback  
*    will need to update the equity adjustment postings with  
*    the cutback run-id  
    mo_output->commit_work_and_wait( ).  
    set update task local.  
  endif.  
  move-corresponding ms_settings-s_t8jv to ls_venture  ##ENH_OK.  
  lv_cbdctx = ms_progpars-bktxt.  
  "Determine the caller ID  < 3553287  
  if ms_progpars-farm_in_out = abap_true.  
    data(lv_caller) = if_jva_cutback=>types-farm.  
  else.  
    lv_caller = if_jva_cutback=>types-eqad.  
  endif.
```

```

*   Set cutback parameters
    mo_cutback->set_run_parameters( iv_caller      = lv_caller
                                   it_bukrs       = value #( ( sign = 'I' option
= 'EQ' low = ms_progpars-bukrs ) )
                                   it_vname       = value #( ( sign = 'I' option
= 'EQ' low = ms_progpars-vname ) )
                                   iv_budat       = ms_progpars-budat
                                   iv_ivpegg      =
ms_progpars-invoice_per_equity_group
                                   iv_ivpptn      =
ms_progpars-invoice_per_partner
                                   iv_ivpexp      =
ms_progpars-invoice_per_expense_item
                                   iv_cbdctx      = lv_cbdctx
                                   iv_curr       = space
                                   iv_error      = space
                                   iv_inter      = abap_true
                                   iv_mxtsks     = 20
                                   iv_one_spool   = abap_true
                                   iv_parall     = space
                                   iv_period     = ms_progpars-period
                                   iv_pfmlog     = space
                                   iv_print      = '3'
                                   iv_rfcgrp     = space
                                   iv_spool_per_bukrs = space
                                   iv_analysis_only = ms_progpars-analysis_only
                                   iv_test       = ms_progpars-test
                                   iv_txdat      = ms_progpars-budat
                                   iv_txdctx     = space
                                   iv_ventsk     = 20
                                   iv_year       = ms_progpars-year
                                   iv_zterm      = space
                                   iv_repid_callback = ms_progpars-repid_callback
                                   iv_egrup_old   = ms_progpars-eqold
                                   iv_egrup_new   = ms_progpars-eqnew
                                   it_shares_old  = ms_settings-t_shares_old[]
                                   it_shares_new  = ms_settings-t_shares_new[]
                                   iv_cbrunid     =
ms_progpars-s_schedman_key-id
                                   iv_no_intco_reposting_for_ea = ms_progpars-icorev
    ).
*   Correct the cutback results
    mo_cutback->run_adjustments( exporting
                                   is_venture    = ls_venture
                                   it_acdoca_cb   = it_acdoca_cb
                                   changing
                                   cs_cb_results = ms_cb_results ).
*   Get max error from cutback processing and set error flag
    set_total_error_flag( exporting
                                   iv_error      = ms_cb_results-max_error
                                   changing
                                   cv_total_error = ms_ea_results-max_error ).

endmethod.

```

ADJUST_EQUITY_GROUP

Description: Make the equity adjustment for the actuals
Instance mthd

Changing parameter

```
CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T

method adjust_equity_group.
  data: lt_acdoca_check   type gty_t_acdoca_check,
        ls_acdoca_check  type gty_s_acdoca_check,
        lt_acdoca_aggr   type gty_t_acdoca_aggregated,
        ls_acdoca_main   type gty_s_acdoca_check,
        lv_is_oi_managed type c,
        lv_tabix         type sy-tabix,
        lt_acdoca_main   type gty_t_acdoca_check.
*   Get the data to be processed
  get_data_ec( changing ct_acdoca_main = lt_acdoca_main
                ct_acdoca_aggr = lt_acdoca_aggr ).
  if lt_acdoca_aggr[] is not initial.
    process_ec_aggregated( exporting
                          iv_jvfunc      = mv_process
                          iv_vname_new   = ms_progpars-vname
                          iv_egrup_new   = ms_progpars-eqnew
                          changing
                          ct_acdoca_aggr = lt_acdoca_aggr
                          ct_acdoca_cb  = ct_acdoca_cb ).
  else.
    prepare_equity_change( exporting
                          iv_jvfunc      = mv_process
                          iv_vname_new   = ms_progpars-vname
                          iv_egrup_new   = ms_progpars-eqnew
                          changing
                          ct_acdoca_main = lt_acdoca_main
                          ct_acdoca_cb  = ct_acdoca_cb ).
  endif.
  get_msgs_from_msg_collector( ).
endmethod.
```

ADJUST_INTERCOMPANY_REVERSAL

Description: Reverse the intercompany postings
Instance mthd

```
method adjust_intercompany_reversal.
  data: lv_no_intco_partner type c,
        lt_acdoca_intco_new type jva_cb_acdoca_t,
        lt_acdoca_intco_old type jva_cb_acdoca_t,
        lv_error           type abap_bool.
  if ms_progpars-test <> abap_true.
*   Commit work and wait must be executed because this step
*   requires the documents of the previous steps to be posted
    mo_output->commit_work_and_wait( ).
    set update task local.
  endif.
```

```

    get_posting_rules( exporting
                        iv_bukrs = ms_progpars-bukrs
                        iv_bmethod = ms_settings-s_t8jv-bmethod
                        iv_function = 'FACN'
                        changing
                        cv_error    = lv_error ).
    "get_settl_account( ).
    check_shares_intco_reversal( changing cv_no_intco_partner = lv_no_intco_partner
).
    check_recid( iv_jvfunc = 'FACN' ).
    get_data_intco( changing ct_acdoca_intco_new = lt_acdoca_intco_new
                        ct_acdoca_intco_old = lt_acdoca_intco_old ).
    if lt_acdoca_intco_new[] is initial.
        return.
    endif.
    prepare_postings_intco( exporting it_acdoca_intco_new = lt_acdoca_intco_new
                                it_acdoca_intco_old = lt_acdoca_intco_old ).

endmethod.
```

APPEND_ADJUST_PRINT_LINE

Description: Append adjustment doc line to print output table
Instance mthd

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)
IV_INTCO TYPE ABAP_BOOL
IS_PRINT TYPE JVA_EA_DOCPRINT (Details of equity adjustment document)

```

method append_adjust_print_line.
    if iv_intco = abap_true.
        append is_print to ms_ea_results-t_print_cc2_intco.
    else.
        append is_print to ms_ea_results-t_print_cc2.
    endif.
endmethod.
```

CALC_CC_CORRECTION_AMOUNT

Description: Calculate cash call correction amount
Instance mthd

Importing parameter

IV_AMNT_OLD TYPE ACDOCA-HSL (Amount in Company Code Currency)
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE

Returning parameter

VALUE(RV_AMNT_DIFF) TYPE ACDOCA-HSL (Amount in Company Code Currency)

```

method calc_cc_correction_amount.
*   calculate the amount for the correction posting
*   example: EG share old: 50%, EG share new: 30%
*           ACDOCA amount: 200 (corresponds to the old 50% share)
*
*   Change amount = ACDCOA-Value (200) * EG new (30) / EG old (50)
*                 - ACDOCA-Value (200)
*
```

```
*      Amount to be posted in example = ( 200 * 30 / 50 ) - 200  = -80
      rv_amnt_diff = ( iv_amnt_old * is_diff_share-eqshare_new /
is_diff_share-eqshare_old )
                  - iv_amnt_old.

      endmethod.
```

CHECK_ADJUSTMENT_DATE

Description: Check the adjustment date
Instance mthd

Importing parameter

IS_T8JG_NEW TYPE T8JG
IS_T8JG_OLD TYPE T8JG

Changing parameter

CV_FRDATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
CV_TODATE TYPE SYST_DATUM (ABAP system field: Current date of application server)

```
method check_adjustment_date.
  data: lv_date_next type sy-datum.
  if ms_progpars-frdate > ms_progpars-todate.
    data(lv_date_range_incons) = abap_true.
  endif.
  if ms_progpars-frdate is initial   or
    ms_progpars-frdate = '@STARTDA' or
    lv_date_range_incons = abap_true.
    data(lv_date_init) = abap_true.
    cv_frdate = is_t8jg_new-fdate.
    translate cv_frdate using '09182736455463728190'.
    ms_progpars-frdate = cv_frdate.
  endif.
  if ms_progpars-todate is initial   or
    ms_progpars-todate = '@STARTDA' or
    lv_date_range_incons = abap_true.
    lv_date_init = abap_true.
*      Get the next equity group and its start date
    select * from t8jg into @data(ls_t8jg_next)
      bypassing buffer
      where bukrs = @is_t8jg_new-bukrs
        and vname = @is_t8jg_new-vname
        and etype = @is_t8jg_new-etype
        and fdate < @is_t8jg_new-fdate
      order by fdate descending.
    lv_date_next = ls_t8jg_next-fdate.
    translate lv_date_next using '09182736455463728190'.
    exit.
  endselect.
  if ls_t8jg_next is initial or
    ms_progpars-budat < lv_date_next.
    cv_todate = ms_progpars-budat.
  else.
    try.
      cv_todate = cl_bs_period_toolset_basics=>subtract_days_from_date( iv_date
= lv_date_next
                                     iv_days
```

```
= 1 ).
    catch cx_bs_period_toolset_basics.
        "Do nothing
    endtry.
endif.
ms_progpars-todate = cv_todate.
endif.
if lv_date_init = abap_true.
    message i240(g5) with cv_frdate cv_todate.
endif.
endmethod.
```

CHECK_ADJUSTMENT_PERIOD

Description: Check the adjustment date

Instance mthd

Importing parameter

```
IS_T8JG_NEW TYPE T8JG
IS_T8JG_OLD TYPE T8JG
```

Changing parameter

```
CV_FRPER TYPE MONAT (Fiscal Period)
CV_FRYEAR TYPE GJAHR (Fiscal Year)
CV_TOPER TYPE MONAT (Fiscal Period)
CV_TOYEAR TYPE GJAHR (Fiscal Year)
CV_ITD TYPE ABAP_B00L (Inception to Date)
```

```
method check_adjustment_period.
    data: lv_date_init type abap_bool,
           lv_poper     type poper,
           lv_year      type gjahr,
           lv_date      type sy-datum,
           lv_date_next type sy-datum,
           lv_from      type string,
           lv_to        type string.
    if ms_progpars-from_year > ms_progpars-to_year or
       ( ms_progpars-from_year = ms_progpars-to_year and
         ms_progpars-from_period > ms_progpars-to_period ).
        data(lv_period_range_incons) = abap_true.
    endif.
    if ms_progpars-from_year is initial or
       ms_progpars-from_period is initial or
       ms_progpars-from_period > '12' or
       lv_period_range_incons = abap_true.
        lv_date = is_t8jg_new-fdate.
        translate lv_date using '09182736455463728190'.
        call function 'DATE_TO_PERIOD_CONVERT'
            exporting
                i_date      = lv_date
                i_periv      = ms_settings-s_t001-periv
            importing
                e_buper      = lv_poper
                e_gjahr      = lv_year
            exceptions
                input_false  = 1
```

```

        t009_notfound = 2
        t009b_notfound = 3
        others = 4.
    if sy-subrc = 0 and
        lv_year is not initial and
        lv_poper is not initial.
        cv_fryear = lv_year.
        cv_frper = lv_poper.
        ms_progpars-from_year = lv_year.
        ms_progpars-from_period = lv_poper.
        lv_date_init = abap_true.
    endif.
endif.
if ms_progpars-to_year is initial or
    ms_progpars-to_period is initial or
    ms_progpars-to_period > '12' or
    lv_period_range_incons = abap_true.
*   Get the next equity group and its start date
    select * from t8jg into @data(ls_t8jg_next)
        bypassing buffer
        where bukrs = @is_t8jg_new-bukrs
            and vname = @is_t8jg_new-vname
            and etype = @is_t8jg_new-etype
            and fdate < @is_t8jg_new-fdate
        order by fdate descending.
    lv_date_next = ls_t8jg_next-fdate.
    translate lv_date_next using '09182736455463728190'.
    exit.
endselect.
if ls_t8jg_next is initial or
    ms_progpars-budat < lv_date_next.
    lv_date = ms_progpars-budat.
else.
    try.
        lv_date = cl_bs_period_toolset_basics=>subtract_days_from_date( iv_date =
lv_date_next
                                                                    iv_days =
1 ).
        catch cx_bs_period_toolset_basics.
            "Do nothing
        endtry.
    endif.
    call function 'DATE_TO_PERIOD_CONVERT'
        exporting
            i_date = lv_date
            i_periv = ms_settings-s_t001-periv
        importing
            e_buper = lv_poper
            e_gjahr = lv_year
        exceptions
            input_false = 1
            t009_notfound = 2
            t009b_notfound = 3
            others = 4.

```

```

    if sy-subrc = 0          and
      lv_year  is not initial and
      lv_poper is not initial.
      cv_toyear = lv_year.
      cv_toper  = lv_poper.
      ms_progpars-to_year  = lv_year.
      ms_progpars-to_period = lv_poper.
      lv_date_init = abap_true.
    endif.
  endif.
  if lv_date_init = abap_true.
    lv_from = cv_frper && | / | && cv_fryear.
    lv_to   = cv_toper && | / | && cv_toyear.
    message i240(g5) with lv_from lv_to.
  endif.
endmethod.
```

CHECK_AUTHORITY

Description: Check the authority

Instance mthd

```

method check_authority.
  data: lv_process_code type t8jpa-jv_proca,
        lv_activity     type tact-actvt.
  if ms_progpars-farm_in_out = abap_true.
    lv_process_code = 'FARM'.
  else.
    lv_process_code = 'EQUITY-ADJ'.
  endif.
  if ms_progpars-test is initial.
    lv_activity = '16'.
  else.
    lv_activity = '48'.
  endif.
  call function 'JV_AUTHORITY_CHECK_PROCESS'
    exporting
      process_code = lv_process_code
      activity      = lv_activity
      bukrs         = ms_progpars-bukrs
    exceptions
      no_authority = 1.
  if sy-subrc <> 0.
    if sy-batch is initial.
      message id sy-msgid type sy-msgty number sy-msgno
        with sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4.
    elseif mo_message_collector is bound.
      mo_message_collector->add_message_sy( ).
    endif.
  endif.
endmethod.
```

CHECK_COMPANY_CODE

Description: Check the company code

Instance mthd

```
method check_company_code.  
  ms_settings-bukrs = ms_progpars-bukrs.  
  select single * from t001  
    into ms_settings-s_t001  
    where bukrs = ms_progpars-bukrs.  
  if sy-subrc <> 0 or  
    ms_settings-s_t001-xjvaa <> 'X'.  
    message e234(g5) with ms_progpars-bukrs.  
  endif.  
  select single * from t8jz  
    into ms_settings-s_t8jz  
    where bukrs = ms_progpars-bukrs.  
  if sy-subrc <> 0.  
    message e234(g5) with ms_progpars-bukrs.  
  endif.  
endmethod.
```

CHECK_EQUITY_GROUP

Description: Check the equity group
Instance mthd

Changing parameter

CS_T8JG_NEW TYPE T8JG
CS_T8JG_OLD TYPE T8JG

```
method check_equity_group.  
  data: ls_t8jg      type t8jg,  
        lv_same_venture type abap_bool,  
        lv_same_type  type abap_bool,  
        lv_same_curr  type abap_bool.  
*  Get old equity group  
  select * from t8jg into ls_t8jg  
    where bukrs = ms_progpars-bukrs  
    and vname = ms_progpars-vname  
    and egrup = ms_progpars-eqold.  
  cs_t8jg_old = ls_t8jg.  
  exit.  
endselect.  
if sy-subrc <> 0.  
  message e235(g5) with ms_progpars-eqold ms_progpars-vname ms_progpars-bukrs.  
elseif cs_t8jg_old-egroupact <> 'X'.  
  message e117(gj) with ms_progpars-vname ms_progpars-eqold.  
endif.  
*  Get new equity group  
  select * from t8jg into ls_t8jg  
    where bukrs = ms_progpars-bukrs  
    and vname = ms_progpars-vname  
    and egrup = ms_progpars-eqnew.  
  cs_t8jg_new = ls_t8jg.  
  exit.  
endselect.  
if sy-subrc <> 0.  
  message e235(g5) with ms_progpars-eqnew ms_progpars-vname ms_progpars-bukrs.  
elseif cs_t8jg_new-egroupact <> 'X'.  
endif.
```

```
        message e117(gj) with ms_progpars-vname ms_progpars-eqnew.
    endif.
*   Check that equity groups are assigned to the same equity type
    if cs_t8jg_old-etype <> cs_t8jg_new-etype.
        message w236(g5) with ms_progpars-eqold ms_progpars-eqnew.
    endif.
*   Check that equity groups are different
    if cs_t8jg_old-egrup = cs_t8jg_new-egrup.
        message e237(g5).
    endif.
*   Check that the equity groups are connected to each other
    if cs_t8jg_old-fdate > cs_t8jg_new-fdate.
        select *      from t8jg into ls_t8jg
            where bukrs = ms_progpars-bukrs
              and vname = ms_progpars-vname
              and etype = cs_t8jg_old-etype
              and fdate > cs_t8jg_new-fdate
              and fdate < cs_t8jg_old-fdate.

        exit.
    endselect.
    else.
        select * from t8jg into ls_t8jg
            where bukrs = ms_progpars-bukrs
              and vname = ms_progpars-vname
              and etype = cs_t8jg_old-etype
              and fdate < cs_t8jg_new-fdate
              and fdate > cs_t8jg_old-fdate.

        exit.
    endselect.
endif.
if sy-subrc = 0.
    message w239(g5) with ls_t8jg-egrup ms_progpars-eqold ms_progpars-eqnew.
endif.
*   Check if the equity group characteristics match
    call function 'COMPARE_2_EQUITY_GROUPS'
        exporting
            bukrs      = ms_progpars-bukrs
            vname       = ms_progpars-vname
            eg_old      = ms_progpars-eqold
            eg_new       = ms_progpars-eqnew
        importing
            same_venture = lv_same_venture
            same_type    = lv_same_type
            equal_curr   = lv_same_curr
        exceptions
            not_found    = 1
            others       = 2.
if sy-subrc <> 0.
    return.
endif.
if lv_same_venture is initial.
*   EGs do not belong to same venture
    message e566(g4) with ms_progpars-eqold ms_progpars-eqnew.
endif.
```

```

    if lv_same_type is initial.
*      EGs do not have the same equity-type
      message w567(g4) with ms_progpars-eqold ms_progpars-eqnew.
    endif.
    if lv_same_curr is initial.
*      EGs do not have the same funding currency
      message w565(g4) with ms_progpars-eqold ms_progpars-eqnew.
    endif.
  endmethod.
```

CHECK_FOR_PREVIOUS_CHANGES

Description: Check for previous equity changes
Instance mthd

Importing parameter

```
IS_ACDOCA_CHECK TYPE GTY_S_ACDOCA_CHECK
IV_TABIX_CHECK TYPE ANY
```

Changing parameter

```
CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
CV_ALREADY_CHANGED TYPE ABAP_BOOL
```

```

method check_for_previous_changes.
  data: ls_acdoca_rev type gty_s_acdoca_check,
        ls_t8j_jvec type t8j_jvec,
        lv_tabix_start type i.
  field-symbols: <fs_acdoca_check> type gty_s_acdoca_check.
  clear: cv_already_changed.
  ls_acdoca_rev = is_acdoca_check.
*  Reverse amounts
  multiply ls_acdoca_rev-wsl by -1.
  multiply ls_acdoca_rev-hsl by -1.
  multiply ls_acdoca_rev-ksl by -1.
  multiply ls_acdoca_rev-osl by -1.
  multiply ls_acdoca_rev-vsl by -1.
  multiply ls_acdoca_rev-bsl by -1.
  multiply ls_acdoca_rev-csl by -1.
  multiply ls_acdoca_rev-dsl by -1.
  multiply ls_acdoca_rev-esl by -1.
  multiply ls_acdoca_rev-fsl by -1.
  multiply ls_acdoca_rev-gsl by -1.
  lv_tabix_start = iv_tabix_check + 1.
  loop at ct_acdoca_check assigning <fs_acdoca_check>
    from lv_tabix_start.
    if <fs_acdoca_check>-src_awref <> ls_acdoca_rev-src_awref or
      <fs_acdoca_check>-src_awitem <> ls_acdoca_rev-src_awitem or
      <fs_acdoca_check>-racct <> ls_acdoca_rev-racct or
      <fs_acdoca_check>-vname <> ls_acdoca_rev-vname or
      <fs_acdoca_check>-egrup <> ls_acdoca_rev-egrup or
      <fs_acdoca_check>-btype <> ls_acdoca_rev-btype or
      <fs_acdoca_check>-vptnr <> ls_acdoca_rev-vptnr or
      <fs_acdoca_check>-prctr <> ls_acdoca_rev-prctr or
      <fs_acdoca_check>-rcntr <> ls_acdoca_rev-rcntr or
      <fs_acdoca_check>-aufnr <> ls_acdoca_rev-aufnr or
      <fs_acdoca_check>-ps_psp_pnr <> ls_acdoca_rev-ps_psp_pnr or
```

```

        <fs_acdoca_check>-nplnr      <> ls_acdoca_rev-nplnr      or
        <fs_acdoca_check>-nplnr_vorgn <> ls_acdoca_rev-nplnr_vorgn.
    exit.
endif.
if <fs_acdoca_check>-already_changed = abap_true.
    continue.
endif.
if <fs_acdoca_check>-xreversed  = abap_true or
    <fs_acdoca_check>-xreversing = abap_true.
    continue.
endif.
*   If the amounts match, a reversal document was posted in a
*   previous run, that is, the equity group change was already made
if <fs_acdoca_check>-wsl = ls_acdoca_rev-wsl and
    <fs_acdoca_check>-hsl = ls_acdoca_rev-hsl and
    <fs_acdoca_check>-ksl = ls_acdoca_rev-ksl and
    <fs_acdoca_check>-osl = ls_acdoca_rev-osl and
    <fs_acdoca_check>-vsl = ls_acdoca_rev-vsl and
    <fs_acdoca_check>-bsl = ls_acdoca_rev-bsl and
    <fs_acdoca_check>-csl = ls_acdoca_rev-csl and
    <fs_acdoca_check>-dsl = ls_acdoca_rev-dsl and
    <fs_acdoca_check>-esl = ls_acdoca_rev-esl and
    <fs_acdoca_check>-fsl = ls_acdoca_rev-fsl and
    <fs_acdoca_check>-gsl = ls_acdoca_rev-gsl.
*   Set the ALREADY_CHANGED flag to avoid re-processing of this line
<fs_acdoca_check>-already_changed = abap_true.
*   Return ABAP_TRUE to indicate that no posting is required
cv_already_changed = abap_true.
    exit.
endif.
endloop.
endmethod.
```

CHECK_INTERCOMPANY_VENTURE

Description: Check the intercompany venture
Instance mthd

```

method check_intercompany_venture.
    data: lt_t8ji type table of t8ji,
          ls_t8ji type t8ji.
    select * from t8ji
        into table lt_t8ji
        where bukrs = ms_progpars-bukrs
            and vname = ms_progpars-vname
            and ( egrup = ms_progpars-eqold or
                  egrup = ms_progpars-eqnew ).
    if sy-subrc = 0.
        loop at lt_t8ji into ls_t8ji.
            call function 'JV_VENTURE_ACTIVE_CHECK'
                exporting
                    bukrs      = ls_t8ji-bukrs
                    vname       = ls_t8ji-vname
                exceptions
                    not_found   = 1
        endloop.
    endif.
endmethod.
```

```

        not_activ      = 2
        error_message = 3
        others         = 4.
    case sy-subrc.
        when 0.
            *      Check if the inter-company equity group associated to
            *      the new equity group is active
            call function 'GJ_EGROUP_ACTIV_CHECK'
                exporting
                    bukrs      = ls_t8ji-intcocc
                    vname       = ls_t8ji-intcomvent
                    egrp        = ls_t8ji-intcompepp
                exceptions
                    no_activ_egrp = 1
                    error_message = 2
                    others         = 4.
            if sy-subrc <> 0.
                message e117(gj) with ls_t8ji-intcomvent
                                     ls_t8ji-intcompepp.
            endif.
        when 1.
            message e220(gj) with ls_t8ji-intcomvent
                                ls_t8ji-intcocc.
        when 2.
            message e349(gj) with ls_t8ji-intcomvent
                                ls_t8ji-intcocc
                                ls_t8ji-bukrs
                                ls_t8ji-vname .
    endcase.
endloop.
endif.
endmethod.
```

CHECK_LINE_ITEMS

Description: Check the ACDOCA line items
Instance mthd

Importing parameter

```

IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))
IV_VNAME_NEW TYPE JV_NAME (Joint venture)
IV_EGRP_NEW TYPE JV_EGROUP (Equity group)
```

Changing parameter

```

CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
```

```

method check_line_items.
    data: lv_tabix_check type sy-tabix,
          ls_acdoca_check type gty_s_acdoca_check,
          lv_already_changed type abap_bool.
    *      Sort by reference document and accounting data
    sort ct_acdoca_check by src_awref
                        src_awitem
                        racct
                        vname
```

```

        egrup
        btype
        vptnr
        prctr
        rcntr
        aufnr
        ps_psp_pnr
        nplnr
        nplnr_vorgn
        timestamp
        belnr
        buzei
        docln.
loop at ct_acdoca_check into ls_acdoca_check.
    lv_tabix_check = sy-tabix.
*   Do not process items with zero amounts in all currencies
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and
       ls_acdoca_check-gsl = 0.
        continue.
    endif.
*   The line has been marked as equity change reversal line and
*   can therefore be skipped.
    if ls_acdoca_check-already_changed = abap_true.
        continue.
    endif.
*   Do not process reversal lines of documents posted by previous runs
    if ls_acdoca_check-jvactivity = 'E1' or
       ( ls_acdoca_check-jvactivity = 'E2' and
         ( ls_acdoca_check-xreversed = abap_true or
           ls_acdoca_check-xreversing = abap_true ) ).
        continue.
    endif.
*   Check if the item was already handled by a previous run
    check_for_previous_changes( exporting
                                iv_tabix_check = lv_tabix_check
                                is_acdoca_check = ls_acdoca_check
                                changing
                                ct_acdoca_check = ct_acdoca_check
                                cv_already_changed = lv_already_changed ).
    if lv_already_changed = abap_true.
        continue.
    endif.
*   Make the equity change posting
    post_change_document( exporting
                          iv_jvfunc = iv_jvfunc
```

```

        iv_vname_new      = iv_vname_new
        iv_egrup_new      = iv_egrup_new
        is_acdoca_check = ls_acdoca_check
    changing
        ct_acdoca_cb = ct_acdoca_cb ).

    endloop.
endmethod.
```

CHECK_PARAMETERS

Description: Check the parameters entered by the user
Instance mthd

Changing parameter

```
CV_FRDATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
CV_TODATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
CV_FRPER TYPE MONAT (Fiscal Period)
CV_FRYEAR TYPE GJAHR (Fiscal Year)
CV_TOPER TYPE MONAT (Fiscal Period)
CV_TOYEAR TYPE GJAHR (Fiscal Year)
CV_ITD TYPE ABAP_BOOL (Inception to Date)
```

```
method check_parameters.
    data: ls_t8jg_old type t8jg,
          ls_t8jg_new type t8jg.
    check_company_code( ).
    check_processing_mode( ).
    check_venture( ).
    check_equity_group( changing
                        cs_t8jg_old = ls_t8jg_old
                        cs_t8jg_new = ls_t8jg_new ).

    check_intercompany_venture( ).
    check_posting_date( ).
    if ms_progpars-farm_in_out = abap_true.
        check_adjustment_period( exporting
                                is_t8jg_old = ls_t8jg_old
                                is_t8jg_new = ls_t8jg_new
                                changing
                                cv_frper  = cv_frper
                                cv_fryear = cv_fryear
                                cv_toper  = cv_toper
                                cv_toyear = cv_toyear
                                cv_itd    = cv_itd ).
    else.
        check_adjustment_date( exporting
                                is_t8jg_old = ls_t8jg_old
                                is_t8jg_new = ls_t8jg_new
                                changing
                                cv_frdate = cv_frdate
                                cv_todate = cv_todate ).
    endif.
    check_settlement_account( ).
endmethod.
```

CHECK_POSTING_DATE

Description: Check the posting date

Instance mthd

```
method check_posting_date.
  data lv_poper type periods-buper.
*   Create list of allowed periods with start date and end date
*   (special periods are not allowed)
  call function 'G_PERIODS_OF_YEAR_GET'
    exporting
      variant          = ms_settings-s_t001-periv
      year             = ms_progpars-year
    importing
      last_normal_period = ms_settings-last_period
  tables
    i_periods          = ms_settings-t_periods
  exceptions
    variant_not_defined = 1
    year_not_defined   = 2.
  if sy-subrc <> 0.
    message e746(gj) with ms_settings-s_t001-periv.
  endif.
*   Check if posting period is allowed
  lv_poper = ms_progpars-period.
  loop at ms_settings-t_periods into data(ls_periods)
    where buper = lv_poper.

    exit.
  endloop.
  if sy-subrc <> 0.
    message e674(gj).
  endif.
*   Check if posting date is filled and if so, if it is allowed
  if ms_progpars-budat is initial.
    ms_progpars-budat = ls_periods-datbi.
  else.
    if ms_progpars-budat < ls_periods-datab or
       ms_progpars-budat > ls_periods-datbi.
      message e682(gj) with ms_progpars-budat.
    endif.
  endif.
  "Get the fiscal year for postings
  call function 'DETERMINE_PERIOD'
    exporting
      date          = ms_progpars-budat
      version       = ms_settings-s_t001-periv
    importing
      year          = ms_settings-gjahr_p
  exceptions
    period_in_not_valid = 1
    period_not_assigned = 2
    version_undefined   = 3
    error_message       = 4
    others              = 8.
```

```
if sy-subrc <> 0.  
  message e108(glofaa_gb) with ms_settings-s_t001-periv ms_progpars-budat.  
endif.  
endmethod.
```

CHECK_PROCESSING_MODE

Description:

Instance mthd

```
method check_processing_mode.  
  if ms_progpars-ec_aggregated = abap_true.  
    return.  
  endif.  
  "If the single item processing mode is active, we need to check  
  "whether the aggregated mode was already used in a previous run.  
  "If yes, the single item mode cannot be used!  
  select *  
    from t8jev  
  where bukrs      = @ms_progpars-bukrs  
    and ( process  = @gc_process_eqad or  
          process  = @gc_process_farm )  
    and ( fyear < @ms_progpars-year          or  
          ( fyear = @ms_progpars-year and  
            poper <= @ms_progpars-period ) )  
    and param      = @gc_event_aggregated  
    and contense = @abap_true  
  order by bukrs, fyear, poper, seqno  
  into table @data(lt_t8jev)  
  bypassing buffer.  
  if lt_t8jev[] is not initial.  
    if mo_message_collector is bound.  
      message e284(g4) into mv_message_text.  
      mo_message_collector->add_message_sy( ).  
    else.  
      message e284(g4).  
    endif.  
  endif.  
endmethod.
```

CHECK_RECID

Description: Check the recovery indicator

Instance mthd

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)

```
method check_recid.  
* For each relevant RI ...  
  loop at ms_settings-t_t8jj into data(ls_t8jj).  
    check ms_settings-s_t8j0a-recindind is not initial.  
    loop at ms_settings-t_t8j0g into data(ls_t8j0g)  
      where jvfunc = iv_jvfunc  
        and itemtype = 'F1'  
        and recid = ls_t8jj-recid.
```

```
        exit.
    endloop.
    if sy-subrc <> 0    or
        ls_t8j0g-debrecid is initial.
        message e764(g5) with iv_jvfunc 'F1' ls_t8jj-recid into mv_message_text.
        save_sy_message( ).
    endif.
    loop at ms_settings-t_t8j0g into ls_t8j0g
        where jvfunc    = iv_jvfunc
        and itemtype = 'F2'
        and recid      = ls_t8jj-recid.

        exit.
    endloop.
    if sy-subrc <> 0    or
        ls_t8j0g-debrecid is initial.
        message e764(g5) with iv_jvfunc 'F2' ls_t8jj-recid into mv_message_text.
        save_sy_message( ).
    endif.
    loop at ms_settings-t_t8j0g into ls_t8j0g
        where jvfunc    = iv_jvfunc
        and itemtype = 'F3'
        and recid      = ls_t8jj-recid.

        exit.
    endloop.
    if sy-subrc <> 0    or
        ls_t8j0g-debrecid is initial.
        message e764(g5) with iv_jvfunc 'F3' ls_t8jj-recid into mv_message_text.
        save_sy_message( ).
    endif.
endloop.
endmethod.
```

CHECK_SETTLEMENT_ACCOUNT

Description: Check the settlement account

Instance mthd

```
method check_settlement_account.
    data: ls_ska1 type ska1,
          ls_t001 type t001.
    if ms_progpars-farm_in_out <> abap_true.
        return.
    endif.
    if ms_progpars-cashc2 <> abap_true.
        return.
    endif.
    if ms_progpars-settlement_acc_cc2 is initial.
        message e076(g4).
    endif.
    select single * from t001 into ls_t001
        where bukrs = ms_progpars-bukrs.
    if sy-subrc = 0.
        select single * from ska1 into ls_ska1
            where saknr = ms_progpars-settlement_acc_cc2
            and ktopl = ls_t001-ktopl.
```

```

        if sy-subrc <> 0.
            clear ls_ska1.
        endif.
    endif.
    if ls_ska1 is initial.
        message e077(g4) with ms_progpars-settlement_acc_cc2.
    endif.
endmethod.

```

CHECK_SHARES_CC1

Description: Check the partner shares for cash call 1

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method check_shares_cc1.
    data: ls_diff_share type jva_diff_share,
          ls_shares_new type jva_partner_shares.
    refresh ms_settings-t_diff_share.
    sort ms_settings-t_shares_old by partn.
*   Build table with partners for which an equity change should be executed
*   Only include partners that are both in the old and in the new equity group
    loop at ms_settings-t_shares_old into data(ls_shares_old)
        where intcocd is initial.

        clear ls_shares_new.
        read table ms_settings-t_shares_new into ls_shares_new
            with key partn = ls_shares_old-partn.
*   Prtner in old equity group is not in new equity group
        if ls_shares_new is initial.
            message i799(g5) with text-nop ls_shares_old-partn ms_progpars-eqold
                into mv_message_text.
            save_sy_message( ).
            continue.
        endif.
        clear ls_diff_share.
        ls_diff_share-eg_old      = ms_progpars-eqold.
        ls_diff_share-partn_old   = ls_shares_old-partn.
        ls_diff_share-opflag     = ls_shares_old-opflag.
        ls_diff_share-eqshare_old = ls_shares_old-eqshare.
        ls_diff_share-intcocd_old = ls_shares_old-intcocd.
        ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
        ls_diff_share-intcompepp_old = ls_shares_old-intcompepp.
        ls_diff_share-partn_new   = ls_shares_new-partn.
        ls_diff_share-eqshare_new = ls_shares_new-eqshare.
        ls_diff_share-intcocd_new = ls_shares_new-intcocd.
        ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
        ls_diff_share-intcompepp_new = ls_shares_new-intcompepp.
        append ls_diff_share to ms_settings-t_diff_share.
    endloop.
    if ms_settings-t_diff_share[] is initial.
        cv_no_differences = abap_true.
    endif.
endmethod.

```

CHECK_SHARES_CC1_INTCO

Description: Check the partner shares for cash call 1

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```
method check_shares_cc1_intco.
  data: ls_diff_share type jva_diff_share,
        ls_shares_new type jva_partner_shares.
  refresh ms_settings-t_diff_share.
* Build table with equity share difference for
* old EGs with intercompany partner
  sort ms_settings-t_shares_old by partn.
  loop at ms_settings-t_shares_old into data(ls_shares_old)
                                where not intcocd is initial.

    clear ls_shares_new.
    read table ms_settings-t_shares_new into ls_shares_new
                                with key partn = ls_shares_old-partn.
* Intercompany partner of old EG is no longer in new EG
    if ls_shares_new is initial.
      message e760(g5) with ls_shares_old-partn into mv_message_text.
      save_sy_message( ).
      continue.
    endif.
* It is mandatory, that the partner of old and new EG
* belong to the same intercompany and same intercompany venture !!
    if ls_shares_new-intcocd <> ls_shares_old-intcocd or
       ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
      message e799(g5) with text-iiv
                        ms_progpars-eqold
                        ls_shares_old-intcocd
                        ls_shares_old-intrcovent
                        into mv_message_text.
      save_sy_message( ).
      continue.
    endif.
    if ls_shares_new-eqshare <> ls_shares_old-eqshare.
      ls_diff_share-eg_old      = ms_progpars-eqold.
      ls_diff_share-partn_old    = ls_shares_old-partn.
      ls_diff_share-opflag      = ls_shares_old-opflag.
      ls_diff_share-eqshare_old  = ls_shares_old-eqshare.
      ls_diff_share-intcocd_old  = ls_shares_old-intcocd.
      ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
      ls_diff_share-intcompepp_old = ls_shares_old-intcompepp.
      ls_diff_share-partn_new    = ls_shares_new-partn.
      ls_diff_share-eqshare_new  = ls_shares_new-eqshare.
      ls_diff_share-intcocd_new  = ls_shares_new-intcocd.
      ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
      ls_diff_share-intcompepp_new = ls_shares_new-intcompepp.
      append ls_diff_share to ms_settings-t_diff_share.
    endif.
  endloop.
```

```

*   If the shares of the partners are identical, issue an information message
    if ms_settings-t_diff_share[] is initial.
        cv_no_differences = abap_true.
    endif.
endmethod.

```

CHECK_SHARES_CC2

Description: Check the partner shares for cash call 2

Instance mthd

Changing parameter

```

CV_NO_DIFFERENCES TYPE ABAP_BOOL

method check_shares_cc2.
    data: ls_diff_share type jva_diff_share,
          ls_shares_new type jva_partner_shares.
    clear cv_no_differences.
    refresh ms_settings-t_diff_share.
*   Build table with equity share difference
    loop at ms_settings-t_shares_old into data(ls_shares_old).
        clear ls_shares_new.
        read table ms_settings-t_shares_new into ls_shares_new
            with key partn = ls_shares_old-partn
                opflag = ls_shares_old-opflag.
*
*   Partner of old EG is not in new EG
        if ls_shares_new is initial.
            message i760(g5) with ls_shares_old-partn into mv_message_text.
            save_sy_message( ).
        endif.
*   It is mandatory, that the partner of old and new EG
*   belong to the same intercompany and same intercompany venture !!
        if ls_shares_new-intcocd <> ls_shares_old-intcocd or
            ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
            message e799(g5) with text-iiv
                ms_progpars-eqold
                ls_shares_old-intcocd
                ls_shares_old-intrcovent
                into mv_message_text.
            save_sy_message( ).
            continue.
        endif.
        clear ls_diff_share.
        ls_diff_share-eg_old      = ms_progpars-eqold.
        ls_diff_share-partn_old   = ls_shares_old-partn.
        ls_diff_share-opflag      = ls_shares_old-opflag.
        ls_diff_share-eqshare_old = ls_shares_old-eqshare.
        ls_diff_share-intcocd_old = ls_shares_old-intcocd.
        ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
        ls_diff_share-intcompepgp_old = ls_shares_old-intcompepgp.
        ls_diff_share-partn_new   = ls_shares_new-partn.
        ls_diff_share-eqshare_new  = ls_shares_new-eqshare.
        ls_diff_share-intcocd_new  = ls_shares_new-intcocd.
        ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
        ls_diff_share-intcompepgp_new = ls_shares_new-intcompepgp.
    endloop.
endmethod.

```

```

        append ls_diff_share to ms_settings-t_diff_share.
    endloop.
    * Check, if a new partner was introduced
    * Build table with equity share difference
    loop at ms_settings-t_shares_new into ls_shares_new.
        * Check if the partner of the new EG was already in the old EG.
        * If yes, go to the next item
        clear ls_shares_old.
        read table ms_settings-t_shares_old into ls_shares_old
            with key partn = ls_shares_new-partn
                opflag = ls_shares_new-opflag.

        if sy-subrc = 0.
            continue.
        endif.
    * Add the new partner
    clear ls_diff_share.
    ls_diff_share-eg_old      = ms_progpars-egold.
    ls_diff_share-partn_new   = ls_shares_new-partn.
    ls_diff_share-eqshare_new = ls_shares_new-eqshare.
    ls_diff_share-intcocd_new = ls_shares_new-intcocd.
    ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
    ls_diff_share-intcompegg_new = ls_shares_new-intcompegg.
    append ls_diff_share to ms_settings-t_diff_share.
    endloop.
    * If the shares of the partners are identical, issue an information message
    if ms_settings-t_diff_share[] is initial.
        cv_no_differences = abap_true.
    endif.
endmethod.

```

CHECK_SHARES_CC2_INTCO

Description: Check the partner shares for intercompany cash call

Instance mthd

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method check_shares_cc2_intco.
    * Build table with equity share difference for
    * old EGs with intercompany partner
    data: ls_diff_share type jva_diff_share,
          lv_diff_exists type abap_bool.
    refresh ms_settings-t_diff_share_intco.
    sort ms_settings-t_shares_old by partn.
    loop at ms_settings-t_shares_old into data(ls_shares_old)
        where not intcocd is initial.

        loop at ms_settings-t_shares_new into data(ls_shares_new)
            where partn = ls_shares_old-partn
                and opflag = ls_shares_old-opflag.

            exit.
        endloop.
    * Intercompany partner of old EG is no longer in new EG
    if sy-subrc <> 0.
        message i760(g5) with ls_shares_old-partn into mv_message_text.
    endif.
endmethod.

```

```

        save_sy_message( ).
        ls_shares_new = ls_shares_old.
        clear ls_shares_new-eqshare.
    endif.
    * It is mandatory, that the partner of old and new EG
    * belong to the same intercompany and same intercompany venture !!
    if ls_shares_new-intcocd <> ls_shares_old-intcocd or
        ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
        message e799(g5) with text-iiiv ms_progpars-eqold ls_shares_old-intcocd
ls_shares_old-intrcovent into mv_message_text.
        save_sy_message( ).
        exit.
    endif.
    lv_diff_exists = abap_true.
    ls_diff_share-eg_old      = ms_progpars-eqold.
    ls_diff_share-partn_old   = ls_shares_old-partn.
    ls_diff_share-opflag      = ls_shares_old-opflag.
    ls_diff_share-eqshare_old = ls_shares_old-eqshare.
    ls_diff_share-intcocd_old = ls_shares_old-intcocd.
    ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
    ls_diff_share-intcompeggp_old = ls_shares_old-intcompeggp.
    ls_diff_share-partn_new   = ls_shares_new-partn.
    ls_diff_share-eqshare_new = ls_shares_new-eqshare.
    ls_diff_share-intcocd_new = ls_shares_new-intcocd.
    ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
    ls_diff_share-intcompeggp_new = ls_shares_new-intcompeggp.
    append ls_diff_share to ms_settings-t_diff_share_intco.
endloop.
if lv_diff_exists <> abap_true.
    cv_no_differences = abap_true.
endif.
endmethod.
```

CHECK_SHARES_INTCO_REVERSAL

Description: Check the partner shares
Instance mthd

Changing parameter

```

CV_NO_INTCO_PARTNER TYPE ABAP_BOOL

method check_shares_intco_reversal.
    data: lv_diff_share      type c,
          lv_no_intco_partner_egold type c,
          lv_no_intco_partner_egnew type c,
          ls_diff_share      type jva_diff_share,
          ls_diff_share_old   type jva_partner_share,
          ls_diff_share_new   type jva_partner_share.
    refresh: ms_settings-t_diff_share_old,
             ms_settings-t_diff_share_new.
    * check that the old EG has an Intercompany partner
    loop at ms_settings-t_shares_old into data(ls_shares_old)
        where not intcocd is initial.
        loop at ms_settings-t_shares_new into data(ls_shares_new)
            where partn      = ls_shares_old-partn
```

```

                                and intcocd      = ls_shares_old-intcocd
                                and intrcovent =
ls_shares_old-intrcovent.
    exit.
endloop.
*   Inercompany partner of old EG is no longer in new EG
    if sy-subrc <> 0.
        message e760(g5) with ls_shares_old-partn into mv_message_text.
        save_sy_message( ).
    else.
        if ls_shares_new-eqshare <> ls_shares_old-eqshare.
            lv_diff_share = 'X'.
            ls_diff_share-partn_old      = ls_shares_old-partn.
            ls_diff_share-opflag         = ls_shares_old-opflag.
            ls_diff_share-eqshare_old    = ls_shares_old-eqshare.
            ls_diff_share-intcocd_old    = ls_shares_old-intcocd.
            ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
            ls_diff_share-intcompepgp_old = ls_shares_old-intcompepgp.
            ls_diff_share-partn_new      = ls_shares_new-partn.
            ls_diff_share-eqshare_new    = ls_shares_new-eqshare.
            ls_diff_share-intcocd_new    = ls_shares_new-intcocd.
            ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
            ls_diff_share-intcompepgp_new = ls_shares_new-intcompepgp.
            append ls_diff_share to ms_settings-t_diff_share.
            ls_diff_share_new-partn      = ls_shares_new-partn.
            ls_diff_share_new-opflag     = ls_shares_new-opflag.
            ls_diff_share_new-eqshare    = ls_shares_new-eqshare.
            ls_diff_share_new-intcocd    = ls_shares_new-intcocd.
            ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.
            ls_diff_share_new-intcompepgp = ls_shares_new-intcompepgp.
            append ls_diff_share_new to ms_settings-t_diff_share_new.
            ls_diff_share_old-partn      = ls_shares_old-partn.
            ls_diff_share_old-opflag     = ls_shares_old-opflag.
            ls_diff_share_old-eqshare    = ls_shares_old-eqshare.
            ls_diff_share_old-intcocd    = ls_shares_old-intcocd.
            ls_diff_share_old-intrcovent = ls_shares_old-intrcovent.
            ls_diff_share_old-intcompepgp = ls_shares_old-intcompepgp.
            append ls_diff_share_old to ms_settings-t_diff_share_old.
        endif.
    endif.
endloop.
*   Old EG has no intercomp-partner
    if sy-subrc <> 0.
        lv_no_intco_partner_egold = 'X'.
    endif.
*   Check that the new EG has an Intercompany partner
    loop at ms_settings-t_shares_new into ls_shares_new
        where not intcocd is initial.
        loop at ms_settings-t_shares_old into ls_shares_old
            where partn      = ls_shares_new-partn
            and intcocd      = ls_shares_new-intcocd
            and intrcovent =
ls_shares_new-intrcovent.
        exit.

```

```

        endloop.
*   Intercompany partner of new EG is no not in old EG
    if sy-subrc <> 0.
        message e762(g5) with ls_shares_new-partn into mv_message_text.
        save_sy_message( ).
    endif.
endloop.
*   New EG has no intercomp-partner
if sy-subrc <> 0.
    lv_no_intco_partner_egnew = 'X'.
endif.
if lv_no_intco_partner_egold = 'X' and
    lv_no_intco_partner_egnew = 'X'.
    cv_no_intco_partner = 'X'.
    return.
endif.
*   Check that at least one of the shares is different
if lv_diff_share is initial.
    cv_no_intco_partner = 'X'.
    return.
endif.
**   Check that a settlement account is defined
*   loop at ms_settings-t_diff_share into ls_diff_share
*       where not intcocd_new is initial.
*
*   loop at mt_intco_settl_acct into data(ls_intco_settl_acct)
*       where intcocd = ls_diff_share-intcocd_new.
*
*   exit.
*   endloop.
*   if sy-subrc <> 0 or ls_intco_settl_acct-racct is initial.
*   if ms_progpars-settlement_account_intco is initial.
        message e783(G5) with ls_diff_share-intcocd_new into mv_message_text.
        save_message( iv_type = 'E'
            iv_class = 'G5'
            iv_number = '783'
            iv_var1 = ls_diff_share-intcocd_new
            iv_var2 = space
            iv_var3 = space
            iv_var4 = space ).
*   endif.
*
*   endloop.
endmethod.

```

CHECK_VENTURE

Description: Check the venture

Instance mthd

```

method check_venture.
    select single * from t8jv into ms_settings-s_t8jv
        where bukrs = ms_progpars-bukrs
        and vname = ms_progpars-vname.

    if sy-subrc <> 0.
        message e232(g5) with ms_progpars-vname ms_progpars-bukrs.
    endif.
endmethod.

```

```
elseif ms_settings-s_t8jv-vtype = '2'
  or ms_settings-s_t8jv-vtype = '5'.
  message e243(g5) with ms_progpars-vname.
endif.
endmethod.
```

FILL_ACCCR

Description: Add the ACCCR structure for an FI doc line
Instance mthd

Importing parameter

```
IS_ACCIT TYPE ACCIT
IS_ACDOCA TYPE ACDOCA (Universal Journal Entry Line Items)
IV_RWCUR TYPE ACDOCA-RWCUR
IS_CURR_INFO TYPE FINSS_CMP_CURR_INFO (Derived Company Code Currency Information)
```

Changing parameter

```
CT_ACCCR TYPE ACCCR_T

method fill_acccr.
  data: ls_acccr type acccr.
  ls_acccr-mandt = is_accit-mandt.
  ls_acccr-awtyp = is_accit-awtyp.
  ls_acccr-posnr = is_accit-posnr.
* Transaction currency
  ls_acccr-curtp = '00'.
  ls_acccr-waers = iv_rwcur.
  ls_acccr-wrbtr = is_acdoca-wsl.
  append ls_acccr to ct_acccr.
* 1st local currency
  ls_acccr-curtp = is_curr_info-curtype1.
  ls_acccr-waers = is_curr_info-waers1.
  ls_acccr-wrbtr = is_acdoca-hsl.
  append ls_acccr to ct_acccr.
* 2nd local currency
  if not is_curr_info-curtype2 is initial.
    ls_acccr-curtp = is_curr_info-curtype2.
    ls_acccr-waers = is_curr_info-waers2.
    ls_acccr-wrbtr = is_acdoca-ksl.
    append ls_acccr to ct_acccr.
  endif.
* 3rd local currency
  if not is_curr_info-curtype3 is initial.
    ls_acccr-curtp = is_curr_info-curtype3.
    ls_acccr-waers = is_curr_info-waers3.
    ls_acccr-wrbtr = is_acdoca-osl.
    append ls_acccr to ct_acccr.
  endif.
* 4th local currency
  if not is_curr_info-curtype4 is initial.
    ls_acccr-curtp = is_curr_info-curtype4.
    ls_acccr-waers = is_curr_info-waers4.
    ls_acccr-wrbtr = is_acdoca-vsl.
    append ls_acccr to ct_acccr.
  endif.
```

```
* 5th local currency
  if not is_curr_info-curtype5 is initial.
    ls_accctr-curtp = is_curr_info-curtype5.
    ls_accctr-waers = is_curr_info-waers5.
    ls_accctr-wrbtr = is_acdoca-bsl.
    append ls_accctr to ct_accctr.
  endif.
* 6th local currency
  if not is_curr_info-curtype6 is initial.
    ls_accctr-curtp = is_curr_info-curtype6.
    ls_accctr-waers = is_curr_info-waers6.
    ls_accctr-wrbtr = is_acdoca-csl.
    append ls_accctr to ct_accctr.
  endif.
* 7th local currency
  if not is_curr_info-curtype7 is initial.
    ls_accctr-curtp = is_curr_info-curtype7.
    ls_accctr-waers = is_curr_info-waers7.
    ls_accctr-wrbtr = is_acdoca-dsl.
    append ls_accctr to ct_accctr.
  endif.
* 8th local currency
  if not is_curr_info-curtype8 is initial.
    ls_accctr-curtp = is_curr_info-curtype8.
    ls_accctr-waers = is_curr_info-waers8.
    ls_accctr-wrbtr = is_acdoca-esl.
    append ls_accctr to ct_accctr.
  endif.
* 9th local currency
  if not is_curr_info-curtype9 is initial.
    ls_accctr-curtp = is_curr_info-curtype9.
    ls_accctr-waers = is_curr_info-waers9.
    ls_accctr-wrbtr = is_acdoca-fsl.
    append ls_accctr to ct_accctr.
  endif.
* 10th local currency
  if not is_curr_info-curtype10 is initial.
    ls_accctr-curtp = is_curr_info-curtype10.
    ls_accctr-waers = is_curr_info-waers10.
    ls_accctr-wrbtr = is_acdoca-gsl.
    append ls_accctr to ct_accctr.
  endif.
endmethod.
```

FILL_EVENT_TABLE

Description: Fill the event table
Instance mthd

```
method fill_event_table.
  data: ls_t8jev type t8jev.
*  Fill the event table
  select single * from t8jev into ms_progpars-s_t8jev
    where bukrs = ms_progpars-bukrs
    and process = mv_process
```

```
        and fyear   = ms_progpars-year
        and poper   = ms_progpars-period. "#EC CI_NOORDER
if sy-subrc = 0.
    add 1 to ms_progpars-s_t8jev-seqno.
else.
    ms_progpars-s_t8jev-seqno = 1.
endif.
ms_progpars-s_t8jev-mandt   = sy-mandt.
ms_progpars-s_t8jev-bukrs   = ms_progpars-bukrs.
ms_progpars-s_t8jev-process = mv_process.
ms_progpars-s_t8jev-fyear   = ms_progpars-year.
ms_progpars-s_t8jev-poper   = ms_progpars-period.
ms_progpars-s_t8jev-ernam   = sy-uname.
ms_progpars-s_t8jev-cpudt   = sy-datum.
ms_progpars-s_t8jev-cputm   = sy-uzeit.
ms_progpars-s_t8jev-status  = '3'.
* Only update when not running in test mode
if ms_progpars-test <> abap_true.
    mo_output->insert_t8jev( ls_t8jev ).
endif.
* Fill select options.
set_event_param_account( ).
set_event_param_cost_center( ).
set_event_param_order( ).
set_event_param_project( ).
* Save the parameters
set_event_param( name = 'P_BUDAT'
                 contense = ms_progpars-budat ).
set_event_param( name = 'P_VNAME'
                 contense = ms_progpars-vname ).
set_event_param( name = 'P_EQOLD'
                 contense = ms_progpars-eqold ).
set_event_param( name = 'P_EQNEW'
                 contense = ms_progpars-eqnew ).
set_event_param( name = 'P_FRDATE'
                 contense = ms_progpars-frdate ).
set_event_param( name = 'P_TODATE'
                 contense = ms_progpars-todate ).
set_event_param( name = 'P_YEAR'
                 contense = ms_progpars-year ).
set_event_param( name = 'P_PERIOD'
                 contense = ms_progpars-period ).
set_event_param( name = 'P_BKTXT'
                 contense = ms_progpars-bktxt ).
set_event_param( name = 'P_TEST'
                 contense = ms_progpars-test ).
"Save the information if the program was run in aggregated mode
set_event_param( name      = gc_event_aggregated
                 contense = ms_progpars-ec_aggregated ).
mo_output->commit_work( ).
endmethod.
```

GET_BILIND_RANGE_CASHCALL

Description: Get the billing indicators used by cash call
Instance mthd

Importing parameter

IV_SIGN TYPE CHAR1
IV_BUKRS TYPE BUKRS
IV_MODE TYPE STRING

Exporting parameter

ET_BILIND TYPE JVA_BILIND_RANGE_T
ET_BILIND_OP TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)

```
method get_billind_range_cashcall.  
  data: lt_t8j0g      type table of t8j0g,  
        ls_bilind     type jva_bilind_range,  
        lt_t8ja       type table of t8ja,  
        lv_bilid_cl   type jv_bilind,  
        ls_t8j0f      type t8j0f.  
  refresh: et_bilind, et_bilind_op.  
*  Get the posting rule header  
  select single * from t8j0f into ls_t8j0f  
                        where bukrs    = ms_progpars-bukrs  
                        and bmethod    = ms_settings-s_t8jv-bmethod  
                        and jvfunc     = 'CCOP'.  
  ls_bilind-sign      = iv_sign.  
  ls_bilind-option    = 'EQ'.  
  case iv_mode.  
    when 'ALL'.  
      select * from t8j0g into table lt_t8j0g  
                        where bukrs    = ms_progpars-bukrs  
                        and bmethod    = ms_settings-s_t8jv-bmethod  
                        and ( jvfunc   = 'CCOP' or  "Cash call billed to  
partner                                                    jvfunc    = 'FACC' or  "Farm in/out cash call  
re-determine                                                jvfunc    = 'FAC2' ).  "Farm in/out cash call  
correction  
  when 'PARTNER'.  
    select * from t8j0g into table lt_t8j0g  
                  where bukrs    = ms_progpars-bukrs  
                  and bmethod    = ms_settings-s_t8jv-bmethod  
                  and ( ( jvfunc   = 'CCOP' and      "Cash Call - Operated  
                        itemtype = 'AB' )          or  "Cash call billed to  
partner                                                    ( jvfunc    = 'FACC' and      "Farm in/out cash  
call re-determine                                           itemtype = 'E1' )          or  
                                                            ( jvfunc    = 'FAC2' and      "Farm in/out cash  
call correction                                             itemtype = 'F1' ) ).  
  when others.  "Default: 'OFFSET'  
    select * from t8j0g into table lt_t8j0g  
                  where bukrs    = ms_progpars-bukrs
```

```

                                and bmethod = ms_settings-s_t8jv-bmethod
                                and ( ( jvfunc   = 'CCOP' and      "Cash Call - Operated
                                      itemtype = 'AC' )      or "Cash call billed to
offset account
                                ( jvfunc   = 'FACC' and      "Farm in/out cash
call re-determine
                                itemtype = 'E2' )      or
                                ( jvfunc   = 'FAC2' and      "Farm in/out cash
call correction
                                itemtype = 'F2' ) ).
endcase.
loop at lt_t8j0g into data(ls_t8j0g).
  if ls_t8j0g-debbillind is not initial.
    ls_bilind-low = ls_t8j0g-debbillind.
    collect ls_bilind into et_bilind.
*   Get clearing billing indicator for cash call
    if iv_mode <> 'OFFSET'      and
      ls_t8j0g-jvfunc = 'CCOP' and
      ls_t8j0g-itemtype = 'AB'.
      call function 'GET_CLEARING_BILLING_IND'
        exporting
          i_clearing_function = ls_t8j0f-clearproc
          i_original_bilid    = ls_t8j0g-debbillind
        importing
          e_clearing_bilid    = lv_bilid_cl.
      if lv_bilid_cl is not initial.
        ls_bilind-low = lv_bilid_cl.
        collect ls_bilind into et_bilind_op.
      endif.
    endif.
  endif.
  if ls_t8j0g-crebillind is not initial.
    ls_bilind-low = ls_t8j0g-crebillind.
    collect ls_bilind into et_bilind.
    if iv_mode = 'ALL'      and
      ls_t8j0g-jvfunc = 'CCOP' and
      ls_t8j0g-itemtype = 'AB'.
      call function 'GET_CLEARING_BILLING_IND'
        exporting
          i_clearing_function = ls_t8j0f-clearproc
          i_original_bilid    = ls_t8j0g-crebillind
        importing
          e_clearing_bilid    = lv_bilid_cl.
      if lv_bilid_cl is not initial.
        ls_bilind-low = lv_bilid_cl.
        collect ls_bilind into et_bilind_op.
      endif.
    endif.
  endif.
endloop.
if lines( et_bilind_op ) = 0.
  "Make sure that no items with wrong billing indicators are picked up
  ls_bilind-low = '!!!'.
  collect ls_bilind into et_bilind_op.

```

```
endif.  
endmethod.
```

GET_BILIND_RANGE_CUTBACK

Description: Get the billing indicators used by cutback
Instance mthd

Importing parameter

```
IV_SIGN TYPE CHAR1  
IV_BUKRS TYPE BUKRS
```

Exporting parameter

```
ET_BILIND TYPE JVA_BILIND_RANGE_T
```

```
method get_billind_range_cutback.  
  data: lt_t8j0g  type table of t8j0g,  
        ls_bilind type jva_bilind_range.  
  refresh et_bilind.  
  ls_bilind-sign    = iv_sign.  
  ls_bilind-option = 'EQ'.  
  select * from t8j0g into table lt_t8j0g  
        where bukr    = iv_bukrs  
        and jvfunc    = 'CUTB'.  
  loop at lt_t8j0g into data(ls_t8j0g).  
    if ls_t8j0g-debbillind is not initial.  
      ls_bilind-low = ls_t8j0g-debbillind.  
      collect ls_bilind into et_bilind.  
    endif.  
    if ls_t8j0g-crebillind is not initial.  
      ls_bilind-low = ls_t8j0g-crebillind.  
      collect ls_bilind into et_bilind.  
    endif.  
  endloop.  
endmethod.
```

GET_BILIND_RANGE_PAYMENTS

Description: Get the billing indicators used by payments
Instance mthd

Importing parameter

```
IV_SIGN TYPE CHAR1  
IV_BUKRS TYPE BUKRS
```

Exporting parameter

```
ET_BILIND TYPE JVA_BILIND_RANGE_T
```

```
method get_billind_range_payments.  
  data: lt_t8j0g  type table of t8j0g,  
        ls_bilind type jva_bilind_range,  
        lt_t8ja   type table of t8ja.  
  refresh et_bilind.  
  ls_bilind-sign    = iv_sign.  
  ls_bilind-option = 'EQ'.  
  select * from t8j0g into table lt_t8j0g  
        where bukr    = ms_progpars-bukrs  
        and jvfunc    = 'CCNP'
```

```

                                and itemtype = 'AB'.
loop at lt_t8j0g into data(ls_t8j0g).
  if not ls_t8j0g-debbillind is initial.
    ls_bilind-low = ls_t8j0g-debbillind.
    collect ls_bilind into et_bilind.
  endif.
  if not ls_t8j0g-crebillind is initial.
    ls_bilind-low = ls_t8j0g-crebillind.
    collect ls_bilind into et_bilind.
  endif.
endloop.
* Get the cash call payment and reclass billing indicators
select * from t8ja into table lt_t8ja
      where ccpay = 'X'.
loop at lt_t8ja into data(ls_t8ja).
  ls_bilind-low = ls_t8ja-bilind.
  collect ls_bilind into et_bilind.
endloop.
endmethod.
```

GET_DATA_CC1

Description: Get the ACDOCA lines for cash call adjustments 1
Instance mthd

Importing parameter

```
IT_BILIND_CUTB TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IT_BILIND_PAY TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE
```

Changing parameter

```
CT_ACDOCA_CC1 TYPE GTY_T_ACDOCA_CHECK
CV_ERROR TYPE ABAP_BOOL
```

```
method get_data_cc1.
  data: lv_date_clause type string,
        lt_sel_fields type rsdd_t_compname,
        lt_group_fields type rsdd_t_compname,
        lr_billind type range of jv_bilind,
        lr_billind_op type range of jv_bilind,
        ls_acdoca_totals type jva_acdoc_amounts.
  refresh ct_acdoca_cc1.
  if is_diff_share-partn_old is initial.
    return.
  endif.
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = abap_true
                                it_table = ct_acdoca_cc1
                                iv_source_table = ms_settings-source_table
                                changing
                                ct_sel_fields = lt_sel_fields
                                ct_group_fields = lt_group_fields ).
  get_billind_range_cashcall( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign = 'I'
                              iv_mode = 'ALL'
```

```

importing
  et_bilind      = lr_billind
  et_bilind_op   = lr_billind_op ).
lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
* Get the intercompany postings from table ACDOCA
select (lt_sel_fields) from (ms_settings-source_table)
  bypassing buffer
  appending corresponding fields of table @ct_acdoca_cc1
  where rldnr      = @ms_settings-rldnr
     and rbukrs    = @ms_progpars-bukrs
     and vname     = @ms_progpars-vname
     and egrupp    = @ms_progpars-egold
     and ( kunnr    = @is_diff_share-partn_old or
         lifnr     = @is_diff_share-partn_old or
         vptnr     = @is_diff_share-partn_old )
     "and ( jvactivity = 'CC' or "Original Cash
Call postings
     "      jvactivity = 'EC' or "Previous Equity
Change postings
     "      jvactivity = 'E1' or "Previous Equity
Adjustment postings
     "      jvactivity = 'E2' or "Previous Equity
Adjustment postings
     "      jvactivity = 'F1' ) "Previous Cash
Call correction postings
     and btype     <> @space "Only lines with
billing indicator
     and ( btype    in @lr_billind or
         ( kunnr     = @ms_settings-s_t8jz-opaccnumb and
           btype     in @lr_billind_op ) )
     and awitem     <> '000000' "Exclude balancing
lines
     and racct      in @ms_progpars-t_acct
     and rcntr      in @ms_progpars-t_cntr
     and ps_psp_pnr in @ms_progpars-t_projk
     and aufnr      in @ms_progpars-t_ordnr
     and nplnr      in @ms_progpars-t_nplnr
     and nplnr_vorgn in @ms_progpars-t_vornr
     and (lv_date_clause)
  group by (lt_group_fields).
* Check if the cash calls have already been payed. If yes, set the error flag
loop at ct_acdoca_cc1 into data(ls_acdoca_cc1).
  if ls_acdoca_cc1-btype in it_bilind_pay.
    add ls_acdoca_cc1-wsl to ls_acdoca_totals-wsl.
    add ls_acdoca_cc1-hsl to ls_acdoca_totals-hsl.
    add ls_acdoca_cc1-ksl to ls_acdoca_totals-ksl.
    add ls_acdoca_cc1-osl to ls_acdoca_totals-osl.
    add ls_acdoca_cc1-vsl to ls_acdoca_totals-vsl.
    add ls_acdoca_cc1-bsl to ls_acdoca_totals-bsl.
    add ls_acdoca_cc1-csl to ls_acdoca_totals-csl.
    add ls_acdoca_cc1-dsl to ls_acdoca_totals-dsl.
    add ls_acdoca_cc1-esl to ls_acdoca_totals-esl.
    add ls_acdoca_cc1-fsl to ls_acdoca_totals-fsl.

```

```

        add ls_acdoca_cc1-gsl to ls_acdoca_totals-gsl.
    endif.
endloop.
if ls_acdoca_totals-wsl <> 0 or
   ls_acdoca_totals-hsl <> 0 or
   ls_acdoca_totals-ksl <> 0 or
   ls_acdoca_totals-osl <> 0 or
   ls_acdoca_totals-vsl <> 0 or
   ls_acdoca_totals-bsl <> 0 or
   ls_acdoca_totals-csl <> 0 or
   ls_acdoca_totals-dsl <> 0 or
   ls_acdoca_totals-esl <> 0 or
   ls_acdoca_totals-fsl <> 0 or
   ls_acdoca_totals-gsl <> 0.
    cv_error = abap_true.
endif.
endmethod.

GET_DATA_CC1_INTCO
Description: Get the ACDOCA lines for cash call adjustments 1
Instance mthd

Importing parameter
IT_BILIND_CUTB TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IT_BILIND_PAY TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE

Changing parameter
CT_ACDOCA_CC1 TYPE GTY_T_ACDOCA_CHECK
CV_ERROR TYPE ABAP_BOOL

method get_data_cc1_intco.
    data: lv_date_clause    type string,
          lt_sel_fields     type rsdd_t_compname,
          lt_group_fields   type rsdd_t_compname,
          lr_billind        type range of jv_billind,
          ls_acdoca_totals type jva_acdoc_amounts.
    refresh ct_acdoca_cc1.
    if is_diff_share-partn_old is initial.
        return.
    endif.
    get_fields_for_acdoca_selects( exporting
                                   iv_single_items = abap_true
                                   it_table         = ct_acdoca_cc1
                                   iv_source_table  = ms_settings-source_table
                                   changing
                                   ct_sel_fields    = lt_sel_fields
                                   ct_group_fields  = lt_group_fields ).
    get_billind_range_cashcall( exporting
                                   iv_bukrs = ms_progpars-bukrs
                                   iv_sign  = 'I'
                                   iv_mode  = 'ALL'
                                   importing
                                   et_billind = lr_billind ).
    lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
```

)).

```

*   Get the intercompany postings from table ACDOCA
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        appending corresponding fields of table @ct_acdoca_cc1
    where rldnr      = @ms_settings-rldnr
        and rbukrs   = @is_diff_share-intcocd_old
        and ( vname  = @is_diff_share-intrcovent_old or
            vname    = @is_diff_share-intrcovent_new )
        and egrup    = @is_diff_share-intcompegp_old
        and ( kunnr   = @is_diff_share-partn_old or
            lifnr     = @is_diff_share-partn_old or
            vptnr     = @is_diff_share-partn_old )
        "and ( jvactivity = 'CC' or                "Original Cash
Call postings      "      jvactivity = 'EC' or                "Previous Equity
Change postings    "      jvactivity = 'E1' or                "Previous Equity
Adjustment postings      jvactivity = 'E2' or                "Previous Equity
Adjustment postings    "      jvactivity = 'F1' )                "Previous Cash
Call correction postings      jvactivity = 'F1' )                "Previous Cash
billing indicator    and btype      <> @space                "Only lines with
balancing lines      and btype      in @lr_billind
                    and awitem      <> '000000'                "Exclude
                    and racct       in @ms_progpars-t_acct
                    and rcntr       in @ms_progpars-t_cntr
                    and ps_psp_pnr  in @ms_progpars-t_projk
                    and aufnr       in @ms_progpars-t_ordnr
                    and nplnr       in @ms_progpars-t_nplnr
                    and nplnr_vorgn in @ms_progpars-t_vornr
                    and (lv_date_clause)
                    group by (lt_group_fields).

*   Check if the cash calls have already been payed. If yes, set the error flag
    loop at ct_acdoca_cc1 into data(ls_acdoca_cc1).
        if ls_acdoca_cc1-btype in it_bilind_pay.
            add ls_acdoca_cc1-wsl to ls_acdoca_totals-wsl.
            add ls_acdoca_cc1-hsl to ls_acdoca_totals-hsl.
            add ls_acdoca_cc1-ksl to ls_acdoca_totals-ksl.
            add ls_acdoca_cc1-osl to ls_acdoca_totals-osl.
            add ls_acdoca_cc1-vsl to ls_acdoca_totals-vsl.
            add ls_acdoca_cc1-bsl to ls_acdoca_totals-bsl.
            add ls_acdoca_cc1-csl to ls_acdoca_totals-csl.
            add ls_acdoca_cc1-dsl to ls_acdoca_totals-dsl.
            add ls_acdoca_cc1-esl to ls_acdoca_totals-esl.
            add ls_acdoca_cc1-fsl to ls_acdoca_totals-fsl.
            add ls_acdoca_cc1-gsl to ls_acdoca_totals-gsl.
        endif.
    endloop.
    if ls_acdoca_totals-wsl <> 0 or
       ls_acdoca_totals-hsl <> 0 or

```

```
ls_acdoca_totals-ksl <> 0 or
ls_acdoca_totals-osl <> 0 or
ls_acdoca_totals-vsl <> 0 or
ls_acdoca_totals-bsl <> 0 or
ls_acdoca_totals-csl <> 0 or
ls_acdoca_totals-dsl <> 0 or
ls_acdoca_totals-esl <> 0 or
ls_acdoca_totals-fsl <> 0 or
ls_acdoca_totals-gsl <> 0.
cv_error = abap_true.
endif.
endmethod.
```

GET_DATA_CC2

Description: Get the ACDOCA lines for cash call adjustments 2
Instance mthd

Changing parameter

```
CT_ACDOCA TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN TYPE REF TO DATA
CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN_POSTED TYPE REF TO DATA
```

```
method get_data_cc2.
  data: lv_date_clause    type string,
        lt_sel_fields     type rsdd_t_compname,
        lt_group_fields   type rsdd_t_compname,
        lr_billind_off    type range of jv_billind,
        lr_billind_partn  type range of jv_billind,
        lr_billind_op     type range of jv_billind,
        lt_fieldcatalog   type lvc_t_fcat,
        lv_single_items   type abap_bool.
  field-symbols: <lt_acdoca_dyn>      type standard table,
                 <lt_acdoca_dyn_posted> type standard table.
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = lv_single_items
                                iv_source_table = ms_settings-source_table
                                importing
                                et_fieldcatalog = lt_fieldcatalog
                                changing
                                ct_sel_fields  = lt_sel_fields
                                ct_group_fields = lt_group_fields ).

  get_billind_range_cashcall( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'I'
                              iv_mode  = 'PARTNER'
                              importing
                              et_billind    = lr_billind_partn
                              et_billind_op = lr_billind_op ).

  get_billind_range_cashcall( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'I'
                              iv_mode  = 'OFFSET'
                              importing
```

```

                                et_bilind = lr_billind_off ).
if lr_billind_off[] is initial.
    return.
endif.
lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
if lv_single_items = abap_false.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       = cr_acdoca_dyn
).
    assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       =
cr_acdoca_dyn_posted ).
    assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
endif.
loop at ms_settings-t_diff_share into data(ls_diff_share).
    if ls_diff_share-eqshare_old = ls_diff_share-eqshare_new.
        continue.
    endif.
    if ls_diff_share-eqshare_old > 0.
*       Get the original cash call postings from table acdoca
        select (lt_sel_fields) from (ms_settings-source_table)
            bypassing buffer
            appending corresponding fields of table
@<lt_acdoca_dyn>
                                where rldnr      = @ms_settings-rldnr
                                and rbukrs       = @ms_progpars-bukrs
                                and vname        = @ms_progpars-vname
                                and egrup        = @ls_diff_share-eg_old
                                and ( kunnr      = @ls_diff_share-partn_old or
                                    lifnr       = @ls_diff_share-partn_old or
                                    vptnr       = @ls_diff_share-partn_old )
                                and btype       <> @space
                                and ( btype      in @lr_billind_off      or "Cash call
lines with offset billing indicator
                                ( jvactivity = 'F1' and                    "Cash call
lines with partner billing indicator
                                btype      in @lr_billind_partn )
                                or
                                ( jvactivity = 'CC' and                    "Operator
postings
                                btype      in @lr_billind_op ) )
                                and awitem     <> '000000'                  "Exclude
balancing lines
                                and racct      in @ms_progpars-t_acct
                                and rcntr      in @ms_progpars-t_cntr
                                and ps_psp_pnr in @ms_progpars-t_projk

```

```

        and aufnr      in @ms_progpars-t_ordnr
        and nplnr      in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and (lv_date_clause)
    group by (lt_group_fields).
endif.
*
    Get any previous adjustment postings from table acdoca
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        appending corresponding fields of table
@<lt_acdoca_dyn_posted>
    where rldnr      = @ms_settings-rldnr
    and rbukrs      = @ms_progpars-bukrs
    and vname       = @ms_progpars-vname
    and ( egrup     = @ms_progpars-eqold or
        egrup     = @ms_progpars-eqnew )
    and ( kunnr     = @ls_diff_share-partn_new or
        lifnr     = @ls_diff_share-partn_new or
        vptnr     = @ls_diff_share-partn_new )
    and jvactivity  = 'F1'                "Previous cash
call corrections
    and awitem      <> '0000000'          "Eclude
balancing lines
    and racct       in @ms_progpars-t_acct
    and rcntr       in @ms_progpars-t_cntr
    and ps_psp_pnr  in @ms_progpars-t_projk
    and aufnr      in @ms_progpars-t_ordnr
    and nplnr      in @ms_progpars-t_nplnr
    and nplnr_vorgn in @ms_progpars-t_vornr
    and (lv_date_clause)
    group by (lt_group_fields).

endloop.
endmethod.
```

GET_DATA_CC2_INTCO

Description: Get the ACDOCA lines for intercompany cash call adjustments
Instance mthd

Changing parameter

CT_ACDOCA TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN TYPE REF TO DATA
CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN_POSTED TYPE REF TO DATA

```

method get_data_cc2_intco.
    data: lv_date_clause type string,
          lt_sel_fields  type rsdd_t_compname,
          lt_group_fields type rsdd_t_compname,
          lr_billind     type range of jv_billind,
          lt_fieldcatalog type lvc_t_fcat,
          lv_single_items type abap_bool.
    field-symbols: <lt_acdoca_dyn> type standard table,
                  <lt_acdoca_dyn_posted> type standard table.
    get_fields_for_acdoca_selects( exporting
```

```

        iv_single_items = lv_single_items
        iv_source_table = ms_settings-source_table
    importing
        et_fieldcatalog = lt_fieldcatalog
    changing
        ct_sel_fields   = lt_sel_fields
        ct_group_fields = lt_group_fields ).

get_billind_range_cashcall( exporting
    iv_bukrs = ms_progpars-bukrs
    iv_sign  = 'I'
    iv_mode  = 'OFFSET'
    importing
        et_billind = lr_billind ).

if lr_billind[] is initial.
    return.
endif.
lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
if lv_single_items = abap_false.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       = cr_acdoca_dyn
    ).
    assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       =
cr_acdoca_dyn_posted ).
    assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
endif.
loop at ms_settings-t_diff_share_intco into data(ls_diff_share).
    check ls_diff_share-eqshare_old <> ls_diff_share-eqshare_new and
        ls_diff_share-eqshare_old > 0.
*   Select the single items from table acdoca
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        appending corresponding fields of table @<lt_acdoca_dyn>
    where rldnr      = @ms_settings-rldnr
       and rbukrs    = @ls_diff_share-intcocd_old
       and vname     = @ls_diff_share-intrcovent_old
       and egrup     = @ls_diff_share-intcompepgp_old
       and ( kunnr    = @ls_diff_share-partn_old or
             lifnr     = @ls_diff_share-partn_old or
             vptnr     = @ls_diff_share-partn_old )
       "and ( jvactivity = 'CC' or "Original Cash
Call postings
       "      jvactivity = 'E2' ) "Previous
Equity Adjustment postings
       and btype     <> @space
       and btype     in @lr_billind "Cash call

```

```
lines with offset billing indicator
                                and awitem      <> '000000'      "Eclude
balancing lines
                                and racct       in @ms_progpars-t_acct
                                and rcntr       in @ms_progpars-t_cntr
                                and ps_psp_pnr  in @ms_progpars-t_projk
                                and aufnr      in @ms_progpars-t_ordnr
                                and nplnr      in @ms_progpars-t_nplnr
                                and nplnr_vorgn in @ms_progpars-t_vornr
                                and (lv_date_clause)
                                group by (lt_group_fields).
*      Select the single items from table acdoca
      select (lt_sel_fields) from (ms_settings-source_table)
      bypassing buffer
      appending corresponding fields of table
@<lt_acdoca_dyn_posted>
                                where rldnr    = @ms_settings-rldnr
                                and rbukrs     = @ls_diff_share-intcocd_new
                                and vname      = @ls_diff_share-intrcovent_new
                                and egrup      = @ls_diff_share-intcompegp_new
                                and ( kunnr    = @ls_diff_share-partn_new or
                                    lifnr     = @ls_diff_share-partn_new or
                                    vptnr     = @ls_diff_share-partn_new )
                                and jvactivity = 'F1'              "Previous cash
call corrections
                                and awitem      <> '000000'      "Eclude
balancing lines
                                and racct       in @ms_progpars-t_acct
                                and rcntr       in @ms_progpars-t_cntr
                                and ps_psp_pnr  in @ms_progpars-t_projk
                                and aufnr      in @ms_progpars-t_ordnr
                                and nplnr      in @ms_progpars-t_nplnr
                                and nplnr_vorgn in @ms_progpars-t_vornr
                                and (lv_date_clause)
                                group by (lt_group_fields).

      endloop.
    endmethod.
```

GET_DATA_EC

Description: Get the ACDOCA lines for equity change
Instance mthd

Changing parameter

```
CT_ACDOCA_MAIN TYPE GTY_T_ACDOCA_CHECK
CT_ACDOCA_AGGR TYPE GTY_T_ACDOCA_AGGREGATED
```

```
method get_data_ec.
  data: lt_sel_fields      type rsdd_t_compname,
        lt_group_fields   type rsdd_t_compname,
        lv_date_clause    type string,
        lv_cbrunid_initial type acdoca-cbrunid,
        lt_acdoca_aggr    type gty_t_acdoca_aggregated.
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = abap_true
```

```

        iv_ec_aggregated = ms_progpars-ec_aggregated
        it_table          = ct_acdoca_main
        iv_source_table   = ms_settings-source_table
        changing
        ct_sel_fields     = lt_sel_fields
        ct_group_fields   = lt_group_fields ).
lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
if ms_settings-t_recid_billable[] is initial.
    return.
endif.
if ms_progpars-ec_aggregated = abap_true.
    "Select aggregated data from table ACDOCA
    select (lt_sel_fields) from (ms_settings-source_table)
        where rldnr      = @ms_settings-rldnr
        and rbukrs       = @ms_progpars-bukrs
        and vname        = @ms_progpars-vname
        and egrup        = @ms_progpars-eqold
        and recid        in @ms_settings-t_recid_billable
        and racct        in @ms_progpars-t_acct
        and rcntr        in @ms_progpars-t_cntr
        and ps_psp_pnr    in @ms_progpars-t_projk
        and aufnr        in @ms_progpars-t_ordnr
        and nplnr        in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and ( ( jvactivity = 'E1' and
                poper >= '001' and poper <= '012' )
              or
              ( ( cbrunid    <> @lv_cbrunid_initial or
                "Only pick up items that were cutbacked, already
                  jvactivity = 'E2' )
                (lv_date_clause)
                budat in @ms_progpars-t_budat ) )
        group by (lt_group_fields)
        into corresponding fields of table @lt_acdoca_aggr
        bypassing buffer.
    loop at lt_acdoca_aggr into data(ls_acdoca_aggr).
        clear: ls_acdoca_aggr-ryear,
               ls_acdoca_aggr-poper.
        if ms_settings-s_t8jz-pm_act = abap_false.
            clear ls_acdoca_aggr-prodper.
        endif.
        collect ls_acdoca_aggr into ct_acdoca_aggr.
    endloop.
    delete ct_acdoca_aggr where wsl = 0
        and hsl = 0
        and ksl = 0
        and osl = 0
        and vsl = 0
        and bsl = 0
        and csl = 0
        and dsl = 0
        and esl = 0
        and fsl = 0

```

```

        and gsl = 0.
    sort ct_acdoca_aggr.
    free lt_acdoca_aggr.
else.
    "Select the single items from table ACDOCA
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        into corresponding fields of table @ct_acdoca_main
    where rldnr      = @ms_settings-rldnr
        and rbukrs   = @ms_progpars-bukrs
        and vname    = @ms_progpars-vname
        and egrup    = @ms_progpars-egrup
        and recid    in @ms_settings-t_recid_billable
        and racct    in @ms_progpars-t_acct
        and rcntr    in @ms_progpars-t_cntr
        and ps_psp_pnr in @ms_progpars-t_projk
        and aufnr    in @ms_progpars-t_ordnr
        and nplnr    in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and ( ( jvactivity = 'E1' and
                poper >= '001' and poper <= '012' )
            or
            ( ( cbrunid    <> @lv_cbrunid_initial or
                jvactivity = 'E2' )
              (lv_date_clause)
              budat in @ms_progpars-t_budat ) )
        order by src_awref,
            src_awitem,
            racct,
            vname,
            egrup,
            btype,
            vptnr,
            prctr,
            rcntr,
            aufnr,
            ps_psp_pnr,
            nplnr,
            nplnr_vorgn,
            timestamp,
            belnr,
            buzei,
            docln.
endif.
endmethod.

```

GET_DATA_INTCO

Description: Get the ACDOCA lines for intercompany adjustments

Instance mthd

Changing parameter

CT_ACDOCA_INTCO_NEW TYPE JVA_CB_ACDOCA_T

CT_ACDOCA_INTCO_OLD TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)

```

method get_data_intco.
  data: lt_acdoca type jva_cb_acdoca_t.
  types: begin of lty_s_intcomp,
          intcocd_new type t8jvt02-intcocd,
          intrcovent_new type t8jvt02-intrcovent,
          intcompegp_new type t8jvt02-intcompegp,
          intcompegp_old type t8jvt02-intcompegp,
        end of lty_s_intcomp.
  data: lv_date_clause type string,
        lt_sel_fields type rsdd_t_compname,
        lt_t8j0g type table of t8j0g,
        lr_recid type range of jv_recind,
        ls_recid like line of lr_recid,
        ls_intcomp type lty_s_intcomp,
        lt_intcomp type table of lty_s_intcomp,
        lv_cbrunid_initial type acdoca-cbrunid.
  refresh: ct_acdoca_intco_new,
           ct_acdoca_intco_old.
* Get fields for acdoca selects
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = abap_true
                                it_table = lt_acdoca
                                iv_source_table = ms_settings-source_table
                                changing
                                ct_sel_fields = lt_sel_fields ).
  lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
* Get the relevant recovery indicators
  ls_recid-sign = 'I'.
  ls_recid-option = 'EQ'.
  select * from t8j0g into table lt_t8j0g
          where bukrs = ms_progpars-bukrs
          and jvfunc = 'FACI'
          and itemtype = 'EX'.
  loop at lt_t8j0g into data(ls_t8j0g).
    if not ls_t8j0g-debrecid is initial.
      ls_recid-low = ls_t8j0g-debrecid.
      collect ls_recid into lr_recid.
    endif.
    if not ls_t8j0g-crerecid is initial.
      ls_recid-low = ls_t8j0g-crerecid.
      collect ls_recid into lr_recid.
    endif.
  endloop.
* Get the relevant intercompany data
  loop at ms_settings-t_diff_share into data(ls_diff_share)
          where intcocd_old <> space
          and intcocd_new <> space.
    move-corresponding ls_diff_share to ls_intcomp.
    collect ls_intcomp into lt_intcomp.
  endloop.
  loop at lt_intcomp into ls_intcomp.
*   Select the single items from table acdoca
    select (lt_sel_fields) from (ms_settings-source_table)

```

```

      bypassing buffer
      appending corresponding fields of table @lt_acdoca
      where rldnr      = @ms_settings-rldnr
         and rbukrs    = @ls_intcomp-intcocd_new
         and vname     = @ls_intcomp-intrcovent_new
         and ( egrup   = @ls_intcomp-intcompegp_old or
              egrup   = @ls_intcomp-intcompegp_new )
         and recid     in @lr_recid
         and cbrunid   <> @lv_cbrunid_initial
         and racct     in @ms_progpars-t_acct
         and rcntr     in @ms_progpars-t_cntr
         and ps_psp_pnr in @ms_progpars-t_projk
         and aufnr     in @ms_progpars-t_ordnr
         and nplnr     in @ms_progpars-t_nplnr
         and nplnr_vorgn in @ms_progpars-t_vornr
         and ( jvactivity = 'E1' or
              ( jvactivity <> 'E1' and
                budat in @ms_progpars-t_budat and
                (lv_date_clause) ) )
      order by primary key.
loop at lt_acdoca into data(ls_acdoca_intco).
  if ls_acdoca_intco-vname = ls_intcomp-intrcovent_new and
     ls_acdoca_intco-egrup = ls_intcomp-intcompegp_new.
    append ls_acdoca_intco to ct_acdoca_intco_new.
  else.
    ls_acdoca_intco-egrup = ls_intcomp-intcompegp_new.
    append ls_acdoca_intco to ct_acdoca_intco_old.
  endif.
endloop.
endloop.
sort ct_acdoca_intco_new by rbukrs
                           rwcure
                           ryear
                           vname
                           egrup
                           racct
                           rbusa
                           rcntr
                           aufnr
                           ps_psp_pnr
                           prctr
                           recid
                           vptnr
                           nplnr
                           nplnr_vorgn
                           anl1
                           anl2
                           anbwa.
sort ct_acdoca_intco_old by rbukrs
                           rwcure
                           ryear
                           vname
                           egrup
                           racct

```

```

        rbusa
        rcntr
        aufnr
        ps_psp_pnr
        prctr
        recid
        vptnr
        nplnr
        nplnr_vorgn
        anln1
        anln2
        anbwa.

    endmethod.
```

GET_FIELDS_FOR_ACDOCA_SELECTS

Description: Get the fields to be retrieved through the ACDOCA select
Instance mthd

Importing parameter

```

IV_SINGLE_ITEMS TYPE ABAP_BOOL (Processing type)
IT_TABLE TYPE ANY TABLE OPTIONAL (Target Table)
IV_EC_AGGREGATED TYPE ABAP_BOOL OPTIONAL
IV_SOURCE_TABLE TYPE RSCOMPNAME OPTIONAL (Source Table)
IV_AGGR_AMNTS TYPE ABAP_BOOL OPTIONAL
IV_PREFIX TYPE STRING OPTIONAL
```

Exporting parameter

```

ET_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)
```

Changing parameter

```

CT_SEL_FIELDS TYPE RSDD_T_COMPNAME (Table type for FIELDNAME)
CT_GROUP_FIELDS TYPE RSDD_T_COMPNAME OPTIONAL (Table type for FIELDNAME)
```

```

method get_fields_for_acdoca_selects.
    data: ls_sel_fields like line of ct_sel_fields,
          lt_fieldlist type ttfieldname,
          lt_dfies type dfies_table,
          lo_structdescr type ref to cl_abap_structdescr,
          lo_tabledescr type ref to cl_abap_tabledescr,
          lt_acdoca_aggr type gty_t_acdoca_aggregated,
          lv_fieldname type string,
          lv_selname type string.
    refresh: ct_sel_fields, ct_group_fields.
* Collect fields to be retrieved for acdoca selects
    if iv_ec_aggregated = abap_true.
        "Get fields for aggregated selects
        cl_jva_util=>get_selection_fields(
            exporting
                it_table = lt_acdoca_aggr
                iv_source_table = iv_source_table
                iv_aggr_amnts = abap_true
                iv_prefix = space
            changing
                ct_sel_fields = ct_sel_fields
                ct_group_fields = ct_group_fields ).
    return.
```

```

endif.
* For equity change postings that go to ACDOCA directly, get the line
* items with document number and line number
if iv_single_items = abap_true.
  lo_tabledescr ?= cl_abap_typedescr=>describe_by_data( it_table ).
  lo_structdescr ?= lo_tabledescr->get_table_line_type( ).
  if iv_source_table is not initial.
    data(lo_typedescr_source) = cl_abap_typedescr=>describe_by_name(
iv_source_table ).
    data(lt_fieldname_source) = lo_typedescr_source->get_ddic_object( ).
  endif.
  loop at lo_structdescr->components[] assigning field-symbol(<ls_component>).
    if iv_source_table is not initial.
      read table lt_fieldname_source transporting no fields
        with key fieldname = <ls_component>-name.

      if sy-subrc <> 0.
        continue.
      endif.
    endif.
    if iv_aggr_amnts = abap_true and
      <ls_component>-name+1(2) = 'SL'.
      append |SUM( { iv_prefix }{ <ls_component>-name } ) AS | &&
<ls_component>-name to ct_sel_fields.
    else.
      lv_selname = iv_prefix && <ls_component>-name.
      lv_fieldname = iv_prefix && <ls_component>-name.
*      Add selection field
      append lv_selname to ct_sel_fields.
*      Add group-by field
      append lv_fieldname to ct_group_fields.
    endif.
  endloop.
  loop at ct_sel_fields into ls_sel_fields.
    try.
      cl_abap_dyn_prg=>check_column_name( ls_sel_fields-compname ).
      catch cx_abap_invalid_name.
      delete ct_sel_fields where compname = ls_sel_fields-compname.
    endtry.
  endloop.
else.
* For processes that post aggregated documents, get the data in an aggregated way
with the relevant fields
call function 'DDIF_NAMETAB_GET'
  exporting
    tabname   = iv_source_table
  tables
    dfies_tab = lt_dfies
  exceptions
    not_found = 1
    others    = 2.
if sy-subrc <> 0.
  message e000(gj) with 'Fatal error when retrieving field catalog!'
    into mv_message_text ##NO_TEXT ##MG_MISSING.
  save_sy_message( ).

```

```

        return.
    endif.
    sort lt_dfies by fieldname.
*   Get the balance sheet accounts
    try.
        cl_fins_acdoc_fieldcat_service=>get_active_fields_bcf_bs( importing
                                                                    et_fields =
lt_fieldlist ).
        catch cx_root ##NO_HANDLER.
            "Do nothing
        endtry.
*   Add the relevant fields to the selection fields table
    loop at lt_fieldlist into data(ls_fieldname).
        add_item_to_select_tables( exporting
                                    it_dfies      = lt_dfies
                                    iv_fieldname   = ls_fieldname
                                changing
                                    ct_fieldcatalog = et_fieldcatalog
                                    ct_sel_fields  = ct_sel_fields
                                    ct_group_fields = ct_group_fields ).
    endloop.
*   Get any additional fields relevant for P&L
    try.
        cl_fins_acdoc_fieldcat_service=>get_fields_bcf_pl_and_split( importing
                                                                    et_fields =
lt_fieldlist ).
        catch cx_root ##NO_HANDLER.
            "Do nothing
        endtry.
    loop at lt_fieldlist into ls_fieldname.
        add_item_to_select_tables( exporting
                                    it_dfies      = lt_dfies
                                    iv_fieldname   = ls_fieldname
                                changing
                                    ct_fieldcatalog = et_fieldcatalog
                                    ct_sel_fields  = ct_sel_fields
                                    ct_group_fields = ct_group_fields ).
    endloop.
*   Make sure that all venture fields and all cost objects are in the lists
    lt_fieldlist = value #(
        ( 'JVACTIVITY' )
        ( 'VNAME' )
        ( 'EGRUP' )
        ( 'ETYPE' )
        ( 'RECID' )
        ( 'BTYPE' )
        ( 'VPTNR' )
        ( 'PVNAME' )
        ( 'PEGRUP' )
        ( 'PRODPER' )
        "( 'CBRACCT' )
        "( 'CBOBJNR' )
        "( 'CBRUNID' )
        ( 'RCNTR' )

```

```

        ( 'AUFNR' )
        ( 'PS_PSP_PNR' )
        ( 'NPLNR' )
        ( 'NPLNR_VORGN' )
    ).
loop at lt_fieldlist into ls_fieldname.
    add_item_to_select_tables( exporting
                               it_dfies      = lt_dfies
                               iv_fieldname   = ls_fieldname
                               changing
                               ct_fieldcatalog = et_fieldcatalog
                               ct_sel_fields  = ct_sel_fields
                               ct_group_fields = ct_group_fields ).
endloop.
endif.
"Add commas for modern SELECT
loop at ct_sel_fields assigning field-symbol(<ls_field>).
    if sy-tabix < lines( ct_sel_fields ).
        <ls_field>-compname &&= ``,``.
    endif.
endloop.
loop at ct_group_fields assigning <ls_field>.
    if sy-tabix < lines( ct_group_fields ).
        <ls_field>-compname &&= ``,``.
    endif.
endloop.
endmethod.
```

GET_INTCO_VENDOR

Description: Get the intercompany vendor
Instance mthd

Importing parameter

- IV_BUKRS TYPE BUKRS (Company Code)
- IV_PARTN TYPE ACDOCA-VPTNR (Partner account number)

Returning parameter

VALUE(RV_LIFNR) TYPE LIFNR (Account Number of Supplier)

```

method get_intco_vendor.
    data: ls_t8jo type t8jo,
          ls_kna1 type kna1.
    if ls_t8jo-bukrs <> iv_bukrs or
       ls_t8jo-intcocd <> ms_progpars-bukrs.
        select single * from t8jo into ls_t8jo
            where bukrs    = iv_bukrs
              and partn    = iv_partn
              and intcocd = ms_progpars-bukrs.
    else.
        sy-subrc = 0.
    endif.
    if sy-subrc = 0.
        clear ls_kna1.
        select single kunnr lifnr
            from kna1 into corresponding fields of ls_kna1
```

```

        where kunnr = ls_t8jo-partn.
    if not ls_kna1-lifnr is initial.
        rv_lifnr = ls_kna1-lifnr.
    else.
        rv_lifnr = ls_t8jo-partn.
    endif.
else.
    message i799(g5) with ms_progpars-bukrs into mv_message_text.
    save_sy_message( ).
endif.
endmethod.
```

GET_MSGS_FROM_MSG_COLLECTOR

Description: Get messages from message collector

Instance mthd

```

method get_msgs_from_msg_collector.
    data: ls_t8jvt01 type t8jvt01.
    loop at mo_message_collector->get_access( )->get_messages( ) into
data(ls_message).
    move-corresponding ls_message to ls_t8jvt01.
    ls_t8jvt01-status = ls_message-msgty.
    ls_t8jvt01-var1 = ls_message-msgv1.
    ls_t8jvt01-var2 = ls_message-msgv2.
    ls_t8jvt01-var3 = ls_message-msgv3.
    ls_t8jvt01-var4 = ls_message-msgv4.
    ls_t8jvt01-text = ls_message-text.
    append ls_t8jvt01 to ms_ea_results-t_messages.
endloop.
endmethod.
```

GET_PARTNER_SHARES

Description: Get the partner shares

Instance mthd

```

method get_partner_shares.
    data: lv_tabix_new      type sy-tabix,
          lv_oper_alloc_error type c,
          lo_message_collector type ref to if_jva_message_collection.
    lo_message_collector = cl_jva_message_factory=>get_message_collector( ).
    mo_partner_shares->get_partner_shares( exporting
ms_settings-s_t8jz
                                     is_t8jz
                                     =
                                     iv_company
                                     = ms_settings-bukrs
                                     iv_equity_grp
                                     = ms_progpars-eqold
                                     iv_include_0_percent
                                     = abap_true
                                     iv_is_npoci
                                     = abap_true
                                     iv_period
                                     =
ms_progpars-period
                                     iv_venture
                                     = ms_progpars-vname
                                     iv_year
                                     = ms_progpars-year
importing
                                     et_shares
                                     =
ms_settings-t_shares_old
```

```

lv_oper_alloc_error      ev_oper_alloc_error  =
lv_oper_alloc_error      eo_message_collector =
lo_message_collector ).
  loop at lo_message_collector->get_access( )->get_messages( ) into
data(ls_message).
  save_message( iv_type   = ls_message-msgty
                iv_class  = ls_message-msgid
                iv_number = ls_message-msgno
                iv_var1   = ls_message-msgv1
                iv_var2   = ls_message-msgv2
                iv_var3   = ls_message-msgv3
                iv_var4   = ls_message-msgv4 ).
endloop.
if lo_message_collector->has_critical_messages( ) = abap_true.
  refresh ms_settings-t_shares_old.
endif.
lo_message_collector->reset( ).
mo_partner_shares->get_partner_shares( exporting
                                     is_t8jz          =
ms_settings-s_t8jz
                                     iv_company       = ms_settings-bukrs
                                     iv_equity_grp     = ms_progpars-eqnew
                                     iv_include_0_percent = abap_true
                                     iv_is_npoci       = abap_true
                                     iv_period        =
ms_progpars-period
                                     iv_venture       = ms_progpars-vname
                                     iv_year          = ms_progpars-year
importing
et_shares          =
ms_settings-t_shares_new
ev_oper_alloc_error =
lv_oper_alloc_error
eo_message_collector =
lo_message_collector ).
  loop at lo_message_collector->get_access( )->get_messages( ) into ls_message.
  save_message( iv_type   = ls_message-msgty
                iv_class  = ls_message-msgid
                iv_number = ls_message-msgno
                iv_var1   = ls_message-msgv1
                iv_var2   = ls_message-msgv2
                iv_var3   = ls_message-msgv3
                iv_var4   = ls_message-msgv4 ).
endloop.
if lo_message_collector->has_critical_messages( ) = abap_true.
  refresh ms_settings-t_shares_new.
endif.
* Delete equity groups where the shares are zero in both tables
loop at ms_settings-t_shares_new into data(ls_shares_new)
  where eqshare = 0.
  lv_tabix_new = sy-tabix.
  loop at ms_settings-t_shares_old into data(ls_shares_old)
    where partn = ls_shares_new-partn

```

```

                                and opflag = ls_shares_new-opflag
                                and eqshare = 0.
    delete ms_settings-t_shares_old index sy-tabix.
    exit.
endloop.
if sy-subrc = 0.
    delete ms_settings-t_shares_new index lv_tabix_new.
endif.
endloop.
endmethod.
```

GET_POSTING_RULE

Description: Get posting rule
Instance mthd

Importing parameter

```
VALUE(IV_BUKRS) TYPE  ACDOCA-RBUKRS
VALUE(IV_JVFUNC) TYPE  JV_FUNC (JV Function)
VALUE(IV_JVACTIVITY) TYPE  ACDOCA-JVACTIVITY
VALUE(IV_RECID) TYPE  ACDOCA-RECID (Recovery Indicator)
```

Changing parameter

```
CS_T8J0G TYPE  T8J0G
CV_FATAL_ERROR TYPE  C
CV_ERROR_TEXT TYPE  STRING
```

```
method get_posting_rule.
    data: lv_itemtype      type t8j0g-itemtype,
          lv_jvfunc       type t8j0a-jvfunc,
          lv_bmethod      type t8jv-bmethod,
          ls_t8j0g        type t8j0g,
          lv_fatal_error  type abap_bool,
          lv_error_text   type string.
    clear cs_t8j0g.
    lv_bmethod = ms_settings-s_t8jv-bmethod.
    lv_jvfunc = iv_jvfunc.
    lv_itemtype = iv_jvactivity.
*   Get JV function
    if ms_settings-s_t8j0a-jvfunc <> lv_jvfunc.
        select single * from t8j0a into ms_settings-s_t8j0a
            where jvfunc = lv_jvfunc.
    endif.
*   Read posting rules without billing method
*   if JV function does not allow a billing method
    if ms_settings-s_t8j0a-billmethid is initial.
        clear lv_bmethod.
    endif.
*   Get the document type
    if ms_settings-s_t8j0f-bukrs <> iv_bukrs or
        ms_settings-s_t8j0f-bmethod <> lv_bmethod or
        ms_settings-s_t8j0f-jvfunc <> lv_jvfunc.
        select single doctyped from t8j0f into ms_settings-s_t8j0f
            where bukrs = iv_bukrs
                and bmethod = lv_bmethod
                and jvfunc = lv_jvfunc.
```

```
    if sy-subrc <> 0.
        lv_fatal_error = 'X'.
    endif.
endif.
* Get all posting rules for the given method and function
read table ms_settings-t_t8j0g into ms_settings-s_t8j0g index 1. "#EC CI_NOORDER
if ls_t8j0g-bukrs <> iv_bukrs or
    ls_t8j0g-bmethod <> lv_bmethod or
    ls_t8j0g-jvfunc <> lv_jvfunc.
    select * from t8j0g into table ms_settings-t_t8j0g
        bypassing buffer
        where bukrs = iv_bukrs
            and bmethod = lv_bmethod
            and jvfunc = lv_jvfunc
        order by jvfunc itemtype recid.

    if sy-subrc <> 0.
        lv_fatal_error = 'X'.
    endif.
endif.
if lv_fatal_error = 'X'.
    message e769(g5) with iv_bukrs lv_bmethod lv_jvfunc into lv_error_text.
    save_sy_message( ).
    return.
endif.
* Get the posting rule for the given recovery indicator
clear cs_t8j0g.
read table ms_settings-t_t8j0g into cs_t8j0g
    with key jvfunc = lv_jvfunc
        itemtype = lv_itemtype
        recid = iv_recid.

* If no posting rule can be found for the given RI, search for a posting rule where
the RI is space
if cs_t8j0g is initial.
    read table ms_settings-t_t8j0g into cs_t8j0g
        with key jvfunc = lv_jvfunc
            itemtype = lv_itemtype
            recid = space.

* If no posting rule can be found by RI, get any posting rule
if cs_t8j0g is initial.
    read table ms_settings-t_t8j0g into cs_t8j0g
        with key jvfunc = lv_jvfunc
            itemtype = lv_itemtype.

    endif.
endif.
ms_settings-s_t8j0g = cs_t8j0g.
if cs_t8j0g is initial.
    lv_fatal_error = 'X'.
    message e769(g5) with iv_bukrs lv_jvfunc lv_itemtype into lv_error_text.
    save_sy_message( ).
endif.
if lv_fatal_error = 'X'.
    cv_fatal_error = 'X'.
    if cv_error_text is initial.
        cv_error_text = lv_error_text.
```

```
endif.  
endif.  
endmethod.
```

GET_POSTING_RULES

Description: Get the posting rules
Instance mthd

Importing parameter

```
IV_BMETHOD TYPE T8JV-BMETHOD  
IV_BUKRS TYPE BUKRS  
IV_FUNCTION TYPE T8J0F-JVFUNC
```

Changing parameter

```
CV_ERROR TYPE ABAP_BOOL
```

```
method get_posting_rules.  
  "Get the JV function  
  select single * from t8j0a into ms_settings-s_t8j0a  
                                where jvfunc = iv_function.  
  
  "The setting in T8J0A determines if the posting rule  
  "is defined for a billing method or not  
  if ms_settings-s_t8j0a-billmethodid is not initial.  
    data(lv_bmethod) = iv_bmethod.  
  endif.  
  "Get the posting rules  
  select single * from t8j0f into ms_settings-s_t8j0f  
                                where bukrs    = iv_bukrs  
                                and bmethod = lv_bmethod  
                                and jvfunc   = iv_function.  
  
  if sy-subrc <> 0.  
    message e769(g5) with iv_bukrs lv_bmethod iv_function into mv_message_text.  
    save_sy_message( ).  
  endif.  
  "Get the posting rule details  
  select * from t8j0g into table ms_settings-t_t8j0g  
                                where bukrs    = iv_bukrs  
                                and bmethod = lv_bmethod  
                                and jvfunc   = iv_function.  
  
endmethod.
```

GET_RI_REBOOK_AND_REVERSE

Description: Get the recovery indicators for reversal and chang line
Instance mthd

Importing parameter

```
IV_ITEM TYPE T8J0G-ITEMTYPE
```

Changing parameter

```
CV_RECID TYPE ACDOCA-RECID
```

```
method get_ri_rebook_and_reverse.  
  data: lv_recid      type t8j0g-recid,  
        lv_entry_found type abap_bool.  
  if  ms_settings-s_t8j0g-debreceid <> cv_recid and  
     ms_settings-s_t8j0g-crereceid <> cv_recid.
```

```
loop at ms_settings-t_t8j0g into ms_settings-s_t8j0g
    where itemtype = iv_item
    and recid      = cv_recid.
if ms_settings-s_t8j0g-debreid = cv_recid.
    if lv_entry_found <> 'X'.
        lv_recid = ms_settings-s_t8j0g-recid.
        lv_entry_found = 'X'.
    else.
        clear lv_recid.
        message e241(g5) with cv_recid into mv_message_text.
        save_sy_message( ).
        exit.
    endif.
elseif ms_settings-s_t8j0g-debreid is initial.
    clear lv_recid.
    message e238(g5) with cv_recid into mv_message_text.
    save_sy_message( ).
endif.
endloop.
else.
    lv_recid = ms_settings-s_t8j0g-recid.
endif.
cv_recid = lv_recid.
endmethod.
```

GET_SETTINGS

Description: Get the company code settings

Instance mthd

```
method get_settings.
    data: lo_jva_settings type ref to if_jva_settings,
          lv_jva_active   type abap_bool,
          lv_error        type abap_bool.
    ms_settings-bukrs = ms_progpars-bukrs.
    try.
        lo_jva_settings = cl_jva_settings=>get_instance( ms_progpars-bukrs ).
        lv_jva_active = lo_jva_settings->is_jva_active( ).
    catch cx_jva_settings.
        lv_jva_active = abap_false.
    endtry.
    if lv_jva_active = abap_false.
        message e579(gj) with ms_progpars-bukrs into mv_message_text.
        save_sy_message( ).
        return.
    endif.
    ms_settings-s_t001 = lo_jva_settings->ms_t001.
    ms_settings-s_t8jz = lo_jva_settings->ms_t8jz.
    select single * from t8jv into ms_settings-s_t8jv
        where bukrs = ms_progpars-bukrs
        and vname = ms_progpars-vname.
*   Get the production-month settings
    if ms_settings-s_t8jz-pm_act = 'X'.
        ms_settings-eg_from_pm = ms_settings-s_t8jz-pm_eg.
    else.
```

```

        clear ms_settings-eg_from_pm.
    endif.
*   Get the ledger to read data from ACDOCA
    ms_settings-rldnr = lo_jva_settings->get_ledger( ).
*   Get the ACDOCA currencies
    lo_jva_settings->get_currency_info( importing es_curr_info =
ms_settings-s_curr_info ).
    ms_settings-t_recid_billable = lo_jva_settings->get_billable_recind_range( ).
    get_posting_rules( exporting
                        iv_bukrs      = ms_progpars-bukrs
                        iv_bmethod    = ms_settings-s_t8jv-bmethod
                        iv_function    = mv_process
                        changing
                        cv_error      = lv_error ).
    "Get the fiscal year for postings
    call function 'DETERMINE_PERIOD'
        exporting
            date          = ms_progpars-budat
            version       = ms_settings-s_t001-periv
        importing
            year          = ms_settings-gjahr_p
        exceptions
            period_in_not_valid = 1
            period_not_assigned = 2
            version_undefined   = 3
            error_message       = 4
            others              = 8.
    if sy-subrc <> 0.
        message e108(glofaa_gb) with ms_settings-s_t001-periv ms_progpars-budat
                                into mv_message_text.

        save_sy_message( ).
    endif.
    "If a start date is set for JVA on ACDOCA, use the appropriate switch view
    "so that data can also be retrieved from the JVS01 table for previous years
    if cl_jva_switch=>get_instance( )->get_jva_on_acdoca_start_date( ) is not
initial.
        ms_settings-source_table = 'JV_ACDOCA_JVS01_SWITCH'.
    else.
        ms_settings-source_table = 'ACDOCA'.
    endif.
endmethod.

```

INITIALIZE_MAIN_OBJECTS

Description: Initialization of global objects

Instance mthd

```

method initialize_main_objects.
    data: lv_period      type monat,
          lv_spool_title type string.
    lv_spool_title = text-001.
    lv_period = ms_progpars-period.
*   Posting class
    mo_jva_post_acdoca = new cl_jva_post_acdoca( ).
*   Output handler for ALV or WRITE commands

```

```

    mo_output = new cl_jva_output( ).
*   Class for partner share calculations
    mo_partner_shares = new cl_jva_partner_shares( ).
*   Instantiate the cutback class
    mo_cutback = new cl_jva_cutback( ).
*   Message handlers
    mo_application_log = cl_jva_message_factory=>get_output(
                        iv_output_type      =
cl_jva_message_factory=>out_application_log
                        iv_bal_object       =
if_jva_message_output=>gc_bal_object-jva
                        iv_bal_subobject    =
if_jva_message_output=>gc_bal_subobject-general
                        iv_bal_save_all_to_db = abap_true ).
*   mo_message_output = cl_jva_message_factory=>get_output(
*                       iv_output_type      =
cl_jva_message_factory=>out_spool_error
*                       io_spool_handler     = mo_spool_handler
*                       iv_lst_disp_all_columns = abap_true ).
    mo_message_collector = cl_jva_message_factory=>get_message_collector(
                        it_output_handler    = value #( ( mo_application_log )
) ). "( mo_message_output ) ) ).
    mo_output_spool = new cl_jva_equity_adjust_output_sp( ).
endmethod.

```

MAKE_DATE_CLAUSE_FOR_SELECT

Description: Make the date clause for ACDOCA selects

Instance mthd

Returning parameter

```

VALUE(RV_DATE_CLAUSE) TYPE STRING

method make_date_clause_for_select.
    data: lv_docdate_clause type string,
          lv_prodper_clause type string,
          lv_poper_clause   type string,
          lv_from_poper      type acdoca-poper,
          lv_to_poper        type acdoca-poper,
          lv_prodper_initial type acdoca-prodper.
    if ms_progpars-farm_in_out = abap_true.
        if ms_progpars-inception_to_date = abap_true.
            "lv_from_poper = '000'.
            lv_from_poper = '001'.
        else.
            lv_from_poper = ms_progpars-from_period.
        endif.
        lv_to_poper = ms_progpars-to_period.
        if ms_progpars-inception_to_date = abap_true.
            rv_date_clause &&= |( ryear < '{ ms_progpars-to_year }' AND ( poper >= '001'
AND poper <= '012' ) )| ##NO_TEXT.
            rv_date_clause &&= | OR | ##NO_TEXT.
            rv_date_clause &&= |( ryear = '{ ms_progpars-to_year }'   AND poper >= '001'
AND poper <= '{ lv_to_poper }' )| ##NO_TEXT.
        else.

```

```

        if ms_progpars-from_year = ms_progpars-to_year.
            rv_date_clause = |ryear = '{ ms_progpars-to_year }' AND ( poper >= '{
lv_from_poper }' AND poper <= '{ lv_to_poper }' )| #
            else.
                rv_date_clause = |( ryear = '{ ms_progpars-from_year }' AND ( poper >= '{
lv_from_poper }' AND poper <= '012' ) )| ##NO_
                rv_date_clause &&= | OR | ##NO_TEXT.
                rv_date_clause &&= |( ryear > '{ ms_progpars-from_year }' AND ryear > '{
ms_progpars-to_year }' AND ( poper >= '001' AND p
                rv_date_clause &&= | OR | ##NO_TEXT.
                rv_date_clause &&= |( ryear = '{ ms_progpars-to_year }'    AND poper >=
'001' AND poper <= '{ lv_to_poper }' )| ##NO_TEXT.
            endif.
        endif.
    else.
*       The items must only be taken from the real periods 1 to 12
        lv_poper_clause = |( poper >= '001' AND poper <= '012' )|    ##NO_TEXT.
        lv_docdate_clause = |( bldat >= '{ ms_progpars-frdate }' AND bldat <= '{
ms_progpars-todate }' )|    ##NO_TEXT.
        if ms_settings-s_t8jz-pm_act = 'X' and ms_settings-s_t8jz-pm_eg  = 'X'.
            "rv_date_clause = |prodper >= ms_progpars-frdate AND prodper <=
ms_progpars-todate|    ##NO_TEXT.
            rv_date_clause = |( ( prodper >= '{ ms_progpars-frdate }' AND prodper <= '{
ms_progpars-todate }' ) OR ( prodper = '{ lv_pro
            else.
                rv_date_clause = lv_docdate_clause.
            endif.
            rv_date_clause &&= | AND | && lv_poper_clause.
        endif.
    endmethod.
```

MAKE_DOC_INFO

Description: Create the document info
Instance mthd

Importing parameter

- IV_BELNR TYPE ACDOCA-BELNR
- IV_BUZEI TYPE ACDOCA-BUZEI
- IV_GJAHR TYPE ACDOCA-GJAHR (Fiscal Year)

Changing parameter

```

CV_DOCINFO TYPE SSTRING

method make_doc_info.
    if iv_belnr is initial.
        clear cv_docinfo.
        return.
    endif.
    concatenate iv_belnr '-' iv_buzei '-' iv_gjahr
        into cv_docinfo.
endmethod.
```

POST_ADJUSTMENT_DOCUMENT

Description: Post the equity change document
Instance mthd

Importing parameter

IT_ACDOCA_CHECK TYPE FINST_ACDOCA (Universal Journal Entry Line Items)
IT_ACDOCA_POST TYPE FINST_ACDOCA (ACDOCA Unified Journal Entry Line Items)
IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))
IV_INTCO TYPE ABAP_BOOL

Changing parameter

CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CV_FATAL_ERROR TYPE ABAP_BOOL
CV_ERROR_TEXT TYPE STRING

```
method post_adjustment_document.  
  data: lt_acdoc_header_posted type finst_acdoc_header,  
        lt_acdoc_items_posted type finst_acdoc_item,  
        lo_message_collector type ref to if_jva_message_collection,  
        lv_belnr_new type acdoca-belnr.  
  if cv_fatal_error <> abap_true.  
    "The update tasks must be executed locally to ensure that  
    "The commit-work-and-wait command works properly before the  
    "cutback adjustments are made  
    if ms_progpars-analysis_only = abap_false and  
      ms_progpars-test = abap_false.  
      set update task local.  
    endif.  
    if ct_accit[] is initial.  
      mo_jva_post_acdoca->post_adjustment( exporting  
                                             it_acdoca =  
it_acdoca_post  
                                             iv_budat =  
ms_progpars-budat  
                                             iv_jvfunc = iv_jvfunc  
                                             iv_rldnr =  
ms_settings-rldnr  
                                             iv_analysis_only =  
ms_progpars-analysis_only  
                                             iv_test =  
ms_progpars-test  
importing  
      et_acdoc_header_posted =  
      et_acdoc_items_posted =  
      eo_message_collector =  
      ev_belnr = lv_belnr_new  
      ev_fatal_error =  
cv_fatal_error ).  
      if cv_fatal_error = 'X'.  
        mo_message_collector->add_collection( lo_message_collector ).  
        loop at mo_message_collector->get_access( )->get_messages( ) into  
data(ls_error_message).  
          cv_error_text = cl_jva_util=>get_message_text( iv_msgid =  
ls_error_message-msgid  
                                                         iv_msgno =  
ls_error_message-msgno
```

```

ls_error_message-msgv1
ls_error_message-msgv2
ls_error_message-msgv3
ls_error_message-msgv4 ).
    concatenate ls_error_message-msgid ls_error_message-msgno cv_error_text
        into cv_error_text
        separated by space.
    exit.
endloop.
endif.
else.
    post_fi_doc( exporting
        iv_testrun      = ms_progpars-test
        changing
            ct_accit      = ct_accit
            ct_accr       = ct_accr
            cv_belnr      = lv_belnr_new
            cv_critical_error = cv_fatal_error
            cv_error_text = cv_error_text ).
    endif.
endif.
* Save posting info for printing
save_adjustment_doc_info( it_acdoca_check = it_acdoca_check
    iv_jvfunc      = iv_jvfunc
    iv_intco       = iv_intco
    iv_posttype    = 'AD'
    it_acdoc_items_posted = lt_acdoc_items_posted
    it_accit_posted = ct_accit
    it_acdoca      = it_acdoca_post
    iv_belnr_new   = lv_belnr_new
    iv_posting_error = cv_fatal_error
    iv_error_text  = cv_error_text ).

endmethod.
```

POST_CHANGE_DOCUMENT

Description: Post the equity change document
Instance mthd

Importing parameter

```
IS_ACDOCA_CHECK TYPE GTY_S_ACDOCA_CHECK  OPTIONAL
IS_ACDOCA_AGGR TYPE GTY_S_ACDOCA_AGGREGATED  OPTIONAL
IV_JVFUNC TYPE JV_FUNC  (JVA Activity (Joint Venture Accounting))
IV_VNAME_NEW TYPE JV_NAME  (Joint venture)
IV_EGRUP_NEW TYPE JV_EGROUP  (Equity group)
```

Changing parameter

```
CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
```

```
method post_change_document.
    data: ls_acdoca      type acdoca,
          ls_acdoca_complete type acdoca,
```

```

    lt_acdoc_header_posted type finst_acdoc_header,
    lt_acdoc_items_posted type finst_acdoc_item,
    ls_acdoc_items_posted type fins_acdoc_item,
    lo_message_collector type ref to if_jva_message_collection,
    lv_belnr_new type acdoca-belnr,
    lv_error_text type string,
    lv_fatal_error type abap_bool,
    ls_acdoca_cb type jva_cb_acdoca,
    lv_subrc type sy-subrc,
    lv_posting_mode type c.
if is_acdoca_check is not initial.
    move-corresponding is_acdoca_check to ls_acdoca ##ENH_OK.
    lv_posting_mode = 'C'.
    if is_acdoca_check-jv_docnr is not initial.
        "Use the WORK_ITEM_ID fields to store the JVS01 doc number
        "This will only happen in migrated systems
        ls_acdoca-work_item_id = is_acdoca_check-jv_docnr.
    endif.
else.
    move-corresponding is_acdoca_aggr to ls_acdoca ##ENH_OK.
    lv_posting_mode = 'A'.
endif.
"The update tasks must be executed locally to ensure that
"The commit-work-and-wait command works properly before the
"cutback adjustments are made
if ms_progpars-analysis_only = abap_false and
    ms_progpars-test = abap_false.
    set update task local.
endif.
mo_jva_post_acdoca->post_equity_change( exporting
                                         iv_jvfunc      = iv_jvfunc
                                         iv_mode         = lv_posting_mode
                                         is_acdoca        = ls_acdoca
                                         iv_vname_new     = iv_vname_new
                                         iv_egrup_new     = iv_egrup_new
                                         iv_etype_new     = space
                                         iv_rldnr         = ms_settings-rldnr
                                         iv_budat         = ms_progpars-budat
                                         iv_analysis_only =
ms_progpars-analysis_only
                                         iv_test         = ms_progpars-test
importing
    es_acdoca_complete =
ls_acdoca_complete
    et_acdoc_header_posted =
lt_acdoc_header_posted
    et_acdoc_items_posted =
lt_acdoc_items_posted
    ev_belnr             = lv_belnr_new
    ev_fatal_error       = lv_fatal_error
    eo_message_collector =
lo_message_collector ).
    if lv_fatal_error = abap_true.
        mo_message_collector->add_collection( lo_message_collector ).

```

```

        loop at mo_message_collector->get_access( )->get_messages( ) into
data(ls_error_message).
        lv_error_text = cl_jva_util=>get_message_text( iv_msgid =
ls_error_message-msgid
                                                    iv_msgno =
ls_error_message-msgno
                                                    iv_msgv1 =
ls_error_message-msgv1
                                                    iv_msgv2 =
ls_error_message-msgv2
                                                    iv_msgv3 =
ls_error_message-msgv3
                                                    iv_msgv4 =
ls_error_message-msgv4 ).
        concatenate ls_error_message-msgid ls_error_message-msgno lv_error_text
into lv_error_text
separated by space.

        exit.
    endloop.
endif.
if lv_fatal_error = abap_true or
ms_progpars-test = abap_true or
ms_progpars-analysis_only = abap_true.
    add 1 to mv_belnr_test.
    lv_belnr_new = |TEST| && mv_belnr_test  ##NO_TEXT.
endif.
* Save posting info for printing
save_change_doc_info( lt_acdoc_header_posted = lt_acdoc_header_posted
lt_acdoc_items_posted = lt_acdoc_items_posted
iv_jvfunc           = iv_jvfunc
is_acdoca           = ls_acdoca_complete
iv_belnr_new        = lv_belnr_new
iv_egrup_new        = iv_egrup_new
iv_posting_error     = lv_fatal_error
iv_error_text       = lv_error_text ).
* In case of a successful posting, add the item to the cutback table
if lv_fatal_error <> abap_true or
ms_progpars-test = abap_true.
* Add reversal line with old equity group and reversed amounts
move-corresponding ls_acdoca_complete to ls_acdoca_cb  ##ENH_OK.
multiply: ls_acdoca_cb-wsl by -1,
ls_acdoca_cb-hsl by -1,
ls_acdoca_cb-ksl by -1,
ls_acdoca_cb-osl by -1,
ls_acdoca_cb-vsl by -1,
ls_acdoca_cb-bsl by -1,
ls_acdoca_cb-csl by -1,
ls_acdoca_cb-dsl by -1,
ls_acdoca_cb-esl by -1,
ls_acdoca_cb-fsl by -1,
ls_acdoca_cb-gsl by -1.
* Get the recovery indicator of the reversal line
read table lt_acdoc_items_posted into ls_acdoc_items_posted index 1.
ls_acdoca_cb-recid = ls_acdoc_items_posted-recid.

```

```

    make_doc_info( exporting
                    iv_belnr = lv_belnr_new
                    iv_buzei = 1
                    iv_gjahr = ls_acdoc_items_posted-gjahr
                    changing
                    cv_docinfo = ls_acdoca_cb-docinfo ).
*   Append ACDOCA line to the table for cutback correction
    append ls_acdoca_cb to ct_acdoca_cb.
*   Add reposting line with new equity group and original amounts
    move-corresponding ls_acdoca_complete to ls_acdoca_cb  ##ENH_OK.
    ls_acdoca_cb-egrup = iv_egrup_new.
*   Get the recovery indicator of the reposting line
    read table lt_acdoc_items_posted into ls_acdoc_items_posted index 2.
    ls_acdoca_cb-recid = ls_acdoc_items_posted-recid.
    make_doc_info( exporting
                    iv_belnr = lv_belnr_new
                    iv_buzei = 2
                    iv_gjahr = ls_acdoc_items_posted-gjahr
                    changing
                    cv_docinfo = ls_acdoca_cb-docinfo ).
*   Append ACDOCA line to the table for cutback correction
    append ls_acdoca_cb to ct_acdoca_cb.
endif.
endmethod.
```

POST_FI_DOC

Description: Post the FI document
Instance mthd

Importing parameter

IV_TESTRUN TYPE ABAP_BOOL

Changing parameter

CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CV_BELNR TYPE BELNR_D (Accounting Document Number)
CV_CRITICAL_ERROR TYPE ABAP_BOOL
CV_ERROR_TEXT TYPE STRING

```

method post_fi_doc.
    data: lt_mesg          type standard table of smesgx,
          lv_error_count   type sy-tabix,
          lv_max_severity  type sy-subrc,
          lv_handler_active type boole_d,
          lv_subrc         type sy-subrc,
          lt_accit_post     type standard table of accit,
          lt_acccr_post     type standard table of acccr,
          lt_acchd         type standard table of acchd,
          lt_acctx         type standard table of acctx,
          lt_accit_ext      type standard table of accit_extension.
    describe table ct_accit lines sy-tfill.
    if sy-tfill = 0.
        exit.
    endif.
*   Add line to ACCHD table
```

```
add_fidoc_header( changing ct_acchd = lt_acchd ).
if ms_progpars-analysis_only <> abap_true.
  lt_accit_post[] = ct_accit[].
  lt_accr_post[] = ct_accr[].
  mo_output->jv_direct_input( exporting
                                iv_mode      = '1'
                                iv_nodata    = '/'
                                iv_testrun   = iv_testrun
                                importing
                                ev_belnr     = cv_belnr
                                ev_subrc     = lv_subrc
                                changing
                                ct_acchd     = lt_acchd
                                ct_accit     = lt_accit_post
                                ct_accr      = lt_accr_post
                                ct_acctx     = lt_acctx
                                ct_accit_ext = lt_accit_ext ).
  if lv_subrc = 2 or lv_subrc = 4.
    cv_critical_error = abap_true.
    message id sy-msgid type sy-msgty number sy-msgno
      with sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4
      into cv_error_text.
    save_message( iv_type = sy-msgty
                  iv_class = sy-msgid
                  iv_number = sy-msgno
                  iv_var1 = sy-msgv1
                  iv_var2 = sy-msgv2
                  iv_var3 = sy-msgv3
                  iv_var4 = sy-msgv4 ).
  endif.
  call function 'MESSAGES_COUNT'
    importing
      count          = lv_error_count
      max_severity   = lv_max_severity
      e_handler_active = lv_handler_active
    exceptions
      inconsistent_range      = 1
      inconsistent_range_severity = 2
      error_message           = 3
      others                  = 4.
  if sy-subrc <> 0.
    clear lv_error_count.
  endif.
  if lv_error_count > 0.
    call function 'MESSAGE_EXPORT_IMPORT'
      exceptions
        empty      = 1
        not_active = 2
        others     = 3.
  if sy-subrc = 0.
    import xmesg to lt_mesg
      from memory id 'TEMP_MESG_EXP_IMP'.
    loop at lt_mesg into data(ls_mesg).
      if ls_mesg-msgty = 'A' or
```

```

        ls_mesg-msgty = 'E' or
        ls_mesg-msgty = 'X'.
    cv_critical_error = abap_true.
    message id ls_mesg-txtnr type ls_mesg-msgty number ls_mesg-arbgb
        with ls_mesg-msgv1 ls_mesg-msgv2 ls_mesg-msgv3 ls_mesg-msgv4
        into cv_error_text.
    save_message( iv_type = ls_mesg-msgty
        iv_class = ls_mesg-arbgb
        iv_number = ls_mesg-txtnr
        iv_var1 = ls_mesg-msgv1
        iv_var2 = ls_mesg-msgv2
        iv_var3 = ls_mesg-msgv3
        iv_var4 = ls_mesg-msgv4 ).
    endif.
endloop.
endif.
endif.
if lv_subrc <> 0 and cv_critical_error <> abap_true.
    cv_critical_error = abap_true.
    message id sy-msgid type sy-msgty number sy-msgno
        with sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4
        into cv_error_text.
    save_message( iv_type = sy-msgty
        iv_class = sy-msgid
        iv_number = sy-msgno
        iv_var1 = sy-msgv1
        iv_var2 = sy-msgv2
        iv_var3 = sy-msgv3
        iv_var4 = sy-msgv4 ).
    endif.
endif.
endmethod.
```

PREPARE_ACCIT_LINE

Description: Prepare an FI doc line
Instance mthd

Importing parameter

- VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
- IV_BUDAT TYPE BUDAT (Posting Date in the Document)
- VALUE(IV_BLDAT) TYPE BLDAT (Document Date in Document)

Changing parameter

- CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)

```
method prepare_accit_line.
    clear cs_accit.
    cs_accit-blart = ms_settings-s_t8j0f-doctyped.    "Document type
    cs_accit-awtyp = 'BKPFF'.                        "AW type
    cs_accit-mandt = sy-mandt.                       "Client
    cs_accit-bukrs = is_acdoca-rbukrs.               "Company code
    cs_accit-gjahr = ms_settings-gjahr_p.            "Fiscal year
    cs_accit-budat = iv_budat.                       "Posting date
    cs_accit-bldat = iv_bldat.                       "Document date
*   Venture data
```

```
cs_accit-vname = is_acdoca-vname.      "Venture
cs_accit-recid = is_acdoca-recid.      "Recovery indicator
cs_accit-prctr  = is_acdoca-prctr.     "Profit center
cs_accit-segment = is_acdoca-segment.  "Profit center
* Cost objects
cs_accit-kostl = is_acdoca-rcntr.      "Cost center
cs_accit-aufnr  = is_acdoca-aufnr.     "Order
cs_accit-ps_psp_pnr = is_acdoca-ps_psp_pnr. "WBS element
cs_accit-nplnr  = is_acdoca-nplnr.     "Network
if cs_accit-nplnr is not initial.
  call function 'READ_NETWORK_AUFPL_APLZL'
  exporting
    nplnr      = is_acdoca-nplnr
    vornr      = is_acdoca-nplnr_vorgn
  importing
    aufpl      = cs_accit-aufpl
    aplzl      = cs_accit-aplzl
  exceptions
    not_found  = 1
    error_message = 2
    others     = 3.
if sy-subrc <> 0.
  clear: cs_accit-aufpl, cs_accit-aplzl.
endif.
endif.
endmethod.
```

PREPARE_CC_ADJUSTMENTS

Description: Adjust the intercompany partner postings
Instance mthd

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)

Changing parameter

CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN TYPE REF TO DATA
CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN_POSTED TYPE REF TO DATA

```
method prepare_cc_adjustments.
  data: lv_error      type abap_bool,
        ls_acdoca_post type acdoca,
        ls_acdoca_post_check type acdoca,
        lt_acdoca_post type standard table of acdoca,
        lv_change_factor type decfloat16,
        lt_acdoca_check type standard table of acdoca,
        ls_acdoca_check type acdoca,
        ls_acdoca_already_posted type acdoca,
        lt_diff_share_new like ms_settings-t_diff_share,
        ls_accit type accit,
        lt_accit type standard table of accit,
        lt_acccr type standard table of acccr,
        lv_bktxt type acchd-bktxt,
        lv_buzei type acdoca-buzei,
```

```

lv_fatal_error      type abap_bool,
lv_error_text       type string,
lv_bldat            type bldat,
lv_already_posted   type abap_bool,
lv_posted_info_saved type abap_bool,
lv_new_partn_as_cashcall type abap_bool value abap_true,
lv_selfclearing     type abap_bool,
lt_sort_fields      type abap_sortorder_tab.
field-symbols: <lt_acdoca_dyn>      type standard table,
               <lt_acdoca_dyn_posted> type standard table.
if ct_acdoca_check is not initial.
  assign ct_acdoca_check to <lt_acdoca_dyn>.
else.
  assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
endif.
if ct_acdoca_posted is not initial.
  assign ct_acdoca_posted to <lt_acdoca_dyn_posted>.
else.
  assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
endif.
* Sort data according to print sorting
lt_sort_fields = value #( ( name = 'EGRUP' )
                        ( name = 'KUNNR' )
                        ( name = 'VPTNR' )
                        ( name = 'RWCUR' )
                        ( name = 'WSL' descending = abap_true ) ).
sort <lt_acdoca_dyn> by (lt_sort_fields).
* Collect any new partners into a new table
loop at ms_settings-t_diff_share into data(ls_diff_share_new)
  where eqshare_old = 0
  and eqshare_new <> 0.
  append ls_diff_share_new to lt_diff_share_new.
endloop.
loop at lt_diff_share_new assigning field-symbol(<ls_diff_share_new>).
* Determine the existing partner from which the new partners should be calculated
* First check if any old partner has exactly the same share as the new one
clear <ls_diff_share_new>-partn_old.
loop at ms_settings-t_diff_share into data(ls_diff_share_old)
  where eqshare_old =
<ls_diff_share_new>-eqshare_new.
  <ls_diff_share_new>-partn_old = ls_diff_share_old-partn_old.
  exit.
endloop.
if <ls_diff_share_new>-partn_old is initial.
* If no exact match is found, take the partner with the highest share
* to reduce the chance of big rounding errors
data(lt_diff_share_sorted) = ms_settings-t_diff_share.
sort lt_diff_share_sorted by eqshare_old descending.
loop at lt_diff_share_sorted into ls_diff_share_old
  where eqshare_old > 0.
* Check if an amount was posted to that partner (should always be so)
loop at <lt_acdoca_dyn> assigning field-symbol(<ls_acdoca_dyn>).
  move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.
  if ls_acdoca_check-egrup = ls_diff_share_old-eg_old and

```

```

        ls_acdoca_check-kunnr = ls_diff_share_old-partn_old.
        <ls_diff_share_new>-partn_old = ls_diff_share_old-partn_old.
        exit.
    endif.
endloop.
if <ls_diff_share_new>-partn_old is not initial.
    exit.
endif.
endloop.
endif.
loop at <lt_acdoca_dyn> assigning <ls_acdoca_dyn>.
    move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and
       ls_acdoca_check-gsl = 0.
        continue.
    endif.
    if ls_acdoca_check-kunnr is not initial.
        data(lv_vptnr) = ls_acdoca_check-kunnr.
    else.
        lv_vptnr = ls_acdoca_check-vptnr.
    endif.
    read table ms_settings-t_diff_share into data(ls_diff_share)
                                with key eg_old    = ls_acdoca_check-egrup
                                partn_old = lv_vptnr.

    if sy-subrc = 0.
        append ls_acdoca_check to lt_acdoca_check.
    else.
        continue.
    endif.
    clear lv_posted_info_saved.
    clear ls_acdoca_post.
    move-corresponding ls_acdoca_check to ls_acdoca_post.
    if ls_acdoca_post-vptnr is initial.
        ls_acdoca_post-vptnr = lv_vptnr.
    endif.
*   If the partner share in the new equity group is not zero,
*   post to the new equity group, otherwise keep the old one
    if ls_diff_share-eqshare_new > 0.
        ls_acdoca_post-egrup = ms_progpars-eqnew.
    endif.
*   Get document date based on the given equity group
    cl_jva_util=>derive_docdate_from_egrup( exporting
                                           iv_bukrs
ls_acdoca_post-rbukrs

```

```
ls_acdoca_post-egrup      iv_egrup      =
ls_acdoca_post-vname      iv_vname      =
                           iv_date      =
ms_progpars-budat        iv_caller      = 'EA'
                           changing
                           co_message_collector =
mo_message_collector      cv_bldat      = lv_bldat
                           cv_fatal_error  = lv_fatal_error
).
  clear ls_acdoca_post-lifnr.
  clear lv_buzei.
*   Add correction lines
  ls_acdoca_post-jvactivity = 'F1'.
  ls_acdoca_post-kunnr = lv_vptnr.
  if ls_diff_share-eqshare_old > 0.
*     Document line 1: Correction of the old partner share
*     -----
      add 1 to lv_buzei.
*     Calculate the amounts for existing partners with changes
      ls_acdoca_post-wsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-wsl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-hsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-hsl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-ksl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-ksl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-osl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-osl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-vsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-vsl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-bsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-bsl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-csl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-csl                                     is_diff_share = ls_diff_share
).
      ls_acdoca_post-dsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-dsl                                     is_diff_share = ls_diff_share
).
```

```

        ls_acdoca_post-esl = calc_cc_correction_amount( iv_amnt_old   =
ls_acdoca_post-esl
                                                    is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-fsl = calc_cc_correction_amount( iv_amnt_old   =
ls_acdoca_post-fsl
                                                    is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-gsl = calc_cc_correction_amount( iv_amnt_old   =
ls_acdoca_post-gsl
                                                    is_diff_share = ls_diff_share
    ).
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and
       ls_acdoca_check-gsl = 0.
        continue.
    endif.
    if ls_diff_share-eqshare_new > 0.
        if ms_settings-eg_from_pm = abap_true.
            cl_jva_util=>get_production_date( exporting
                                                    iv_caller          = 'EA'
                                                    iv_retain_orig_prodper = abap_false
                                                    iv_budat           =
ms_progpars-budat
                                                    iv_bukrs           =
ms_progpars-bukrs
                                                    iv_egrup           =
ls_acdoca_post-egrup
                                                    iv_prodper          =
ls_acdoca_post-prodper(6)
                                                    iv_vname            =
ls_acdoca_post-vname
                                                    changing
                                                    cv_validddate       =
ls_acdoca_post-prodper ).
        endif.
    endif.
    * Check if this item was already posted before
    clear lv_already_posted.
    ls_acdoca_post_check = ls_acdoca_post.
    loop at <lt_acdoca_dyn_posted> assigning
field-symbol(<ls_acdoca_dyn_posted>).
        move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
        if ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
           ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct and
           ls_acdoca_already_posted-vptnr = ls_diff_share-partnr_new.

```

```

ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.
if ls_acdoca_post_check-wsl = 0 and
   ls_acdoca_post_check-hsl = 0 and
   ls_acdoca_post_check-ksl = 0 and
   ls_acdoca_post_check-osl = 0 and
   ls_acdoca_post_check-vsl = 0 and
   ls_acdoca_post_check-bsl = 0 and
   ls_acdoca_post_check-csl = 0 and
   ls_acdoca_post_check-dsl = 0 and
   ls_acdoca_post_check-esl = 0 and
   ls_acdoca_post_check-fsl = 0 and
   ls_acdoca_post_check-gsl = 0.
   lv_already_posted = abap_true.
endif.
exit.                                "#EC CI_NOORDER
endif.
endloop.
if lv_already_posted <> abap_true.
  if lv_posted_info_saved <> abap_true.
    save_cash_call_info( is_acdoca_check = ls_acdoca_check
                        iv_jvfunc       = iv_jvfunc
                        iv_intco        = abap_false ).
    lv_posted_info_saved = abap_true.
  endif.
  append ls_acdoca_post to lt_acdoca_post.
  prepare_accit_line( exporting
                      is_acdoca = ls_acdoca_post
                      iv_budat   = ms_progpars-budat
                      iv_bldat   = lv_bldat
                      changing
                      cs_accit   = ls_accit ).
  add_accit_line_correction( exporting
                            iv_jvfunc       = iv_jvfunc
                            iv_jvactivity   = ls_acdoca_post-jvactivity
                            iv_buzei        = lv_buzei
                            is_acdoca       = ls_acdoca_post
                            changing
                            cs_accit        = ls_accit
                            ct_accit        = lt_accit
                            ct_accr         = lt_accr
                            cv_fatal_error  = lv_fatal_error
                            cv_error_text   = lv_error_text ).
*   Document line 2: Offset posting to settlement account
*   -----

```

```

      add 1 to lv_buzei.
*      Create line for settlement account (to new equity group)
      ls_acdoca_post-jvactivity = 'F2'.
*      If the partner share in the new equity group is not zero,
*      post to the new equity group, otherwise keep the old one
      if ls_diff_share-eqshare_new > 0.
        ls_acdoca_post-egrup = ms_progpar-s-eqnew.
      endif.
      ls_acdoca_post-racct = ms_progpar-s-settlement_acc_cc2.
      clear: ls_acdoca_post-kunnr,
             ls_acdoca_post-lifnr.
      ls_acdoca_post-wsl *= -1.
      ls_acdoca_post-hsl *= -1.
      ls_acdoca_post-ksl *= -1.
      ls_acdoca_post-osl *= -1.
      ls_acdoca_post-vsl *= -1.
      ls_acdoca_post-bsl *= -1.
      ls_acdoca_post-csl *= -1.
      ls_acdoca_post-dsl *= -1.
      ls_acdoca_post-esl *= -1.
      ls_acdoca_post-fsl *= -1.
      ls_acdoca_post-gsl *= -1.
      if ls_diff_share-eqshare_new > 0.
        if ms_settings-eg_from_pm = abap_true.
          cl_jva_util=>get_production_date( exporting
                                             iv_caller              = 'EA'
                                             iv_retain_orig_prodper = abap_false
                                             iv_budat              =
ms_progpar-s-budat
                                             iv_bukrs              =
ms_progpar-s-bukrs
                                             iv_egrup              =
ls_acdoca_post-egrup
                                             iv_prodper           =
ls_acdoca_post-prodper(6)
                                             iv_vname             =
ls_acdoca_post-vname
                                             changing
                                             cv_validddate        =
ls_acdoca_post-prodper ).
          endif.
        endif.
        append ls_acdoca_post to lt_acdoca_post.
        add_accit_line_settlement( exporting
                                     iv_jvfunc      = iv_jvfunc
                                     iv_jvactivity   = ls_acdoca_post-jvactivity
                                     iv_buzei        = lv_buzei
                                     is_acdoca       = ls_acdoca_post
                                     changing
                                     cs_accit        = ls_accit
                                     ct_accit        = lt_accit
                                     ct_accr         = lt_accr
                                     cv_fatal_error  = lv_fatal_error
                                     cv_error_text   = lv_error_text ).

```

```

*      -----
      post_adjustment_document( exporting
                                it_acdoca_check = lt_acdoca_check
                                it_acdoca_post  = lt_acdoca_post
                                iv_jvfunc       = iv_jvfunc
                                iv_intco        = abap_false
                                changing
                                ct_accit        = lt_accit
                                ct_acccr        = lt_acccr
                                cv_fatal_error  = lv_fatal_error
                                cv_error_text   = lv_error_text ).

      endif.
      refresh: lt_acdoca_post,
               lt_accit, lt_acccr.
      clear: lv_fatal_error, lv_error_text.
    endif.
*      Create the documents for any new partners
      loop at lt_diff_share_new into ls_diff_share_new.
        if ls_diff_share_new-partn_old <> ls_diff_share-partn_old.
          continue.
        endif.
        if ms_settings-eg_from_pm = abap_true.
          cl_jva_util=>get_production_date( exporting
                                              iv_caller          = 'EA'
                                              iv_retain_orig_prodper = abap_false
                                              iv_budat            =
ms_progpars-budat
                                              iv_bukrs            =
ms_progpars-bukrs
                                              iv_egrup            =
ms_progpars-egnew
                                              iv_prodper          =
ls_acdoca_check-prodper(6)
                                              iv_vname           =
ls_acdoca_check-vname
                                              changing
                                              cv_validddate      =
ls_acdoca_check-prodper ).
        endif.
        clear ls_acdoca_post.
        move-corresponding ls_acdoca_check to ls_acdoca_post.
        if ls_acdoca_post-vptnr is initial.
          ls_acdoca_post-vptnr = lv_vptnr.
        endif.
        clear lv_buzei.
        Document line 1: Amount with new partner share
*      -----
        add 1 to lv_buzei.
        ls_acdoca_post-jvactivity = 'F1'.
*      Calculate the change factor based on a given equity share of an old partner
(can be any)
        lv_change_factor = ls_diff_share_new-egshare_new
                          / ls_diff_share-egshare_old.
*      Calculate the share of the new partner

```

```

multiply ls_acdoca_post-wsl by lv_change_factor.
multiply ls_acdoca_post-hsl by lv_change_factor.
multiply ls_acdoca_post-ksl by lv_change_factor.
multiply ls_acdoca_post-osl by lv_change_factor.
multiply ls_acdoca_post-vsl by lv_change_factor.
multiply ls_acdoca_post-bsl by lv_change_factor.
multiply ls_acdoca_post-csl by lv_change_factor.
multiply ls_acdoca_post-dsl by lv_change_factor.
multiply ls_acdoca_post-esl by lv_change_factor.
multiply ls_acdoca_post-fsl by lv_change_factor.
multiply ls_acdoca_post-gsl by lv_change_factor.
if ls_acdoca_check-wsl = 0 and
  ls_acdoca_check-hsl = 0 and
  ls_acdoca_check-ksl = 0 and
  ls_acdoca_check-osl = 0 and
  ls_acdoca_check-vsl = 0 and
  ls_acdoca_check-bsl = 0 and
  ls_acdoca_check-csl = 0 and
  ls_acdoca_check-dsl = 0 and
  ls_acdoca_check-esl = 0 and
  ls_acdoca_check-fsl = 0 and
  ls_acdoca_check-gsl = 0.
  continue.
endif.
ls_acdoca_post-egrup = ms_progpars-eqnew.
ls_acdoca_post-vptnr = ls_diff_share_new-partn_new.
ls_acdoca_post-kunnr = ls_diff_share_new-partn_new.
*
Check if this item was already posted before
clear lv_already_posted.
ls_acdoca_post_check = ls_acdoca_post.
loop at <lt_acdoca_dyn_posted> assigning <ls_acdoca_dyn_posted>.
  move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
  if ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
    ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct and
    ls_acdoca_already_posted-vptnr = ls_diff_share_new-partn_new.
    ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
    ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
    ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
    ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
    ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
    ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
    ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
    ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
    ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
    ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
    ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.
  if ls_acdoca_post_check-wsl = 0 and
    ls_acdoca_post_check-hsl = 0 and
    ls_acdoca_post_check-ksl = 0 and
    ls_acdoca_post_check-osl = 0 and
    ls_acdoca_post_check-vsl = 0 and
    ls_acdoca_post_check-bsl = 0 and
    ls_acdoca_post_check-csl = 0 and
    ls_acdoca_post_check-dsl = 0 and

```

```
        ls_acdoca_post_check-esl = 0 and
        ls_acdoca_post_check-fsl = 0 and
        ls_acdoca_post_check-gsl = 0.
        lv_already_posted = abap_true.
        exit.                                "#EC CI_NOORDER
    endif.
endif.
endloop.
if lv_already_posted <> abap_true.
    if lv_posted_info_saved <> abap_true.
        save_cash_call_info( is_acdoca_check = ls_acdoca_check
                              iv_jvfunc      = iv_jvfunc
                              iv_intco       = abap_false ).
        lv_posted_info_saved = abap_true.
    endif.
    append ls_acdoca_post to lt_acdoca_post.
    prepare_accit_line( exporting
                        is_acdoca = ls_acdoca_post
                        iv_budat  = ms_progpars-budat
                        iv_bldat  = lv_bldat
                        changing
                        cs_accit  = ls_accit ).
    if lv_new_partn_as_cashcall = abap_true.
        add_accit_line_cashcall( exporting
                                is_acdoca      = ls_acdoca_post
                                iv_jvfunc      = iv_jvfunc
                                iv_jvactivity   = ls_acdoca_post-jvactivity
                                iv_buzei       = lv_buzei
                                iv_selfclearing = lv_selfclearing
                                changing
                                cs_accit       = ls_accit
                                ct_accit       = lt_accit
                                ct_accctr      = lt_accctr
                                cv_fatal_error = lv_fatal_error
                                cv_error_text  = lv_error_text ).
    else.
        add_accit_line_correction( exporting
                                   is_acdoca      = ls_acdoca_post
                                   iv_jvfunc      = iv_jvfunc
                                   iv_jvactivity   = ls_acdoca_post-jvactivity
                                   iv_buzei       = lv_buzei
                                   changing
                                   cs_accit       = ls_accit
                                   ct_accit       = lt_accit
                                   ct_accctr      = lt_accctr
                                   cv_fatal_error = lv_fatal_error
                                   cv_error_text  = lv_error_text ).
    endif.
    * Document line 2: Offset posting to settlement account
    * -----
    * add 1 to lv_buzei.
    * Create line for settlement account (to new equity group)
    ls_acdoca_post-jvactivity = 'F2'.
    ls_acdoca_post-egrup = ms_progpars-eqnew.
```

```
ls_acdoca_post-racct = ms_progpars-settlement_acc_cc2.
clear: ls_acdoca_post-kunnr,
      ls_acdoca_post-lifnr.
ls_acdoca_post-wsl  *= -1.
ls_acdoca_post-hsl  *= -1.
ls_acdoca_post-ksl  *= -1.
ls_acdoca_post-osl  *= -1.
ls_acdoca_post-vsl  *= -1.
ls_acdoca_post-bsl  *= -1.
ls_acdoca_post-csl  *= -1.
ls_acdoca_post-dsl  *= -1.
ls_acdoca_post-esl  *= -1.
ls_acdoca_post-fsl  *= -1.
ls_acdoca_post-gsl  *= -1.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_settlement( exporting
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = ls_acdoca_post-jvactivity
                          iv_buzei       = lv_buzei
                          is_acdoca      = ls_acdoca_post
                          changing
                          cs_accit       = ls_accit
                          ct_accit       = lt_accit
                          ct_accctr      = lt_accctr
                          cv_fatal_error = lv_fatal_error
                          cv_error_text  = lv_error_text ).
* -----
post_adjustment_document( exporting
                          it_acdoca_check = lt_acdoca_check
                          it_acdoca_post  = lt_acdoca_post
                          iv_jvfunc       = iv_jvfunc
                          iv_intco        = abap_false
                          changing
                          ct_accit        = lt_accit
                          ct_accctr       = lt_accctr
                          cv_fatal_error  = lv_fatal_error
                          cv_error_text   = lv_error_text ).

endif.
refresh: lt_acdoca_post,
        lt_accit, lt_accctr.
clear: lv_fatal_error, lv_error_text.
endloop.      " lt_diff_share_new
refresh lt_acdoca_check.
endloop.
endmethod.
```

PREPARE_CC_ADJUSTMENTS_INTCO

Description: Adjust the intercompany partner postings
Instance mthd

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)

Changing parameter

CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK

```

CR_ACDOCA_DYN TYPE REF TO DATA
CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN_POSTED TYPE REF TO DATA

method prepare_cc_adjustments_intco.
  data: lv_error                type abap_bool,
        ls_acdoca_post          type acdoca,
        ls_acdoca_post_check    type acdoca,
        lt_acdoca_post          type standard table of acdoca,
        lv_change_factor        type decfloat16,
        lt_acdoca_check         type standard table of acdoca,
        ls_acdoca_check         type acdoca,
        ls_acdoca_already_posted type acdoca,
        ls_t8jo                 type t8jo,
        lv_lifnr                type kna1-lifnr,
        lv_buzei                type acdoca-buzei,
        ls_accit                type accit,
        lt_accit                type standard table of accit,
        lt_acccr                type standard table of acccr,
        lv_bldat                type bldat,
        lv_fatal_error          type abap_bool,
        lv_error_text           type string,
        lv_already_posted       type abap_bool,
        lt_sort_fields          type abap_sortorder_tab.
  field-symbols: <lt_acdoca_dyn> type standard table,
                 <lt_acdoca_dyn_posted> type standard table.
  if ct_acdoca_check is not initial.
    assign ct_acdoca_check to <lt_acdoca_dyn>.
  else.
    assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
  endif.
  if ct_acdoca_posted is not initial.
    assign ct_acdoca_posted to <lt_acdoca_dyn_posted>.
  else.
    assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
  endif.
  * Sort data according to print sorting
  lt_sort_fields = value #( ( name = 'EGRUP' )
                           ( name = 'LIFNR' )
                           ( name = 'VPTNR' )
                           ( name = 'RWCUR' ) ).
  sort <lt_acdoca_dyn> by (lt_sort_fields).
  loop at <lt_acdoca_dyn> assigning field-symbol(<ls_acdoca_dyn>).
    move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and

```

```

        ls_acdoca_check-gsl = 0.
        continue.
    endif.
    if ls_acdoca_check-vptnr is not initial.
        data(lv_vptnr) = ls_acdoca_check-vptnr.
    else.
        lv_vptnr = ls_acdoca_check-lifnr.
    endif.
    read table ms_settings-t_diff_share_intco into data(ls_diff_share)
                                         with key intcocd_old =
ls_acdoca_check-rbukrs
                                         intcompegp_old =
ls_acdoca_check-egrup
                                         partn_old = lv_vptnr.

    if sy-subrc = 0.
        append ls_acdoca_check to lt_acdoca_check.
    else.
        continue.
    endif.
*   Get document date based on the new equity group
    cl_jva_util=>derive_docdate_from_egrup( exporting
ls_acdoca_check-rbukrs
                                         iv_bukrs =
ls_acdoca_check-egrup
                                         iv_egrup =
ls_diff_share-intcompegp_new
                                         iv_vname =
ls_acdoca_check-vname
                                         iv_date =
ms_progpars-budat
                                         iv_caller = 'EA'
                                         changing
                                         co_message_collector =
mo_message_collector
                                         cv_bldat = lv_bldat
                                         cv_fatal_error = lv_fatal_error
    ).
    clear lv_buzei.
    if ls_acdoca_check-vptnr is not initial.
        lv_lifnr = get_intco_vendor( exporting
                                         iv_bukrs = ls_diff_share-intcocd_old
                                         iv_partn = ls_acdoca_check-vptnr ).
    else.
        lv_lifnr = ls_acdoca_check-lifnr.
    endif.
*   Document line 1: Nonop cash call reverse of old equity group
*   -----
    add 1 to lv_buzei.
    clear ls_acdoca_post.
    move-corresponding ls_acdoca_check to ls_acdoca_post.
    if ls_acdoca_post-vptnr is initial.
        ls_acdoca_post-vptnr = lv_vptnr.
    endif.
    clear ls_acdoca_post-kunnr.
    ls_acdoca_post-jvactivity = 'F1'.

```

```

ls_acdoca_post-lifnr = lv_lifnr.
ls_acdoca_post-wsl *= -1.
ls_acdoca_post-hsl *= -1.
ls_acdoca_post-ksl *= -1.
ls_acdoca_post-osl *= -1.
ls_acdoca_post-vsl *= -1.
ls_acdoca_post-bsl *= -1.
ls_acdoca_post-csl *= -1.
ls_acdoca_post-dsl *= -1.
ls_acdoca_post-esl *= -1.
ls_acdoca_post-fsl *= -1.
ls_acdoca_post-gsl *= -1.
*
Check if this item was already posted before
clear lv_already_posted.
ls_acdoca_post_check = ls_acdoca_post.
loop at <lt_acdoca_dyn_posted> assigning field-symbol(<ls_acdoca_dyn_posted>).
  move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
  if ls_acdoca_already_posted-rbukrs = ls_acdoca_post_check-rbukrs and
    ls_acdoca_already_posted-vname = ls_acdoca_post_check-vname and
    ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
    ls_acdoca_already_posted-vptnr = ls_acdoca_post_check-vptnr and
    ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct.
    ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
    ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
    ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
    ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
    ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
    ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
    ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
    ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
    ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
    ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
    ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.
    if ls_acdoca_post_check-wsl = 0 and
      ls_acdoca_post_check-hsl = 0 and
      ls_acdoca_post_check-ksl = 0 and
      ls_acdoca_post_check-osl = 0 and
      ls_acdoca_post_check-vsl = 0 and
      ls_acdoca_post_check-bsl = 0 and
      ls_acdoca_post_check-csl = 0 and
      ls_acdoca_post_check-dsl = 0 and
      ls_acdoca_post_check-esl = 0 and
      ls_acdoca_post_check-fsl = 0 and
      ls_acdoca_post_check-gsl = 0.
      lv_already_posted = abap_true.
      exit.                                "#EC CI_NOORDER
    endif.
  endif.
endloop.
if lv_already_posted = abap_true.
  continue.
endif.
save_cash_call_info( is_acdoca_check = ls_acdoca_check
                    iv_jvfunc       = iv_jvfunc

```

```
        iv_intco      = abap_true ).
append ls_acdoca_post to lt_acdoca_post.
prepare_accit_line( exporting
                    is_acdoca = ls_acdoca_post
                    iv_budat  = ms_progpars-budat
                    iv_bldat  = lv_bldat
                    changing
                    cs_accit  = ls_accit ).
add_accit_line_correction( exporting
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = ls_acdoca_post-jvactivity
                          iv_buzei       = lv_buzei
                          is_acdoca      = ls_acdoca_post
                          changing
                          cs_accit       = ls_accit
                          ct_accit       = lt_accit
                          ct_acccr       = lt_acccr
                          cv_fatal_error = lv_fatal_error
                          cv_error_text  = lv_error_text ).
* Document line 2: Nonop cash call rebook to new equity group with new share
* -----
add 1 to lv_buzei.
clear ls_acdoca_post.
move-corresponding ls_acdoca_check to ls_acdoca_post.
if ls_acdoca_post-vptnr is initial.
    ls_acdoca_post-vptnr = lv_vptnr.
endif.
ls_acdoca_post-jvactivity = 'F2'.
ls_acdoca_post-egrup = ls_diff_share-intcompegp_new.
ls_acdoca_post-lifnr = lv_lifnr.
* Calculate the amounts
lv_change_factor = ls_diff_share-eqshare_new
                  / ls_diff_share-eqshare_old.
* Calculate the share of the new partner
multiply ls_acdoca_post-wsl by lv_change_factor.
multiply ls_acdoca_post-hsl by lv_change_factor.
multiply ls_acdoca_post-ksl by lv_change_factor.
multiply ls_acdoca_post-osl by lv_change_factor.
multiply ls_acdoca_post-vsl by lv_change_factor.
multiply ls_acdoca_post-bsl by lv_change_factor.
multiply ls_acdoca_post-csl by lv_change_factor.
multiply ls_acdoca_post-dsl by lv_change_factor.
multiply ls_acdoca_post-esl by lv_change_factor.
multiply ls_acdoca_post-fsl by lv_change_factor.
multiply ls_acdoca_post-gsl by lv_change_factor.
if ls_acdoca_check-wsl = 0 and
    ls_acdoca_check-hsl = 0 and
    ls_acdoca_check-ksl = 0 and
    ls_acdoca_check-osl = 0 and
    ls_acdoca_check-vsl = 0 and
    ls_acdoca_check-bsl = 0 and
    ls_acdoca_check-csl = 0 and
    ls_acdoca_check-dsl = 0 and
    ls_acdoca_check-esl = 0 and
```

```

    ls_acdoca_check-fsl = 0 and
    ls_acdoca_check-gsl = 0.
  continue.
endif.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_correction( exporting
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = ls_acdoca_post-jvactivity
                          iv_buzei       = lv_buzei
                          is_acdoca      = ls_acdoca_post
                          changing
                          cs_accit       = ls_accit
                          ct_accit       = lt_accit
                          ct_accctr      = lt_accctr
                          cv_fatal_error = lv_fatal_error
                          cv_error_text  = lv_error_text ).
* Document line 3: Settlement Line (delta of old and new partner share)
* -----
add 1 to lv_buzei.
ls_acdoca_post-jvactivity = 'F3'.
ls_acdoca_post-egrup = ls_diff_share-intcompepgp_new.
ls_acdoca_post-racct = ms_progpar-s-settlement_acc_cc2.
ls_acdoca_post-wsl = ls_acdoca_check-wsl - ls_acdoca_post-wsl.
ls_acdoca_post-hsl = ls_acdoca_check-hsl - ls_acdoca_post-hsl.
ls_acdoca_post-ksl = ls_acdoca_check-ksl - ls_acdoca_post-ksl.
ls_acdoca_post-osl = ls_acdoca_check-osl - ls_acdoca_post-osl.
ls_acdoca_post-vsl = ls_acdoca_check-vsl - ls_acdoca_post-vsl.
ls_acdoca_post-bsl = ls_acdoca_check-bsl - ls_acdoca_post-bsl.
ls_acdoca_post-csl = ls_acdoca_check-csl - ls_acdoca_post-csl.
ls_acdoca_post-dsl = ls_acdoca_check-dsl - ls_acdoca_post-dsl.
ls_acdoca_post-esl = ls_acdoca_check-esl - ls_acdoca_post-esl.
ls_acdoca_post-fsl = ls_acdoca_check-fsl - ls_acdoca_post-fsl.
ls_acdoca_post-gsl = ls_acdoca_check-gsl - ls_acdoca_post-gsl.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_settlement( exporting
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = ls_acdoca_post-jvactivity
                          iv_buzei       = lv_buzei
                          is_acdoca      = ls_acdoca_post
                          changing
                          cs_accit       = ls_accit
                          ct_accit       = lt_accit
                          ct_accctr      = lt_accctr
                          cv_fatal_error = lv_fatal_error
                          cv_error_text  = lv_error_text ).
* -----
post_adjustment_document( exporting
                          it_acdoca_check = lt_acdoca_check
                          it_acdoca_post = lt_acdoca_post
                          iv_jvfunc      = iv_jvfunc
                          iv_intco       = abap_true
                          changing
                          ct_accit       = lt_accit
                          ct_accctr      = lt_accctr

```

```

                                cv_fatal_error = lv_fatal_error
                                cv_error_text  = lv_error_text ).
refresh: lt_acdoca_check, lt_acdoca_post,
         lt_accit, lt_accr.
clear: lv_fatal_error, lv_error_text.
endloop.
endmethod.

```

PREPARE_DIFF_SHARE_DATA

Description: Prepare the shares differing from the original shares

Instance mthd

```

method prepare_diff_share_data.
  data: ls_diff_share_old type jva_partner_share,
        ls_diff_share_new type jva_partner_share.
  refresh: ms_settings-t_diff_share_old,
           ms_settings-t_diff_share_new.
  loop at ms_settings-t_shares_old into data(ls_shares_old).
    clear ls_diff_share_old.
    ls_diff_share_old-partn      = ls_shares_old-partn.
    ls_diff_share_old-opflag     = ls_shares_old-opflag.
    ls_diff_share_old-eqshare    = ls_shares_old-eqshare.
    ls_diff_share_old-opflag     = ls_shares_old-opflag.
    ls_diff_share_old-intcocd    = ls_shares_old-intcocd.
    ls_diff_share_old-intrcovent = ls_shares_old-intrcovent.
    ls_diff_share_old-intcompegp = ls_shares_old-intcompegp.
    append ls_diff_share_old to ms_settings-t_diff_share_old.
    loop at ms_settings-t_shares_new into data(ls_shares_new)
      where partn = ls_shares_old-partn
        and opflag = ls_shares_old-opflag.

      clear ls_diff_share_new.
      ls_diff_share_new-partn      = ls_shares_new-partn.
      ls_diff_share_new-opflag     = ls_shares_new-opflag.
      ls_diff_share_new-eqshare    = ls_shares_new-eqshare.
      ls_diff_share_new-opflag     = ls_shares_new-opflag.
      ls_diff_share_new-intcocd    = ls_shares_new-intcocd.
      ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.
      ls_diff_share_new-intcompegp = ls_shares_new-intcompegp.
      append ls_diff_share_new to ms_settings-t_diff_share_new.
    endloop.
  endloop.
* Add items that did not exist in the old equity group
  loop at ms_settings-t_shares_new into ls_shares_new.
    read table ms_settings-t_diff_share_old transporting no fields
      with key partn = ls_shares_new-partn
        opflag = ls_shares_new-opflag.

    if sy-subrc > 2.
      clear ls_diff_share_new.
      ls_diff_share_new-partn      = ls_shares_new-partn.
      ls_diff_share_new-eqshare    = ls_shares_new-eqshare.
      ls_diff_share_new-intcocd    = ls_shares_new-intcocd.
      ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.
      ls_diff_share_new-intcompegp = ls_shares_new-intcompegp.
      append ls_diff_share_new to ms_settings-t_diff_share_new.
    endloop.
  endloop.

```

```
endif.  
endloop.  
endmethod.
```

PREPARE_EQUITY_CHANGE

Description: Process the retrieved ACDOCA items
Instance mthd

Importing parameter

```
IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))  
IV_VNAME_NEW TYPE JV_NAME (Joint venture)  
IV_EGRUP_NEW TYPE JV_EGROUP (Equity group)
```

Changing parameter

```
CT_ACDOCA_MAIN TYPE GTY_T_ACDOCA_CHECK  
CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
```

```
method prepare_equity_change.  
  data: lv_is_oi_managed type c,  
        lv_tabix          type sy-tabix.  
*   Prepare items to be checked  
  loop at ct_acdoca_main assigning field-symbol(<ls_acdoca>).  
    if ms_progpars-excloi = 'X'.  
      lv_tabix = sy-tabix.  
*     If the account is open item managed, do not process it  
      cl_jva_util=>check_oi_managed_account( exporting  
                                              iv_bukrs = <ls_acdoca>-rbukrs  
                                              iv_racct = <ls_acdoca>-racct  
                                              changing  
                                              cv_is_oi_managed = lv_is_oi_managed  
      ).  
      if lv_is_oi_managed = 'X'.  
        delete ct_acdoca_main index lv_tabix.  
        continue.  
      endif.  
    endif.  
    if <ls_acdoca>-src_awref is initial or  
      not ( <ls_acdoca>-jvactivity = 'EC' or  
            <ls_acdoca>-jvactivity = 'E1' or  
            <ls_acdoca>-jvactivity = 'E2' or  
            <ls_acdoca>-jvactivity = 'SU' or  
            <ls_acdoca>-jvactivity = 'US' ).  
*     Lines where the PREC fields are empty, need to be filled with the  
*     reference fields so that the previous equity change postings  
*     can easily be identified  
      <ls_acdoca>-src_awref = <ls_acdoca>-awref.  
      <ls_acdoca>-src_awitem = <ls_acdoca>-awitem.  
    endif.  
  endloop.  
*   Check lines and post the change documents, if necessary  
  check_line_items( exporting  
                    iv_jvfunc      = iv_jvfunc  
                    iv_vname_new   = iv_vname_new  
                    iv_egrup_new   = iv_egrup_new  
                    changing
```

```

                                ct_acdoca_check = ct_acdoca_main
                                ct_acdoca_cb     = ct_acdoca_cb ).

endmethod.
```

PREPARE_POSTINGS_INTCO

Description: Prepare the intercompany reversal postings
Instance mthd

Importing parameter

```
IT_ACDOCA_INTCO_NEW TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
IT_ACDOCA_INTCO_OLD TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
```

```
method prepare_postings_intco.
  data: lv_tabix_next  type sy-tabix,
        ls_acdoca_next type jva_cb_acdoca.
  loop at it_acdoca_intco_new into data(ls_acdoca).
    lv_tabix_next = sy-tabix + 1.
    clear ls_acdoca_next.
    read table it_acdoca_intco_new into ls_acdoca_next index lv_tabix_next.
    read table it_acdoca_intco_old into data(ls_acdoca_old)
                                with key rbukrs = ls_acdoca-rbukrs
                                    rwcure = ls_acdoca-rwcure
                                    ryear  = ls_acdoca-ryear
                                    vname   = ls_acdoca-vname
                                    egrupe  = ls_acdoca-egrupe
                                    racct   = ls_acdoca-racct
                                    rbusa   = ls_acdoca-rbusa
                                    rcntr   = ls_acdoca-rcntr
                                    aufnr   = ls_acdoca-aufnr
                                    ps_psp_pnr = ls_acdoca-ps_psp_pnr
                                    prctr   = ls_acdoca-prctr
                                    recid   = ls_acdoca-recid
                                    vptnr   = ls_acdoca-vptnr
                                    nplnr   = ls_acdoca-nplnr
                                    nplnr_vorgn = ls_acdoca-nplnr_vorgn
                                    anl1    = ls_acdoca-anl1
                                    anl2    = ls_acdoca-anl2
                                    anbwa   = ls_acdoca-anbwa
                                binary search.
    if ls_acdoca-rbukrs <> ls_acdoca_next-rbukrs or
       ls_acdoca-rwcure <> ls_acdoca_next-rwcure.
      endif.
    endloop.
endmethod.
```

PROCESS_EC_AGGREGATED

Description:
Instance mthd

Importing parameter

```
IV_JVFUNC TYPE JV_FUNC
IV_VNAME_NEW TYPE JV_NAME
IV_EGRUP_NEW TYPE JV_EGROUP
```

Changing parameter

CT_ACDOCA_AGGR TYPE GTY_T_ACDOCA_AGGREGATED

CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T

method process_ec_aggregated.

data: lv_is_oi_managed type abap_bool.

loop at ct_acdoca_aggr into data(ls_acdoca_aggr).

if ms_progpars-excloi = abap_true.

"If the account is open item managed, do not process it

cl_jva_util=>check_oi_managed_account(exporting

iv_bukrs =

ls_acdoca_aggr-rbukrs

iv_racct =

ls_acdoca_aggr-racct

changing

cv_is_oi_managed = lv_is_oi_managed

).

if lv_is_oi_managed = abap_true.

continue.

endif.

endif.

post_change_document(exporting

iv_jvfunc = iv_jvfunc

iv_vname_new = iv_vname_new

iv_egrup_new = iv_egrup_new

is_acdoca_aggr = ls_acdoca_aggr

changing

ct_acdoca_cb = ct_acdoca_cb).

endloop.

endmethod.

PRINT_RESULTS

Description: Print the results

Instance mthd

method print_results.

add_general_information().

mo_output_spool->set_output_data(is_progpars = ms_progpars

is_settings = ms_settings

is_ea_results = ms_ea_results

is_cb_results = ms_cb_results

io_cutback = mo_cutback).

mo_output_spool->create_output().

endmethod.

RUN_ADJUSTMENTS

Description: Run the adjustment process

Instance mthd

method run_adjustments.

data: lt_acdoca_cb type jva_cb_acdoca_t.

if ms_progpars-eqchnng = 'X'.

* Create the equity group adjustment postings

adjust_equity_group(changing ct_acdoca_cb = lt_acdoca_cb).

```

    else.
        return.
    endif.
    * If there are cutback data and if no critical errors have occurred,
    * run cutback for the successful equity adjustment postings
    if ms_progpars-cutbck = 'X' and
        not lt_acdoca_cb[] is initial.
    *     Adjust the cutback results
        adjust_cutback_results( it_acdoca_cb = lt_acdoca_cb ).
    endif.
    if ms_progpars-intcoc = 'X'.
    *     Adjust the intercompany postings
        adjust_intercompany_reversal( ).
    endif.
    if ms_progpars-cashc1 = 'X'.
    *     Adjust the cash call postings step 1
        adjust_cashcall_equity_group( ).
    endif.
    if ms_progpars-cashc2 = 'X'.
    *     Adjust the cashl postings step 2
        adjust_cashcall_partner_shares( ).
    endif.
    if ms_progpars-test <> abap_true.
        mo_output->commit_work( ).
    endif.
    loop at mo_message_collector->get_access( )->get_messages( ) transporting no
fields
        where msgty = 'E'
            or msgty = 'A'
            or msgty = 'X'.
        add 1 to ms_ea_results-no_of_errors.
    endloop.
endmethod.

```

RUN_PROCESS

Description: Main processing

Instance mthd

```

method run_process.
    if ms_progpars-farm_in_out = abap_true.
        mv_process = gc_process_farm.
    else.
        mv_process = gc_process_eqad.
    endif.
    * Fill event table
    fill_event_table( ).
    * Prepare the schedule manager
    schedman_initialize( ).
    * Get Cutback Run ID
    ms_progpars-cbrunid = ms_progpars-s_schedman_key-id.
    * Get settings
    get_settings( ).
    get_partner_shares( ).
    if ms_ea_results-max_error <> 'E' and

```

```

    ms_ea_results-max_error <> 'A'.
    if ms_progpars-test <> abap_true.
*      Initialize local updating to avoid deadlocks during
*      CO table updating
        set update task local.
    endif.
*      Make the adjustments according to the settings
        run_adjustments( ).
    endif.
    if mo_message_collector->get_msg_count( ) > 0.
        mo_application_log->submit_output( ).
    endif.
    mo_application_log->on_reset( ).
*      Print the results
        print_results( ).
*      Update event table
        update_event_table( ).
*      Close the schedule manager
        schedman_close( ).
        update_farminout_settings( ).
*      Print the spool overview screen, if appropriate
        mo_output_spool->print_overview_screen( ).
    endmethod.
```

SAVE_ADJUSTMENT_DOC_INFO

Description: Save the change doc info
Instance mthd

Importing parameter

```
IT_ACDOCA_CHECK TYPE FINST_ACDOCA (Universal Journal Entry Line Items)
IV_JVFUNC TYPE JV_FUNC (JV Function)
IV_INTCO TYPE ABAP_BOOL
IV_BELNR_NEW TYPE ACDOCA-BELNR
IV_ERROR_TEXT TYPE STRING
IV_POSTING_ERROR TYPE ABAP_BOOL
IV_POSTTYPE TYPE C
IT_ACDOC_ITEMS_POSTED TYPE FINST_ACDOC_ITEM
IT_ACCIT_POSTED TYPE ACCIT_T (Accounting Interface: Item Information)
IT_ACDOCA TYPE FINST_ACDOCA (ACDOCA Unified Journal Entry Line Items)
```

```
method save_adjustment_doc_info.
    data: ls_acdoca          type acdoca,
          lv_belnr_new      type acdoca-belnr,
          ls_acdoc_item_posted type fins_acdoc_item,
          ls_accit_posted   type accit,
          ls_print          type jva_ea_docprint,
          ls_color          type slis_specialcol_alv,
          lv_otype          type c,
          lv_object         type char24,
          lv_posid          type prps-posid,
          lv_tabix          type sy-tabix.
    if iv_posting_error = abap_true or
       ms_progpars-test = abap_true.
        add 1 to mv_belnr_test.
```

```
lv_belnr_new = |TEST| && mv_belnr_test  ##NO_TEXT.
else.
  lv_belnr_new = iv_belnr_new.
endif.
loop at it_acdoca into ls_acdoca.
  lv_tabix = sy-tabix.
  move-corresponding ls_acdoca to ls_print  ##ENH_OK.
  ls_print-jvfunc = iv_jvfunc.
  ls_print-belnr = lv_belnr_new.
  if not it_acdoc_items_posted[] is initial.
    clear: ls_acdoc_item_posted.
    read table it_acdoc_items_posted into ls_acdoc_item_posted index lv_tabix.
    ls_print-budat = ls_acdoc_item_posted-budat.
    ls_print-bldat = ls_acdoc_item_posted-bldat.
    ls_print-buzei = ls_acdoc_item_posted-buzei.
    ls_print-bschl = ls_acdoc_item_posted-bschl.
    ls_print-umskz = ls_acdoc_item_posted-umskz.
    ls_print-recid = ls_acdoc_item_posted-recid.
    ls_print-btype = ls_acdoc_item_posted-btype.
    if ls_acdoc_item_posted-kunnr is not initial.
      ls_print-racct = ls_acdoc_item_posted-kunnr.
    elseif ls_acdoc_item_posted-lifnr is not initial.
      ls_print-racct = ls_acdoc_item_posted-lifnr.
    elseif ls_acdoc_item_posted-hkont is not initial.
      ls_print-racct = ls_acdoc_item_posted-hkont.
    else.
      clear ls_print-racct.
    endif.
  else.
    clear: ls_accit_posted.
    read table it_accit_posted into ls_accit_posted index lv_tabix.
    ls_print-budat = ls_accit_posted-budat.
    ls_print-bldat = ls_accit_posted-bldat.
    ls_print-buzei = ls_accit_posted-buzei.
    ls_print-bschl = ls_accit_posted-bschl.
    ls_print-umskz = ls_accit_posted-umskz.
    ls_print-recid = ls_accit_posted-recid.
    ls_print-btype = ls_accit_posted-btype.
    if ls_accit_posted-kunnr is not initial.
      ls_print-racct = ls_accit_posted-kunnr.
    elseif ls_accit_posted-lifnr is not initial.
      ls_print-racct = ls_accit_posted-lifnr.
    elseif ls_accit_posted-hkont is not initial.
      ls_print-racct = ls_accit_posted-hkont.
    else.
      clear ls_print-racct.
    endif.
  endif.
* Identify cost object for record
  if not ls_acdoca-rcntr is initial.
    lv_otype = 'C'. " cost center
    lv_object = ls_acdoca-rcntr.
  elseif not ls_acdoca-aufnr is initial.
    lv_otype = 'O'. " order
```

```
lv_object = ls_acdoca-aufnr.
elseif not ls_acdoca-ps_psp_pnr is initial.
  lv_otype = 'W'.          " WBS element
  select single posid
    from prps
    into lv_posid
    where pspnr = ls_acdoca-ps_psp_pnr.
  lv_object = lv_posid.
elseif not ls_acdoca-nplnr is initial.
  lv_otype = 'N'.          " Network
  lv_object = ls_acdoca-nplnr.
elseif not ls_acdoca-prctr is initial.
  lv_otype = 'P'.          " Profit Center
  lv_object = ls_acdoca-prctr.
endif.
ls_print-co_name = lv_object.
ls_print-error = iv_posting_error.
ls_print-error_text = iv_error_text.
append_adjust_print_line( exporting
                          iv_jvfunc = iv_jvfunc
                          iv_intco  = iv_intco
                          is_print  = ls_print ).

endloop.
endmethod.
```

SAVE_CASH_CALL_INFO

Description: Save info about existing cash call amount
Instance mthd

Importing parameter

```
IS_ACDOCA_CHECK TYPE ACDOCA (Universal Journal Entry Line Items)
IV_JVFUNC TYPE JV_FUNC (JV Function)
IV_INTCO TYPE ABAP_BOOL
```

```
method save_cash_call_info.
  data: ls_print type jva_ea_docprint.
*  Add original line to print output table
  move-corresponding is_acdoca_check to ls_print.
  if ls_print-vptnr is initial.
    if is_acdoca_check-kunnr is not initial.
      ls_print-vptnr = is_acdoca_check-kunnr.
    elseif is_acdoca_check-lifnr is not initial.
      ls_print-vptnr = is_acdoca_check-lifnr.
    endif.
  endif.
  ls_print-is_original_data = abap_true.
  ls_print-jvfunc = iv_jvfunc.
  append_adjust_print_line( exporting
                          iv_jvfunc = iv_jvfunc
                          iv_intco  = iv_intco
                          is_print  = ls_print ).

endmethod.
```

SAVE_CHANGE_DOC_INFO

Description: Save the change doc info

Instance mthd

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)
IS_ACDOCA TYPE ACDOCA
IV_BELNR_NEW TYPE ACDOCA-BELNR
IV_EGRUP_NEW TYPE ACDOCA-EGRUP
IV_ERROR_TEXT TYPE STRING
IV_POSTING_ERROR TYPE ABAP_BOOL
LT_ACDOC_HEADER_POSTED TYPE FINST_ACDOC_HEADER
LT_ACDOC_ITEMS_POSTED TYPE FINST_ACDOC_ITEM

```
method save_change_doc_info.  
  data: lv_belnr_new      type acdoca-belnr,  
        ls_acdoc_header_posted type fins_acdoc_header,  
        ls_acdoc_item_posted  type fins_acdoc_item,  
        ls_print           type jva_ec_docprint,  
        ls_color            type slis_specialcol_alv,  
        lv_otype            type c,  
        lv_object           type char24,  
        lv_posid            type prps-posid,  
        lv_rcntr            type acdoca-rcntr,  
        lv_aufnr            type acdoca-aufnr,  
        lv_ps_psp_pnr       type acdoca-ps_psp_pnr,  
        lv_nplnr            type acdoca-nplnr,  
        lv_nplnr_vorgn      type acdoca-nplnr_vorgn.  
  move-corresponding is_acdoca to ls_print  ##ENH_OK.  
  ls_print-jvfunc = iv_jvfunc.  
  read table lt_acdoc_header_posted into ls_acdoc_header_posted index 1.  
  read table lt_acdoc_items_posted  into ls_acdoc_item_posted index 1.  
  ls_print-budat = ls_acdoc_item_posted-budat.  
  ls_print-bldat = ls_acdoc_item_posted-bldat.  
  if iv_posting_error = 'X'.  
    lv_belnr_new = 'ERROR'.  
  elseif ms_progpars-test = 'X'.  
    lv_belnr_new = text-003.  
  else.  
    lv_belnr_new = iv_belnr_new.  
  endif.  
  ls_print-belnr_corr = lv_belnr_new.  
  ls_print-buzei_corr = 1.  
  ls_print-vname_corr = is_acdoca-vname.  
  ls_print-egrup_corr = iv_egrup_new.  
  ls_print-etype_corr = is_acdoca-etype.  
  if ls_acdoc_item_posted-blart = 'K' or  
    ls_acdoc_item_posted-blart = 'D'.  
    if ls_acdoc_item_posted-kunnr is not initial.  
      ls_print-racct = ls_acdoc_item_posted-kunnr.  
    elseif ls_acdoc_item_posted-lifnr is not initial.  
      ls_print-racct = ls_acdoc_item_posted-lifnr.  
    elseif ls_acdoc_item_posted-hkont is not initial.
```

```

        ls_print-racct = ls_acdoc_item_posted-hkont.
    else.
        clear ls_print-racct.
    endif.
elseif ls_acdoc_item_posted-hkont is not initial.
    ls_print-racct = ls_acdoc_item_posted-hkont.
else.
    clear ls_print-racct.
endif.
lv_rcntr      = is_acdoca-rcntr.
lv_aufnr     = is_acdoca-aufnr.
lv_ps_psp_pnr = is_acdoca-ps_psp_pnr.
lv_nplnr     = is_acdoca-nplnr.
lv_nplnr_vorgn = is_acdoca-nplnr_vorgn.
* Identify the non-statistical cost object for the output
cl_jva_util=>determine_relevant_cost_object( exporting
                                             iv_accasty      = is_acdoca-accasty
                                             changing
                                             cv_rcntr        = lv_rcntr
                                             cv_aufnr         = lv_aufnr
                                             cv_ps_psp_pnr    = lv_ps_psp_pnr
                                             cv_nplnr         = lv_nplnr
                                             cv_nplnr_vorgn   = lv_nplnr_vorgn ).

if not lv_rcntr is initial.
    lv_otype = 'C'.                " cost center
    lv_object = lv_rcntr.
elseif not lv_aufnr is initial.
    lv_otype = 'O'.                " order
    lv_object = lv_aufnr.
elseif not lv_ps_psp_pnr is initial.
    lv_otype = 'W'.                " WBS element
    select single posid
        from prps
        into lv_posid
        where pspnr = lv_ps_psp_pnr.
    lv_object = lv_posid.
elseif not lv_nplnr is initial.
    lv_otype = 'N'.                " Network
    lv_object = lv_nplnr.
elseif not is_acdoca-prctr is initial.
    lv_otype = 'P'.                " Profit Center
    lv_object = is_acdoca-prctr.
endif.
ls_print-co_name = lv_object.
ls_print-error = iv_posting_error.
ls_print-error_text = iv_error_text.
* Add coloring information for ALV printing
ls_color-fieldname = 'BELNR_CORR'.
if iv_posting_error = 'X'.
    ls_color-color-col = '6'. "Red background
    append ls_color to ls_print-t_cell_color.
else.
    ls_color-color-col = '3'. "Col total (yellow)
    append ls_color to ls_print-t_cell_color.

```

```
endif.  
if iv_jvfunc = 'FACC'.  
    append ls_print to ms_ea_results-t_print_cc1.  
else.  
    append ls_print to ms_ea_results-t_print_ec.  
endif.  
endmethod.
```

SAVE_MESSAGE

Description: Save a message
Instance mthd

Importing parameter

```
IV_CLASS TYPE ANY  
IV_NUMBER TYPE ANY  
IV_TYPE TYPE ANY  
IV_VAR1 TYPE ANY OPTIONAL  
IV_VAR2 TYPE ANY OPTIONAL  
IV_VAR3 TYPE ANY OPTIONAL  
IV_VAR4 TYPE ANY OPTIONAL  
IV_MESSAGE_TEXT TYPE STRING OPTIONAL
```

```
method save_message.  
    data: ls_messages type t8jvt01,  
          lv_msgid     type symsgid,  
          lv_msgno     type symsgno,  
          lv_msgty     type symsgty.  
    lv_msgid = iv_class.  
    lv_msgno = iv_number.  
    lv_msgty = iv_type.  
    mo_message_collector->add_message( iv_msgid = lv_msgid  
                                       iv_msgno = lv_msgno  
                                       iv_msgty = lv_msgty  
                                       iv_msgv1 = iv_var1  
                                       iv_msgv2 = iv_var2  
                                       iv_msgv3 = iv_var3  
                                       iv_msgv4 = iv_var4 ).
```

```
* Set max error  
set_total_error_flag( exporting  
                      iv_error = iv_type  
                      changing  
                      cv_total_error = ms_ea_results-max_error ).  
  
ls_messages-msgid = iv_class.  
ls_messages-msgno = iv_number.  
ls_messages-status = iv_type.  
ls_messages-var1 = iv_var1.  
ls_messages-var2 = iv_var2.  
ls_messages-var3 = iv_var3.  
ls_messages-var4 = iv_var4.  
if not iv_message_text is initial.  
    ls_messages-text = iv_message_text.  
else.  
    message id lv_msgid type lv_msgty number lv_msgno  
        with iv_var1 iv_var2 iv_var3 iv_var4
```

```
        into mv_message_text.  
    ls_messages-text = mv_message_text.  
endif.  
collect ls_messages into ms_ea_results-t_messages.  
endmethod.
```

SAVE_SY_MESSAGE

Description: Save a sy message

Instance mthd

```
method save_sy_message.  
    if sy-msgid is initial.  
        return.  
    endif.  
    save_message( iv_type    = sy-msgty  
                  iv_class  = sy-msgid  
                  iv_number = sy-msgno  
                  iv_var1   = sy-msgv1  
                  iv_var2   = sy-msgv2  
                  iv_var3   = sy-msgv3  
                  iv_var4   = sy-msgv4 ).  
  
endmethod.
```

SCHEDMAN_CLOSE

Description: Close the schedule manager

Instance mthd

```
method schedman_close.  
    data: lv_messages_balobject    type balobj_d value 'JVA',  
          lv_messages_balsubobject type balsubobj value 'SCHEDMAN',  
          lv_messages_id          type sy-uzeit,  
          ls_message              type schedman_message,  
          lv_aplstat              type smmain-aplstat.  
    case ms_ea_results-max_error.  
        when 'A'.  
            lv_aplstat = 4.  
        when 'E'.  
            lv_aplstat = 4.  
        when 'W'.  
            lv_aplstat = 2.  
        when others.  
            lv_aplstat = 0.  
    endcase.  
    data(lt_spool) = mo_output_spool->get_spool_table( ).  
* Update and close the schedule manager log  
    mo_output->kpep_moni_close_record( exporting  
                                     is_key      = ms_progpars-s_schedman_key  
                                     is_message = ls_message  
                                     it_spool   = lt_spool  
                                     changing  
                                     cv_aplstat = lv_aplstat ).  
  
    mo_output->commit_work( ).  
endmethod.
```

SCHEDMAN_INITIALIZE

Description: Initialize the schedule manager

Instance mthd

```
method schedman_initialize.  
  data: ls_detail type schedman_detail_user,  
        lt_selkrit type schedman_selkrit_t,  
        ls_selkrit type schedman_selkrit,  
        ls_appl_jv type schedman_specific_jv.  
*  Company code  
  ls_selkrit = value #( structure = 'ACDOCA'  
                        field      = 'BUKRS'  
                        entry      = 1  
                        sign       = 'I'  
                        optio      = 'EQ'  
                        low        = ms_progpars-bukrs  
                        high       = ms_progpars-bukrs ).  
  append ls_selkrit to lt_selkrit.  
*  Venture  
  ls_selkrit = value #( structure = 'ACDOCA'  
                        field      = 'VNAME'  
                        entry      = 1  
                        sign       = 'I'  
                        optio      = 'EQ'  
                        low        = ms_progpars-vname  
                        high       = ms_progpars-vname ).  
  append ls_selkrit to lt_selkrit.  
*  Year  
  ls_selkrit = value #( structure = 'ACDOCA'  
                        field      = 'GJAHR'  
                        entry      = 1  
                        sign       = 'I'  
                        optio      = 'EQ'  
                        low        = ms_progpars-year  
                        high       = ms_progpars-year ).  
  append ls_selkrit to lt_selkrit.  
*  Period  
  ls_selkrit = value #( structure = 'BKPF'  
                        field      = 'MONAT'  
                        entry      = 1  
                        sign       = 'I'  
                        optio      = 'EQ'  
                        low        = ms_progpars-period  
                        high       = ms_progpars-period ).  
  append ls_selkrit to lt_selkrit.  
*  Old equity group  
  ls_selkrit = value #( structure = 'ACDOCA'  
                        field      = 'EGRUP'  
                        entry      = 1  
                        sign       = 'I'  
                        optio      = 'EQ'  
                        low        = ms_progpars-eqold  
                        high       = ms_progpars-eqold ).
```

```
append ls_selkrit to lt_selkrit.
* New equity group
ls_selkrit = value #( structure = 'ACDOCA'
                      field      = 'EGRUP'
                      entry      = 1
                      sign       = 'I'
                      optio      = 'EQ'
                      low        = ms_progpars-eqnew
                      high       = ms_progpars-eqnew ).
append ls_selkrit to lt_selkrit.
* From date
ls_selkrit = value #( structure = 'SYST'
                      field      = 'DATUM'
                      entry      = 1
                      sign       = 'I'
                      optio      = 'EQ'
                      low        = ms_progpars-frdate
                      high       = ms_progpars-frdate ).
append ls_selkrit to lt_selkrit.
* To date
ls_selkrit = value #( structure = 'SYST'
                      field      = 'DATUM'
                      entry      = 1
                      sign       = 'I'
                      optio      = 'EQ'
                      low        = ms_progpars-todate
                      high       = ms_progpars-todate ).
append ls_selkrit to lt_selkrit.
* Posting period selection
loop at ms_progpars-t_budat into data(ls_budat).
    ls_selkrit = value #( structure = 'SYST'
                        field      = 'DATUM'
                        entry      = sy-tabix
                        sign       = ls_budat-sign
                        optio      = ls_budat-option
                        low        = ls_budat-low
                        high       = ls_budat-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Accounts
loop at ms_progpars-t_acct into data(ls_acct).
    ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'RACCT'
                        entry      = sy-tabix
                        sign       = ls_acct-sign
                        optio      = ls_acct-option
                        low        = ls_acct-low
                        high       = ls_acct-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Cost center
loop at ms_progpars-t_cntr into data(ls_cntr).
    ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'RCNTR'
```

```
        entry      = sy-tabix
        sign       = ls_cntr-sign
        optio      = ls_cntr-option
        low        = ls_cntr-low
        high       = ls_cntr-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Order
loop at ms_progpars-t_ordnr into data(ls_ordnr).
    ls_selkrit = value #( structure = 'ACDOCA'
        field      = 'AUFNR'
        entry      = sy-tabix
        sign       = ls_ordnr-sign
        optio      = ls_ordnr-option
        low        = ls_ordnr-low
        high       = ls_ordnr-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Project
loop at ms_progpars-t_projk into data(ls_projk).
    ls_selkrit = value #( structure = 'ACDOCA'
        field      = 'PS_PSP_PNR'
        entry      = sy-tabix
        sign       = ls_projk-sign
        optio      = ls_projk-option
        low        = ls_projk-low
        high       = ls_projk-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Network
loop at ms_progpars-t_nplnr into data(ls_nplnr).
    ls_selkrit = value #( structure = 'ACDOCA'
        field      = 'NPLNR'
        entry      = sy-tabix
        sign       = ls_nplnr-sign
        optio      = ls_nplnr-option
        low        = ls_nplnr-low
        high       = ls_nplnr-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Network activity
loop at ms_progpars-t_vornr into data(ls_vornr).
    ls_selkrit = value #( structure = 'ACDOCA'
        field      = 'NPLNR_VORGN'
        entry      = sy-tabix
        sign       = ls_vornr-sign
        optio      = ls_vornr-option
        low        = ls_vornr-low
        high       = ls_vornr-high ).
    append ls_selkrit to lt_selkrit.
endloop.
* Posting date
ls_selkrit = value #( structure = 'SYST'
    field      = 'DATUM'
```

```

        entry      = 1
        sign       = 'I'
        optio      = 'EQ'
        low        = ms_progpars-budat
        high       = ms_progpars-budat ).
    append ls_selkrit to lt_selkrit.
*   Text
    ls_selkrit = value #( structure = 'BKPF'
                          field     = 'BKTXT'
                          entry     = 1
                          sign      = 'I'
                          optio     = 'EQ'
                          low       = ms_progpars-bktxt
                          high      = ms_progpars-bktxt ).
    append ls_selkrit to lt_selkrit.
*   Fill detail structure
    ls_detail-tcode   = sy-tcode.
    ls_detail-repid   = ms_progpars-repid_callback.
    ls_detail-testflag = ms_progpars-test.
*   ls_detail-function = ''.
*   ls_detail-activity = ''.
*   ls_detail-variante = ''.
*   ls_detail-application = ''.
*   ls_detail-nr_of_objects = 0.
*   Fill application data
    ls_appl_jv-bukrs   = ms_progpars-bukrs.
    ls_appl_jv-perio_from = ms_progpars-period.
    ls_appl_jv-perio_to   = ms_progpars-period.
    ls_appl_jv-gjahr     = ms_progpars-year.
    ls_appl_jv-versn     = '000'.
    ls_appl_jv-budat     = ms_progpars-budat.
*   Initialize monitor recording
    mo_output->kpep_moni_init_record(
        exporting
            is_detail = ls_detail
            it_selkrit = lt_selkrit
            is_appl   = ls_appl_jv
        importing
            es_key    = ms_progpars-s_schedman_key ).
endmethod.
```

SET_EVENT_PARAM

Description: Get the event parameters
Instance mthd

Importing parameter

CONTENSE TYPE ANY
NAME TYPE ANY

```

method set_event_param.
    data: ls_t8jevp type t8jevp.
    clear ls_t8jevp.
    move-corresponding ms_progpars-s_t8jev to ls_t8jevp.
    ls_t8jevp-param    = name.
```

```
ls_t8jevp-contense = contense.  
* Only update when not running in test mode  
if ms_progpars-test <> abap_true.  
    mo_output->insert_t8jevp( ls_t8jevp ).  
endif.  
endmethod.
```

SET_EVENT_PARAM_ACCOUNT

Description: Fill the account field

Instance mthd

```
method set_event_param_account.  
    data: ls_t8jevs type t8jevs.  
    move-corresponding ms_progpars-s_t8jev to ls_t8jevs.  
    ls_t8jevs-selpar = 'A'.  
    ls_t8jevs-seqn2 = 0.  
    loop at ms_progpars-t_acct into data(ls_acct).  
        ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.  
        move-corresponding ls_acct to ls_t8jevs.  
        ls_t8jevs-soption = ls_acct-option.  
* Only update when not running in test mode  
if ms_progpars-test <> abap_true.  
    mo_output->insert_t8jevs( ls_t8jevs ).  
endif.  
endloop.  
if sy-subrc <> 0.  
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.  
* Only update when not running in test mode  
if ms_progpars-test <> abap_true.  
    mo_output->insert_t8jevs( ls_t8jevs ).  
endif.  
endif.  
endmethod.
```

SET_EVENT_PARAM_COST_CENTER

Description: Fill the cost center fields

Instance mthd

```
method set_event_param_cost_center.  
    data: ls_t8jevs type t8jevs.  
    move-corresponding ms_progpars-s_t8jev to ls_t8jevs.  
    ls_t8jevs-selpar = 'K'.  
    ls_t8jevs-seqn2 = 0.  
    loop at ms_progpars-t_cntr into data(ls_cntr).  
        add 1 to ls_t8jevs-seqn2.  
        move-corresponding ls_cntr to ls_t8jevs.  
        ls_t8jevs-soption = ls_cntr-option.  
* Only update when not running in test mode  
if ms_progpars-test <> abap_true.  
    mo_output->insert_t8jevs( ls_t8jevs ).  
endif.  
endloop.  
if sy-subrc <> 0.  
    add 1 to ls_t8jevs-seqn2.
```

```
*      Only update when not running in test mode
      if ms_progpars-test <> abap_true.
        mo_output->insert_t8jevs( ls_t8jevs ).
      endif.
    endif.
  endmethod.
```

SET_EVENT_PARAM_ORDER

Description: Fill the order field

Instance mthd

```
method set_event_param_order.
  data: ls_t8jevs type t8jevs.
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.
  ls_t8jevs-selpar = '0'.
  ls_t8jevs-seqn2 = 0.
  loop at ms_progpars-t_ordnr into data(ls_ordnr).
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
    move-corresponding ls_ordnr to ls_t8jevs.
    ls_t8jevs-soption = ls_ordnr-option.
*      Only update when not running in test mode
    if ms_progpars-test <> abap_true.
      mo_output->insert_t8jevs( ls_t8jevs ).
    endif.
  endloop.
  if sy-subrc <> 0.
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
*      Only update when not running in test mode
    if ms_progpars-test <> abap_true.
      mo_output->insert_t8jevs( ls_t8jevs ).
    endif.
  endif.
endmethod.
```

SET_EVENT_PARAM_PROJECT

Description: Fille the project field

Instance mthd

```
method set_event_param_project.
  data: ls_t8jevs type t8jevs.
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.
  ls_t8jevs-selpar = 'W'.
  ls_t8jevs-seqn2 = 0.
  loop at ms_progpars-t_projk into data(ls_projk).
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
    move-corresponding ls_projk to ls_t8jevs.
    ls_t8jevs-soption = ls_projk-option.
*      Only update when not running in test mode
    if ms_progpars-test <> abap_true.
      mo_output->insert_t8jevs( ls_t8jevs ).
    endif.
  endloop.
  if sy-subrc <> 0.
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
```

```
*      Only update when not running in test mode
      if ms_progpars-test <> abap_true.
        mo_output->insert_t8jevs( ls_t8jevs ).
      endif.
    endif.
  endmethod.
```

SET_POSTING_INDICATORS

Description: Set posting key and indicators for FI doc line
Instance mthd

Importing parameter

```
VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
```

Changing parameter

```
CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING
```

```
method set_posting_indicators.
  data: ls_t8j0g      type t8j0g,
        lv_fatal_error type abap_bool,
        lv_error_text type string.
  get_posting_rule( exporting
                    iv_bukrs      = is_acdoca-rbukrs
                    iv_jvfunc     = iv_jvfunc
                    iv_jvactivity = iv_jvactivity
                    iv_recid      = is_acdoca-recid
                    changing
                    cs_t8j0g      = ls_t8j0g
                    cv_fatal_error = lv_fatal_error
                    cv_error_text = lv_error_text ).

  if is_acdoca-wsl >= 0 and
     is_acdoca-hsl >= 0 and
     is_acdoca-ksl >= 0 and
     is_acdoca-osl >= 0 and
     is_acdoca-vsl >= 0 and
     is_acdoca-bsl >= 0 and
     is_acdoca-csl >= 0 and
     is_acdoca-dsl >= 0 and
     is_acdoca-esl >= 0 and
     is_acdoca-fsl >= 0 and
     is_acdoca-gsl >= 0.
    cs_accit-shkzg = 'S'.
  else.
    cs_accit-shkzg = 'H'.
  endif.
  if cs_accit-shkzg = 'S'.
    cs_accit-bschl = ls_t8j0g-debpostkey.
    cs_accit-umskz = ls_t8j0g-debseind.
    cs_accit-btype = ls_t8j0g-debbillind.
    if not ls_t8j0g-debrecid is initial.
      cs_accit-recid = ls_t8j0g-debrecid.
```

```
endif.
else.
  cs_accit-bschl = ls_t8j0g-crepostkey.
  cs_accit-umskz = ls_t8j0g-creseind.
  cs_accit-btype = ls_t8j0g-crebillind.
  if not ls_t8j0g-crerecid is initial.
    cs_accit-recid = ls_t8j0g-crerecid.
  endif.
endif.
if lv_fatal_error = 'X'.
  cv_fatal_error = 'X'.
  if cv_error_text is initial.
    cv_error_text = lv_error_text.
  endif.
endif.
endmethod.
```

SET_TOTAL_ERROR_FLAG

Description: Set the maximum error flag

Instance mthd

Importing parameter

IV_ERROR TYPE ANY

Changing parameter

CV_TOTAL_ERROR TYPE ANY

```
method set_total_error_flag.
  case iv_error.
    when 'A'.
      cv_total_error = 'A'.
    when 'E'.
      if cv_total_error <> 'A'.
        cv_total_error = 'E'.
      endif.
    when 'W'.
      if cv_total_error <> 'A' and
        cv_total_error <> 'E'.
        cv_total_error = 'W'.
      endif.
  endcase.
endmethod.
```

UPDATE_FARMINOUT_SETTINGS

Description: Update the Farm In/Out settings tables

Instance mthd

```
method update_farminout_settings.
  data: ls_t8jfrm    type t8jfrm,
        ls_t8jfrm_eg type t8jfrm_eg,
        lv_frm_name type t8jfrm-frm_name.
  "Do not update the settings tables in the case of
  "equity adjustments and test runs
  if ms_progpars-farm_in_out = abap_false or
    ms_progpars-test = abap_true.
```

```

        return.
    endif.
    lv_frm_name = ms_progpars-vname+2(4) && ms_progpars-eqold && ms_progpars-eqnew.
    select single * from t8jfrm into @ls_t8jfrm
        where bukrs      = @ms_progpars-bukrs
        and frm_name     = @lv_frm_name.
    if ls_t8jfrm is initial.
        ls_t8jfrm = value #( bukrs      = ms_progpars-bukrs
                             frm_name   = lv_frm_name
                             ctime     = sy-uzeit ).
    endif.
    ls_t8jfrm-vname      = ms_progpars-vname.
    ls_t8jfrm-eg_new     = ms_progpars-eqnew.
    ls_t8jfrm-per_from   = ms_progpars-from_period.
    ls_t8jfrm-year_from  = ms_progpars-from_year.
    ls_t8jfrm-per_to     = ms_progpars-to_period.
    ls_t8jfrm-year_to    = ms_progpars-to_year.
    ls_t8jfrm-itd        = ms_progpars-inception_to_date.
    ls_t8jfrm-post_date  = ms_progpars-budat.
    ls_t8jfrm-doc_date   = ms_progpars-budat.
    ls_t8jfrm-post_year  = ms_progpars-year.
    ls_t8jfrm-post_per   = ms_progpars-period.
    ls_t8jfrm-post_text  = ms_progpars-bktxt.
    ls_t8jfrm-recid_type = '1'. "Billable only
    ls_t8jfrm-old_eg_blocked = ms_progpars-block_old_eg.
    ls_t8jfrm-process_compl = '2'. "Possible Values: 1 - Open; 2 - Complete; 9 - In
Process
    ls_t8jfrm-cputime    = sy-uzeit.
    ls_t8jfrm-cpudt     = sy-datum.
    ls_t8jfrm-lst_user   = sy-uname.
    ls_t8jfrm-proc_type  = '1'. "Possible Values: 1 - Farm In; 2 -
Redetermination
    modify t8jfrm from ls_t8jfrm.
    ls_t8jfrm_eg = value #( bukrs      = ms_progpars-bukrs
                             frm_name  = lv_frm_name
                             eg_old    = ms_progpars-eqold
                             vname     = ms_progpars-vname
                             eg_new    = ms_progpars-eqnew
                             cputime   = sy-uzeit
                             cpudt     = sy-datum
                             lst_user  = sy-uname ).
    modify t8jfrm_eg from ls_t8jfrm_eg.
    mo_output->commit_work( ).
endmethod.

```

UPDATE_EVENT_TABLE

Description: Update the JVA event table

Instance mthd

```

method update_event_table.
*   Update event table with success/failure indicator
    if ms_ea_results-max_error = 'E' or
        ms_ea_results-max_error = 'A'.
        ms_progpars-s_t8jsev-status = '3'. "Failure
    endif.
endmethod.

```

```
elseif ms_cb_results-vent_count_errors > 0.  
    ms_progpars-s_t8jev-status = '2'.  "Incomplete  
else.  
    ms_progpars-s_t8jev-status = '1'.  "Complete  
endif.  
* Only update in productive run  
if ms_progpars-test <> abap_true.  
    mo_output->update_t8jev( ms_progpars-s_t8jev ).  
endif.  
endmethod.
```

Redefined Methods

Macros

```
*** use this source file for any macro definitions you need  
*** in the implementation part of the class
```

Overview

Attributes	1
Attributes	1
Private attribute	1
Intern. types	2
Private types	2
Methods	2
Private methods	2
ADD_ACCIT_LINE_CASHCALL	2
ADD_ACCIT_LINE_CORRECTION	4
ADD_ACCIT_LINE_SETTLEMENT	5
ADD_FIDOC_HEADER	6
ADD_GENERAL_INFORMATION	6
ADD_INFO	7
ADD_ITEM_TO_FIELDCATALOG	7
ADD_ITEM_TO_SELECT_TABLES	8
ADJUST_CASHCALL_EG	10
ADJUST_CASHCALL_EG_INTCO	11
ADJUST_CASHCALL_EQUITY_GROUP	12
ADJUST_CASHCALL_PARTNERS	12
ADJUST_CASHCALL_PARTNERS_INTCO	13
ADJUST_CASHCALL_PARTNER_SHARES	13
ADJUST_CUTBACK_RESULTS	14
ADJUST_EQUITY_GROUP	16
ADJUST_INTERCOMPANY_REVERSAL	16
APPEND_ADJUST_PRINT_LINE	17
CALC_CC_CORRECTION_AMOUNT	17
CHECK_ADJUSTMENT_DATE	18
CHECK_ADJUSTMENT_PERIOD	19
CHECK_AUTHORITY	21
CHECK_COMPANY_CODE	21
CHECK_EQUITY_GROUP	22
CHECK_FOR_PREVIOUS_CHANGES	24
CHECK_INTERCOMPANY_VENTURE	25
CHECK_LINE_ITEMS	26
CHECK_PARAMETERS	28
CHECK_POSTING_DATE	28
CHECK_PROCESSING_MODE	30
CHECK_RECID	30
CHECK_SETTLEMENT_ACCOUNT	31
CHECK_SHARES_CC1	32
CHECK_SHARES_CC1_INTCO	33
CHECK_SHARES_CC2	34
CHECK_SHARES_CC2_INTCO	35
CHECK_SHARES_INTCO_REVERSAL	36
CHECK_VENTURE	38
FILL_ACCCR	39
FILL_EVENT_TABLE	40
GET_BILLIND_RANGE_CASHCALL	41
GET_BILLIND_RANGE_CUTBACK	44

GET_BILLIND_RANGE_PAYMENTS	44
GET_DATA_CC1	45
GET_DATA_CC1_INTCO	47
GET_DATA_CC2	49
GET_DATA_CC2_INTCO	51
GET_DATA_EC	53
GET_DATA_INTCO	55
GET_FIELDS_FOR_ACDOCA_SELECTS	58
GET_INTCO_VENDOR	61
GET_MSGS_FROM_MSG_COLLECTOR	62
GET_PARTNER_SHARES	62
GET_POSTING_RULE	64
GET_POSTING_RULES	66
GET_RI_REBOOK_AND_REVERSE	66
GET_SETTINGS	67
INITIALIZE_MAIN_OBJECTS	68
MAKE_DATE_CLAUSE_FOR_SELECT	69
MAKE_DOC_INFO	70
POST_ADJUSTMENT_DOCUMENT	70
POST_CHANGE_DOCUMENT	72
POST_FI_DOC	75
PREPARE_ACCIT_LINE	77
PREPARE_CC_ADJUSTMENTS	78
PREPARE_CC_ADJUSTMENTS_INTCO	88
PREPARE_DIFF_SHARE_DATA	94
PREPARE_EQUITY_CHANGE	95
PREPARE_POSTINGS_INTCO	96
PROCESS_EC_AGGREGATED	96
PRINT_RESULTS	97
RUN_ADJUSTMENTS	97
RUN_PROCESS	98
SAVE_ADJUSTMENT_DOC_INFO	99
SAVE_CASH_CALL_INFO	101
SAVE_CHANGE_DOC_INFO	101
SAVE_MESSAGE	104
SAVE_SY_MESSAGE	105
SCHEDMAN_CLOSE	105
SCHEDMAN_INITIALIZE	106
SET_EVENT_PARAM	109
SET_EVENT_PARAM_ACCOUNT	110
SET_EVENT_PARAM_COST_CENTER	110
SET_EVENT_PARAM_ORDER	111
SET_EVENT_PARAM_PROJECT	111
SET_POSTING_INDICATORS	112
SET_TOTAL_ERROR_FLAG	113
UPDATE_FARMINOUT_SETTINGS	113
UPDATE_EVENT_TABLE	114
Redefined Methods	115
Macros	115