

Class: CL_JVA_EQUITY_ADJUST

Status: Active

Implemented interfaces

IF_JVA_EQUITY_ADJUST (Interface for Equity Adjustment)

Attributes

Description: Equity Adjustment for JVA
Instantiation: Public
Not final

Not released
Fixed Point Arithmetic
Program status: SAP Standard Production Program
Category: General Object Type
Package: GJVA
Original lang.: EN

Created by: SAP
Created On: 27.12.2018
Last changed on: 15.05.2025

Forward declaration type grps.

ABAP

Forward declaration interfaces

CL_JVA_EQUITY_ADJUST

Attributes

Private attribute

Attrib. Ref. Type	Cat	Description	Init. value
MV_BELNR_TEST TYPE NUMC06	Inst	Document number for testing	
MV_MESSAGE_TEXT TYPE STRING	Inst	Message Text	
MO_APPLICATION_LOG TYPE REF TO IF_JVA_MESSAGE_OUTPUT	Inst		
MO_CUTBACK TYPE REF TO IF_JVA_CUTBACK	Inst		
MO_MESSAGE_COLLECTOR TYPE REF TO IF_JVA_MESSAGE_COLLECTION	Inst		
MO_MESSAGE_OUTPUT TYPE REF TO IF_JVA_MESSAGE_OUTPUT	Inst		
MO_OUTPUT TYPE REF TO IF_JVA_OUTPUT	Inst		
MS_ALV_CALLBACK_DATA TYPE GTY_S_ALV_CALLBACK_DATA	Inst		
MS_CB_RESULTS TYPE JVA_CB_RESULTS	Inst		

Attrib. Ref. Type	Cat	Description	Init. value
MS_EA_RESULTS TYPE JVA_EA_RESULTS	Inst		
MS_PROGPARS TYPE JVA_EA_PROGPARS	Inst		
MS_SETTINGS TYPE JVA_EA_SETTINGS	Inst		
MO_JVA_POST_ACDOCA TYPE REF TO IF_JVA_POST_ACDOCA	Inst	Post ACDOCA document	
MO_PARTNER_SHARES TYPE REF TO IF_JVA_PARTNER_SHARES	Inst	JVA partner share calculations	
MO_OUTPUT_SPOOL TYPE REF TO IF_JVA_EQUITY_ADJUST_OUTPUT	Inst	Interface for equity adjustment printing	

Intern. types

Private types

Cat	Cat	Ref. Type	Description
GTY_S_INTCO_SETTL_ACCT	TYPE REF TO		
GTY_S_ACDOCA_CHECK	TYPE REF TO		
GTY_T_ACDOCA_CHECK	TYPE REF TO		
GTY_S_DISP	TYPE REF TO		
GTY_S_BELNR	TYPE REF TO		
GTY_S_ALV_INFOS	TYPE REF TO		
GTY_S_ALV_CALLBACK_DATA	TYPE REF TO		

Methods

Private methods

ADD_ACCIT_LINE_CASHCALL

Description: Add correction line to
Inst. Method

Importing parameter

VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)
VALUE(IV_SELFCLEARING) TYPE ABAP_BOOL (Create the document as self-clearing document)

Changing parameter

CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING

```

method add_accit_line_cashcall.
  data: lv_fatal_error type abap_bool,
        lv_error_text  type string.
  cs_accit-jvactivity = iv_jvactivity.
  cs_accit-awtyp = 'BKPFF'.      "AW type
  cs_accit-mandt = sy-mandt.     "Client
  cs_accit-bukrs = is_acdoca-rbukrs. "Company code
  cs_accit-posnr = iv_buzei.     "Line number
* Venture data
  cs_accit-vname = is_acdoca-vname. "Venture
  cs_accit-egrup = is_acdoca-egrup. "Equity group
  cs_accit-recid = is_acdoca-recid. "Recovery indicator
  cs_accit-prctr = is_acdoca-prctr. "Profit center
  cs_accit-segment = is_acdoca-segment. "Segment
  if not is_acdoca-lifnr is initial.
    cs_accit-lifnr = is_acdoca-lifnr.
    "Get the payment terms
    select single zterm from lfb1 into cs_accit-zterm
      where bukrs = cs_accit-bukrs
      and lifnr = cs_accit-lifnr.

    clear cs_accit-hkont.
  elseif not is_acdoca-kunnr is initial.
    cs_accit-kunnr = is_acdoca-kunnr.
    "Get the payment terms
    select single zterm from knb1 into cs_accit-zterm
      where bukrs = cs_accit-bukrs
      and kunnr = cs_accit-kunnr.

    clear cs_accit-hkont.
  else.
    cs_accit-hkont = is_acdoca-racct.
  endif.
  cs_accit-blart = ms_settings-s_t8j0f-doctyped. "Document type
  set_posting_indicators( exporting
    iv_jvfunc      = iv_jvfunc
    iv_jvactivity  = iv_jvactivity
    is_acdoca      = is_acdoca
    changing
    cs_accit       = cs_accit
    cv_fatal_error = lv_fatal_error
    cv_error_text  = lv_error_text ).

  if iv_selfclearing = abap_true.
    cs_accit-augbl = '*'. "Self clearing indicator
  endif.
  append cs_accit to ct_accit.
  fill_accr( exporting
    is_accit      = cs_accit
    is_acdoca     = is_acdoca
    iv_rwcur      = is_acdoca-rwcur
    is_curr_info  = ms_settings-s_curr_info
    changing
    ct_accr      = ct_accr ).
  if lv_fatal_error = 'X'.
    cv_fatal_error = 'X'.
    if cv_error_text is initial.

```

```
        cv_error_text = lv_error_text.  
    endif.  
endif.  
endmethod.
```

ADD_ACCIT_LINE_CORRECTION

Description: Add correction line to
Inst. Method

Importing parameter

```
VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)  
VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)  
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))  
VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)
```

Changing parameter

```
CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)  
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)  
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)  
CV_FATAL_ERROR TYPE C  
CV_ERROR_TEXT TYPE STRING
```

```
method add_accit_line_correction.  
    data: lv_fatal_error type abap_bool,  
          lv_error_text type string.  
    cs_accit-jvactivity = iv_jvactivity.  
    cs_accit-posnr = iv_buzei. "Line number  
    cs_accit-egrup = is_acdoca-egrup. "Equity group  
    cs_accit-vptnr = is_acdoca-vptnr. "Partner  
    if not is_acdoca-lifnr is initial.  
        cs_accit-lifnr = is_acdoca-lifnr.  
        clear cs_accit-hkont.  
    elseif not is_acdoca-kunnr is initial.  
        cs_accit-kunnr = is_acdoca-kunnr.  
        clear cs_accit-hkont.  
    else.  
        cs_accit-hkont = is_acdoca-racct.  
    endif.  
    cs_accit-koart = is_acdoca-koart.  
    set_posting_indicators( exporting  
                            iv_jvfunc      = iv_jvfunc  
                            iv_jvactivity  = iv_jvactivity  
                            is_acdoca      = is_acdoca  
                            changing  
                                cs_accit    = cs_accit  
                                cv_fatal_error = lv_fatal_error  
                                cv_error_text = lv_error_text ).  
    append cs_accit to ct_accit.  
    fill_acccr( exporting  
                is_accit      = cs_accit  
                is_acdoca     = is_acdoca  
                iv_rwcur      = is_acdoca-rwcur  
                is_curr_info  = ms_settings-s_curr_info  
                changing  
                    ct_acccr  = ct_acccr ).
```

```
if lv_fatal_error = 'X'.
  cv_fatal_error = 'X'.
  if cv_error_text is initial.
    cv_error_text = lv_error_text.
  endif.
endif.
endmethod.
```

ADD_ACCIT_LINE_SETTLEMENT

Description: Add settlement line to FI document
Inst. Method

Importing parameter

```
VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)
IV_JVACTIVITY TYPE ACDOCA-JVACTIVITY (JVA Activity (Joint Venture Accounting))
VALUE(IV_BUZEI) TYPE ACDOCA-BUZEI (Number of Line Item Within Accounting Document)
```

Changing parameter

```
CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING
```

```
method add_accit_line_settlement.
  cs_accit-jvactivity = iv_jvactivity.
  cs_accit-posnr = iv_buzei. "Line number
  cs_accit-egrup = is_acdoca-egrup. "Equity group
  cs_accit-vptnr = is_acdoca-vptnr. "Partner
  cs_accit-hkont = is_acdoca-racct. "Account
  "Clear customer and vendor number
  clear: cs_accit-kunnr,
         cs_accit-lifnr.
  cs_accit-koart = is_acdoca-koart.
  set_posting_indicators( exporting
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = iv_jvactivity
                          is_acdoca      = is_acdoca
                          changing
                          cs_accit       = cs_accit
                          cv_fatal_error = cv_fatal_error
                          cv_error_text  = cv_error_text ).
  append cs_accit to ct_accit.
  fill_accr( exporting
            is_accit      = cs_accit
            is_acdoca     = is_acdoca
            iv_rwcur      = is_acdoca-rwcur
            is_curr_info  = ms_settings-s_curr_info
            changing
            ct_accr       = ct_accr ).
endmethod.
```

ADD_FIDOC_HEADER

Description: Add FI doc header
Inst. Method

Changing parameter

CT_ACCHD TYPE ACCHD_T (Transfer Table: Header Information for FI Documents)

```
method add_fidoc_header.  
  data: lv_hd_text(25) type c,  
        ls_acchd      type acchd.  
  lv_hd_text = 'Cash Call Adjustment'  ##NO_TEXT.  
  ls_acchd-mandt = sy-mandt.  
  ls_acchd-awtyp = 'BKPFF'.  
  ls_acchd-glvor = 'RFBU'.  
  ls_acchd-tcode = sy-tcode.  
  ls_acchd-usnam = sy-uname.  
  ls_acchd-cpudt = sy-datum.  
  ls_acchd-cputm = sy-uzeit.  
  ls_acchd-bktxt = lv_hd_text.  
  append ls_acchd to ct_acchd.  
endmethod.
```

ADD_GENERAL_INFORMATION

Description: Add general information for output
Inst. Method

```
method add_general_information.  
  data: lv_text type string.  
*  Add info about test or real run  
  lv_text = text-rty && |: |.  
  if ms_progpars-analysis_only = abap_true.  
    lv_text = lv_text && text-ano.  
  elseif ms_progpars-test = abap_true.  
    lv_text = lv_text && text-tst.  
  else.  
    lv_text = lv_text && text-rru.  
  endif.  
  add_info( exporting  
            iv_info_text = lv_text  
            changing  
            ct_infos_print = ms_ea_results-t_infos ).  
  if ms_ea_results-t_print_ec[] is initial.  
    lv_text = text-nod.  
  else.  
    lv_text = text-ner && |: | && ms_ea_results-no_of_errors.  
  endif.  
  add_info( exporting  
            iv_info_text = lv_text  
            changing  
            ct_infos_print = ms_ea_results-t_infos ).  
endmethod.
```

ADD_INFO

Description: Add info about errors in the settings
Inst. Method

Importing parameter

IV_INFO_TEXT TYPE ANY

Changing parameter

CT_INFOS_PRINT TYPE JVA_INFO_PRINT_T (Info text to be printed)

```
method add_info.  
  data: ls_infos_print type jva_info_print.  
  ls_infos_print-text = iv_info_text.  
  append ls_infos_print to ct_infos_print.  
endmethod.
```

ADD_ITEM_TO_FIELDCATALOG

Description: Add an item to a field catalog for ACDOCA selects
Inst. Method

Importing parameter

IT_DFIES TYPE DFIES_TABLE (DD Interface: Table Fields for DDIF_FIELDINFO_GET)
IV_FIELDNAME TYPE FIELDNAME (Field Name)

Changing parameter

CS_DFIES TYPE DFIES (DD Interface: Table Fields for DDIF_FIELDINFO_GET)
CT_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)

```
method add_item_to_fieldcatalog.  
  data: ls_fieldcatalog type lvc_s_fcat,  
        lv_tabix        type sy-tabix.  
  clear cs_dfies.  
*  Check if the item is already in the field catalog  
  read table ct_fieldcatalog transporting no fields  
                                with key fieldname = iv_fieldname  
                                binary search.  
  
  lv_tabix = sy-tabix.  
  if sy-subrc > 2.  
*    Add the item to the field catalog  
    read table it_dfies into cs_dfies  
                                with key fieldname = iv_fieldname  
                                binary search.  
  
    if sy-subrc = 0.  
      move-corresponding cs_dfies to ls_fieldcatalog.  
      insert ls_fieldcatalog into ct_fieldcatalog index lv_tabix.  
    endif.  
  endif.  
endmethod.
```

ADD_ITEM_TO_SELECT_TABLES

Description: Add item to tables used for database selects
Inst. Method

Importing parameter

IT_DFIES TYPE DFIES_TABLE (Table for dfies entries)

IV_FIELDNAME TYPE FIELDNAME (Field Name)

Changing parameter

CT_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)

CT_SEL_FIELDS TYPE FIELDLIST_T

CT_GROUP_FIELDS TYPE FIELDLIST_T

method add_item_to_select_tables.

data: ls_dfies type dfies,

lv_strlen type i,

ls_sel_fields like line of ct_sel_fields.

"Do not add the following fields

if iv_fieldname = 'EPRCTR' or

iv_fieldname = 'PSEGMENT' or

iv_fieldname = 'PS_POSID' or

iv_fieldname = 'RFAREA' or

iv_fieldname = 'RMVCT' or

iv_fieldname = 'AFABE' or

iv_fieldname = 'ANLGR' or

iv_fieldname = 'ANLGR2' or

iv_fieldname = 'BWKEY' or

iv_fieldname = 'BWTAR' or

iv_fieldname = 'CO_OSL' or

iv_fieldname = 'FCSL' or

iv_fieldname = 'GLACCOUNT_TYPE' or

iv_fieldname = 'HBKID' or

iv_fieldname = 'HKTID' or

iv_fieldname = 'HVKWRT' or

iv_fieldname = 'KALNR' or

iv_fieldname = 'KDAUF' or

iv_fieldname = 'KDPOS' or

iv_fieldname = 'KOART' or

iv_fieldname = 'KTOP2' or

iv_fieldname = 'KTOPL' or

iv_fieldname = 'KZBWS' or

iv_fieldname = 'LOKKT' or

iv_fieldname = 'MAT_KDAUF' or

iv_fieldname = 'MAT_KDPOS' or

iv_fieldname = 'MAT_LIFNR' or

iv_fieldname = 'MOVCAT' or

iv_fieldname = 'PEGRUP' or

iv_fieldname = 'PERIV' or

iv_fieldname = 'PFSL' or

iv_fieldname = 'PKDAUF' or

iv_fieldname = 'PKDPOS' or

iv_fieldname = 'PPS_POSID' or

iv_fieldname = 'PPS_PSP_PNR' or

iv_fieldname = 'PSL' or

iv_fieldname = 'PS_PRJ_PNR' or

iv_fieldname = 'PS_PSPID' or

iv_fieldname = 'PVNAME' or

iv_fieldname = 'QUANT1' or

iv_fieldname = 'QUANT2' or

iv_fieldname = 'QUANT3' or

iv_fieldname = 'RASSC' or

```
    iv_fieldname = 'RBUNIT' or
    iv_fieldname = 'RBUPTR' or
    iv_fieldname = 'RCLNT' or
    iv_fieldname = 'RCOMP' or
    iv_fieldname = 'RCO_OCUR' or
    iv_fieldname = 'RFCCUR' or
    iv_fieldname = 'RHOART' or
    iv_fieldname = 'RISK_CLASS' or
    iv_fieldname = 'RITCLG' or
    iv_fieldname = 'RITEM' or
    iv_fieldname = 'RRCTY' or
    iv_fieldname = 'RTCUR' or
    iv_fieldname = 'RVUNIT' or
    iv_fieldname = 'SBUSA' or
    iv_fieldname = 'SCNTR' or
    iv_fieldname = 'SITYP' or
    iv_fieldname = 'SLALITTYPE' or
    iv_fieldname = 'SOBKZ' or
    iv_fieldname = 'SUBIT' or
    iv_fieldname = 'TSL' or
    iv_fieldname = 'VALOBJTYPE' or
    iv_fieldname = 'VALOBJ_ID' or
    iv_fieldname = 'VALSOBJ_ID' or
    iv_fieldname = 'VMSL' or
    iv_fieldname = 'VRGNG' or
    iv_fieldname = 'XOBEW' or
    iv_fieldname = 'PPRCTR'.
    return.
endif.
* Do not add the currency fields, except for the document currency
lv_strlen = strlen( iv_fieldname ).
if lv_strlen = 5 and iv_fieldname(1) = 'R' and iv_fieldname+2(3) = 'CUR'.
    if iv_fieldname <> 'RWCUR'.
        return.
    endif.
endif.
try.
    cl_abap_dyn_prg=>check_column_name( iv_fieldname ).
    catch cx_abap_invalid_name.
        return.
endtry.
* Add item to the fieldcatalog
add_item_to_fieldcatalog( exporting
                        it_dfies      = it_dfies
                        iv_fieldname  = iv_fieldname
                        changing
                        ct_fieldcatalog = ct_fieldcatalog
                        cs_dfies      = ls_dfies ).

if not ls_dfies is initial.
    if ls_dfies-sign = abap_true.
        ls_sel_fields = |SUM( { iv_fieldname } ) AS { iv_fieldname }|.
    else.
        ls_sel_fields = iv_fieldname.
    endif.
* Add item to group-by list
```

```

        append iv_fieldname to ct_group_fields.
    endif.
*   Add item to list of fields to be selected
    append ls_sel_fields to ct_sel_fields.
endif.
endmethod.

```

ADJUST_CASHCALL_EG

Description: Adjust the cash call postings for equity group

Inst. Method

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method adjust_cashcall_eg.
    data: lv_bukrs      type bukrs,
          lt_bilind_cutb type jva_bilind_range_t,
          lt_bilind_pay  type jva_bilind_range_t,
          lt_acdoca_cc1  type gty_t_acdoca_check,
          lt_acdoca_cb   type jva_cb_acdoca_t,
          lv_error       type abap_bool.
    check_shares_cc1( changing
                      cv_no_differences = cv_no_differences ).
    if cv_no_differences = abap_true.
        return.
    endif.
*   First get the billing indicators to be EXcluded from ACDOCA select
    get_billind_range_cutback( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'E'
                              importing
                              et_bilind = lt_bilind_cutb ).
*   Now get the billing indicator needed for zero balance checking
    get_billind_range_payments( exporting
                               iv_bukrs = ms_progpars-bukrs
                               iv_sign  = 'I'
                               importing
                               et_bilind = lt_bilind_pay ).
    sort ms_settings-t_diff_share by partn_old.
    loop at ms_settings-t_diff_share into data(ls_diff_share).
        get_data_cc1( exporting
                      it_bilind_cutb = lt_bilind_cutb
                      it_bilind_pay  = lt_bilind_pay
                      is_diff_share  = ls_diff_share
                      changing
                      ct_acdoca_cc1  = lt_acdoca_cc1
                      cv_error       = lv_error ).
        if lv_error <> abap_true and
           lines( lt_acdoca_cc1 ) > 0.
            prepare_equity_change( exporting
                                   iv_jvfunc      = 'FACC'
                                   iv_vname_new   = ms_progpars-vname
                                   iv_egrup_new   = ms_progpars-eqnew
                                   changing

```

```

ct_acdoca_main = lt_acdoca_cc1
ct_acdoca_cb   = lt_acdoca_cb ).

endif.
endloop.
endmethod.

```

ADJUST_CASHCALL_EG_INTCO

Description: Adjust the cash call postings for equity group

Inst. Method

Changing parameter

```

CV_NO_DIFFERENCES TYPE ABAP_BOOL

method adjust_cashcall_eg_intco.
  data: lv_bukrs      type bukrs,
        lt_bilind_cutb type jva_bilind_range_t,
        lt_bilind_pay  type jva_bilind_range_t,
        lt_acdoca_cc1  type gty_t_acdoca_check,
        lt_acdoca_cb   type jva_cb_acdoca_t,
        lv_error       type abap_bool.
  check_shares_cc1_intco( changing
                          cv_no_differences = cv_no_differences ).
  if cv_no_differences = abap_true.
    return.
  endif.
* First get the billing indicators to be EXcluded from ACDOCA select
  get_billind_range_cutback( exporting
                             iv_bukrs = ms_progpars-bukrs
                             iv_sign  = 'E'
                             importing
                             et_bilind = lt_bilind_cutb ).
* Now get the billing indicator needed for zero balance checking
  get_billind_range_payments( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'I'
                              importing
                              et_bilind = lt_bilind_pay ).
  sort ms_settings-t_diff_share by intcocd_old
                                     intrcovent_old
                                     intcompepp_old
                                     partn_old.
  loop at ms_settings-t_diff_share into data(ls_diff_share).
    get_data_cc1_intco( exporting
                       it_bilind_cutb = lt_bilind_cutb
                       it_bilind_pay  = lt_bilind_pay
                       is_diff_share  = ls_diff_share
                       changing
                       ct_acdoca_cc1  = lt_acdoca_cc1
                       cv_error       = lv_error ).
    if lv_error <> abap_true and
       lines( lt_acdoca_cc1 ) > 0.
      prepare_equity_change( exporting
                             iv_jvfunc      = 'FACC'
                             iv_vname_new   = ls_diff_share-intrcovent_new

```

```

                                iv_egrup_new    = ls_diff_share-intcompegp_new
                                changing
                                ct_acdoca_main = lt_acdoca_cc1
                                ct_acdoca_cb   = lt_acdoca_cb ).

endif.
endloop.
endmethod.
```

ADJUST_CASHCALL_EQUITY_GROUP

Description: Adjust the cash call postings for equity group
Inst. Method

```

method adjust_cashcall_equity_group.
  data: lv_no_differences      type abap_bool,
        lv_no_differences_intco type abap_bool.
  if ms_progpars-test <> abap_true.
*    Commit work and wait must be executed because this step
*    requires the documents of the previous steps to be posted
    mo_output->commit_work_and_wait( ).
    set update task local.
  endif.
  adjust_cashcall_eg( changing
                      cv_no_differences = lv_no_differences ).
  adjust_cashcall_eg_intco( changing
                             cv_no_differences = lv_no_differences_intco ).
*  If the shares of the partners are identical, issue an information message
  if lv_no_differences      = abap_true and
     lv_no_differences_intco = abap_true.
    message i799(g5) with text-ndi
                                ms_progpars-eqnew
                                ms_progpars-vname
                                into mv_message_text.
    save_sy_message( ).
  endif.
endmethod.
```

ADJUST_CASHCALL_PARTNERS

Description: Prepare the adjustment postings for intercompany cash call
Inst. Method

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method adjust_cashcall_partners.
  data: lt_acdoca      type gty_t_acdoca_check,
        lt_acdoca_posted type gty_t_acdoca_check,
        lr_acdoca_dyn   type ref to data,
        lr_acdoca_dyn_posted type ref to data.
  check_shares_cc2( changing
                    cv_no_differences = cv_no_differences ).
  if cv_no_differences = abap_true.
    return.
  endif.
  get_data_cc2( changing
```

```
        ct_acdoca      = lt_acdoca
        ct_acdoca_posted      = lt_acdoca_posted
        cr_acdoca_dyn      = lr_acdoca_dyn
        cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).
prepare_cc_adjustments( exporting
                        iv_jvfunc      = 'FAC2'
                        it_acdoca_check = lt_acdoca
                        it_acdoca_posted      = lt_acdoca_posted
                        ir_acdoca_dyn      = lr_acdoca_dyn
                        ir_acdoca_dyn_posted = lr_acdoca_dyn_posted ).

endmethod.
```

ADJUST_CASHCALL_PARTNERS_INTCO

Description: Adjust the intercompany partner postings

Inst. Method

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```
method adjust_cashcall_partners_intco.
  data: lt_acdoca      type gty_t_acdoca_check,
        lt_acdoca_posted      type gty_t_acdoca_check,
        lr_acdoca_dyn      type ref to data,
        lr_acdoca_dyn_posted type ref to data.
  check_shares_cc2_intco( changing
                        cv_no_differences = cv_no_differences ).
  if cv_no_differences = abap_true.
    return.
  endif.
  sort ms_settings-t_diff_share_intco by partn_old intcompepp_old.
  get_data_cc2_intco( changing
                    ct_acdoca      = lt_acdoca
                    ct_acdoca_posted      = lt_acdoca_posted
                    cr_acdoca_dyn      = lr_acdoca_dyn
                    cr_acdoca_dyn_posted = lr_acdoca_dyn_posted ).
  prepare_cc_adjustments_intco( exporting
                              iv_jvfunc      = 'FAC1'
                              it_acdoca_check = lt_acdoca
                              it_acdoca_posted      = lt_acdoca_posted
                              ir_acdoca_dyn      = lr_acdoca_dyn
                              ir_acdoca_dyn_posted = lr_acdoca_dyn_posted ).

endmethod.
```

ADJUST_CASHCALL_PARTNER_SHARES

Description: Adjust the partner shares of cash call postings

Inst. Method

```
method adjust_cashcall_partner_shares.
  data: lv_no_differences      type abap_bool,
        lv_no_differences_intco type abap_bool.
  if ms_progpars-test <> abap_true.
*    Commit work and wait must be executed because this step
*    requires the documents of the previous steps to be posted
    mo_output->commit_work_and_wait( ).
```

```

    set update task local.
endif.
adjust_cashcall_partners( changing
                        cv_no_differences = lv_no_differences ).
adjust_cashcall_partners_intco( changing
                        cv_no_differences = lv_no_differences_intco ).
* If the shares of the partners are identical, issue an information message
if lv_no_differences      = abap_true and
   lv_no_differences_intco = abap_true.
   message i799(g5) with text-ndi
                        ms_progpars-eqnew
                        ms_progpars-vname
                        into mv_message_text.
   save_sy_message( ).
endif.
endmethod.
```

ADJUST_CUTBACK_RESULTS

Description: Adjust the cutback results

Inst. Method

Importing parameter

```

IT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T

method adjust_cutback_results.
  data: ls_venture type jva_cb_venture,
        lv_cbdctx type jv_text22.
  if ms_progpars-test <> abap_true.
*   Commit work and wait must be executed because cutback
*   will need to update the equity adjustment postings with
*   the cutback run-id
    mo_output->commit_work_and_wait( ).
    set update task local.
  endif.
  move-corresponding ms_settings-s_t8jv to ls_venture ##ENH_OK.
  lv_cbdctx = ms_progpars-bktxt.
* Set cutback parameters
  mo_cutback->set_run_parameters( iv_caller      = if_jva_cutback=>types-eqad
                                it_bukrs       = value #( ( sign = 'I' option
= 'EQ' low = ms_progpars-bukrs ) )
                                it_vname       = value #( ( sign = 'I' option
= 'EQ' low = ms_progpars-vname ) )
                                iv_budat       = ms_progpars-budat
                                iv_ivpeqq      =
ms_progpars-invoice_per_equity_group
                                iv_ivpptn      =
ms_progpars-invoice_per_partner
                                iv_ivpexp      =
ms_progpars-invoice_per_expense_item
                                iv_cbdctx      = lv_cbdctx
                                iv_curr        = space
                                iv_error       = space
                                iv_inter       = abap_true
                                iv_mxtsks      = 20
```

```

        iv_one_spool      = abap_true
        iv_parall         = space
        iv_period         = ms_progpars-period
        iv_pfmlog         = space
        iv_print          = '3'
        iv_rfcgrp         = space
        iv_spool_per_bukrs = space
        iv_analysis_only  = ms_progpars-analysis_only
        iv_test           = ms_progpars-test
        iv_txdat          = ms_progpars-budat
        iv_txdctx         = space
        iv_ventsk         = 20
        iv_year           = ms_progpars-year
        iv_zterm          = space
        iv_repid_callback = ms_progpars-repid_callback
        iv_egrup_old      = ms_progpars-eqold
        iv_egrup_new      = ms_progpars-eqnew
        it_shares_old     = ms_settings-t_shares_old[]
        it_shares_new     = ms_settings-t_shares_new[]
        iv_cbrunid        =

ms_progpars-s_schedman_key-id
        iv_no_intco_reposting_for_ea = ms_progpars-icorev
    ).
*   Correct the cutback results
    mo_cutback->run_adjustments( exporting
                                is_venture = ls_venture
                                it_acdoca_cb = it_acdoca_cb
                                changing
                                cs_cb_results = ms_cb_results ).
*   Get max error from cutback processing and set error flag
    set_total_error_flag( exporting
                          iv_error = ms_cb_results-max_error
                          changing
                          cv_total_error = ms_ea_results-max_error ).

endmethod.
```

ADJUST_EQUITY_GROUP

Description: Make the equity adjustment for the actuals
Inst. Method

Changing parameter

```

CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T

method adjust_equity_group.
    data: lt_acdoca_check type gty_t_acdoca_check,
          ls_acdoca_check type gty_s_acdoca_check,
          ls_acdoca_main  type gty_s_acdoca_check,
          lv_is_oi_managed type c,
          lv_tabix         type sy-tabix,
          lt_acdoca_main   type gty_t_acdoca_check.
*   Get the data to be processed
    get_data_ec( changing ct_acdoca_main = lt_acdoca_main ).
    prepare_equity_change( exporting
                          iv_jvfunc      = 'EQAD'
```

```

            iv_vname_new    = ms_progpars-vname
            iv_egrup_new    = ms_progpars-eqnew
        changing
            ct_acdoca_main = lt_acdoca_main
            ct_acdoca_cb   = ct_acdoca_cb ).
    get_msgs_from_msg_collector( ).
endmethod.
```

ADJUST_INTERCOMPANY_REVERSAL

Description: Reverse the intercompany postings
Inst. Method

```

method adjust_intercompany_reversal.
    data: lv_no_intco_partner type c,
          lt_acdoca_intco_new type jva_cb_acdoca_t,
          lt_acdoca_intco_old type jva_cb_acdoca_t,
          lv_error            type abap_bool.
    if ms_progpars-test <> abap_true.
*       Commit work and wait must be executed because this step
*       requires the documents of the previous steps to be posted
        mo_output->commit_work_and_wait( ).
        set update task local.
    endif.
    get_posting_rules( exporting
                        iv_bukrs = ms_progpars-bukrs
                        iv_bmethod = ms_settings-s_t8jv-bmethod
                        iv_function = 'FACN'
                        changing
                            cv_error      = lv_error ).
    "get_settl_account( ).
    check_shares_intco_reversal( changing cv_no_intco_partner = lv_no_intco_partner
).
    check_recid( iv_jvfunc = 'FACN' ).
    get_data_intco( changing ct_acdoca_intco_new = lt_acdoca_intco_new
                          ct_acdoca_intco_old = lt_acdoca_intco_old ).
    if lt_acdoca_intco_new[] is initial.
        return.
    endif.
    prepare_postings_intco( exporting it_acdoca_intco_new = lt_acdoca_intco_new
                                it_acdoca_intco_old = lt_acdoca_intco_old ).

endmethod.
```

APPEND_ADJUST_PRINT_LINE

Description: Append adjustment doc line to print output table
Inst. Method

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)
IV_INTCO TYPE ABAP_BOOL
IS_PRINT TYPE JVA_EA_DOCPRINT (Details of equity adjustment document)

```

method append_adjust_print_line.
    if iv_intco = abap_true.
        append is_print to ms_ea_results-t_print_cc2_intco.
```

```
else.  
  append is_print to ms_ea_results-t_print_cc2.  
endif.  
endmethod.
```

CALC_CC_CORRECTION_AMOUNT

Description: Calculate cash call correction amount
Inst. Method

Importing parameter

```
IV_AMNT_OLD TYPE ACDOCA-HSL (Amount in Company Code Currency)  
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE
```

Returning parameter

```
VALUE(RV_AMNT_DIFF) TYPE ACDOCA-HSL (Amount in Company Code Currency)
```

```
method calc_cc_correction_amount.  
* calculate the amount for the correction posting  
* example: EG share old: 50%, EG share new: 30%  
*           ACDOCA amount: 200 (corresponds to the old 50% share)  
*  
* Change amount = ACDCOA-Value (200) * EG new (30) / EG old (50)  
*                - ACDOCA-Value (200)  
*  
* Amount to be posted in example = ( 200 * 30 / 50 ) - 200 = -80  
  rv_amnt_diff = ( iv_amnt_old * is_diff_share-eqshare_new /  
is_diff_share-eqshare_old )  
                - iv_amnt_old.  
  
endmethod.
```

CHECK_ADJUSTMENT_DATE

Description: Check the adjustment date
Inst. Method

Importing parameter

```
IS_T8JG_NEW TYPE T8JG  
IS_T8JG_OLD TYPE T8JG
```

Changing parameter

```
CV_FRDATE TYPE SYST_DATUM (ABAP system field: Current date of application server)  
CV_TODATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
```

```
method check_adjustment_date.  
  data: lv_date_next type sy-datum.  
  if ms_progpars-frdate > ms_progpars-todate.  
    data(lv_date_range_incons) = abap_true.  
  endif.  
  if ms_progpars-frdate is initial or  
    ms_progpars-frdate = '@STARTDA' or  
    lv_date_range_incons = abap_true.  
    data(lv_date_init) = abap_true.  
    cv_frdate = is_t8jg_new-fdate.  
    translate cv_frdate using '09182736455463728190'.  
    ms_progpars-frdate = cv_frdate.  
  endif.  
  if ms_progpars-todate is initial or
```

```

        ms_progpars-todate = '@STARTDA' or
        lv_date_range_incons = abap_true.
        lv_date_init = abap_true.
*      Get the next equity group and its start date
        select * from t8jg into @data(ls_t8jg_next)
              bypassing buffer
              where bukrs = @is_t8jg_new-bukrs
                 and vname = @is_t8jg_new-vname
                 and etype = @is_t8jg_new-etype
                 and fdate < @is_t8jg_new-fdate
              order by fdate descending.
        lv_date_next = ls_t8jg_next-fdate.
        translate lv_date_next using '09182736455463728190'.
        exit.
    endselect.
    if ls_t8jg_next is initial or
       ms_progpars-budat < lv_date_next.
       cv_todate = ms_progpars-budat.
    else.
       try.
           cv_todate = cl_bs_period_toolset_basics=>subtract_days_from_date( iv_date
= lv_date_next
                                                    iv_days
= 1 ).
           catch cx_bs_period_toolset_basics.
               "Do nothing
           endtry.
       endif.
       ms_progpars-todate = cv_todate.
    endif.
    if lv_date_init = abap_true.
       message i240(g5) with cv_frdate cv_todate.
    endif.
endmethod.
```

CHECK_ADJUSTMENT_PERIOD

Description: Check the adjustment date

Inst. Method

Importing parameter

IS_T8JG_NEW TYPE T8JG

IS_T8JG_OLD TYPE T8JG

Changing parameter

CV_FRPER TYPE MONAT (Fiscal Period)

CV_FRYEAR TYPE GJAHR (Fiscal Year)

CV_TOPER TYPE MONAT (Fiscal Period)

CV_TOYEAR TYPE GJAHR (Fiscal Year)

CV_ITD TYPE ABAP_BOOL (Inception to Date)

```

method check_adjustment_period.
    data: lv_date_init type abap_bool,
          lv_poper      type poper,
          lv_year       type gjahr,
          lv_date       type sy-datum,
```

```

        lv_date_next type sy-datum,
        lv_from      type string,
        lv_to        type string.
if ms_progpars-from_year > ms_progpars-to_year or
  ( ms_progpars-from_year = ms_progpars-to_year and
    ms_progpars-from_period > ms_progpars-to_period ).
  data(lv_period_range_incons) = abap_true.
endif.
if ms_progpars-from_year is initial or
  ms_progpars-from_period is initial or
  ms_progpars-from_period > '12' or
  lv_period_range_incons = abap_true.
  lv_date = is_t8jg_new-fdate.
  translate lv_date using '09182736455463728190'.
  call function 'DATE_TO_PERIOD_CONVERT'
    exporting
      i_date      = lv_date
      i_periv     = ms_settings-s_t001-periv
    importing
      e_buper     = lv_poper
      e_gjahr     = lv_year
    exceptions
      input_false = 1
      t009_notfound = 2
      t009b_notfound = 3
      others      = 4.
if sy-subrc = 0 and
  lv_year is not initial and
  lv_poper is not initial.
  cv_fryear = lv_year.
  cv_frper = lv_poper.
  ms_progpars-from_year = lv_year.
  ms_progpars-from_period = lv_poper.
  lv_date_init = abap_true.
endif.
endif.
if ms_progpars-to_year is initial or
  ms_progpars-to_period is initial or
  ms_progpars-to_period > '12' or
  lv_period_range_incons = abap_true.
* Get the next equity group and its start date
select * from t8jg into @data(ls_t8jg_next)
  bypassing buffer
  where bukrs = @is_t8jg_new-bukrs
    and vname = @is_t8jg_new-vname
    and etype = @is_t8jg_new-etype
    and fdate < @is_t8jg_new-fdate
  order by fdate descending.
  lv_date_next = ls_t8jg_next-fdate.
  translate lv_date_next using '09182736455463728190'.
  exit.
endselect.
if ls_t8jg_next is initial or
  ms_progpars-budat < lv_date_next.

```

```
        lv_date = ms_progpars-budat.
    else.
        try.
            lv_date = cl_bs_period_toolset_basics=>subtract_days_from_date( iv_date =
lv_date_next
                                                    iv_days =
1 ).
            catch cx_bs_period_toolset_basics.
                "Do nothing
            endtry.
        endif.
    call function 'DATE_TO_PERIOD_CONVERT'
        exporting
            i_date      = lv_date
            i_periv      = ms_settings-s_t001-periv
        importing
            e_buper      = lv_poper
            e_gjahr      = lv_year
        exceptions
            input_false   = 1
            t009_notfound = 2
            t009b_notfound = 3
            others        = 4.
    if sy-subrc = 0 and
        lv_year is not initial and
        lv_poper is not initial.
        cv_toyear = lv_year.
        cv_toper  = lv_poper.
        ms_progpars-to_year  = lv_year.
        ms_progpars-to_period = lv_poper.
        lv_date_init = abap_true.
    endif.
endif.
if lv_date_init = abap_true.
    lv_from = cv_frper && | / | && cv_fryear.
    lv_to   = cv_toper && | / | && cv_toyear.
    message i240(g5) with lv_from lv_to.
endif.
endmethod.
```

CHECK_AUTHORITY

Description: Check the authority

Inst. Method

```
method check_authority.
    data: lv_process_code type t8jpa-jv_proca,
          lv_activity     type tact-actvt.
    if ms_progpars-farm_in_out = abap_true.
        lv_process_code = 'FARM'.
    else.
        lv_process_code = 'EQUITY-ADJ'.
    endif.
    if ms_progpars-test is initial.
        lv_activity = '16'.
```

```
else.  
    lv_activity = '48'.  
endif.  
call function 'JV_AUTHORITY_CHECK_PROCESS'  
    exporting  
        process_code = lv_process_code  
        activity      = lv_activity  
        bukrs         = ms_progpars-bukrs.  
endmethod.
```

CHECK_COMPANY_CODE

Description: Check the company code
Inst. Method

```
method check_company_code.  
    ms_settings-bukrs = ms_progpars-bukrs.  
    select single * from t001  
        into ms_settings-s_t001  
        where bukrs = ms_progpars-bukrs.  
    if sy-subrc <> 0 or  
        ms_settings-s_t001-xjvaa <> 'X'.  
        message e234(g5) with ms_progpars-bukrs.  
    endif.  
    select single * from t8jz  
        into ms_settings-s_t8jz  
        where bukrs = ms_progpars-bukrs.  
    if sy-subrc <> 0.  
        message e234(g5) with ms_progpars-bukrs.  
    endif.  
endmethod.
```

CHECK_EQUITY_GROUP

Description: Check the equity group
Inst. Method

Changing parameter

CS_T8JG_NEW TYPE T8JG
CS_T8JG_OLD TYPE T8JG

```
method check_equity_group.  
    data: ls_t8jg      type t8jg,  
          lv_same_venture type abap_bool,  
          lv_same_type   type abap_bool,  
          lv_same_curr   type abap_bool.  
*   Get old equity group  
    select * from t8jg into ls_t8jg  
        where bukrs = ms_progpars-bukrs  
        and vname = ms_progpars-vname  
        and egrup = ms_progpars-eqold.  
    cs_t8jg_old = ls_t8jg.  
    exit.  
endselect.  
if sy-subrc <> 0.  
    message e235(g5) with ms_progpars-eqold ms_progpars-vname ms_progpars-bukrs.
```

```
elseif cs_t8jg_old-egroupact <> 'X'.
    message e117(gj) with ms_progpars-vname ms_progpars-eqold.
endif.
* Get new equity group
select * from t8jg into ls_t8jg
    where bukrs = ms_progpars-bukrs
    and vname = ms_progpars-vname
    and egrup = ms_progpars-eqnew.
    cs_t8jg_new = ls_t8jg.
    exit.
endselect.
if sy-subrc <> 0.
    message e235(g5) with ms_progpars-eqnew ms_progpars-vname ms_progpars-bukrs.
elseif cs_t8jg_new-egroupact <> 'X'.
    message e117(gj) with ms_progpars-vname ms_progpars-eqnew.
endif.
* Check that equity groups are assigned to the same equity type
if cs_t8jg_old-etype <> cs_t8jg_new-etype.
    message w236(g5) with ms_progpars-eqold ms_progpars-eqnew.
endif.
* Check that equity groups are different
if cs_t8jg_old-egrup = cs_t8jg_new-egrup.
    message e237(g5).
endif.
* Check that the equity groups are connected to each other
if cs_t8jg_old-fdate > cs_t8jg_new-fdate.
    select * from t8jg into ls_t8jg
        where bukrs = ms_progpars-bukrs
        and vname = ms_progpars-vname
        and etype = cs_t8jg_old-etype
        and fdate > cs_t8jg_new-fdate
        and fdate < cs_t8jg_old-fdate.

    exit.
endselect.
else.
    select * from t8jg into ls_t8jg
        where bukrs = ms_progpars-bukrs
        and vname = ms_progpars-vname
        and etype = cs_t8jg_old-etype
        and fdate < cs_t8jg_new-fdate
        and fdate > cs_t8jg_old-fdate.

    exit.
endselect.
endif.
if sy-subrc = 0.
    message w239(g5) with ls_t8jg-egrup ms_progpars-eqold ms_progpars-eqnew.
endif.
* Check if the equity group characteristics match
call function 'COMPARE_2_EQUITY_GROUPS'
    exporting
        bukrs      = ms_progpars-bukrs
        vname      = ms_progpars-vname
        eg_old     = ms_progpars-eqold
        eg_new     = ms_progpars-eqnew
```

```
importing
  same_venture = lv_same_venture
  same_type    = lv_same_type
  equal_curr   = lv_same_curr
exceptions
  not_found    = 1
  others       = 2.
if sy-subrc <> 0.
  return.
endif.
if lv_same_venture is initial.
*   EGs do not belong to same venture
  message e566(g4) with ms_progpars-eqold ms_progpars-eqnew.
endif.
if lv_same_type is initial.
*   EGs do not have the same equity-type
  message w567(g4) with ms_progpars-eqold ms_progpars-eqnew.
endif.
if lv_same_curr is initial.
*   EGs do not have the same funding currency
  message w565(g4) with ms_progpars-eqold ms_progpars-eqnew.
endif.
endmethod.
```

CHECK_FOR_PREVIOUS_CHANGES

Description: Check for previous equity changes

Inst. Method

Importing parameter

```
IS_ACDOCA_CHECK TYPE GTY_S_ACDOCA_CHECK
IV_TABIX_CHECK TYPE ANY
```

Changing parameter

```
CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
CV_ALREADY_CHANGED TYPE ABAP_BOOL
```

```
method check_for_previous_changes.
  data: ls_acdoca_rev type gty_s_acdoca_check,
        ls_t8j_jvec type t8j_jvec,
        lv_tabix_start type i.
  field-symbols: <fs_acdoca_check> type gty_s_acdoca_check.
  clear: cv_already_changed.
  ls_acdoca_rev = is_acdoca_check.
*   Reverse amounts
  multiply ls_acdoca_rev-wsl by -1.
  multiply ls_acdoca_rev-hsl by -1.
  multiply ls_acdoca_rev-ksl by -1.
  multiply ls_acdoca_rev-osl by -1.
  multiply ls_acdoca_rev-vsl by -1.
  multiply ls_acdoca_rev-bsl by -1.
  multiply ls_acdoca_rev-csl by -1.
  multiply ls_acdoca_rev-dsl by -1.
  multiply ls_acdoca_rev-esl by -1.
  multiply ls_acdoca_rev-fsl by -1.
  multiply ls_acdoca_rev-gsl by -1.
```

```

lv_tabix_start = iv_tabix_check + 1.
loop at ct_acdoca_check assigning <fs_acdoca_check>
    from lv_tabix_start.
    if <fs_acdoca_check>-src_awref <> ls_acdoca_rev-src_awref or
       <fs_acdoca_check>-src_awitem <> ls_acdoca_rev-src_awitem or
       <fs_acdoca_check>-racct <> ls_acdoca_rev-racct or
       <fs_acdoca_check>-vname <> ls_acdoca_rev-vname or
       <fs_acdoca_check>-egrup <> ls_acdoca_rev-egrup or
       <fs_acdoca_check>-btype <> ls_acdoca_rev-btype or
       <fs_acdoca_check>-vptnr <> ls_acdoca_rev-vptnr or
       <fs_acdoca_check>-prctr <> ls_acdoca_rev-prctr or
       <fs_acdoca_check>-rcntr <> ls_acdoca_rev-rcntr or
       <fs_acdoca_check>-aufnr <> ls_acdoca_rev-aufnr or
       <fs_acdoca_check>-ps_psp_pnr <> ls_acdoca_rev-ps_psp_pnr or
       <fs_acdoca_check>-nplnr <> ls_acdoca_rev-nplnr or
       <fs_acdoca_check>-nplnr_vorgn <> ls_acdoca_rev-nplnr_vorgn.
        exit.
    endif.
    if <fs_acdoca_check>-already_changed = abap_true.
        continue.
    endif.
    * If the amounts match, a reversal document was posted in a
    * previous run, that is, the equity group change was already made
    if <fs_acdoca_check>-wsl = ls_acdoca_rev-wsl and
       <fs_acdoca_check>-hsl = ls_acdoca_rev-hsl and
       <fs_acdoca_check>-ksl = ls_acdoca_rev-ksl and
       <fs_acdoca_check>-osl = ls_acdoca_rev-osl and
       <fs_acdoca_check>-vsl = ls_acdoca_rev-vsl and
       <fs_acdoca_check>-bsl = ls_acdoca_rev-bsl and
       <fs_acdoca_check>-csl = ls_acdoca_rev-csl and
       <fs_acdoca_check>-dsl = ls_acdoca_rev-dsl and
       <fs_acdoca_check>-esl = ls_acdoca_rev-esl and
       <fs_acdoca_check>-fsl = ls_acdoca_rev-fsl and
       <fs_acdoca_check>-gsl = ls_acdoca_rev-gsl.
    * Set the ALREADY_CHANGED flag to avoid re-processing of this line
    <fs_acdoca_check>-already_changed = abap_true.
    * Return ABAP_TRUE to indicate that no posting is required
    cv_already_changed = abap_true.
    exit.
    endif.
endloop.
endmethod.

```

CHECK_INTERCOMPANY_VENTURE

Description: Check the intercompany venture

Inst. Method

```

method check_intercompany_venture.
    data: lt_t8ji type table of t8ji,
          ls_t8ji type t8ji.
    select * from t8ji
        into table lt_t8ji
        where bukrs = ms_progpars-bukrs
        and vname = ms_progpars-vname

```

```

        and ( egrup = ms_progpars-eqold or
              egrup = ms_progpars-eqnew ).
if sy-subrc = 0.
  loop at lt_t8ji into ls_t8ji.
    call function 'JV_VENTURE_ACTIVE_CHECK'
      exporting
        bukrs      = ls_t8ji-bukrs
        vname      = ls_t8ji-vname
      exceptions
        not_found  = 1
        not_activ  = 2
        error_message = 3
        others     = 4.
  case sy-subrc.
    when 0.
      *      Check if the inter-company equity group associated to
      *      the new equity group is active
      call function 'GJ_EGROUP_ACTIV_CHECK'
        exporting
          bukrs      = ls_t8ji-intcocc
          vname      = ls_t8ji-intcomvent
          egrup      = ls_t8ji-intcompegg
        exceptions
          no_activ_egrup = 1
          error_message  = 2
          others         = 4.
      if sy-subrc <> 0.
        message e117(gj) with ls_t8ji-intcomvent
                               ls_t8ji-intcompegg.
      endif.
    when 1.
      message e220(gj) with ls_t8ji-intcomvent
                           ls_t8ji-intcocc.
    when 2.
      message e349(gj) with ls_t8ji-intcomvent
                           ls_t8ji-intcocc
                           ls_t8ji-bukrs
                           ls_t8ji-vname .
  endcase.
endloop.
endif.
endmethod.
```

CHECK_LINE_ITEMS

Description: Check the ACDOCA line items
Inst. Method

Importing parameter

- IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))
- IV_VNAME_NEW TYPE JV_NAME (Joint venture)
- IV_EGRUP_NEW TYPE JV_EGROUP (Equity group)

Changing parameter

- CT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
- CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)

```
method check_line_items.
  data: lv_tabix_check      type sy-tabix,
        ls_acdoca_check    type gty_s_acdoca_check,
        lv_already_changed type abap_bool.
*   Sort by reference document and accounting data
  sort ct_acdoca_check by src_awref
                        src_awitem
                        racct
                        vname
                        egrup
                        btype
                        vptnr
                        prctr
                        rcntr
                        aufnr
                        ps_psp_pnr
                        nplnr
                        nplnr_vorgn
                        timestamp
                        belnr
                        buzei
                        docln.
  loop at ct_acdoca_check into ls_acdoca_check.
    lv_tabix_check = sy-tabix.
*   Do not process items with zero amounts in all currencies
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and
       ls_acdoca_check-gsl = 0.
      continue.
    endif.
*   The line has been marked as equity change reversal line and
*   can therefore be skipped.
    if ls_acdoca_check-already_changed = abap_true.
      continue.
    endif.
*   Do not process reversal lines of documents posted by previous runs
    if ls_acdoca_check-jvactivity = 'E1'.
      continue.
    endif.
*   Check if the item was already handled by a previous run
    check_for_previous_changes( exporting
                                iv_tabix_check   = lv_tabix_check
                                is_acdoca_check  = ls_acdoca_check
                                changing
                                ct_acdoca_check   = ct_acdoca_check
                                cv_already_changed = lv_already_changed ).
```

```

        if lv_already_changed = abap_true.
            continue.
        endif.
*       Make the equity change posting
        post_change_document( exporting
                                iv_jvfunc      = iv_jvfunc
                                iv_vname_new   = iv_vname_new
                                iv_egrup_new    = iv_egrup_new
                                is_acdoca_check = ls_acdoca_check
                                changing
                                ct_acdoca_cb    = ct_acdoca_cb ).

    endloop.
endmethod.
```

CHECK_PARAMETERS

Description: Check the parameters entered by the user
Inst. Method

Changing parameter

```

CV_FRDATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
CV_TODATE TYPE SYST_DATUM (ABAP system field: Current date of application server)
CV_FRPER TYPE MONAT (Fiscal Period)
CV_FRYEAR TYPE GJAHR (Fiscal Year)
CV_TOPER TYPE MONAT (Fiscal Period)
CV_TOYEAR TYPE GJAHR (Fiscal Year)
CV_ITD TYPE ABAP_BOOL (Inception to Date)
```

```

method check_parameters.
    data: ls_t8jg_old type t8jg,
          ls_t8jg_new type t8jg.
    check_company_code( ).
    check_venture( ).
    check_equity_group( changing
                        cs_t8jg_old = ls_t8jg_old
                        cs_t8jg_new = ls_t8jg_new ).
    check_intercompany_venture( ).
    check_posting_date( ).
    if ms_progpars-farm_in_out = abap_true.
        check_adjustment_period( exporting
                                    is_t8jg_old = ls_t8jg_old
                                    is_t8jg_new = ls_t8jg_new
                                    changing
                                    cv_frper  = cv_frper
                                    cv_fryear = cv_fryear
                                    cv_toper  = cv_toper
                                    cv_toyear = cv_toyear
                                    cv_itd    = cv_itd ).
    else.
        check_adjustment_date( exporting
                                    is_t8jg_old = ls_t8jg_old
                                    is_t8jg_new = ls_t8jg_new
                                    changing
                                    cv_frdate = cv_frdate
                                    cv_todate = cv_todate ).
    endif.
endmethod.
```

```
endif.  
check_settlement_account( ).  
endmethod.
```

CHECK_POSTING_DATE

Description: Check the posting date

Inst. Method

```
method check_posting_date.  
  data lv_poper type periods-buper.  
  * Create list of allowed periods with start date and end date  
  * (special periods are not allowed)  
  call function 'G_PERIODS_OF_YEAR_GET'  
    exporting  
      variant          = ms_settings-s_t001-periv  
      year             = ms_progpars-year  
    importing  
      last_normal_period = ms_settings-last_period  
  tables  
    i_periods          = ms_settings-t_periods  
  exceptions  
    variant_not_defined = 1  
    year_not_defined    = 2.  
  if sy-subrc <> 0.  
    message e746(gj) with ms_settings-s_t001-periv.  
  endif.  
  * Check if posting period is allowed  
  lv_poper = ms_progpars-period.  
  loop at ms_settings-t_periods into data(ls_periods)  
    where buper = lv_poper.  
  
    exit.  
  endloop.  
  if sy-subrc <> 0.  
    message e674(gj).  
  endif.  
  * Check if posting date is filled and if so, if it is allowed  
  if ms_progpars-budat is initial.  
    ms_progpars-budat = ls_periods-datbi.  
  else.  
    if ms_progpars-budat < ls_periods-datab or  
       ms_progpars-budat > ls_periods-datbi.  
      message e682(gj) with ms_progpars-budat.  
    endif.  
  endif.  
  "Get the fiscal year for postings  
  call function 'DETERMINE_PERIOD'  
    exporting  
      date          = ms_progpars-budat  
      version       = ms_settings-s_t001-periv  
    importing  
      year          = ms_settings-gjahr_p  
  exceptions  
    period_in_not_valid = 1  
    period_not_assigned = 2
```

```
        version_undefined    = 3
        error_message        = 4
        others                = 8.
if sy-subrc <> 0.
    message e108(glofaa_gb) with ms_settings-s_t001-periv ms_progpars-budat.
endif.
endmethod.
```

CHECK_RECID

Description: Check the recovery indicator

Inst. Method

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)

```
method check_recid.
*   For each relevant RI ...
    loop at ms_settings-t_t8jj into data(ls_t8jj).
        check ms_settings-s_t8j0a-recindind is not initial.
        loop at ms_settings-t_t8j0g into data(ls_t8j0g)
            where jvfunc    = iv_jvfunc
            and itemtype    = 'F1'
            and recid       = ls_t8jj-recid.

            exit.
        endloop.
        if sy-subrc <> 0    or
            ls_t8j0g-debreid is initial.
            message e764(g5) with iv_jvfunc 'F1' ls_t8jj-recid into mv_message_text.
            save_sy_message( ).
        endif.
        loop at ms_settings-t_t8j0g into ls_t8j0g
            where jvfunc    = iv_jvfunc
            and itemtype    = 'F2'
            and recid       = ls_t8jj-recid.

            exit.
        endloop.
        if sy-subrc <> 0    or
            ls_t8j0g-debreid is initial.
            message e764(g5) with iv_jvfunc 'F2' ls_t8jj-recid into mv_message_text.
            save_sy_message( ).
        endif.
        loop at ms_settings-t_t8j0g into ls_t8j0g
            where jvfunc    = iv_jvfunc
            and itemtype    = 'F3'
            and recid       = ls_t8jj-recid.

            exit.
        endloop.
        if sy-subrc <> 0    or
            ls_t8j0g-debreid is initial.
            message e764(g5) with iv_jvfunc 'F3' ls_t8jj-recid into mv_message_text.
            save_sy_message( ).
        endif.
    endloop.
endmethod.
```

CHECK_SETTLEMENT_ACCOUNT

Description: Check the settlement account

Inst. Method

```
method check_settlement_account.  
  data: ls_ska1 type ska1,  
        ls_t001 type t001.  
  if ms_progpars-farm_in_out <> abap_true.  
    return.  
  endif.  
  if ms_progpars-cashc2 <> abap_true.  
    return.  
  endif.  
  if ms_progpars-settlement_acc_cc2 is initial.  
    message e076(g4).  
  endif.  
  select single * from t001 into ls_t001  
              where bukrs = ms_progpars-bukrs.  
  if sy-subrc = 0.  
    select single * from ska1 into ls_ska1  
              where saknr = ms_progpars-settlement_acc_cc2  
              and ktopl = ls_t001-ktopl.  
    if sy-subrc <> 0.  
      clear ls_ska1.  
    endif.  
  endif.  
  if ls_ska1 is initial.  
    message e077(g4) with ms_progpars-settlement_acc_cc2.  
  endif.  
endmethod.
```

CHECK_SHARES_CC1

Description: Check the partner shares for cash call 1

Inst. Method

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```
method check_shares_cc1.  
  data: ls_diff_share type jva_diff_share,  
        ls_shares_new type jva_partner_shares.  
  refresh ms_settings-t_diff_share.  
  sort ms_settings-t_shares_old by partn.  
  * Build table with partners for which an equity change should be executed  
  * Only include partners that are both in the old and in the new equity group  
  loop at ms_settings-t_shares_old into data(ls_shares_old)  
    where intcocd is initial.  
    clear ls_shares_new.  
    read table ms_settings-t_shares_new into ls_shares_new  
        with key partn = ls_shares_old-partn.  
  * Prtner in old equity group is not in new equity group  
  if ls_shares_new is initial.  
    message i799(g5) with text-nop ls_shares_old-partn ms_progpars-eqold
```

```

        into mv_message_text.
    save_sy_message( ).
    continue.
endif.
clear ls_diff_share.
ls_diff_share-eg_old      = ms_progpars-egold.
ls_diff_share-partn_old   = ls_shares_old-partn.
ls_diff_share-opflag      = ls_shares_old-opflag.
ls_diff_share-eqshare_old = ls_shares_old-eqshare.
ls_diff_share-intcocd_old = ls_shares_old-intcocd.
ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
ls_diff_share-intcompegp_old = ls_shares_old-intcompegp.
ls_diff_share-partn_new   = ls_shares_new-partn.
ls_diff_share-eqshare_new = ls_shares_new-eqshare.
ls_diff_share-intcocd_new = ls_shares_new-intcocd.
ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
ls_diff_share-intcompegp_new = ls_shares_new-intcompegp.
append ls_diff_share to ms_settings-t_diff_share.
endloop.
if ms_settings-t_diff_share[] is initial.
    cv_no_differences = abap_true.
endif.
endmethod.

```

CHECK_SHARES_CC1_INTCO

Description: Check the partner shares for cash call 1

Inst. Method

Changing parameter

CV_NO_DIFFERENCES TYPE ABAP_BOOL

```

method check_shares_cc1_intco.
    data: ls_diff_share type jva_diff_share,
          ls_shares_new type jva_partner_shares.
    refresh ms_settings-t_diff_share.
*   Build table with equity share difference for
*   old EGs with intercompany partner
    sort ms_settings-t_shares_old by partn.
    loop at ms_settings-t_shares_old into data(ls_shares_old)
        where not intcocd is initial.

        clear ls_shares_new.
        read table ms_settings-t_shares_new into ls_shares_new
            with key partn = ls_shares_old-partn.
*       Intercompany partner of old EG is no longer in new EG
        if ls_shares_new is initial.
            message e760(g5) with ls_shares_old-partn into mv_message_text.
            save_sy_message( ).
            continue.
        endif.
*       It is mandatory, that the partner of old and new EG
*       belong to the same intercompany and same intercompany venture !!
        if ls_shares_new-intcocd <> ls_shares_old-intcocd or
            ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
            message e799(g5) with text-iiiv

```

```

                ms_progpars-eqold
                ls_shares_old-intcocd
                ls_shares_old-intrcovent
            into mv_message_text.
        save_sy_message( ).
        continue.
    endif.
    if ls_shares_new-eqshare <> ls_shares_old-eqshare.
        ls_diff_share-eg_old      = ms_progpars-eqold.
        ls_diff_share-partn_old   = ls_shares_old-partn.
        ls_diff_share-opflag      = ls_shares_old-opflag.
        ls_diff_share-eqshare_old = ls_shares_old-eqshare.
        ls_diff_share-intcocd_old = ls_shares_old-intcocd.
        ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
        ls_diff_share-intcompeggp_old = ls_shares_old-intcompeggp.
        ls_diff_share-partn_new   = ls_shares_new-partn.
        ls_diff_share-eqshare_new = ls_shares_new-eqshare.
        ls_diff_share-intcocd_new = ls_shares_new-intcocd.
        ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
        ls_diff_share-intcompeggp_new = ls_shares_new-intcompeggp.
        append ls_diff_share to ms_settings-t_diff_share.
    endif.
endloop.
*   If the shares of the partners are identical, issue an information message
    if ms_settings-t_diff_share[] is initial.
        cv_no_differences = abap_true.
    endif.
endmethod.

```

CHECK_SHARES_CC2

Description: Check the partner shares for cash call 2

Inst. Method

Changing parameter

```

CV_NO_DIFFERENCES TYPE ABAP_BOOL

method check_shares_cc2.
    data: ls_diff_share type jva_diff_share,
          ls_shares_new type jva_partner_shares.
    clear cv_no_differences.
    refresh ms_settings-t_diff_share.
*   Build table with equity share difference
    loop at ms_settings-t_shares_old into data(ls_shares_old).
        clear ls_shares_new.
        read table ms_settings-t_shares_new into ls_shares_new
            with key partn = ls_shares_old-partn
                  opflag = ls_shares_old-opflag.
*
*   Partner of old EG is not in new EG
        if ls_shares_new is initial.
            message i760(g5) with ls_shares_old-partn into mv_message_text.
            save_sy_message( ).
        endif.
*   It is mandatory, that the partner of old and new EG
*   belong to the same intercompany and same intercompany venture !!
    endloop.
endmethod.

```

```

if ls_shares_new-intcocd <> ls_shares_old-intcocd or
   ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
   message e799(g5) with text-iiv
       ms_progpars-eqold
       ls_shares_old-intcocd
       ls_shares_old-intrcovent
   into mv_message_text.
   save_sy_message( ).
   continue.
endif.
clear ls_diff_share.
ls_diff_share-eg_old      = ms_progpars-eqold.
ls_diff_share-partn_old   = ls_shares_old-partn.
ls_diff_share-opflag      = ls_shares_old-opflag.
ls_diff_share-eqshare_old = ls_shares_old-eqshare.
ls_diff_share-intcocd_old = ls_shares_old-intcocd.
ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
ls_diff_share-intcompepgp_old = ls_shares_old-intcompepgp.
ls_diff_share-partn_new   = ls_shares_new-partn.
ls_diff_share-eqshare_new = ls_shares_new-eqshare.
ls_diff_share-intcocd_new = ls_shares_new-intcocd.
ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
ls_diff_share-intcompepgp_new = ls_shares_new-intcompepgp.
append ls_diff_share to ms_settings-t_diff_share.
endloop.
* Check, if a new partner was introduced
* Build table with equity share difference
loop at ms_settings-t_shares_new into ls_shares_new.
* Check if the partner of the new EG was already in the old EG.
* If yes, go to the next item
clear ls_shares_old.
read table ms_settings-t_shares_old into ls_shares_old
      with key partn = ls_shares_new-partn
      opflag = ls_shares_new-opflag.

if sy-subrc = 0.
   continue.
endif.
* Add the new partner
clear ls_diff_share.
ls_diff_share-eg_old      = ms_progpars-eqold.
ls_diff_share-partn_new   = ls_shares_new-partn.
ls_diff_share-eqshare_new = ls_shares_new-eqshare.
ls_diff_share-intcocd_new = ls_shares_new-intcocd.
ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
ls_diff_share-intcompepgp_new = ls_shares_new-intcompepgp.
append ls_diff_share to ms_settings-t_diff_share.
endloop.
* If the shares of the partners are identical, issue an information message
if ms_settings-t_diff_share[] is initial.
   cv_no_differences = abap_true.
endif.
endmethod.

```

CHECK_SHARES_CC2_INTCO

Description: Check the partner shares for intercompany cash call

Inst. Method

Changing parameter

```
CV_NO_DIFFERENCES TYPE ABAP_BOOL

method check_shares_cc2_intco.
*   Build table with equity share difference for
*   old EGs with intercompany partner
data: ls_diff_share type jva_diff_share,
      lv_diff_exists type abap_bool.
refresh ms_settings-t_diff_share_intco.
sort ms_settings-t_shares_old by partn.
loop at ms_settings-t_shares_old into data(ls_shares_old)
      where not intcocd is initial.
      loop at ms_settings-t_shares_new into data(ls_shares_new)
            where partn = ls_shares_old-partn
              and opflag = ls_shares_old-opflag.

            exit.
      endloop.
*   Intercompany partner of old EG is no longer in new EG
if sy-subrc <> 0.
  message i760(g5) with ls_shares_old-partn into mv_message_text.
  save_sy_message( ).
  ls_shares_new = ls_shares_old.
  clear ls_shares_new-eqshare.
endif.
*   It is mandatory, that the partner of old and new EG
*   belong to the same intercompany and same intercompany venture !!
if ls_shares_new-intcocd <> ls_shares_old-intcocd or
   ls_shares_new-intrcovent <> ls_shares_old-intrcovent.
  message e799(g5) with text-iiiv ms_progpars-eqold ls_shares_old-intcocd
ls_shares_old-intrcovent into mv_message_text.
  save_sy_message( ).
  exit.
endif.
lv_diff_exists = abap_true.
ls_diff_share-eg_old      = ms_progpars-eqold.
ls_diff_share-partn_old   = ls_shares_old-partn.
ls_diff_share-opflag      = ls_shares_old-opflag.
ls_diff_share-eqshare_old = ls_shares_old-eqshare.
ls_diff_share-intcocd_old = ls_shares_old-intcocd.
ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
ls_diff_share-intcompepp_old = ls_shares_old-intcompepp.
ls_diff_share-partn_new   = ls_shares_new-partn.
ls_diff_share-eqshare_new = ls_shares_new-eqshare.
ls_diff_share-intcocd_new = ls_shares_new-intcocd.
ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
ls_diff_share-intcompepp_new = ls_shares_new-intcompepp.
append ls_diff_share to ms_settings-t_diff_share_intco.
endloop.
if lv_diff_exists <> abap_true.
```

```

        cv_no_differences = abap_true.
    endif.
endmethod.

```

CHECK_SHARES_INTCO_REVERSAL

Description: Check the partner shares

Inst. Method

Changing parameter

CV_NO_INTCO_PARTNER TYPE ABAP_BOOL

```

method check_shares_intco_reversal.
    data: lv_diff_share      type c,
          lv_no_intco_partner_egold type c,
          lv_no_intco_partner_egnew type c,
          ls_diff_share      type jva_diff_share,
          ls_diff_share_old   type jva_partner_share,
          ls_diff_share_new   type jva_partner_share.
    refresh: ms_settings-t_diff_share_old,
             ms_settings-t_diff_share_new.
*   check that the old EG has an Intercompany partner
    loop at ms_settings-t_shares_old into data(ls_shares_old)
        where not intcocd is initial.
        loop at ms_settings-t_shares_new into data(ls_shares_new)
            where partn      = ls_shares_old-partn
            and intcocd      = ls_shares_old-intcocd
            and intrcovent =
ls_shares_old-intrcovent.
            exit.
        endloop.
*   Inercompany partner of old EG is no longer in new EG
    if sy-subrc <> 0.
        message e760(g5) with ls_shares_old-partn into mv_message_text.
        save_sy_message( ).
    else.
        if ls_shares_new-eqshare <> ls_shares_old-eqshare.
            lv_diff_share = 'X'.
            ls_diff_share-partn_old      = ls_shares_old-partn.
            ls_diff_share-opflag         = ls_shares_old-opflag.
            ls_diff_share-eqshare_old    = ls_shares_old-eqshare.
            ls_diff_share-intcocd_old    = ls_shares_old-intcocd.
            ls_diff_share-intrcovent_old = ls_shares_old-intrcovent.
            ls_diff_share-intcompepgp_old = ls_shares_old-intcompepgp.
            ls_diff_share-partn_new      = ls_shares_new-partn.
            ls_diff_share-eqshare_new    = ls_shares_new-eqshare.
            ls_diff_share-intcocd_new    = ls_shares_new-intcocd.
            ls_diff_share-intrcovent_new = ls_shares_new-intrcovent.
            ls_diff_share-intcompepgp_new = ls_shares_new-intcompepgp.
            append ls_diff_share to ms_settings-t_diff_share.
            ls_diff_share_new-partn      = ls_shares_new-partn.
            ls_diff_share_new-opflag     = ls_shares_new-opflag.
            ls_diff_share_new-eqshare    = ls_shares_new-eqshare.
            ls_diff_share_new-intcocd    = ls_shares_new-intcocd.
            ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.

```

```

        ls_diff_share_new-intcompepp = ls_shares_new-intcompepp.
        append ls_diff_share_new to ms_settings-t_diff_share_new.
        ls_diff_share_old-partn      = ls_shares_old-partn.
        ls_diff_share_old-opflag     = ls_shares_old-opflag.
        ls_diff_share_old-eqshare    = ls_shares_old-eqshare.
        ls_diff_share_old-intcocd    = ls_shares_old-intcocd.
        ls_diff_share_old-intrcovent = ls_shares_old-intrcovent.
        ls_diff_share_old-intcompepp = ls_shares_old-intcompepp.
        append ls_diff_share_old to ms_settings-t_diff_share_old.
    endif.
endif.
endloop.
* Old EG has no intercomp-partner
if sy-subrc <> 0.
    lv_no_intco_partner_egold = 'X'.
endif.
* Check that the new EG has an Intercompany partner
loop at ms_settings-t_shares_new into ls_shares_new
    where not intcocd is initial.
    loop at ms_settings-t_shares_old into ls_shares_old
        where partn      = ls_shares_new-partn
        and intcocd      = ls_shares_new-intcocd
        and intrcovent =
ls_shares_new-intrcovent.
        exit.
    endloop.
* Intercompany partner of new EG is no not in old EG
if sy-subrc <> 0.
    message e762(g5) with ls_shares_new-partn into mv_message_text.
    save_sy_message( ).
endif.
endloop.
* New EG has no intercomp-partner
if sy-subrc <> 0.
    lv_no_intco_partner_egnew = 'X'.
endif.
if lv_no_intco_partner_egold = 'X' and
   lv_no_intco_partner_egnew = 'X'.
    cv_no_intco_partner = 'X'.
    return.
endif.
* Check that at least one of the shares is different
if lv_diff_share is initial.
    cv_no_intco_partner = 'X'.
    return.
endif.
** Check that a settlement account is defined
* loop at ms_settings-t_diff_share into ls_diff_share
*     where not intcocd_new is initial.
*
*     loop at mt_intco_settl_acct into data(ls_intco_settl_acct)
*         where intcocd = ls_diff_share-intcocd_new.
*     exit.
* endloop.

```

```
*      if sy-subrc <> 0 or ls_intco_settl_acct-racct is initial.
*      if ms_progpars-settlement_account_intco is initial.
*          message e783(G5) with ls_diff_share-intcocd_new into mv_message_text.
*          save_message( iv_type = 'E'
*                        iv_class = 'G5'
*                        iv_number = '783'
*                        iv_var1 = ls_diff_share-intcocd_new
*                        iv_var2 = space
*                        iv_var3 = space
*                        iv_var4 = space ).
*      endif.
*
*  endloop.
endmethod.
```

CHECK_VENTURE

Description: Check the venture
Inst. Method

```
method check_venture.
    select single * from t8jv into ms_settings-s_t8jv
                                where bukrs = ms_progpars-bukrs
                                and vname = ms_progpars-vname.

    if sy-subrc <> 0.
        message e232(g5) with ms_progpars-vname ms_progpars-bukrs.
    elseif ms_settings-s_t8jv-vtype = '2'
        or ms_settings-s_t8jv-vtype = '5'.
        message e243(g5) with ms_progpars-vname.
    endif.
endmethod.
```

FILL_ACCCR

Description: Add the ACCCR structure for an FI doc line
Inst. Method

Importing parameter

- IS_ACCIT TYPE ACCIT
- IS_ACDOCA TYPE ACDOCA (Universal Journal Entry Line Items)
- IV_RWCUR TYPE ACDOCA-RWCUR
- IS_CURR_INFO TYPE FINSS_CMP_CURR_INFO (Derived Company Code Currency Information)

Changing parameter

```
CT_ACCCR TYPE ACCCR_T

method fill_acccr.
    data: ls_acccr type acccr.
    ls_acccr-mandt = is_accit-mandt.
    ls_acccr-awtyp = is_accit-awtyp.
    ls_acccr-posnr = is_accit-posnr.
* Transaction currency
    ls_acccr-curtp = '00'.
    ls_acccr-waers = iv_rwcur.
    ls_acccr-wrbtr = is_acdoca-wsl.
    append ls_acccr to ct_acccr.
* 1st local currency
```

```
ls_accr-curtp = is_curr_info-curtype1.  
ls_accr-waers = is_curr_info-waers1.  
ls_accr-wrbtr = is_acdoca-hsl.  
append ls_accr to ct_accr.  
* 2nd local currency  
if not is_curr_info-curtype2 is initial.  
  ls_accr-curtp = is_curr_info-curtype2.  
  ls_accr-waers = is_curr_info-waers2.  
  ls_accr-wrbtr = is_acdoca-ksl.  
  append ls_accr to ct_accr.  
endif.  
* 3rd local currency  
if not is_curr_info-curtype3 is initial.  
  ls_accr-curtp = is_curr_info-curtype3.  
  ls_accr-waers = is_curr_info-waers3.  
  ls_accr-wrbtr = is_acdoca-osl.  
  append ls_accr to ct_accr.  
endif.  
* 4th local currency  
if not is_curr_info-curtype4 is initial.  
  ls_accr-curtp = is_curr_info-curtype4.  
  ls_accr-waers = is_curr_info-waers4.  
  ls_accr-wrbtr = is_acdoca-vsl.  
  append ls_accr to ct_accr.  
endif.  
* 5th local currency  
if not is_curr_info-curtype5 is initial.  
  ls_accr-curtp = is_curr_info-curtype5.  
  ls_accr-waers = is_curr_info-waers5.  
  ls_accr-wrbtr = is_acdoca-bsl.  
  append ls_accr to ct_accr.  
endif.  
* 6th local currency  
if not is_curr_info-curtype6 is initial.  
  ls_accr-curtp = is_curr_info-curtype6.  
  ls_accr-waers = is_curr_info-waers6.  
  ls_accr-wrbtr = is_acdoca-csl.  
  append ls_accr to ct_accr.  
endif.  
* 7th local currency  
if not is_curr_info-curtype7 is initial.  
  ls_accr-curtp = is_curr_info-curtype7.  
  ls_accr-waers = is_curr_info-waers7.  
  ls_accr-wrbtr = is_acdoca-dsl.  
  append ls_accr to ct_accr.  
endif.  
* 8th local currency  
if not is_curr_info-curtype8 is initial.  
  ls_accr-curtp = is_curr_info-curtype8.  
  ls_accr-waers = is_curr_info-waers8.  
  ls_accr-wrbtr = is_acdoca-esl.  
  append ls_accr to ct_accr.  
endif.  
* 9th local currency
```

```
    if not is_curr_info-curtype9 is initial.  
        ls_accr-curtp = is_curr_info-curtype9.  
        ls_accr-waers = is_curr_info-waers9.  
        ls_accr-wrbtr = is_acdoca-fsl.  
        append ls_accr to ct_accr.  
    endif.  
* 10th local currency  
    if not is_curr_info-curtype10 is initial.  
        ls_accr-curtp = is_curr_info-curtype10.  
        ls_accr-waers = is_curr_info-waers10.  
        ls_accr-wrbtr = is_acdoca-gsl.  
        append ls_accr to ct_accr.  
    endif.  
endmethod.
```

FILL_EVENT_TABLE

Description: Fill the event table

Inst. Method

```
method fill_event_table.  
    data: ls_process type jv_proc_ev value 'EQAD',  
          ls_t8jev type t8jev.  
* Fill the event table  
    select single * from t8jev into ms_progpars-s_t8jev  
        where bukrs = ms_progpars-bukrs  
        and process = ls_process  
        and fyear = ms_progpars-year  
        and poper = ms_progpars-period. "#EC CI_NOORDER  
  
    if sy-subrc = 0.  
        add 1 to ms_progpars-s_t8jev-seqno.  
    else.  
        ms_progpars-s_t8jev-seqno = 1.  
    endif.  
    ms_progpars-s_t8jev-mandt = sy-mandt.  
    ms_progpars-s_t8jev-bukrs = ms_progpars-bukrs.  
    ms_progpars-s_t8jev-process = ls_process.  
    ms_progpars-s_t8jev-fyear = ms_progpars-year.  
    ms_progpars-s_t8jev-poper = ms_progpars-period.  
    ms_progpars-s_t8jev-ernam = sy-uname.  
    ms_progpars-s_t8jev-cpudt = sy-datum.  
    ms_progpars-s_t8jev-cputm = sy-uzeit.  
    ms_progpars-s_t8jev-status = '3'.  
* Only update when not running in test mode  
    if ms_progpars-test <> abap_true.  
        mo_output->insert_t8jev( ls_t8jev ).  
    endif.  
* Fill select options.  
    set_event_param_account( ).  
    set_event_param_cost_center( ).  
    set_event_param_order( ).  
    set_event_param_project( ).  
* Save the parameters  
    set_event_param( name = 'P_BUDAT'  
        contense = ms_progpars-budat ).
```

```
set_event_param( name = 'P_VNAME'
                  contense = ms_progpars-vname ).
set_event_param( name = 'P_EQOLD'
                  contense = ms_progpars-eqold ).
set_event_param( name = 'P_EQNEW'
                  contense = ms_progpars-eqnew ).
set_event_param( name = 'P_FRDATE'
                  contense = ms_progpars-frdate ).
set_event_param( name = 'P_TODATE'
                  contense = ms_progpars-todate ).
set_event_param( name = 'P_YEAR'
                  contense = ms_progpars-year ).
set_event_param( name = 'P_PERIOD'
                  contense = ms_progpars-period ).
set_event_param( name = 'P_BKTXT'
                  contense = ms_progpars-bktxt ).
set_event_param( name = 'P_TEST'
                  contense = ms_progpars-test ).
mo_output->commit_work( ).
endmethod.
```

GET_BILIND_RANGE_CASHCALL

Description: Get the billing indicators used by cash call
Inst. Method

Importing parameter

IV_SIGN TYPE CHAR1
IV_BUKRS TYPE BUKRS
IV_MODE TYPE STRING

Exporting parameter

ET_BILIND TYPE JVA_BILIND_RANGE_T
ET_BILIND_OP TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)

```
method get_billind_range_cashcall.
  data: lt_t8j0g type table of t8j0g,
        ls_billind type jva_billind_range,
        lt_t8ja type table of t8ja,
        lv_billid_cl type jv_billind,
        ls_t8j0f type t8j0f.
  refresh: et_billind, et_billind_op.
* Get the posting rule header
  select single * from t8j0f into ls_t8j0f
    where bukrs = ms_progpars-bukrs
    and bmethod = ms_settings-s_t8jv-bmethod
    and jvfunc = 'CCOP'.
  ls_billind-sign = iv_sign.
  ls_billind-option = 'EQ'.
  case iv_mode.
    when 'ALL'.
      select * from t8j0g into table lt_t8j0g
        where bukrs = ms_progpars-bukrs
        and bmethod = ms_settings-s_t8jv-bmethod
        and ( jvfunc = 'CCOP' or "Cash call billed to
partner
```

```

                                jvfunc   = 'FACC' or  "Farm in/out cash call
re-determine
                                jvfunc   = 'FAC2' ).  "Farm in/out cash call
correction
    when 'PARTNER'.
        select * from t8j0g into table lt_t8j0g
            where bukrs   = ms_progpars-bukrs
              and bmethod = ms_settings-s_t8jv-bmethod
              and ( ( jvfunc   = 'CCOP' and  "Cash Call - Operated
                    itemtype = 'AB' )      or "Cash call billed to
partner
                                ( jvfunc   = 'FACC' and  "Farm in/out cash
call re-determine
                                itemtype = 'E1' )      or
                                ( jvfunc   = 'FAC2' and  "Farm in/out cash
call correction
                                itemtype = 'F1' ) ).
    when others.  "Default: 'OFFSET'
        select * from t8j0g into table lt_t8j0g
            where bukrs   = ms_progpars-bukrs
              and bmethod = ms_settings-s_t8jv-bmethod
              and ( ( jvfunc   = 'CCOP' and  "Cash Call - Operated
                    itemtype = 'AC' )      or "Cash call billed to
offset account
                                ( jvfunc   = 'FACC' and  "Farm in/out cash
call re-determine
                                itemtype = 'E2' )      or
                                ( jvfunc   = 'FAC2' and  "Farm in/out cash
call correction
                                itemtype = 'F2' ) ).
endcase.
loop at lt_t8j0g into data(ls_t8j0g).
    if ls_t8j0g-debbillind is not initial.
        ls_bilind-low = ls_t8j0g-debbillind.
        collect ls_bilind into et_bilind.
*   Get clearing billing indicator for cash call
    if iv_mode <> 'OFFSET'      and
        ls_t8j0g-jvfunc = 'CCOP' and
        ls_t8j0g-itemtype = 'AB'.
        call function 'GET_CLEARING_BILLING_IND'
            exporting
                i_clearing_function = ls_t8j0f-clearproc
                i_original_bilid    = ls_t8j0g-debbillind
            importing
                e_clearing_bilid    = lv_bilid_cl.
        if lv_bilid_cl is not initial.
            ls_bilind-low = lv_bilid_cl.
            collect ls_bilind into et_bilind_op.
        endif.
    endif.
endif.
if ls_t8j0g-crebillind is not initial.
    ls_bilind-low = ls_t8j0g-crebillind.
    collect ls_bilind into et_bilind.

```

```

    if iv_mode = 'ALL'          and
       ls_t8j0g-jvfunc = 'CCOP' and
       ls_t8j0g-itemtype = 'AB'.
    call function 'GET_CLEARING_BILLING_IND'
    exporting
       i_clearing_function = ls_t8j0f-clearproc
       i_original_bilid    = ls_t8j0g-crebillind
    importing
       e_clearing_bilid    = lv_bilid_cl.
    if lv_bilid_cl is not initial.
       ls_bilind-low = lv_bilid_cl.
       collect ls_bilind into et_bilind_op.
    endif.
  endif.
endif.
endloop.
if lines( et_bilind_op ) = 0.
  "Make sure that no items with wrong billing indicators are picked up
  ls_bilind-low = '!!!'.
  collect ls_bilind into et_bilind_op.
endif.
endmethod.

```

GET_BILIND_RANGE_CUTBACK

Description: Get the billing indicators used by cutback

Inst. Method

Importing parameter

IV_SIGN TYPE CHAR1

IV_BUKRS TYPE BUKRS

Exporting parameter

ET_BILIND TYPE JVA_BILIND_RANGE_T

```

method get_billind_range_cutback.
  data: lt_t8j0g  type table of t8j0g,
        ls_bilind type jva_bilind_range.
  refresh et_bilind.
  ls_bilind-sign    = iv_sign.
  ls_bilind-option = 'EQ'.
  select * from t8j0g into table lt_t8j0g
        where bukrs    = iv_bukrs
        and jvfunc     = 'CUTB'.
  loop at lt_t8j0g into data(ls_t8j0g).
    if ls_t8j0g-debbillind is not initial.
      ls_bilind-low = ls_t8j0g-debbillind.
      collect ls_bilind into et_bilind.
    endif.
    if ls_t8j0g-crebillind is not initial.
      ls_bilind-low = ls_t8j0g-crebillind.
      collect ls_bilind into et_bilind.
    endif.
  endloop.
endmethod.

```

GET_BILIND_RANGE_PAYMENTS

Description: Get the billing indicators used by payments
Inst. Method

Importing parameter

IV_SIGN TYPE CHAR1
IV_BUKRS TYPE BUKRS

Exporting parameter

ET_BILIND TYPE JVA_BILIND_RANGE_T

```
method get_billind_range_payments.  
  data: lt_t8j0g  type table of t8j0g,  
        ls_billind type jva_billind_range,  
        lt_t8ja   type table of t8ja.  
  refresh et_billind.  
  ls_billind-sign   = iv_sign.  
  ls_billind-option = 'EQ'.  
  select * from t8j0g into table lt_t8j0g  
        where bukrs   = ms_progpars-bukrs  
          and jvfunc  = 'CCNP'  
          and itemtype = 'AB'.  
  loop at lt_t8j0g into data(ls_t8j0g).  
    if not ls_t8j0g-debbillind is initial.  
      ls_billind-low = ls_t8j0g-debbillind.  
      collect ls_billind into et_billind.  
    endif.  
    if not ls_t8j0g-crebillind is initial.  
      ls_billind-low = ls_t8j0g-crebillind.  
      collect ls_billind into et_billind.  
    endif.  
  endloop.  
* Get the cash call payment and reclass billing indicators  
  select * from t8ja into table lt_t8ja  
        where ccpay = 'X'.  
  loop at lt_t8ja into data(ls_t8ja).  
    ls_billind-low = ls_t8ja-bilind.  
    collect ls_billind into et_billind.  
  endloop.  
endmethod.
```

GET_DATA_CC1

Description: Get the ACDOCA lines for cash call adjustments 1
Inst. Method

Importing parameter

IT_BILIND_CUTB TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IT_BILIND_PAY TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE

Changing parameter

CT_ACDOCA_CC1 TYPE GTY_T_ACDOCA_CHECK
CV_ERROR TYPE ABAP_BOOL

```
method get_data_cc1.
```

```

data: lv_date_clause   type string,
      lt_sel_fields    type fieldlist_t,
      lt_group_fields  type fieldlist_t,
      lr_billind       type range of jv_billind,
      lr_billind_op    type range of jv_billind,
      ls_acdoca_totals type jva_acdoc_amounts.
refresh ct_acdoca_cc1.
if is_diff_share-partn_old is initial.
  return.
endif.
get_fields_for_acdoca_selects( exporting
                              iv_single_items = abap_true
                              it_table       = ct_acdoca_cc1
                              iv_source_table = ms_settings-source_table
                              changing
                                ct_sel_fields  = lt_sel_fields
                                ct_group_fields = lt_group_fields ).

get_billind_range_cashcall( exporting
                             iv_bukrs = ms_progpara-bukrs
                             iv_sign  = 'I'
                             iv_mode  = 'ALL'
                             importing
                               et_billind  = lr_billind
                               et_billind_op = lr_billind_op ).

lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
* Get the intercompany postings from table ACDOCA
select (lt_sel_fields) from (ms_settings-source_table)
  bypassing buffer
  appending corresponding fields of table @ct_acdoca_cc1
  where rldnr      = @ms_settings-rldnr
     and rbukrs    = @ms_progpara-bukrs
     and vname     = @ms_progpara-vname
     and egrupp    = @ms_progpara-egold
     and ( kunnr    = @is_diff_share-partn_old or
           lifnr    = @is_diff_share-partn_old or
           vptnr    = @is_diff_share-partn_old )
     "and ( jvactivity = 'CC' or
Call postings      "Original Cash
     "      jvactivity = 'EC' or
Change postings    "Previous Equity
     "      jvactivity = 'E1' or
Adjustment postings "Previous Equity
     "      jvactivity = 'E2' or
Adjustment postings "Previous Equity
     "      jvactivity = 'F1' )
Call correction postings "Previous Cash
     and btype      <> @space
billing indicator   "Only lines with
     and ( btype     in @lr_billind or
           ( kunnr    = @ms_settings-s_t8jz-opaccnumb and
             btype    in @lr_billind_op ) )
     and awitem      <> '000000'
lines              "Exclude balancing

```

```

        and racct      in @ms_progpars-t_acct
        and rcntr      in @ms_progpars-t_cntr
        and ps_psp_pnr in @ms_progpars-t_projk
        and aufnr      in @ms_progpars-t_ordnr
        and nplnr      in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and (lv_date_clause)
    group by (lt_group_fields).
*   Check if the cash calls have already been payed. If yes, set the error flag
    loop at ct_acdoca_cc1 into data(ls_acdoca_cc1).
        if ls_acdoca_cc1-btype in it_bilind_pay.
            add ls_acdoca_cc1-wsl to ls_acdoca_totals-wsl.
            add ls_acdoca_cc1-hsl to ls_acdoca_totals-hsl.
            add ls_acdoca_cc1-ksl to ls_acdoca_totals-ksl.
            add ls_acdoca_cc1-osl to ls_acdoca_totals-osl.
            add ls_acdoca_cc1-vsl to ls_acdoca_totals-vsl.
            add ls_acdoca_cc1-bsl to ls_acdoca_totals-bsl.
            add ls_acdoca_cc1-csl to ls_acdoca_totals-csl.
            add ls_acdoca_cc1-dsl to ls_acdoca_totals-dsl.
            add ls_acdoca_cc1-esl to ls_acdoca_totals-esl.
            add ls_acdoca_cc1-fsl to ls_acdoca_totals-fsl.
            add ls_acdoca_cc1-gsl to ls_acdoca_totals-gsl.
        endif.
    endloop.
    if ls_acdoca_totals-wsl <> 0 or
       ls_acdoca_totals-hsl <> 0 or
       ls_acdoca_totals-ksl <> 0 or
       ls_acdoca_totals-osl <> 0 or
       ls_acdoca_totals-vsl <> 0 or
       ls_acdoca_totals-bsl <> 0 or
       ls_acdoca_totals-csl <> 0 or
       ls_acdoca_totals-dsl <> 0 or
       ls_acdoca_totals-esl <> 0 or
       ls_acdoca_totals-fsl <> 0 or
       ls_acdoca_totals-gsl <> 0.
        cv_error = abap_true.
    endif.
endmethod.
```

GET_DATA_CC1_INTCO
Description: Get the ACDOCA lines for cash call adjustments 1
Inst. Method

Importing parameter
IT_BILIND_CUTB TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IT_BILIND_PAY TYPE JVA_BILIND_RANGE_T (Range table for the JVA billing indicator)
IS_DIFF_SHARE TYPE JVA_DIFF_SHARE

Changing parameter
CT_ACDOCA_CC1 TYPE GTY_T_ACDOCA_CHECK
CV_ERROR TYPE ABAP_BOOL

```

method get_data_cc1_intco.
    data: lv_date_clause type string,
          lt_sel_fields  type fieldlist_t,
```

```

        lt_group_fields type fieldlist_t,
        lr_billind      type range of jv_billind,
        ls_acdoca_totals type jva_acdoc_amounts.
refresh ct_acdoca_cc1.
if is_diff_share-partn_old is initial.
    return.
endif.
get_fields_for_acdoca_selects( exporting
                                iv_single_items = abap_true
                                it_table         = ct_acdoca_cc1
                                iv_source_table  = ms_settings-source_table
                                changing
                                ct_sel_fields    = lt_sel_fields
                                ct_group_fields = lt_group_fields ).

get_billind_range_cashcall( exporting
                             iv_bukrs = ms_progpars-bukrs
                             iv_sign  = 'I'
                             iv_mode  = 'ALL'
                             importing
                             et_billind = lr_billind ).

lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
* Get the intercompany postings from table ACDOCA
select (lt_sel_fields) from (ms_settings-source_table)
    bypassing buffer
    appending corresponding fields of table @ct_acdoca_cc1
    where rldnr      = @ms_settings-rldnr
       and rbukrs    = @is_diff_share-intcocd_old
       and ( vname    = @is_diff_share-intrcovent_old or
             vname    = @is_diff_share-intrcovent_new )
       and egrupp    = @is_diff_share-intcompepp_old
       and ( kunnr    = @is_diff_share-partn_old or
             lifnr    = @is_diff_share-partn_old or
             vptnr    = @is_diff_share-partn_old )
       "and ( jvactivity = 'CC' or
             "Original Cash
Call postings
       "      jvactivity = 'EC' or
             "Previous Equity
Change postings
       "      jvactivity = 'E1' or
             "Previous Equity
Adjustment postings
       "      jvactivity = 'E2' or
             "Previous Equity
Adjustment postings
       "      jvactivity = 'F1' )
             "Previous Cash
Call correction postings
       and btype      <> @space
             "Only lines with
billing indicator
       and btype      in @lr_billind
       and awitem      <> '000000'
             "Exclude
balancing lines
       and racct       in @ms_progpars-t_acct
       and rcntr       in @ms_progpars-t_cntr
       and ps_psp_pnr  in @ms_progpars-t_projk
       and aufnr       in @ms_progpars-t_ordnr
       and nplnr       in @ms_progpars-t_nplnr

```

```

        and nplnr_vorgn in @ms_progpars-t_vornr
        and (lv_date_clause)
        group by (lt_group_fields).
* Check if the cash calls have already been payed. If yes, set the error flag
loop at ct_acdoca_cc1 into data(ls_acdoca_cc1).
  if ls_acdoca_cc1-btype in it_bilind_pay.
    add ls_acdoca_cc1-wsl to ls_acdoca_totals-wsl.
    add ls_acdoca_cc1-hsl to ls_acdoca_totals-hsl.
    add ls_acdoca_cc1-ksl to ls_acdoca_totals-ksl.
    add ls_acdoca_cc1-osl to ls_acdoca_totals-osl.
    add ls_acdoca_cc1-vsl to ls_acdoca_totals-vsl.
    add ls_acdoca_cc1-bsl to ls_acdoca_totals-bsl.
    add ls_acdoca_cc1-csl to ls_acdoca_totals-csl.
    add ls_acdoca_cc1-dsl to ls_acdoca_totals-dsl.
    add ls_acdoca_cc1-esl to ls_acdoca_totals-esl.
    add ls_acdoca_cc1-fsl to ls_acdoca_totals-fsl.
    add ls_acdoca_cc1-gsl to ls_acdoca_totals-gsl.
  endif.
endloop.
if ls_acdoca_totals-wsl <> 0 or
ls_acdoca_totals-hsl <> 0 or
ls_acdoca_totals-ksl <> 0 or
ls_acdoca_totals-osl <> 0 or
ls_acdoca_totals-vsl <> 0 or
ls_acdoca_totals-bsl <> 0 or
ls_acdoca_totals-csl <> 0 or
ls_acdoca_totals-dsl <> 0 or
ls_acdoca_totals-esl <> 0 or
ls_acdoca_totals-fsl <> 0 or
ls_acdoca_totals-gsl <> 0.
  cv_error = abap_true.
endif.
endmethod.
```

GET_DATA_CC2

Description: Get the ACDOCA lines for cash call adjustments 2
Inst. Method

Changing parameter

```

CT_ACDOCA TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN TYPE REF TO DATA
CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
CR_ACDOCA_DYN_POSTED TYPE REF TO DATA
```

```

method get_data_cc2.
  data: lv_date_clause   type string,
        lt_sel_fields   type fieldlist_t,
        lt_group_fields type fieldlist_t,
        lr_billind_off  type range of jv_bilind,
        lr_billind_partn type range of jv_bilind,
        lr_billind_op   type range of jv_bilind,
        lt_fieldcatalog type lvc_t_fcat,
        lv_single_items type abap_bool.
  field-symbols: <lt_acdoca_dyn>          type standard table,
```

```

        <lt_acdoca_dyn_posted> type standard table.
get_fields_for_acdoca_selects( exporting
    iv_single_items = lv_single_items
    iv_source_table = ms_settings-source_table
    importing
    et_fieldcatalog = lt_fieldcatalog
    changing
    ct_sel_fields   = lt_sel_fields
    ct_group_fields = lt_group_fields ).

get_billind_range_cashcall( exporting
    iv_bukrs = ms_progpara-bukrs
    iv_sign  = 'I'
    iv_mode  = 'PARTNER'
    importing
    et_billind   = lr_billind_partn
    et_billind_op = lr_billind_op ).

get_billind_range_cashcall( exporting
    iv_bukrs = ms_progpara-bukrs
    iv_sign  = 'I'
    iv_mode  = 'OFFSET'
    importing
    et_billind = lr_billind_off ).

if lr_billind_off[] is initial.
    return.
endif.
lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
if lv_single_items = abap_false.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
        it_fieldcatalog = lt_fieldcatalog
        importing
        ep_table        = cr_acdoca_dyn
    ).
    assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
        it_fieldcatalog = lt_fieldcatalog
        importing
        ep_table        =
cr_acdoca_dyn_posted ).
    assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
endif.
loop at ms_settings-t_diff_share into data(ls_diff_share).
    if ls_diff_share-eqshare_old = ls_diff_share-eqshare_new.
        continue.
    endif.
    if ls_diff_share-eqshare_old > 0.
*       Get the original cash call postings from table acdoca
        select (lt_sel_fields) from (ms_settings-source_table)
            bypassing buffer
            appending corresponding fields of table
@<lt_acdoca_dyn>
            where rldnr          = @ms_settings-rldnr

```

```

        and rbukrs      = @ms_progpars-bukrs
        and vname       = @ms_progpars-vname
        and egrup       = @ls_diff_share-eg_old
        and ( kunnr     = @ls_diff_share-partn_old or
              lifnr     = @ls_diff_share-partn_old or
              vptnr     = @ls_diff_share-partn_old )
        and btype       <> @space
        and ( btype     in @lr_billind_off      or "Cash call
lines with offset billing indicator
        ( jvactivity = 'F1' and                  "Cash call
lines with partner billing indicator
              btype   in @lr_billind_partn )
              or
        ( jvactivity = 'CC' and                  "Operator
postings
              btype   in @lr_billind_op ) )
        and awitem     <> '000000'              "Eclude
balancing lines
        and racct      in @ms_progpars-t_acct
        and rcntr      in @ms_progpars-t_cntr
        and ps_psp_pnr in @ms_progpars-t_projk
        and aufnr      in @ms_progpars-t_ordnr
        and nplnr      in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and (lv_date_clause)
        group by (lt_group_fields).
    endif.
*   Get any previous adjustment postings from table acdoca
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        appending corresponding fields of table
@<lt_acdoca_dyn_posted>
        where rldnr     = @ms_settings-rldnr
        and rbukrs      = @ms_progpars-bukrs
        and vname       = @ms_progpars-vname
        and ( egrup     = @ms_progpars-egold or
              egrup     = @ms_progpars-egnew )
        and ( kunnr     = @ls_diff_share-partn_new or
              lifnr     = @ls_diff_share-partn_new or
              vptnr     = @ls_diff_share-partn_new )
        and jvactivity = 'F1'                  "Previous cash
call corrections
        and awitem     <> '000000'              "Eclude
balancing lines
        and racct      in @ms_progpars-t_acct
        and rcntr      in @ms_progpars-t_cntr
        and ps_psp_pnr in @ms_progpars-t_projk
        and aufnr      in @ms_progpars-t_ordnr
        and nplnr      in @ms_progpars-t_nplnr
        and nplnr_vorgn in @ms_progpars-t_vornr
        and (lv_date_clause)
        group by (lt_group_fields).

    endloop.
endmethod.

```

GET_DATA_CC2_INTCO

Description: Get the ACDOCA lines for intercompany cash call adjustments

Inst. Method

Changing parameter

CT_ACDOCA TYPE GTY_T_ACDOCA_CHECK

CR_ACDOCA_DYN TYPE REF TO DATA

CT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK

CR_ACDOCA_DYN_POSTED TYPE REF TO DATA

```
method get_data_cc2_intco.
  data: lv_date_clause  type string,
        lt_sel_fields   type fieldlist_t,
        lt_group_fields type fieldlist_t,
        lr_billind      type range of jv_bilind,
        lt_fieldcatalog type lvc_t_fcat,
        lv_single_items type abap_bool.
  field-symbols: <lt_acdoca_dyn>      type standard table,
                 <lt_acdoca_dyn_posted> type standard table.
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = lv_single_items
                                iv_source_table = ms_settings-source_table
                                importing
                                et_fieldcatalog = lt_fieldcatalog
                                changing
                                ct_sel_fields  = lt_sel_fields
                                ct_group_fields = lt_group_fields ).
  get_billind_range_cashcall( exporting
                              iv_bukrs = ms_progpars-bukrs
                              iv_sign  = 'I'
                              iv_mode  = 'OFFSET'
                              importing
                              et_bilind = lr_billind ).

  if lr_billind[] is initial.
    return.
  endif.
  lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
  if lv_single_items = abap_false.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       = cr_acdoca_dyn
).
    assign cr_acdoca_dyn->* to <lt_acdoca_dyn>.
*   Create dynamic internal table and assign to FS
    cl_alv_table_create=>create_dynamic_table( exporting
                                                it_fieldcatalog = lt_fieldcatalog
                                                importing
                                                ep_table       =
cr_acdoca_dyn_posted ).
    assign cr_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
```

```

endif.
loop at ms_settings-t_diff_share_intco into data(ls_diff_share).
  check ls_diff_share-eqshare_old <> ls_diff_share-eqshare_new and
    ls_diff_share-eqshare_old > 0.
*   Select the single items from table acdoca
  select (lt_sel_fields) from (ms_settings-source_table)
    bypassing buffer
    appending corresponding fields of table @<lt_acdoca_dyn>
    where rldnr      = @ms_settings-rldnr
      and rbukrs     = @ls_diff_share-intcocd_old
      and vname      = @ls_diff_share-intrcovent_old
      and egrup      = @ls_diff_share-intcompepgp_old
      and ( kunnr     = @ls_diff_share-partn_old or
        lifnr        = @ls_diff_share-partn_old or
        vptnr        = @ls_diff_share-partn_old )
      "and ( jvactivity = 'CC' or "Original Cash
Call postings      "      jvactivity = 'E2' )      "Previous
Equity Adjustment postings
                  and btype      <> @space
                  and btype      in @lr_billind      "Cash call
lines with offset billing indicator
                  and awitem      <> '0000000'      "Eclude
balancing lines
                  and racct       in @ms_progpars-t_acct
                  and rcntr       in @ms_progpars-t_cntr
                  and ps_psp_pnr  in @ms_progpars-t_projk
                  and aufnr       in @ms_progpars-t_ordnr
                  and nplnr       in @ms_progpars-t_nplnr
                  and nplnr_vorgn in @ms_progpars-t_vornr
                  and (lv_date_clause)
                  group by (lt_group_fields).
*   Select the single items from table acdoca
  select (lt_sel_fields) from (ms_settings-source_table)
    bypassing buffer
    appending corresponding fields of table
@<lt_acdoca_dyn_posted>
    where rldnr      = @ms_settings-rldnr
      and rbukrs     = @ls_diff_share-intcocd_new
      and vname      = @ls_diff_share-intrcovent_new
      and egrup      = @ls_diff_share-intcompepgp_new
      and ( kunnr     = @ls_diff_share-partn_new or
        lifnr        = @ls_diff_share-partn_new or
        vptnr        = @ls_diff_share-partn_new )
      and jvactivity = 'F1'      "Previous cash
call corrections
                  and awitem      <> '0000000'      "Eclude
balancing lines
                  and racct       in @ms_progpars-t_acct
                  and rcntr       in @ms_progpars-t_cntr
                  and ps_psp_pnr  in @ms_progpars-t_projk
                  and aufnr       in @ms_progpars-t_ordnr
                  and nplnr       in @ms_progpars-t_nplnr
                  and nplnr_vorgn in @ms_progpars-t_vornr

```

```

        and (lv_date_clause)
        group by (lt_group_fields).

    endloop.
endmethod.

```

GET_DATA_EC

Description: Get the ACDOCA lines for equity change

Inst. Method

Changing parameter

CT_ACDOCA_MAIN TYPE GTY_T_ACDOCA_CHECK

```

method get_data_ec.
    data: lt_sel_fields      type fieldlist_t,
          lv_date_clause    type string,
          lv_cbrunid_initial type acdoca-cbrunid.
    get_fields_for_acdoca_selects( exporting
                                    iv_single_items = abap_true
                                    it_table         = ct_acdoca_main
                                    iv_source_table  = ms_settings-source_table
                                    changing
                                    ct_sel_fields = lt_sel_fields ).
    lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
    if ms_settings-t_recid_billable[] is initial.
        return.
    endif.
*   Select the single items from table acdoca
    select (lt_sel_fields) from (ms_settings-source_table)
        bypassing buffer
        into corresponding fields of table @ct_acdoca_main
    where rldnr      = @ms_settings-rldnr
      and rbukrs     = @ms_progpars-bukrs
      and vname      = @ms_progpars-vname
      and egrup      = @ms_progpars-eqold
      and recid      in @ms_settings-t_recid_billable
      and racct      in @ms_progpars-t_acct
      and rcntr      in @ms_progpars-t_cntr
      and ps_psp_pnr in @ms_progpars-t_projk
      and aufnr      in @ms_progpars-t_ordnr
      and nplnr      in @ms_progpars-t_nplnr
      and nplnr_vorgn in @ms_progpars-t_vornr
      and ( ( jvactivity = 'E1' and
              poper >= '001' and poper <= '012' )
            or
              ( ( cbrunid <> @lv_cbrunid_initial or
"Only pick up items that were cutbacked, already
              jvactivity = 'E2' )
              (lv_date_clause)
              budat in @ms_progpars-t_budat ) )
            and
            and
        order by src_awref,
                 src_awitem,
                 racct,
                 vname,

```

```

                                egrup,
                                btype,
                                vptnr,
                                prctr,
                                rcntr,
                                aufnr,
                                ps_psp_pnr,
                                nplnr,
                                nplnr_vorgn,
                                timestamp,
                                belnr,
                                buzei,
                                docln.

endmethod.
```

GET_DATA_INTCO

Description: Get the ACDOCA lines for intercompany adjustments
Inst. Method

Changing parameter

```

CT_ACDOCA_INTCO_NEW TYPE JVA_CB_ACDOCA_T
CT_ACDOCA_INTCO_OLD TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)

method get_data_intco.
  data: lt_acdoca type jva_cb_acdoca_t.
  types: begin of lty_s_intcomp,
          intcocd_new   type t8jvt02-intcocd,
          intrcovent_new type t8jvt02-intrcovent,
          intcompegp_new type t8jvt02-intcompegp,
          intcompegp_old type t8jvt02-intcompegp,
          end of lty_s_intcomp.
  data: lv_date_clause   type string,
        lt_sel_fields    type fieldlist_t,
        lt_t8j0g         type table of t8j0g,
        lr_recid         type range of jv_recind,
        ls_recid         like line of lr_recid,
        ls_intcomp       type lty_s_intcomp,
        lt_intcomp       type table of lty_s_intcomp,
        lv_cbrunid_initial type acdoca-cbrunid.
  refresh: ct_acdoca_intco_new,
           ct_acdoca_intco_old.
*   Get fields for acdoca selects
  get_fields_for_acdoca_selects( exporting
                                iv_single_items = abap_true
                                it_table        = lt_acdoca
                                iv_source_table = ms_settings-source_table
                                changing
                                ct_sel_fields = lt_sel_fields ).
  lv_date_clause = cl_abap_dyn_prg=>escape_quotes_str( make_date_clause_for_select(
) ).
*   Get the relevant recovery indicators
  ls_recid-sign   = 'I'.
  ls_recid-option = 'EQ'.
  select * from t8j0g into table lt_t8j0g
```

```

        where bukrs      = ms_progpars-bukrs
          and jvfunc     = 'FACI'
          and itemtype   = 'EX'.
loop at lt_t8j0g into data(ls_t8j0g).
  if not ls_t8j0g-debrecid is initial.
    ls_recid-low = ls_t8j0g-debrecid.
    collect ls_recid into lr_recid.
  endif.
  if not ls_t8j0g-crerecid is initial.
    ls_recid-low = ls_t8j0g-crerecid.
    collect ls_recid into lr_recid.
  endif.
endloop.
* Get the relevant intercompany data
loop at ms_settings-t_diff_share into data(ls_diff_share)
      where intcocd_old <> space
      and intcocd_new <> space.

  move-corresponding ls_diff_share to ls_intcomp.
  collect ls_intcomp into lt_intcomp.
endloop.
loop at lt_intcomp into ls_intcomp.
*   Select the single items from table acdoca
  select (lt_sel_fields) from (ms_settings-source_table)
    bypassing buffer
    appending corresponding fields of table @lt_acdoca
    where rldnr      = @ms_settings-rldnr
      and rbukrs     = @ls_intcomp-intcocd_new
      and vname      = @ls_intcomp-intrcoevent_new
      and ( egrup    = @ls_intcomp-intcompepgp_old or
        egrup      = @ls_intcomp-intcompepgp_new )
      and recid      in @lr_recid
      and cbrunid    <> @lv_cbrunid_initial
      and racct      in @ms_progpars-t_acct
      and rcntr      in @ms_progpars-t_cntr
      and ps_psp_pnr in @ms_progpars-t_projk
      and aufnr      in @ms_progpars-t_ordnr
      and nplnr      in @ms_progpars-t_nplnr
      and nplnr_vorgn in @ms_progpars-t_vornr
      and ( jvactivity = 'E1' or
        ( jvactivity <> 'E1' and
          budat in @ms_progpars-t_budat and
          (lv_date_clause) ) )

    order by primary key.
loop at lt_acdoca into data(ls_acdoca_intco).
  if ls_acdoca_intco-vname = ls_intcomp-intrcoevent_new and
    ls_acdoca_intco-egrup = ls_intcomp-intcompepgp_new.
    append ls_acdoca_intco to ct_acdoca_intco_new.
  else.
    ls_acdoca_intco-egrup = ls_intcomp-intcompepgp_new.
    append ls_acdoca_intco to ct_acdoca_intco_old.
  endif.
endloop.
endloop.
sort ct_acdoca_intco_new by rbukrs

```

```

        rwcurn
        ryear
        vname
        egrupp
        racct
        rbusa
        rcntr
        aufnr
        ps_psp_pnr
        prctr
        recid
        vptnr
        nplnr
        nplnr_vorgn
        anl1n
        anl2n
        anbwa.
sort ct_acdoca_intco_old by rbukrs
        rwcurn
        ryear
        vname
        egrupp
        racct
        rbusa
        rcntr
        aufnr
        ps_psp_pnr
        prctr
        recid
        vptnr
        nplnr
        nplnr_vorgn
        anl1n
        anl2n
        anbwa.

endmethod.
```

GET_FIELDS_FOR_ACDOCA_SELECTS

Description: Get the fields to be retrieved through the ACDOCA select
Inst. Method

Importing parameter

IV_SINGLE_ITEMS TYPE ABAP_BOOL (Processing type)
IT_TABLE TYPE ANY TABLE OPTIONAL (Target Table)
IV_SOURCE_TABLE TYPE RSCOMPNAME OPTIONAL (Source Table)
IV_AGGR_AMNTS TYPE ABAP_BOOL OPTIONAL
IV_PREFIX TYPE STRING OPTIONAL

Exporting parameter

ET_FIELDCATALOG TYPE LVC_T_FCAT (Field Catalog for List Viewer Control)

Changing parameter

CT_SEL_FIELDS TYPE FIELDLIST_T (Table type for FIELDNAME)
CT_GROUP_FIELDS TYPE FIELDLIST_T OPTIONAL (Table type for FIELDNAME)

method get_fields_for_acdoca_selects.

```

data: ls_sel_fields like line of ct_sel_fields,
      lt_fieldlist type ttfieldname,
      lt_dfies type dfies_table,
      lo_structdescr type ref to cl_abap_structdescr,
      lo_tabledescr type ref to cl_abap_tabledescr,
      lv_fieldname type string,
      lv_selname type string.
refresh: ct_sel_fields, ct_group_fields.
* Collect fields to be retrieved for acdoca selects
* For equity change postings that go to ACDOCA directly, get the line
* items with document number and line number
if iv_single_items = abap_true.
  lo_tabledescr ?= cl_abap_typedescr=>describe_by_data( it_table ).
  lo_structdescr ?= lo_tabledescr->get_table_line_type( ).
  if iv_source_table is not initial.
    data(lo_typedescr_source) = cl_abap_typedescr=>describe_by_name(
iv_source_table ).
    data(lt_fieldname_source) = lo_typedescr_source->get_ddic_object( ).
  endif.
  loop at lo_structdescr->components[] assigning field-symbol(<ls_component>).
    if iv_source_table is not initial.
      read table lt_fieldname_source transporting no fields
        with key fieldname = <ls_component>-name.

      if sy-subrc <> 0.
        continue.
      endif.
    endif.
    if iv_aggr_amnts = abap_true and
      <ls_component>-name+1(2) = 'SL'.
      append |SUM( { iv_prefix }{ <ls_component>-name } ) AS | &&
<ls_component>-name to ct_sel_fields.
    else.
      lv_selname = iv_prefix && <ls_component>-name.
      lv_fieldname = iv_prefix && <ls_component>-name.
* Add selection field
      append lv_selname to ct_sel_fields.
* Add group-by field
      append lv_fieldname to ct_group_fields.
    endif.
  endloop.
  loop at ct_sel_fields into ls_sel_fields.
    try.
      cl_abap_dyn_prg=>check_column_name( ls_sel_fields ).
      catch cx_abap_invalid_name.
        delete ct_sel_fields from ls_sel_fields.
      endtry.
    endloop.
  else.
* For processes that post aggregated documents, get the data in an aggregated way
with the relevant fields
    call function 'DDIF_NAMETAB_GET'
      exporting
        tabname = iv_source_table
      tables

```

```

        dfies_tab = lt_dfies
    exceptions
        not_found = 1
        others     = 2.
    if sy-subrc <> 0.
        message e000(gj) with 'Fatal error when retrieving field catalog!'
                           into mv_message_text ##NO_TEXT ##MG_MISSING.
        save_sy_message( ).
        return.
    endif.
    sort lt_dfies by fieldname.
*   Get the balance sheet accounts
    try.
        cl_fins_acdoc_fieldcat_service=>get_active_fields_bcf_bs( importing
                                                                    et_fields =
lt_fieldlist ).
        catch cx_root ##NO_HANDLER.
            "Do nothing
        endtry.
*   Add the relevant fields to the selection fields table
    loop at lt_fieldlist into data(ls_fieldname).
        add_item_to_select_tables( exporting
                                    it_dfies      = lt_dfies
                                    iv_fieldname   = ls_fieldname
                                    changing
                                    ct_fieldcatalog = et_fieldcatalog
                                    ct_sel_fields  = ct_sel_fields
                                    ct_group_fields = ct_group_fields ).
    endloop.
*   Get any additional fields relevant for P&L
    try.
        cl_fins_acdoc_fieldcat_service=>get_fields_bcf_pl_and_split( importing
                                                                    et_fields =
lt_fieldlist ).
        catch cx_root ##NO_HANDLER.
            "Do nothing
        endtry.
    loop at lt_fieldlist into ls_fieldname.
        add_item_to_select_tables( exporting
                                    it_dfies      = lt_dfies
                                    iv_fieldname   = ls_fieldname
                                    changing
                                    ct_fieldcatalog = et_fieldcatalog
                                    ct_sel_fields  = ct_sel_fields
                                    ct_group_fields = ct_group_fields ).
    endloop.
*   Make sure that all venture fields and all cost objects are in the lists
    lt_fieldlist = value #(
        ( 'JVACTIVITY' )
        ( 'VNAME' )
        ( 'EGRUP' )
        ( 'ETYPE' )
        ( 'RECID' )
        ( 'BTYP' )

```

```

        ( 'VPTNR' )
        ( 'PVNAME' )
        ( 'PEGRUP' )
        ( 'PRODPER' )
        "( 'CBRACCT' )
        "( 'CBOBJNR' )
        "( 'CBRUNID' )
        ( 'RCNTR' )
        ( 'AUFNR' )
        ( 'PS_PSP_PNR' )
        ( 'NPLNR' )
        ( 'NPLNR_VORGN' )
    ).
loop at lt_fieldlist into ls_fieldname.
    add_item_to_select_tables( exporting
                               it_dfies      = lt_dfies
                               iv_fieldname   = ls_fieldname
                               changing
                               ct_fieldcatalog = et_fieldcatalog
                               ct_sel_fields  = ct_sel_fields
                               ct_group_fields = ct_group_fields ).
endloop.
endif.
"Add commas for modern SELECT
loop at ct_sel_fields assigning field-symbol(<ls_field>).
    if sy-tabix < lines( ct_sel_fields ).
        <ls_field> &&= ``,``.
    endif.
endloop.
loop at ct_group_fields assigning <ls_field>.
    if sy-tabix < lines( ct_group_fields ).
        <ls_field> &&= ``,``.
    endif.
endloop.
endmethod.
```

GET_INTCO_VENDOR

Description: Get the intercompany vendor
Inst. Method

Importing parameter

IV_BUKRS TYPE BUKRS (Company Code)
IV_PARTN TYPE ACDOCA-VPTNR (Partner account number)

Returning parameter

VALUE(RV_LIFNR) TYPE LIFNR (Account Number of Supplier)

```

method get_intco_vendor.
    data: ls_t8jo type t8jo,
          ls_kna1 type kna1.
    if ls_t8jo-bukrs <> iv_bukrs or
       ls_t8jo-intcocd <> ms_progpars-bukrs.
        select single * from t8jo into ls_t8jo
            where bukrs = iv_bukrs
            and partn = iv_partn
```

```

                                and intcocd = ms_progpars-bukrs.
else.
    sy-subrc = 0.
endif.
if sy-subrc = 0.
    clear ls_kna1.
    select single kunnr lifnr
                from kna1 into corresponding fields of ls_kna1
                where kunnr = ls_t8jo-partn.
    if not ls_kna1-lifnr is initial.
        rv_lifnr = ls_kna1-lifnr.
    else.
        rv_lifnr = ls_t8jo-partn.
    endif.
else.
    message i799(g5) with ms_progpars-bukrs into mv_message_text.
    save_sy_message( ).
endif.
endmethod.
```

GET_MSGS_FROM_MSG_COLLECTOR

Description: Get messages from message collector
Inst. Method

```

method get_msgs_from_msg_collector.
    data: ls_t8jvt01 type t8jvt01.
    loop at mo_message_collector->get_access( )->get_messages( ) into
data(ls_message).
    move-corresponding ls_message to ls_t8jvt01.
    ls_t8jvt01-status = ls_message-msgty.
    ls_t8jvt01-var1 = ls_message-msgv1.
    ls_t8jvt01-var2 = ls_message-msgv2.
    ls_t8jvt01-var3 = ls_message-msgv3.
    ls_t8jvt01-var4 = ls_message-msgv4.
    ls_t8jvt01-text = ls_message-text.
    append ls_t8jvt01 to ms_ea_results-t_messages.
endloop.
endmethod.
```

GET_PARTNER_SHARES

Description: Get the partner shares
Inst. Method

```

method get_partner_shares.
    data: lv_tabix_new      type sy-tabix,
          lv_oper_alloc_error type c,
          lo_message_collector type ref to if_jva_message_collection.
    lo_message_collector = cl_jva_message_factory=>get_message_collector( ).
    mo_partner_shares->get_partner_shares( exporting
ms_settings-s_t8jz
                                is_t8jz
                                =
                                iv_company
                                = ms_settings-bukrs
                                iv_equity_grp
                                = ms_progpars-eqold
                                iv_include_0_percent =
ms_settings-s_t8jz-ci_gross
```

```

                                iv_is_npoci      = abap_true
                                iv_period        =
ms_progpars-period

                                iv_venture       = ms_progpars-vname
                                iv_year          = ms_progpars-year
                                importing
                                et_shares        =
ms_settings-t_shares_old

                                ev_oper_alloc_error =
lv_oper_alloc_error

                                eo_message_collector =
lo_message_collector ).
  loop at lo_message_collector->get_access( )->get_messages( ) into
data(ls_message).
  save_message( iv_type   = ls_message-msgty
                iv_class  = ls_message-msgid
                iv_number = ls_message-msgno
                iv_var1   = ls_message-msgv1
                iv_var2   = ls_message-msgv2
                iv_var3   = ls_message-msgv3
                iv_var4   = ls_message-msgv4 ).
endloop.
if lo_message_collector->has_critical_messages( ) = abap_true.
  refresh ms_settings-t_shares_old.
endif.
lo_message_collector->reset( ).
mo_partner_shares->get_partner_shares( exporting
                                is_t8jz          =
ms_settings-s_t8jz

                                iv_company       = ms_settings-bukrs
                                iv_equity_grp    = ms_progpars-eqnew
                                iv_include_0_percent =
ms_settings-s_t8jz-ci_gross

                                iv_is_npoci      = abap_true
                                iv_period        =
ms_progpars-period

                                iv_venture       = ms_progpars-vname
                                iv_year          = ms_progpars-year
                                importing
                                et_shares        =
ms_settings-t_shares_new

                                ev_oper_alloc_error =
lv_oper_alloc_error

                                eo_message_collector =
lo_message_collector ).
  loop at lo_message_collector->get_access( )->get_messages( ) into ls_message.
  save_message( iv_type   = ls_message-msgty
                iv_class  = ls_message-msgid
                iv_number = ls_message-msgno
                iv_var1   = ls_message-msgv1
                iv_var2   = ls_message-msgv2
                iv_var3   = ls_message-msgv3
                iv_var4   = ls_message-msgv4 ).
endloop.

```

```

    if lo_message_collector->has_critical_messages( ) = abap_true.
        refresh ms_settings-t_shares_new.
    endif.
*   Delete equity groups where the shares are zero in both tables
    loop at ms_settings-t_shares_new into data(ls_shares_new)
        where eqshare = 0.

        lv_tabix_new = sy-tabix.
        loop at ms_settings-t_shares_old into data(ls_shares_old)
            where partn    = ls_shares_new-partn
            and opflag    = ls_shares_new-opflag
            and eqshare = 0.

            delete ms_settings-t_shares_old index sy-tabix.
        exit.
    endloop.
    if sy-subrc = 0.
        delete ms_settings-t_shares_new index lv_tabix_new.
    endif.
endloop.
endmethod.

```

GET_POSTING_RULE

Description: Get posting rule

Inst. Method

Importing parameter

```

VALUE(IV_BUKRS) TYPE ACDOCA-RBUKRS
VALUE(IV_JVFUNC) TYPE JV_FUNC (JV Function)
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY
VALUE(IV_RECID) TYPE ACDOCA-RECID (Recovery Indicator)

```

Changing parameter

```

CS_T8J0G TYPE T8J0G
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING

```

```

method get_posting_rule.
    data: lv_itemtype    type t8j0g-itemtype,
          lv_jvfunc     type t8j0a-jvfunc,
          lv_bmethod    type t8jv-bmethod,
          ls_t8j0g      type t8j0g,
          lv_fatal_error type abap_bool,
          lv_error_text type string.

    clear cs_t8j0g.
    lv_bmethod = ms_settings-s_t8jv-bmethod.
    lv_jvfunc = iv_jvfunc.
    lv_itemtype = iv_jvactivity.
*   Get JV function
    if ms_settings-s_t8j0a-jvfunc <> lv_jvfunc.
        select single * from t8j0a into ms_settings-s_t8j0a
            where jvfunc = lv_jvfunc.
    endif.
*   Read posting rules without billing method
*   if JV function does not allow a billing method
    if ms_settings-s_t8j0a-billmethid is initial.
        clear lv_bmethod.
    endif.

```

```
endif.
* Get the document type
if ms_settings-s_t8j0f-bukrs <> iv_bukrs or
   ms_settings-s_t8j0f-bmethod <> lv_bmethod or
   ms_settings-s_t8j0f-jvfunc <> lv_jvfunc.
   select single doctyped from t8j0f into ms_settings-s_t8j0f
       where bukrs = iv_bukrs
       and bmethod = lv_bmethod
       and jvfunc = lv_jvfunc.

   if sy-subrc <> 0.
       lv_fatal_error = 'X'.
   endif.
endif.
* Get all posting rules for the given method and function
read table ms_settings-t_t8j0g into ms_settings-s_t8j0g index 1. "#EC CI_NOORDER
if ls_t8j0g-bukrs <> iv_bukrs or
   ls_t8j0g-bmethod <> lv_bmethod or
   ls_t8j0g-jvfunc <> lv_jvfunc.
   select * from t8j0g into table ms_settings-t_t8j0g
       bypassing buffer
       where bukrs = iv_bukrs
       and bmethod = lv_bmethod
       and jvfunc = lv_jvfunc
       order by jvfunc itemtype recid.

   if sy-subrc <> 0.
       lv_fatal_error = 'X'.
   endif.
endif.
if lv_fatal_error = 'X'.
   message e769(g5) with iv_bukrs lv_bmethod lv_jvfunc into lv_error_text.
   save_sy_message( ).
   return.
endif.
* Get the posting rule for the given recovery indicator
clear cs_t8j0g.
read table ms_settings-t_t8j0g into cs_t8j0g
    with key jvfunc = lv_jvfunc
         itemtype = lv_itemtype
         recid = iv_recid.

* If no posting rule can be found for the given RI, search for a posting rule where
the RI is space
if cs_t8j0g is initial.
   read table ms_settings-t_t8j0g into cs_t8j0g
       with key jvfunc = lv_jvfunc
            itemtype = lv_itemtype
            recid = space.

* If no posting rule can be found by RI, get any posting rule
if cs_t8j0g is initial.
   read table ms_settings-t_t8j0g into cs_t8j0g
       with key jvfunc = lv_jvfunc
            itemtype = lv_itemtype.

   endif.
endif.
ms_settings-s_t8j0g = cs_t8j0g.
```

```

    if cs_t8j0g is initial.
        lv_fatal_error = 'X'.
        message e769(g5) with iv_bukrs lv_jvfunc lv_itemtype into lv_error_text.
        save_sy_message( ).
    endif.
    if lv_fatal_error = 'X'.
        cv_fatal_error = 'X'.
        if cv_error_text is initial.
            cv_error_text = lv_error_text.
        endif.
    endif.
endmethod.
```

GET_POSTING_RULES
Description: Get the posting rules
Inst. Method

Importing parameter
IV_BMETHOD TYPE T8JV-BMETHOD
IV_BUKRS TYPE BUKRS
IV_FUNCTION TYPE T8J0F-JVFUNC

Changing parameter
CV_ERROR TYPE ABAP_BOOL

```

method get_posting_rules.
    "Get the JV function
    select single * from t8j0a into ms_settings-s_t8j0a
                                where jvfunc = iv_function.

    "The setting in T8J0A determines if the posting rule
    "is defined for a billing method or not
    if ms_settings-s_t8j0a-billmethid is not initial.
        data(lv_bmethod) = iv_bmethod.
    endif.
    "Get the posting rules
    select single * from t8j0f into ms_settings-s_t8j0f
                                where bukrs    = iv_bukrs
                                and bmethod    = lv_bmethod
                                and jvfunc     = iv_function.

    if sy-subrc <> 0.
        message e769(g5) with iv_bukrs lv_bmethod iv_function into mv_message_text.
        save_sy_message( ).
    endif.
    "Get the posting rule details
    select * from t8j0g into table ms_settings-t_t8j0g
                                where bukrs    = iv_bukrs
                                and bmethod    = lv_bmethod
                                and jvfunc     = iv_function.

endmethod.
```

GET_RI_REBOOK_AND_REVERSE
Description: Get the recovery indicators for reversal and chang line
Inst. Method

Importing parameter

IV_ITEM TYPE T8J0G-ITEMTYPE

Changing parameter

CV_RECID TYPE ACDOCA-RECID

```
method get_ri_rebook_and_reverse.
  data: lv_recid      type t8j0g-recid,
        lv_entry_found type abap_bool.
  if ms_settings-s_t8j0g-debreced <> cv_recid and
     ms_settings-s_t8j0g-crerecid <> cv_recid.
    loop at ms_settings-t_t8j0g into ms_settings-s_t8j0g
      where itemtype = iv_item
      and recid      = cv_recid.
      if ms_settings-s_t8j0g-debreced = cv_recid.
        if lv_entry_found <> 'X'.
          lv_recid = ms_settings-s_t8j0g-recid.
          lv_entry_found = 'X'.
        else.
          clear lv_recid.
          message e241(g5) with cv_recid into mv_message_text.
          save_sy_message( ).
          exit.
        endif.
      elseif ms_settings-s_t8j0g-debreced is initial.
        clear lv_recid.
        message e238(g5) with cv_recid into mv_message_text.
        save_sy_message( ).
      endif.
    endloop.
  else.
    lv_recid = ms_settings-s_t8j0g-recid.
  endif.
  cv_recid = lv_recid.
endmethod.
```

GET_SETTINGS

Description: Get the company code settings

Inst. Method

```
method get_settings.
  data: lo_jva_settings type ref to if_jva_settings,
        lv_jva_active  type abap_bool,
        lv_error        type abap_bool.
  ms_settings-bukrs = ms_progpars-bukrs.
  try.
    lo_jva_settings = cl_jva_settings=>get_instance( ms_progpars-bukrs ).
    lv_jva_active = lo_jva_settings->is_jva_active( ).
  catch cx_jva_settings.
    lv_jva_active = abap_false.
  endtry.
  if lv_jva_active = abap_false.
    message e579(gj) with ms_progpars-bukrs into mv_message_text.
    save_sy_message( ).
    return.
  endif.
endmethod.
```

```

endif.
ms_settings-s_t001 = lo_jva_settings->ms_t001.
ms_settings-s_t8jz = lo_jva_settings->ms_t8jz.
select single * from t8jv into ms_settings-s_t8jv
      where bukrs = ms_progpars-bukrs
      and vname = ms_progpars-vname.
* Get the production-month settings
if ms_settings-s_t8jz-pm_act = 'X'.
    ms_settings-eg_from_pm = ms_settings-s_t8jz-pm_eg.
else.
    clear ms_settings-eg_from_pm.
endif.
* Get the ledger to read data from ACDOCA
ms_settings-rldnr = lo_jva_settings->get_ledger( ).
* Get the ACDOCA currencies
lo_jva_settings->get_currency_info( importing es_curr_info =
ms_settings-s_curr_info ).
ms_settings-t_recid_billable = lo_jva_settings->get_billable_recind_range( ).
get_posting_rules( exporting
      iv_bukrs      = ms_progpars-bukrs
      iv_bmethod    = ms_settings-s_t8jv-bmethod
      iv_function    = 'EQAD'
      changing
      cv_error      = lv_error ).
"Get the fiscal year for postings
call function 'DETERMINE_PERIOD'
      exporting
      date          = ms_progpars-budat
      version       = ms_settings-s_t001-periv
      importing
      year          = ms_settings-gjahr_p
      exceptions
      period_in_not_valid = 1
      period_not_assigned = 2
      version_undefined  = 3
      error_message      = 4
      others             = 8.
if sy-subrc <> 0.
    message e108(glofaa_gb) with ms_settings-s_t001-periv ms_progpars-budat
      into mv_message_text.
    save_sy_message( ).
endif.
"If a start date is set for JVA on ACDOCA, use the appropriate switch view
"so that data can also be retrieved from the JVS01 table for previous years
if cl_jva_switch=>get_instance( )->get_jva_on_acdoca_start_date( ) is not
initial.
    ms_settings-source_table = 'JV_ACDOCA_JVS01_SWITCH'.
else.
    ms_settings-source_table = 'ACDOCA'.
endif.
endmethod.

```

INITIALIZE_MAIN_OBJECTS

Description: Initialization of global objects
Inst. Method

```
method initialize_main_objects.  
  data: lv_period      type monat,  
        lv_spool_title type string.  
  lv_spool_title = text-001.  
  lv_period = ms_progpars-period.  
* Posting class  
  mo_jva_post_acdoca = new cl_jva_post_acdoca( ).  
* Output handler for ALV or WRITE commands  
  mo_output = new cl_jva_output( ).  
* Class for partner share calculations  
  mo_partner_shares = new cl_jva_partner_shares( ).  
* Instantiate the cutback class  
  mo_cutback = new cl_jva_cutback( ).  
* Message handlers  
  mo_application_log = cl_jva_message_factory=>get_output(  
    iv_output_type =  
cl_jva_message_factory=>out_application_log  
    iv_bal_object =  
if_jva_message_output=>gc_bal_object-jva  
    iv_bal_subobject =  
if_jva_message_output=>gc_bal_subobject-general  
    iv_bal_save_all_to_db = abap_true ).  
*   mo_message_output = cl_jva_message_factory=>get_output(  
*   iv_output_type =  
cl_jva_message_factory=>out_spool_error  
*   io_spool_handler = mo_spool_handler  
*   iv_lst_disp_all_columns = abap_true ).  
  mo_message_collector = cl_jva_message_factory=>get_message_collector(  
    it_output_handler = value #( ( mo_application_log )  
  ) ). "( mo_message_output ) ) ).  
  mo_output_spool = new cl_jva_equity_adjust_output_sp( ).  
endmethod.
```

MAKE_DATE_CLAUSE_FOR_SELECT

Description: Make the date clause for ACDOCA selects
Inst. Method

Returning parameter

VALUE(RV_DATE_CLAUSE) TYPE STRING

```
method make_date_clause_for_select.  
  data: lv_docdate_clause type string,  
        lv_prodper_clause type string,  
        lv_poper_clause   type string,  
        lv_from_poper      type acdoca-poper,  
        lv_to_poper        type acdoca-poper,  
        lv_prodper_initial type acdoca-prodper.  
  if ms_progpars-farm_in_out = abap_true.  
    if ms_progpars-inception_to_date = abap_true.
```

```

        "lv_from_poper = '000'.
        lv_from_poper = '001'.
    else.
        lv_from_poper = ms_progpars-from_period.
    endif.
    lv_to_poper    = ms_progpars-to_period.
    if ms_progpars-inception_to_date = abap_true.
        rv_date_clause &&= |( ryear < '{ ms_progpars-to_year }' AND ( poper >= '001'
AND poper <= '012' ) )| ##NO_TEXT.
        rv_date_clause &&= | OR | ##NO_TEXT.
        rv_date_clause &&= |( ryear = '{ ms_progpars-to_year }'    AND poper >= '001'
AND poper <= '{ lv_to_poper }' )| ##NO_TEXT.
    else.
        if ms_progpars-from_year = ms_progpars-to_year.
            rv_date_clause = | ryear = '{ ms_progpars-to_year }' AND ( poper >= '{
lv_from_poper }' AND poper <= '{ lv_to_poper }' )| #
        else.
            rv_date_clause = |( ryear = '{ ms_progpars-from_year }' AND ( poper >= '{
lv_from_poper }' AND poper <= '012' ) )| ##NO_
            rv_date_clause &&= | OR | ##NO_TEXT.
            rv_date_clause &&= |( ryear > '{ ms_progpars-from_year }' AND ryear > '{
ms_progpars-to_year }' AND ( poper >= '001' AND p
            rv_date_clause &&= | OR | ##NO_TEXT.
            rv_date_clause &&= |( ryear = '{ ms_progpars-to_year }'    AND poper >=
'001' AND poper <= '{ lv_to_poper }' )| ##NO_TEXT.
        endif.
    endif.
else.
*   The items must only be taken from the real periods 1 to 12
    lv_poper_clause = |( poper >= '001' AND poper <= '012' )| ##NO_TEXT.
    lv_docdate_clause = |( bldat >= '{ ms_progpars-frdate }' AND bldat <= '{
ms_progpars-todate }' )| ##NO_TEXT.
    if ms_settings-s_t8jz-pm_act = 'X' and ms_settings-s_t8jz-pm_eg = 'X'.
        "rv_date_clause = | prodper >= ms_progpars-frdate AND prodper <=
ms_progpars-todate| ##NO_TEXT.
        rv_date_clause = |( ( prodper >= '{ ms_progpars-frdate }' AND prodper <= '{
ms_progpars-todate }' ) OR ( prodper = '{ lv_pro
    else.
        rv_date_clause = lv_docdate_clause.
    endif.
    rv_date_clause &&= | AND | && lv_poper_clause.
endif.
endmethod.
```

MAKE_DOC_INFO

Description: Create the document info
Inst. Method

Importing parameter

- IV_BELNR TYPE ACDOCA-BELNR
- IV_BUZEI TYPE ACDOCA-BUZEI
- IV_GJAHR TYPE ACDOCA-GJAHR (Fiscal Year)

Changing parameter

- CV_DOCINFO TYPE SSTRING

```
method make_doc_info.  
  if iv_belnr is initial.  
    clear cv_docinfo.  
    return.  
  endif.  
  concatenate iv_belnr '-' iv_buzei '-' iv_gjahr  
              into cv_docinfo.  
endmethod.
```

POST_ADJUSTMENT_DOCUMENT

Description: Post the equity change document
Inst. Method

Importing parameter

```
IT_ACDOCA_CHECK TYPE FINST_ACDOCA (Universal Journal Entry Line Items)  
IT_ACDOCA_POST TYPE FINST_ACDOCA (ACDOCA Unified Journal Entry Line Items)  
IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))  
IV_INTCO TYPE ABAP_BOOL
```

Changing parameter

```
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)  
CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)  
CV_FATAL_ERROR TYPE ABAP_BOOL  
CV_ERROR_TEXT TYPE STRING
```

```
method post_adjustment_document.  
  data: lt_acdoc_header_posted type finst_acdoc_header,  
        lt_acdoc_items_posted type finst_acdoc_item,  
        lo_message_collector type ref to if_jva_message_collection,  
        lv_belnr_new type acdoca-belnr.  
  if cv_fatal_error <> abap_true.  
    "The update tasks must be executed locally to ensure that  
    "The commit-work-and-wait command works properly before the  
    "cutback adjustments are made  
    if ms_progpars-analysis_only = abap_false and  
      ms_progpars-test = abap_false.  
      set update task local.  
    endif.  
    if ct_accit[] is initial.  
      mo_jva_post_acdoca->post_adjustment( exporting  
                                             it_acdoca =  
it_acdoca_post  
                                             iv_budat =  
ms_progpars-budat  
                                             iv_jvfunc = iv_jvfunc  
                                             iv_rldnr =  
ms_settings-rldnr  
                                             iv_analysis_only =  
ms_progpars-analysis_only  
                                             iv_test =  
ms_progpars-test  
importing  
et_acdoc_header_posted =  
lt_acdoc_header_posted  
et_acdoc_items_posted =  
lt_acdoc_items_posted
```

```

                                eo_message_collector   =
lo_message_collector
                                ev_belnr              = lv_belnr_new
                                ev_fatal_error         =
cv_fatal_error ).
    if cv_fatal_error = 'X'.
        mo_message_collector->add_collection( lo_message_collector ).
        loop at mo_message_collector->get_access( )->get_messages( ) into
data(ls_error_message).
        cv_error_text = cl_jva_util=>get_message_text( iv_msgid =
ls_error_message-msgid
                                iv_msgno =
ls_error_message-msgno
                                iv_msgv1 =
ls_error_message-msgv1
                                iv_msgv2 =
ls_error_message-msgv2
                                iv_msgv3 =
ls_error_message-msgv3
                                iv_msgv4 =
ls_error_message-msgv4 ).
        concatenate ls_error_message-msgid ls_error_message-msgno cv_error_text
into cv_error_text
        separated by space.
    exit.
endloop.
endif.
else.
    post-fi-doc( exporting
                    iv_testrun      = ms_progpar-test
                    changing
                    ct_accit        = ct_accit
                    ct_accr         = ct_accr
                    cv_belnr        = lv_belnr_new
                    cv_critical_error = cv_fatal_error
                    cv_error_text   = cv_error_text ).
endif.
endif.
* Save posting info for printing
save_adjustment_doc_info( it_acdoca_check = it_acdoca_check
                            iv_jvfunc      = iv_jvfunc
                            iv_intco       = iv_intco
                            iv_posttype    = 'AD'
                            it_acdoc_items_posted = lt_acdoc_items_posted
                            it_accit_posted = ct_accit
                            it_acdoca      = it_acdoca_post
                            iv_belnr_new   = lv_belnr_new
                            iv_posting_error = cv_fatal_error
                            iv_error_text  = cv_error_text ).

endmethod.

```

POST_CHANGE_DOCUMENT

Description: Post the equity change document
Inst. Method

Importing parameter

IS_ACDOCA_CHECK TYPE GTY_S_ACDOCA_CHECK
IV_JVFUNC TYPE JV_FUNC (JVA Activity (Joint Venture Accounting))
IV_VNAME_NEW TYPE JV_NAME (Joint venture)
IV_EGRUP_NEW TYPE JV_EGROUP (Equity group)

Changing parameter

CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)

```
method post_change_document.  
  data: ls_acdoca          type acdoca,  
        ls_acdoca_complete type acdoca,  
        lt_acdoc_header_posted type finst_acdoc_header,  
        lt_acdoc_items_posted type finst_acdoc_item,  
        ls_acdoc_items_posted type fins_acdoc_item,  
        lo_message_collector type ref to if_jva_message_collection,  
        lv_belnr_new         type acdoca-belnr,  
        lv_error_text        type string,  
        lv_fatal_error       type abap_bool,  
        ls_acdoca_cb         type jva_cb_acdoca,  
        lv_subrc             type sy-subrc.  
  move-corresponding is_acdoca_check to ls_acdoca ##ENH_OK.  
  if is_acdoca_check-jv_docnr is not initial.  
    "Use the WORK_ITEM_ID fields to store the JVS01 doc number  
    "This will only happen in migrated systems  
    ls_acdoca-work_item_id = is_acdoca_check-jv_docnr.  
  endif.  
  "The update tasks must be executed locally to ensure that  
  "The commit-work-and-wait command works properly before the  
  "cutback adjustments are made  
  if ms_progpars-analysis_only = abap_false and  
    ms_progpars-test           = abap_false.  
    set update task local.  
  endif.  
  mo_jva_post_acdoca->post_equity_change( exporting  
                                           iv_jvfunc      = iv_jvfunc  
                                           iv_mode        = 'C'  
                                           is_acdoca      = ls_acdoca  
                                           iv_vname_new   = iv_vname_new  
                                           iv_egrup_new   = iv_egrup_new  
                                           iv_etype_new   = space  
                                           iv_rldnr       = ms_settings-rldnr  
                                           iv_budat       = ms_progpars-budat  
                                           iv_analysis_only =  
ms_progpars-analysis_only  
                                           iv_test        = ms_progpars-test  
importing  
  es_acdoca_complete           =  
ls_acdoca_complete  
  et_acdoc_header_posted =  
lt_acdoc_header_posted
```

```

lt_acdoc_items_posted      et_acdoc_items_posted =

                           ev_belnr          = lv_belnr_new
                           ev_fatal_error     = lv_fatal_error
                           eo_message_collector =

lo_message_collector ).
  if lv_fatal_error = abap_true.
    mo_message_collector->add_collection( lo_message_collector ).
    loop at mo_message_collector->get_access( )->get_messages( ) into
data(ls_error_message).
    lv_error_text = cl_jva_util=>get_message_text( iv_msgid =
ls_error_message-msgid
                                                    iv_msgno =
ls_error_message-msgno
                                                    iv_msgv1 =
ls_error_message-msgv1
                                                    iv_msgv2 =
ls_error_message-msgv2
                                                    iv_msgv3 =
ls_error_message-msgv3
                                                    iv_msgv4 =
ls_error_message-msgv4 ).
    concatenate ls_error_message-msgid ls_error_message-msgno lv_error_text
               into lv_error_text
               separated by space.

    exit.
  endloop.
endif.
if lv_fatal_error = abap_true or
ms_progpars-test = abap_true or
ms_progpars-analysis_only = abap_true.
  add 1 to mv_belnr_test.
  lv_belnr_new = |TEST| && mv_belnr_test  ##NO_TEXT.
endif.
* Save posting info for printing
save_change_doc_info( lt_acdoc_header_posted = lt_acdoc_header_posted
                     lt_acdoc_items_posted  = lt_acdoc_items_posted
                     iv_jvfunc              = iv_jvfunc
                     is_acdoca              = ls_acdoca_complete
                     iv_belnr_new           = lv_belnr_new
                     iv_egrup_new           = iv_egrup_new
                     iv_posting_error       = lv_fatal_error
                     iv_error_text          = lv_error_text ).
* In case of a successful posting, add the item to the cutback table
if lv_fatal_error <> abap_true or
ms_progpars-test = abap_true.
* Add reversal line with old equity group and reversed amounts
move-corresponding ls_acdoca_complete to ls_acdoca_cb  ##ENH_OK.
multiply: ls_acdoca_cb-wsl by -1,
          ls_acdoca_cb-hsl by -1,
          ls_acdoca_cb-ksl by -1,
          ls_acdoca_cb-osl by -1,
          ls_acdoca_cb-vsl by -1,
          ls_acdoca_cb-bsl by -1,

```

```

        ls_acdoca_cb-csl by -1,
        ls_acdoca_cb-dsl by -1,
        ls_acdoca_cb-esl by -1,
        ls_acdoca_cb-fsl by -1,
        ls_acdoca_cb-gsl by -1.
*   Get the recovery indicator of the reversal line
    read table lt_acdoc_items_posted into ls_acdoc_items_posted index 1.
    ls_acdoca_cb-rcid = ls_acdoc_items_posted-rcid.
    make_doc_info( exporting
                    iv_belnr = lv_belnr_new
                    iv_buzei = 1
                    iv_gjahr = ls_acdoc_items_posted-gjahr
                    changing
                        cv_docinfo = ls_acdoca_cb-docinfo ).
*   Append ACDOCA line to the table for cutback correction
    append ls_acdoca_cb to ct_acdoca_cb.
*   Add reposting line with new equity group and original amounts
    move-corresponding ls_acdoca_complete to ls_acdoca_cb  ##ENH_OK.
    ls_acdoca_cb-egrup = iv_egrup_new.
*   Get the recovery indicator of the reposting line
    read table lt_acdoc_items_posted into ls_acdoc_items_posted index 2.
    ls_acdoca_cb-rcid = ls_acdoc_items_posted-rcid.
    make_doc_info( exporting
                    iv_belnr = lv_belnr_new
                    iv_buzei = 2
                    iv_gjahr = ls_acdoc_items_posted-gjahr
                    changing
                        cv_docinfo = ls_acdoca_cb-docinfo ).
*   Append ACDOCA line to the table for cutback correction
    append ls_acdoca_cb to ct_acdoca_cb.
endif.
endmethod.
```

POST_FI_DOC

Description: Post the FI document
Inst. Method

Importing parameter

IV_TESTRUN TYPE ABAP_BOOL

Changing parameter

CT_ACCCR TYPE ACCCR_T (Accounting interface: Currency information)
CT_ACCIT TYPE ACCIT_T (Accounting Interface: Item Information)
CV_BELNR TYPE BELNR_D (Accounting Document Number)
CV_CRITICAL_ERROR TYPE ABAP_BOOL
CV_ERROR_TEXT TYPE STRING

```
method post_fi_doc.
    data: lt_mesg          type standard table of smesgx,
          lv_error_count   type sy-tabix,
          lv_max_severity  type sy-subrc,
          lv_handler_active type boole_d,
          lv_subrc         type sy-subrc,
          lt_accit_post     type standard table of accit,
          lt_acccr_post     type standard table of acccr,
```

```

        lt_acchd      type standard table of acchd,
        lt_acctx      type standard table of accbset,
        lt_accit_ext  type standard table of accit_extension.
describe table ct_accit lines sy-tfilll.
if sy-tfilll = 0.
    exit.
endif.
* Add line to ACCHD table
add_fidoc_header( changing ct_acchd = lt_acchd ).
if ms_progpars-analysis_only <> abap_true.
    lt_accit_post[] = ct_accit[].
    lt_accctr_post[] = ct_accctr[].
    mo_output->jv_direct_input( exporting
                                iv_mode      = '1'
                                iv_nodata    = '/'
                                iv_testrun   = iv_testrun
                                importing
                                ev_belnr     = cv_belnr
                                ev_subrc    = lv_subrc
                                changing
                                ct_acchd    = lt_acchd
                                ct_accit    = lt_accit_post
                                ct_accctr   = lt_accctr_post
                                ct_acctx    = lt_acctx
                                ct_accit_ext = lt_accit_ext ).

    if lv_subrc = 2 or lv_subrc = 4.
        cv_critical_error = abap_true.
        message id sy-msgid type sy-msgty number sy-msgno
            with sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4
            into cv_error_text.
        save_message( iv_type = sy-msgty
                      iv_class = sy-msgid
                      iv_number = sy-msgno
                      iv_var1 = sy-msgv1
                      iv_var2 = sy-msgv2
                      iv_var3 = sy-msgv3
                      iv_var4 = sy-msgv4 ).
    endif.
call function 'MESSAGES_COUNT'
    importing
        count                = lv_error_count
        max_severity         = lv_max_severity
        e_handler_active     = lv_handler_active
    exceptions
        inconsistent_range   = 1
        inconsistent_range_severity = 2
        error_message        = 3
        others                = 4.
if sy-subrc <> 0.
    clear lv_error_count.
endif.
if lv_error_count > 0.
    call function 'MESSAGE_EXPORT_IMPORT'
        exceptions

```

```
        empty      = 1
        not_active = 2
        others     = 3.
if sy-subrc = 0.
    import xmesg to lt_mesg
        from memory id 'TEMP_MESG_EXP_IMP'.
    loop at lt_mesg into data(ls_mesg).
        if ls_mesg-msgty = 'A' or
           ls_mesg-msgty = 'E' or
           ls_mesg-msgty = 'X'.
            cv_critical_error = abap_true.
            message id ls_mesg-txtnr type ls_mesg-msgty number ls_mesg-arbgb
                with ls_mesg-msgv1 ls_mesg-msgv2 ls_mesg-msgv3 ls_mesg-msgv4
                into cv_error_text.
            save_message( iv_type = ls_mesg-msgty
                iv_class = ls_mesg-arbgb
                iv_number = ls_mesg-txtnr
                iv_var1 = ls_mesg-msgv1
                iv_var2 = ls_mesg-msgv2
                iv_var3 = ls_mesg-msgv3
                iv_var4 = ls_mesg-msgv4 ).
        endif.
    endloop.
endif.
endif.
if lv_subrc <> 0 and cv_critical_error <> abap_true.
    cv_critical_error = abap_true.
    message id sy-msgid type sy-msgty number sy-msgno
        with sy-msgv1 sy-msgv2 sy-msgv3 sy-msgv4
        into cv_error_text.
    save_message( iv_type  = sy-msgty
        iv_class  = sy-msgid
        iv_number = sy-msgno
        iv_var1   = sy-msgv1
        iv_var2   = sy-msgv2
        iv_var3   = sy-msgv3
        iv_var4   = sy-msgv4 ).
endif.
endif.
endmethod.
```

PREPARE_ACCIT_LINE

Description: Prepare an FI doc line

Inst. Method

Importing parameter

VALUE(IS_ACDOCA) TYPE ACDOCA (Universal Journal Entry Line Items)

IV_BUDAT TYPE BUDAT (Posting Date in the Document)

VALUE(IV_BLDAT) TYPE BLDAT (Document Date in Document)

Changing parameter

CS_ACCIT TYPE ACCIT (Accounting Interface: Item Information)

method prepare_accit_line.

clear cs_accit.

```
cs_accit-blart = ms_settings-s_t8j0f-doctyped.    "Document type
cs_accit-awtyp = 'BKPFF'.                        "AW type
cs_accit-mandt = sy-mandt.                        "Client
cs_accit-bukrs = is_acdoca-rbukrs.               "Company code
cs_accit-gjahr = ms_settings-gjahr_p.            "Fiscal year
cs_accit-budat = iv_budat.                        "Posting date
cs_accit-bldat = iv_bldat.                        "Document date
* Venture data
cs_accit-vname = is_acdoca-vname.                "Venture
cs_accit-recid = is_acdoca-recid.                "Recovery indicator
cs_accit-prctr = is_acdoca-prctr.                "Profit center
cs_accit-segment = is_acdoca-segment.            "Profit center
* Cost objects
cs_accit-kostl = is_acdoca-rcntr.                "Cost center
cs_accit-aufnr = is_acdoca-aufnr.                "Order
cs_accit-ps_psp_pnr = is_acdoca-ps_psp_pnr.      "WBS element
cs_accit-nplnr = is_acdoca-nplnr.                "Network
if cs_accit-nplnr is not initial.
  call function 'READ_NETWORK_AUFPL_APLZL'
  exporting
    nplnr          = is_acdoca-nplnr
    vornr          = is_acdoca-nplnr_vorgn
  importing
    aufpl          = cs_accit-aufpl
    aplzl          = cs_accit-aplzl
  exceptions
    not_found      = 1
    error_message  = 2
    others         = 3.
if sy-subrc <> 0.
  clear: cs_accit-aufpl, cs_accit-aplzl.
endif.
endif.
endmethod.
```

PREPARE_CC_ADJUSTMENTS

Description: Adjust the intercompany partner postings
Inst. Method

Importing parameter

```
IT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK
IR_ACDOCA_DYN TYPE REF TO DATA
IT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK
IV_JVFUNC TYPE JV_FUNC (JV Function)
IR_ACDOCA_DYN_POSTED TYPE REF TO DATA
```

```
method prepare_cc_adjustments.
  data: lv_error          type abap_bool,
        ls_acdoca_post    type acdoca,
        ls_acdoca_post_check type acdoca,
        lt_acdoca_post    type standard table of acdoca,
        lv_change_factor  type decfloat16,
        lt_acdoca_check   type standard table of acdoca,
        ls_acdoca_check   type acdoca,
```

```

ls_acdoca_already_posted type acdoca,
lt_diff_share_new       like ms_settings-t_diff_share,
ls_accit                type accit,
lt_accit                type standard table of accit,
lt_acccr                type standard table of acccr,
lv_bktxt                type acchd-bktxt,
lv_buzei                type acdoca-buzei,
lv_fatal_error          type abap_bool,
lv_error_text           type string,
lv_bldat                type bldat,
lv_already_posted       type abap_bool,
lv_posted_info_saved    type abap_bool,
lv_new_partn_as_cashcall type abap_bool value abap_true,
lv_selfclearing          type abap_bool,
lt_sort_fields          type abap_sortorder_tab.
field-symbols: <lt_acdoca_dyn>      type standard table,
               <lt_acdoca_dyn_posted> type standard table.
if it_acdoca_check is not initial.
  assign it_acdoca_check to <lt_acdoca_dyn>.
else.
  assign ir_acdoca_dyn->* to <lt_acdoca_dyn>.
endif.
if it_acdoca_posted is not initial.
  assign it_acdoca_posted to <lt_acdoca_dyn_posted>.
else.
  assign ir_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.
endif.
* Sort data according to print sorting
lt_sort_fields = value #( ( name = 'EGRUP' )
                          ( name = 'KUNNR' )
                          ( name = 'VPTNR' )
                          ( name = 'RWCUR' )
                          ( name = 'WSL' descending = abap_true ) ).
sort <lt_acdoca_dyn> by (lt_sort_fields).
* Collect any new partners into a new table
loop at ms_settings-t_diff_share into data(ls_diff_share_new)
  where eqshare_old = 0
  and eqshare_new <> 0.
  append ls_diff_share_new to lt_diff_share_new.
endloop.
loop at lt_diff_share_new assigning field-symbol(<ls_diff_share_new>).
* Determine the existing partner from which the new partners should be calculated
* First check if any old partner has exactly the same share as the new one
clear <ls_diff_share_new>-partn_old.
loop at ms_settings-t_diff_share into data(ls_diff_share_old)
  where eqshare_old =
<ls_diff_share_new>-eqshare_new.
  <ls_diff_share_new>-partn_old = ls_diff_share_old-partn_old.
  exit.
endloop.
if <ls_diff_share_new>-partn_old is initial.
* If no exact match is found, take the partner with the highest share
* to reduce the chance of big rounding errors
data(lt_diff_share_sorted) = ms_settings-t_diff_share.

```

```
sort lt_diff_share_sorted by eqshare_old descending.
loop at lt_diff_share_sorted into ls_diff_share_old
    where eqshare_old > 0.
*   Check if an amount was posted to that partner (should always be so)
    loop at <lt_acdoca_dyn> assigning field-symbol(<ls_acdoca_dyn>).
        move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.
        if ls_acdoca_check-egrup = ls_diff_share_old-eg_old and
            ls_acdoca_check-kunnr = ls_diff_share_old-partn_old.
            <ls_diff_share_new>-partn_old = ls_diff_share_old-partn_old.
            exit.
        endif.
    endloop.
    if <ls_diff_share_new>-partn_old is not initial.
        exit.
    endif.
endloop.
loop at <lt_acdoca_dyn> assigning <ls_acdoca_dyn>.
    move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.
    if ls_acdoca_check-wsl = 0 and
        ls_acdoca_check-hsl = 0 and
        ls_acdoca_check-ksl = 0 and
        ls_acdoca_check-osl = 0 and
        ls_acdoca_check-vsl = 0 and
        ls_acdoca_check-bsl = 0 and
        ls_acdoca_check-csl = 0 and
        ls_acdoca_check-dsl = 0 and
        ls_acdoca_check-esl = 0 and
        ls_acdoca_check-fsl = 0 and
        ls_acdoca_check-gsl = 0.
        continue.
    endif.
    if ls_acdoca_check-kunnr is not initial.
        data(lv_vptnr) = ls_acdoca_check-kunnr.
    else.
        lv_vptnr = ls_acdoca_check-vptnr.
    endif.
    read table ms_settings-t_diff_share into data(ls_diff_share)
        with key eg_old      = ls_acdoca_check-egrup
            partn_old = lv_vptnr.

    if sy-subrc = 0.
        append ls_acdoca_check to lt_acdoca_check.
    else.
        continue.
    endif.
    clear lv_posted_info_saved.
    clear ls_acdoca_post.
    move-corresponding ls_acdoca_check to ls_acdoca_post.
    if ls_acdoca_post-vptnr is initial.
        ls_acdoca_post-vptnr = lv_vptnr.
    endif.
*   If the partner share in the new equity group is not zero,
*   post to the new equity group, otherwise keep the old one
```

```

        if ls_diff_share-eqshare_new > 0.
            ls_acdoca_post-egrup = ms_progpars-eqnew.
        endif.
*       Get document date based on the given equity group
        cl_jva_util=>derive_docdate_from_egrup( exporting
                                                iv_bukrs          =
ls_acdoca_post-rbukrs
                                                iv_egrup          =
ls_acdoca_post-egrup
                                                iv_vname         =
ls_acdoca_post-vname
                                                iv_date          =
ms_progpars-budat
                                                iv_caller         = 'EA'
changing
                                                co_message_collector =
mo_message_collector
                                                cv_bldat          = lv_bldat
                                                cv_fatal_error    = lv_fatal_error
    ).
        clear ls_acdoca_post-lifnr.
        clear lv_buzei.
*       Add correction lines
        ls_acdoca_post-jvactivity = 'F1'.
        ls_acdoca_post-kunnr = lv_vptnr.
        if ls_diff_share-eqshare_old > 0.
*       Document line 1: Correction of the old partner share
*       -----
            add 1 to lv_buzei.
*       Calculate the amounts for existing partners with changes
            ls_acdoca_post-wsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-wsl
                                                         is_diff_share = ls_diff_share
    ).
            ls_acdoca_post-hsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-hsl
                                                         is_diff_share = ls_diff_share
    ).
            ls_acdoca_post-ksl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-ksl
                                                         is_diff_share = ls_diff_share
    ).
            ls_acdoca_post-osl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-osl
                                                         is_diff_share = ls_diff_share
    ).
            ls_acdoca_post-vsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-vsl
                                                         is_diff_share = ls_diff_share
    ).
            ls_acdoca_post-bsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-bsl
                                                         is_diff_share = ls_diff_share
    ).

```

```

        ls_acdoca_post-csl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-csl                                     is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-dsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-dsl                                     is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-esl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-esl                                     is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-fsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-fsl                                     is_diff_share = ls_diff_share
    ).
        ls_acdoca_post-gsl = calc_cc_correction_amount( iv_amnt_old  =
ls_acdoca_post-gsl                                     is_diff_share = ls_diff_share
    ).
    if ls_acdoca_check-wsl = 0 and
       ls_acdoca_check-hsl = 0 and
       ls_acdoca_check-ksl = 0 and
       ls_acdoca_check-osl = 0 and
       ls_acdoca_check-vsl = 0 and
       ls_acdoca_check-bsl = 0 and
       ls_acdoca_check-csl = 0 and
       ls_acdoca_check-dsl = 0 and
       ls_acdoca_check-esl = 0 and
       ls_acdoca_check-fsl = 0 and
       ls_acdoca_check-gsl = 0.
        continue.
    endif.
    if ls_diff_share-eqshare_new > 0.
        if ms_settings-eg_from_pm = abap_true.
            cl_jva_util=>get_production_date( exporting
                                                iv_caller          = 'EA'
                                                iv_retain_orig_prodper = abap_false
                                                iv_budat            =
ms_progpars-budat
                                                iv_bukrs           =
ms_progpars-bukrs
                                                iv_egrup           =
ls_acdoca_post-egrup
                                                iv_prodper          =
ls_acdoca_post-prodper(6)
                                                iv_vname           =
ls_acdoca_post-vname
                                                changing
                                                cv_validddate      =
ls_acdoca_post-prodper ).
            endif.
        endif.
    *    Check if this item was already posted before

```

```
clear lv_already_posted.
ls_acdoca_post_check = ls_acdoca_post.
loop at <lt_acdoca_dyn_posted> assigning
field-symbol(<ls_acdoca_dyn_posted>).
  move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
  if ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
     ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct and
     ls_acdoca_already_posted-vptnr = ls_diff_share-partnr_new.
    ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
    ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
    ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
    ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
    ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
    ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
    ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
    ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
    ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
    ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
    ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.
    if ls_acdoca_post_check-wsl = 0 and
       ls_acdoca_post_check-hsl = 0 and
       ls_acdoca_post_check-ksl = 0 and
       ls_acdoca_post_check-osl = 0 and
       ls_acdoca_post_check-vsl = 0 and
       ls_acdoca_post_check-bsl = 0 and
       ls_acdoca_post_check-csl = 0 and
       ls_acdoca_post_check-dsl = 0 and
       ls_acdoca_post_check-esl = 0 and
       ls_acdoca_post_check-fsl = 0 and
       ls_acdoca_post_check-gsl = 0.
      lv_already_posted = abap_true.
    endif.
    exit.                  "#EC CI_NOORDER
  endif.
endloop.
if lv_already_posted <> abap_true.
  if lv_posted_info_saved <> abap_true.
    save_cash_call_info( is_acdoca_check = ls_acdoca_check
                        iv_jvfunc       = iv_jvfunc
                        iv_intco        = abap_false ).
    lv_posted_info_saved = abap_true.
  endif.
  append ls_acdoca_post to lt_acdoca_post.
  prepare_accit_line( exporting
                     is_acdoca = ls_acdoca_post
                     iv_budat  = ms_progpars-budat
                     iv_bldat  = lv_bldat
                     changing
                     cs_accit  = ls_accit ).
  add_accit_line_correction( exporting
                           iv_jvfunc       = iv_jvfunc
                           iv_jvactivity  = ls_acdoca_post-jvactivity
                           iv_buzei       = lv_buzei
                           is_acdoca      = ls_acdoca_post
```

```

                                changing
                                cs_accit      = ls_accit
                                ct_accit      = lt_accit
                                ct_accr       = lt_accr
                                cv_fatal_error = lv_fatal_error
                                cv_error_text = lv_error_text ).
*      Document line 2: Offset posting to settlement account
*      -----
      add 1 to lv_buzei.
*      Create line for settlement account (to new equity group)
      ls_acdoca_post-jvactivity = 'F2'.
*      If the partner share in the new equity group is not zero,
*      post to the new equity group, otherwise keep the old one
      if ls_diff_share-eqshare_new > 0.
        ls_acdoca_post-egrup = ms_progpar-s-eqnew.
      endif.
      ls_acdoca_post-racct = ms_progpar-settlement_acc_cc2.
      clear: ls_acdoca_post-kunnr,
             ls_acdoca_post-lifnr.
      ls_acdoca_post-wsl *= -1.
      ls_acdoca_post-hsl *= -1.
      ls_acdoca_post-ksl *= -1.
      ls_acdoca_post-osl *= -1.
      ls_acdoca_post-vsl *= -1.
      ls_acdoca_post-bsl *= -1.
      ls_acdoca_post-csl *= -1.
      ls_acdoca_post-dsl *= -1.
      ls_acdoca_post-esl *= -1.
      ls_acdoca_post-fsl *= -1.
      ls_acdoca_post-gsl *= -1.
      if ls_diff_share-eqshare_new > 0.
        if ms_settings-eg_from_pm = abap_true.
          cl_jva_util=>get_production_date( exporting
                                           iv_caller      = 'EA'
                                           iv_retain_orig_prodper = abap_false
                                           iv_budat       =
ms_progpar-s-budat
                                           iv_bukrs       =
ms_progpar-s-bukrs
                                           iv_egrup       =
ls_acdoca_post-egrup
                                           iv_prodper     =
ls_acdoca_post-prodper(6)
                                           iv_vname      =
ls_acdoca_post-vname
                                           changing
                                           cv_validdat   =
ls_acdoca_post-prodper ).
          endif.
        endif.
      append ls_acdoca_post to lt_acdoca_post.
      add_accit_line_settlement( exporting
                                iv_jvfunc      = iv_jvfunc
                                iv_jvactivity   = ls_acdoca_post-jvactivity

```

```

        iv_buzei      = lv_buzei
        is_acdoca     = ls_acdoca_post
    changing
        cs_accit      = ls_accit
        ct_accit      = lt_accit
        ct_accchr     = lt_accchr
        cv_fatal_error = lv_fatal_error
        cv_error_text = lv_error_text ).
*
    -----
    post_adjustment_document( exporting
        it_acdoca_check = lt_acdoca_check
        it_acdoca_post  = lt_acdoca_post
        iv_jvfunc       = iv_jvfunc
        iv_intco        = abap_false
    changing
        ct_accit      = lt_accit
        ct_accchr     = lt_accchr
        cv_fatal_error = lv_fatal_error
        cv_error_text = lv_error_text ).

    endif.
    refresh: lt_acdoca_post,
             lt_accit, lt_accchr.
    clear: lv_fatal_error, lv_error_text.
    endif.
*
    Create the documents for any new partners
    loop at lt_diff_share_new into ls_diff_share_new.
        if ls_diff_share_new-partn_old <> ls_diff_share-partn_old.
            continue.
        endif.
        if ms_settings-eg_from_pm = abap_true.
            cl_jva_util=>get_production_date( exporting
                iv_caller      = 'EA'
                iv_retain_orig_prodper = abap_false
                iv_budat       =
ms_progpars-budat
                iv_bukrs       =
ms_progpars-bukrs
                iv_egrup       =
ms_progpars-egnew
                iv_prodper     =
ls_acdoca_check-prodper(6)
                iv_vname       =
ls_acdoca_check-vname
                changing
                    cv_validdate =
ls_acdoca_check-prodper ).
            endif.
            clear ls_acdoca_post.
            move-corresponding ls_acdoca_check to ls_acdoca_post.
            if ls_acdoca_post-vptnr is initial.
                ls_acdoca_post-vptnr = lv_vptnr.
            endif.
            clear lv_buzei.
*
            Document line 1: Amount with new partner share

```

```

* -----
  add 1 to lv_buzei.
  ls_acdoca_post-jvactivity = 'F1'.
* Calculate the change factor based on a given equity share of an old partner
(can be any)
  lv_change_factor = ls_diff_share_new-eqshare_new
                    / ls_diff_share-eqshare_old.
* Calculate the share of the new partner
  multiply ls_acdoca_post-wsl by lv_change_factor.
  multiply ls_acdoca_post-hsl by lv_change_factor.
  multiply ls_acdoca_post-ksl by lv_change_factor.
  multiply ls_acdoca_post-osl by lv_change_factor.
  multiply ls_acdoca_post-vsl by lv_change_factor.
  multiply ls_acdoca_post-bsl by lv_change_factor.
  multiply ls_acdoca_post-csl by lv_change_factor.
  multiply ls_acdoca_post-dsl by lv_change_factor.
  multiply ls_acdoca_post-esl by lv_change_factor.
  multiply ls_acdoca_post-fsl by lv_change_factor.
  multiply ls_acdoca_post-gsl by lv_change_factor.
  if ls_acdoca_check-wsl = 0 and
    ls_acdoca_check-hsl = 0 and
    ls_acdoca_check-ksl = 0 and
    ls_acdoca_check-osl = 0 and
    ls_acdoca_check-vsl = 0 and
    ls_acdoca_check-bsl = 0 and
    ls_acdoca_check-csl = 0 and
    ls_acdoca_check-dsl = 0 and
    ls_acdoca_check-esl = 0 and
    ls_acdoca_check-fsl = 0 and
    ls_acdoca_check-gsl = 0.
    continue.
  endif.
  ls_acdoca_post-egrup = ms_progpars-eqnew.
  ls_acdoca_post-vptnr = ls_diff_share_new-partn_new.
  ls_acdoca_post-kunnr = ls_diff_share_new-partn_new.
* Check if this item was already posted before
  clear lv_already_posted.
  ls_acdoca_post_check = ls_acdoca_post.
  loop at <lt_acdoca_dyn_posted> assigning <ls_acdoca_dyn_posted>.
    move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
    if ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
      ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct and
      ls_acdoca_already_posted-vptnr = ls_diff_share_new-partn_new.
      ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
      ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
      ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
      ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
      ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
      ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
      ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
      ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
      ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
      ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
      ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.

```

```
if ls_acdoca_post_check-wsl = 0 and
  ls_acdoca_post_check-hsl = 0 and
  ls_acdoca_post_check-ksl = 0 and
  ls_acdoca_post_check-osl = 0 and
  ls_acdoca_post_check-vsl = 0 and
  ls_acdoca_post_check-bsl = 0 and
  ls_acdoca_post_check-csl = 0 and
  ls_acdoca_post_check-dsl = 0 and
  ls_acdoca_post_check-esl = 0 and
  ls_acdoca_post_check-fsl = 0 and
  ls_acdoca_post_check-gsl = 0.
  lv_already_posted = abap_true.
  exit.                                "#EC CI_NOORDER
endif.
endif.
endloop.
if lv_already_posted <> abap_true.
  if lv_posted_info_saved <> abap_true.
    save_cash_call_info( is_acdoca_check = ls_acdoca_check
                        iv_jvfunc       = iv_jvfunc
                        iv_intco        = abap_false ).
    lv_posted_info_saved = abap_true.
  endif.
  append ls_acdoca_post to lt_acdoca_post.
  prepare_accit_line( exporting
                    is_acdoca = ls_acdoca_post
                    iv_budat  = ms_progpars-budat
                    iv_bldat  = lv_bldat
                    changing
                    cs_accit  = ls_accit ).
  if lv_new_partn_as_cashcall = abap_true.
    add_accit_line_cashcall( exporting
                          is_acdoca      = ls_acdoca_post
                          iv_jvfunc      = iv_jvfunc
                          iv_jvactivity  = ls_acdoca_post-jvactivity
                          iv_buzei       = lv_buzei
                          iv_selfclearing = lv_selfclearing
                          changing
                          cs_accit       = ls_accit
                          ct_accit       = lt_accit
                          ct_accrr       = lt_accrr
                          cv_fatal_error = lv_fatal_error
                          cv_error_text  = lv_error_text ).
  else.
    add_accit_line_correction( exporting
                              is_acdoca      = ls_acdoca_post
                              iv_jvfunc      = iv_jvfunc
                              iv_jvactivity  = ls_acdoca_post-jvactivity
                              iv_buzei       = lv_buzei
                              changing
                              cs_accit       = ls_accit
                              ct_accit       = lt_accit
                              ct_accrr       = lt_accrr
                              cv_fatal_error = lv_fatal_error
```

```

                                cv_error_text = lv_error_text ).
endif.
Document line 2: Offset posting to settlement account
*
* -----
add 1 to lv_buzei.
*
Create line for settlement account (to new equity group)
ls_acdoca_post-jvactivity = 'F2'.
ls_acdoca_post-egrup = ms_progpars-eqnew.
ls_acdoca_post-racct = ms_progpars-settlement_acc_cc2.
clear: ls_acdoca_post-kunnr,
       ls_acdoca_post-lifnr.
ls_acdoca_post-wsl *= -1.
ls_acdoca_post-hsl *= -1.
ls_acdoca_post-ksl *= -1.
ls_acdoca_post-osl *= -1.
ls_acdoca_post-vsl *= -1.
ls_acdoca_post-bsl *= -1.
ls_acdoca_post-csl *= -1.
ls_acdoca_post-dsl *= -1.
ls_acdoca_post-esl *= -1.
ls_acdoca_post-fsl *= -1.
ls_acdoca_post-gsl *= -1.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_settlement( exporting
                           iv_jvfunc      = iv_jvfunc
                           iv_jvactivity   = ls_acdoca_post-jvactivity
                           iv_buzei       = lv_buzei
                           is_acdoca      = ls_acdoca_post
                           changing
                           cs_accit        = ls_accit
                           ct_accit        = lt_accit
                           ct_accctr       = lt_accctr
                           cv_fatal_error = lv_fatal_error
                           cv_error_text  = lv_error_text ).
*
* -----
post_adjustment_document( exporting
                           it_acdoca_check = lt_acdoca_check
                           it_acdoca_post  = lt_acdoca_post
                           iv_jvfunc       = iv_jvfunc
                           iv_intco        = abap_false
                           changing
                           ct_accit        = lt_accit
                           ct_accctr       = lt_accctr
                           cv_fatal_error = lv_fatal_error
                           cv_error_text  = lv_error_text ).

endif.
refresh: lt_acdoca_post,
        lt_accit, lt_accctr.
clear: lv_fatal_error, lv_error_text.
endloop.
refresh lt_acdoca_check.
endloop.
endmethod.

```

PREPARE_CC_ADJUSTMENTS_INTCO

Description: Adjust the intercompany partner postings

Inst. Method

Importing parameter

IT_ACDOCA_CHECK TYPE GTY_T_ACDOCA_CHECK

IR_ACDOCA_DYN TYPE REF TO DATA

IT_ACDOCA_POSTED TYPE GTY_T_ACDOCA_CHECK

IV_JVFUNC TYPE JV_FUNC (JV Function)

IR_ACDOCA_DYN_POSTED TYPE REF TO DATA

method prepare_cc_adjustments_intco.

```
data: lv_error          type abap_bool,
      ls_acdoca_post     type acdoca,
      ls_acdoca_post_check type acdoca,
      lt_acdoca_post     type standard table of acdoca,
      lv_change_factor   type decfloat16,
      lt_acdoca_check     type standard table of acdoca,
      ls_acdoca_check     type acdoca,
      ls_acdoca_already_posted type acdoca,
      ls_t8jo            type t8jo,
      lv_lifnr           type kna1-lifnr,
      lv_buzei           type acdoca-buzei,
      ls_accit           type accit,
      lt_accit           type standard table of accit,
      lt_acccr           type standard table of acccr,
      lv_bldat           type bldat,
      lv_fatal_error     type abap_bool,
      lv_error_text      type string,
      lv_already_posted  type abap_bool,
      lt_sort_fields     type abap_sortorder_tab.
```

```
field-symbols: <lt_acdoca_dyn>      type standard table,
                <lt_acdoca_dyn_posted> type standard table.
```

if it_acdoca_check is not initial.

assign it_acdoca_check to <lt_acdoca_dyn>.

else.

assign ir_acdoca_dyn->* to <lt_acdoca_dyn>.

endif.

if it_acdoca_posted is not initial.

assign it_acdoca_posted to <lt_acdoca_dyn_posted>.

else.

assign ir_acdoca_dyn_posted->* to <lt_acdoca_dyn_posted>.

endif.

* Sort data according to print sorting

```
lt_sort_fields = value #( ( name = 'EGRUP' )
                          ( name = 'LIFNR' )
                          ( name = 'VPTNR' )
                          ( name = 'RWCUR' ) ).
```

sort <lt_acdoca_dyn> by (lt_sort_fields).

loop at <lt_acdoca_dyn> assigning field-symbol(<ls_acdoca_dyn>).

move-corresponding <ls_acdoca_dyn> to ls_acdoca_check.

if ls_acdoca_check-wsl = 0 and

ls_acdoca_check-hsl = 0 and

```

ls_acdoca_check-ksl = 0 and
ls_acdoca_check-osl = 0 and
ls_acdoca_check-vsl = 0 and
ls_acdoca_check-bsl = 0 and
ls_acdoca_check-csl = 0 and
ls_acdoca_check-dsl = 0 and
ls_acdoca_check-esl = 0 and
ls_acdoca_check-fsl = 0 and
ls_acdoca_check-gsl = 0.
continue.
endif.
if ls_acdoca_check-vptnr is not initial.
  data(lv_vptnr) = ls_acdoca_check-vptnr.
else.
  lv_vptnr = ls_acdoca_check-lifnr.
endif.
read table ms_settings-t_diff_share_intco into data(ls_diff_share)
                                         with key intcocd_old =
ls_acdoca_check-rbukrs
                                         intcompegp_old =
ls_acdoca_check-egrup
                                         partn_old = lv_vptnr.
  if sy-subrc = 0.
    append ls_acdoca_check to lt_acdoca_check.
  else.
    continue.
  endif.
*   Get document date based on the new equity group
  cl_jva_util=>derive_docdate_from_egrup( exporting
                                         iv_bukrs =
ls_acdoca_check-rbukrs
                                         iv_egrup =
ls_diff_share-intcompegp_new
                                         iv_vname =
ls_acdoca_check-vname
                                         iv_date =
ms_progpars-budat
                                         iv_caller = 'EA'
                                         changing
                                         co_message_collector =
mo_message_collector
                                         cv_bldat = lv_bldat
                                         cv_fatal_error = lv_fatal_error
).
  clear lv_buzei.
  if ls_acdoca_check-vptnr is not initial.
    lv_lifnr = get_intco_vendor( exporting
                                iv_bukrs = ls_diff_share-intcocd_old
                                iv_partn = ls_acdoca_check-vptnr ).
  else.
    lv_lifnr = ls_acdoca_check-lifnr.
  endif.
*   Document line 1: Nonop cash call reverse of old equity group
*   -----

```

```
add 1 to lv_buzei.
clear ls_acdoca_post.
move-corresponding ls_acdoca_check to ls_acdoca_post.
if ls_acdoca_post-vptnr is initial.
    ls_acdoca_post-vptnr = lv_vptnr.
endif.
clear ls_acdoca_post-kunnr.
ls_acdoca_post-jvactivity = 'F1'.
ls_acdoca_post-lifnr = lv_lifnr.
ls_acdoca_post-wsl *= -1.
ls_acdoca_post-hsl *= -1.
ls_acdoca_post-ksl *= -1.
ls_acdoca_post-osl *= -1.
ls_acdoca_post-vsl *= -1.
ls_acdoca_post-bsl *= -1.
ls_acdoca_post-csl *= -1.
ls_acdoca_post-dsl *= -1.
ls_acdoca_post-esl *= -1.
ls_acdoca_post-fsl *= -1.
ls_acdoca_post-gsl *= -1.
*
Check if this item was already posted before
clear lv_already_posted.
ls_acdoca_post_check = ls_acdoca_post.
loop at <lt_acdoca_dyn_posted> assigning field-symbol(<ls_acdoca_dyn_posted>).
    move-corresponding <ls_acdoca_dyn_posted> to ls_acdoca_already_posted.
    if ls_acdoca_already_posted-rbukrs = ls_acdoca_post_check-rbukrs and
        ls_acdoca_already_posted-vname = ls_acdoca_post_check-vname and
        ls_acdoca_already_posted-egrup = ls_acdoca_post_check-egrup and
        ls_acdoca_already_posted-vptnr = ls_acdoca_post_check-vptnr and
        ls_acdoca_already_posted-racct = ls_acdoca_post_check-racct.
        ls_acdoca_post_check-wsl -= ls_acdoca_already_posted-wsl.
        ls_acdoca_post_check-hsl -= ls_acdoca_already_posted-hsl.
        ls_acdoca_post_check-ksl -= ls_acdoca_already_posted-ksl.
        ls_acdoca_post_check-osl -= ls_acdoca_already_posted-osl.
        ls_acdoca_post_check-vsl -= ls_acdoca_already_posted-vsl.
        ls_acdoca_post_check-bsl -= ls_acdoca_already_posted-bsl.
        ls_acdoca_post_check-csl -= ls_acdoca_already_posted-csl.
        ls_acdoca_post_check-dsl -= ls_acdoca_already_posted-dsl.
        ls_acdoca_post_check-esl -= ls_acdoca_already_posted-esl.
        ls_acdoca_post_check-fsl -= ls_acdoca_already_posted-fsl.
        ls_acdoca_post_check-gsl -= ls_acdoca_already_posted-gsl.
    if ls_acdoca_post_check-wsl = 0 and
        ls_acdoca_post_check-hsl = 0 and
        ls_acdoca_post_check-ksl = 0 and
        ls_acdoca_post_check-osl = 0 and
        ls_acdoca_post_check-vsl = 0 and
        ls_acdoca_post_check-bsl = 0 and
        ls_acdoca_post_check-csl = 0 and
        ls_acdoca_post_check-dsl = 0 and
        ls_acdoca_post_check-esl = 0 and
        ls_acdoca_post_check-fsl = 0 and
        ls_acdoca_post_check-gsl = 0.
        lv_already_posted = abap_true.
    exit.
"#EC CI_NOORDER
```

```

        endif.
    endif.
endloop.
if lv_already_posted = abap_true.
    continue.
endif.
save_cash_call_info( is_acdoca_check = ls_acdoca_check
                    iv_jvfunc       = iv_jvfunc
                    iv_intco        = abap_true ).
append ls_acdoca_post to lt_acdoca_post.
prepare_accit_line( exporting
                    is_acdoca = ls_acdoca_post
                    iv_budat  = ms_progpars-budat
                    iv_bldat  = lv_bldat
                    changing
                    cs_accit  = ls_accit ).
add_accit_line_correction( exporting
                          iv_jvfunc       = iv_jvfunc
                          iv_jvactivity   = ls_acdoca_post-jvactivity
                          iv_buzei        = lv_buzei
                          is_acdoca       = ls_acdoca_post
                          changing
                          cs_accit        = ls_accit
                          ct_accit        = lt_accit
                          ct_accr         = lt_accr
                          cv_fatal_error  = lv_fatal_error
                          cv_error_text   = lv_error_text ).
* Document line 2: Nonop cash call rebook to new equity group with new share
* -----
add 1 to lv_buzei.
clear ls_acdoca_post.
move-corresponding ls_acdoca_check to ls_acdoca_post.
if ls_acdoca_post-vptnr is initial.
    ls_acdoca_post-vptnr = lv_vptnr.
endif.
ls_acdoca_post-jvactivity = 'F2'.
ls_acdoca_post-egrup = ls_diff_share-intcompegp_new.
ls_acdoca_post-lifnr = lv_lifnr.
* Calculate the amounts
lv_change_factor = ls_diff_share-eqshare_new
                  / ls_diff_share-eqshare_old.
* Calculate the share of the new partner
multiply ls_acdoca_post-wsl by lv_change_factor.
multiply ls_acdoca_post-hsl by lv_change_factor.
multiply ls_acdoca_post-ksl by lv_change_factor.
multiply ls_acdoca_post-osl by lv_change_factor.
multiply ls_acdoca_post-vsl by lv_change_factor.
multiply ls_acdoca_post-bsl by lv_change_factor.
multiply ls_acdoca_post-csl by lv_change_factor.
multiply ls_acdoca_post-dsl by lv_change_factor.
multiply ls_acdoca_post-esl by lv_change_factor.
multiply ls_acdoca_post-fsl by lv_change_factor.
multiply ls_acdoca_post-gsl by lv_change_factor.
if ls_acdoca_check-wsl = 0 and

```

```
ls_acdoca_check-hsl = 0 and
ls_acdoca_check-ksl = 0 and
ls_acdoca_check-osl = 0 and
ls_acdoca_check-vsl = 0 and
ls_acdoca_check-bsl = 0 and
ls_acdoca_check-csl = 0 and
ls_acdoca_check-dsl = 0 and
ls_acdoca_check-esl = 0 and
ls_acdoca_check-fsl = 0 and
ls_acdoca_check-gsl = 0.
continue.
endif.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_correction( exporting
                           iv_jvfunc      = iv_jvfunc
                           iv_jvactivity  = ls_acdoca_post-jvactivity
                           iv_buzei      = lv_buzei
                           is_acdoca     = ls_acdoca_post
                           changing
                           cs_accit      = ls_accit
                           ct_accit      = lt_accit
                           ct_accctr     = lt_accctr
                           cv_fatal_error = lv_fatal_error
                           cv_error_text = lv_error_text ).
* Document line 3: Settlement Line (delta of old and new partner share)
* -----
add 1 to lv_buzei.
ls_acdoca_post-jvactivity = 'F3'.
ls_acdoca_post-egrup = ls_diff_share-intcompepgp_new.
ls_acdoca_post-racct = ms_progpars-settlement_acc_cc2.
ls_acdoca_post-wsl = ls_acdoca_check-wsl - ls_acdoca_post-wsl.
ls_acdoca_post-hsl = ls_acdoca_check-hsl - ls_acdoca_post-hsl.
ls_acdoca_post-ksl = ls_acdoca_check-ksl - ls_acdoca_post-ksl.
ls_acdoca_post-osl = ls_acdoca_check-osl - ls_acdoca_post-osl.
ls_acdoca_post-vsl = ls_acdoca_check-vsl - ls_acdoca_post-vsl.
ls_acdoca_post-bsl = ls_acdoca_check-bsl - ls_acdoca_post-bsl.
ls_acdoca_post-csl = ls_acdoca_check-csl - ls_acdoca_post-csl.
ls_acdoca_post-dsl = ls_acdoca_check-dsl - ls_acdoca_post-dsl.
ls_acdoca_post-esl = ls_acdoca_check-esl - ls_acdoca_post-esl.
ls_acdoca_post-fsl = ls_acdoca_check-fsl - ls_acdoca_post-fsl.
ls_acdoca_post-gsl = ls_acdoca_check-gsl - ls_acdoca_post-gsl.
append ls_acdoca_post to lt_acdoca_post.
add_accit_line_settlement( exporting
                           iv_jvfunc      = iv_jvfunc
                           iv_jvactivity  = ls_acdoca_post-jvactivity
                           iv_buzei      = lv_buzei
                           is_acdoca     = ls_acdoca_post
                           changing
                           cs_accit      = ls_accit
                           ct_accit      = lt_accit
                           ct_accctr     = lt_accctr
                           cv_fatal_error = lv_fatal_error
                           cv_error_text = lv_error_text ).
* -----
```

```

post_adjustment_document( exporting
                          it_acdoca_check = lt_acdoca_check
                          it_acdoca_post  = lt_acdoca_post
                          iv_jvfunc       = iv_jvfunc
                          iv_intco        = abap_true
                          changing
                          ct_accit        = lt_accit
                          ct_acccr        = lt_acccr
                          cv_fatal_error  = lv_fatal_error
                          cv_error_text   = lv_error_text ).
refresh: lt_acdoca_check, lt_acdoca_post,
         lt_accit, lt_acccr.
clear: lv_fatal_error, lv_error_text.
endloop.
endmethod.

```

PREPARE_DIFF_SHARE_DATA

Description: Prepare the shares differing from the original shares

Inst. Method

```

method prepare_diff_share_data.
  data: ls_diff_share_old type jva_partner_share,
        ls_diff_share_new type jva_partner_share.
  refresh: ms_settings-t_diff_share_old,
           ms_settings-t_diff_share_new.
  loop at ms_settings-t_shares_old into data(ls_shares_old).
    clear ls_diff_share_old.
    ls_diff_share_old-partn    = ls_shares_old-partn.
    ls_diff_share_old-opflag   = ls_shares_old-opflag.
    ls_diff_share_old-eqshare  = ls_shares_old-eqshare.
    ls_diff_share_old-opflag   = ls_shares_old-opflag.
    ls_diff_share_old-intcocd  = ls_shares_old-intcocd.
    ls_diff_share_old-intrcovent = ls_shares_old-intrcovent.
    ls_diff_share_old-intcompegp = ls_shares_old-intcompegp.
    append ls_diff_share_old to ms_settings-t_diff_share_old.
    loop at ms_settings-t_shares_new into data(ls_shares_new)
      where partn = ls_shares_old-partn
        and opflag = ls_shares_old-opflag.

      clear ls_diff_share_new.
      ls_diff_share_new-partn    = ls_shares_new-partn.
      ls_diff_share_new-opflag   = ls_shares_new-opflag.
      ls_diff_share_new-eqshare  = ls_shares_new-eqshare.
      ls_diff_share_new-opflag   = ls_shares_new-opflag.
      ls_diff_share_new-intcocd  = ls_shares_new-intcocd.
      ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.
      ls_diff_share_new-intcompegp = ls_shares_new-intcompegp.
      append ls_diff_share_new to ms_settings-t_diff_share_new.
    endloop.
  endloop.
* Add items that did not exist in the old equity group
  loop at ms_settings-t_shares_new into ls_shares_new.
    read table ms_settings-t_diff_share_old transporting no fields
      with key partn = ls_shares_new-partn
        opflag = ls_shares_new-opflag.

```

```

    if sy-subrc > 2.
      clear ls_diff_share_new.
      ls_diff_share_new-partn      = ls_shares_new-partn.
      ls_diff_share_new-eqshare    = ls_shares_new-eqshare.
      ls_diff_share_new-intcoco    = ls_shares_new-intcoco.
      ls_diff_share_new-intrcovent = ls_shares_new-intrcovent.
      ls_diff_share_new-intcompegg = ls_shares_new-intcompegg.
      append ls_diff_share_new to ms_settings-t_diff_share_new.
    endif.
  endloop.
endmethod.
```

PREPARE_EQUITY_CHANGE

Description: Process the retrieved ACDOCA items

Inst. Method

Importing parameter

```

IV_JVFUNC TYPE JV_FUNC  (JVA Activity (Joint Venture Accounting))
IV_VNAME_NEW TYPE JV_NAME  (Joint venture)
IV_EGRUP_NEW TYPE JV_EGROUP (Equity group)
```

Changing parameter

```

CT_ACDOCA_MAIN TYPE GTY_T_ACDOCA_CHECK
CT_ACDOCA_CB TYPE JVA_CB_ACDOCA_T  (ACDOCA items for cutback processing)
```

```

method prepare_equity_change.
  data: lv_is_oi_managed type c,
        lv_tabix         type sy-tabix.
*   Prepare items to be checked
  loop at ct_acdoca_main assigning field-symbol(<ls_acdoca>).
    if ms_progpars-exclci = 'X'.
      lv_tabix = sy-tabix.
*     If the account is open item managed, do not process it
      cl_jva_util=>check_oi_managed_account( exporting
                                                iv_bukrs = <ls_acdoca>-rbukrs
                                                iv_racct = <ls_acdoca>-racct
                                                changing
                                                cv_is_oi_managed = lv_is_oi_managed
).
      if lv_is_oi_managed = 'X'.
        delete ct_acdoca_main index lv_tabix.
        continue.
      endif.
    endif.
  if <ls_acdoca>-src_awref is initial or
    not ( <ls_acdoca>-jvactivity = 'EC' or
          <ls_acdoca>-jvactivity = 'E1' or
          <ls_acdoca>-jvactivity = 'E2' or
          <ls_acdoca>-jvactivity = 'SU' or
          <ls_acdoca>-jvactivity = 'US' ).
*   Lines where the PREC fields are empty, need to be filled with the
*   reference fields so that the previous equity change postings
*   can easily be identified
    <ls_acdoca>-src_awref  = <ls_acdoca>-awref.
    <ls_acdoca>-src_awitem = <ls_acdoca>-awitem.
```

```
endif.
endloop.
* Check lines and post the change documents, if necessary
check_line_items( exporting
                    iv_jvfunc      = iv_jvfunc
                    iv_vname_new   = iv_vname_new
                    iv_egrup_new   = iv_egrup_new
                    changing
                    ct_acdoca_check = ct_acdoca_main
                    ct_acdoca_cb   = ct_acdoca_cb ).

endmethod.
```

PREPARE_POSTINGS_INTCO

Description: Prepare the intercompany reversal postings

Inst. Method

Importing parameter

```
IT_ACDOCA_INTCO_NEW TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
IT_ACDOCA_INTCO_OLD TYPE JVA_CB_ACDOCA_T (ACDOCA items for cutback processing)
```

```
method prepare_postings_intco.
  data: lv_tabix_next type sy-tabix,
        ls_acdoca_next type jva_cb_acdoca.
  loop at it_acdoca_intco_new into data(ls_acdoca).
    lv_tabix_next = sy-tabix + 1.
    clear ls_acdoca_next.
    read table it_acdoca_intco_new into ls_acdoca_next index lv_tabix_next.
    read table it_acdoca_intco_old into data(ls_acdoca_old)
      with key rbukrs = ls_acdoca-rbukrs
            rwcure = ls_acdoca-rwcure
            ryear = ls_acdoca-ryear
            vname = ls_acdoca-vname
            egrupe = ls_acdoca-egrupe
            racct = ls_acdoca-racct
            rbusa = ls_acdoca-rbusa
            rcntr = ls_acdoca-rcntr
            aufnr = ls_acdoca-aufnr
            ps_psp_pnr = ls_acdoca-ps_psp_pnr
            prctr = ls_acdoca-prctr
            recid = ls_acdoca-recid
            vptnr = ls_acdoca-vptnr
            nplnr = ls_acdoca-nplnr
            nplnr_vorgn = ls_acdoca-nplnr_vorgn
            anl1 = ls_acdoca-anl1
            anl2 = ls_acdoca-anl2
            anbwa = ls_acdoca-anbwa
      binary search.
    if ls_acdoca-rbukrs <> ls_acdoca_next-rbukrs or
       ls_acdoca-rwcure <> ls_acdoca_next-rwcure.
      endif.
    endloop.
endmethod.
```

PRINT_RESULTS

Description: Print the results

Inst. Method

```
method print_results.  
  add_general_information( ).  
  mo_output_spool->set_output_data( is_progpars   = ms_progpars  
                                   is_settings    = ms_settings  
                                   is_ea_results   = ms_ea_results  
                                   is_cb_results   = ms_cb_results  
                                   io_cutback     = mo_cutback ).  
  
  mo_output_spool->create_output( ).  
endmethod.
```

RUN_ADJUSTMENTS

Description: Run the adjustment process

Inst. Method

```
method run_adjustments.  
  data: lt_acdoca_cb type jva_cb_acdoca_t.  
  if ms_progpars-eqchng = 'X'.  
*    Create the equity group adjustment postings  
    adjust_equity_group( changing ct_acdoca_cb = lt_acdoca_cb ).  
  else.  
    return.  
  endif.  
*  If there are cutback data and if no critical errors have occurred,  
*  run cutback for the successful equity adjustment postings  
  if ms_progpars-cutbck = 'X' and  
    not lt_acdoca_cb[] is initial.  
*    Adjust the cutback results  
    adjust_cutback_results( it_acdoca_cb = lt_acdoca_cb ).  
  endif.  
  if ms_progpars-intcoc = 'X'.  
*    Adjust the intercompany postings  
    adjust_intercompany_reversal( ).  
  endif.  
  if ms_progpars-cashc1 = 'X'.  
*    Adjust the cash call postings step 1  
    adjust_cashcall_equity_group( ).  
  endif.  
  if ms_progpars-cashc2 = 'X'.  
*    Adjust the cashl postings step 2  
    adjust_cashcall_partner_shares( ).  
  endif.  
  if ms_progpars-test <> abap_true.  
    mo_output->commit_work( ).  
  endif.  
  loop at mo_message_collector->get_access( )->get_messages( ) transporting no  
fields  
    where msgty = 'E'  
      or msgty = 'A'  
      or msgty = 'X'.  
endmethod.
```

```
        add 1 to ms_ea_results-no_of_errors.  
    endloop.  
endmethod.
```

RUN_PROCESS

Description: Main processing
Inst. Method

```
method run_process.  
*   Fill event table  
    fill_event_table( ).  
*   Prepare the schedule manager  
    schedman_initialize( ).  
*   Get Cutback Run ID  
    ms_progpars-cbrunid = ms_progpars-s_schedman_key-id.  
*   Get settings  
    get_settings( ).  
    get_partner_shares( ).  
    if ms_ea_results-max_error <> 'E' and  
       ms_ea_results-max_error <> 'A'.  
       if ms_progpars-test <> abap_true.  
*           Initialize local updating to avoid deadlocks during  
*           CO table updating  
           set update task local.  
       endif.  
*   Make the adjustments according to the settings  
    run_adjustments( ).  
endif.  
*   Print the results  
    print_results( ).  
*   Update event table  
    update_event_table( ).  
    if mo_message_collector->get_msg_count( ) > 0.  
        mo_application_log->submit_output( ).  
    endif.  
*   Close the schedule manager  
    schedman_close( ).  
*   Print the spool overview screen, if appropriate  
    mo_output_spool->print_overview_screen( ).  
endmethod.
```

SAVE_ADJUSTMENT_DOC_INFO

Description: Save the change doc info
Inst. Method

Importing parameter

```
IT_ACDOCA_CHECK TYPE FINST_ACDOCA  (Universal Journal Entry Line Items)  
IV_JVFUNC TYPE JV_FUNC  (JV Function)  
IV_INTCO TYPE ABAP_BOOL  
IV_BELNR_NEW TYPE ACDOCA-BELNR  
IV_ERROR_TEXT TYPE STRING  
IV_POSTING_ERROR TYPE ABAP_BOOL  
IV_POSTTYPE TYPE C  
IT_ACDOC_ITEMS_POSTED TYPE FINST_ACDOC_ITEM
```

IT_ACCIT_POSTED TYPE ACCIT_T (Accounting Interface: Item Information)
IT_ACDOCA TYPE FINST_ACDOCA (ACDOCA Unified Journal Entry Line Items)

```
method save_adjustment_doc_info.  
  data: ls_acdoca          type acdoca,  
        lv_belnr_new       type acdoca-belnr,  
        ls_acdoc_item_posted type fins_acdoc_item,  
        ls_accit_posted    type accit,  
        ls_print           type jva_ea_docprint,  
        ls_color           type slis_specialcol_alv,  
        lv_otype           type c,  
        lv_object          type char24,  
        lv_posid           type prps-posid,  
        lv_tabix           type sy-tabix.  
  if iv_posting_error = abap_true or  
    ms_progpars-test = abap_true.  
    add 1 to mv_belnr_test.  
    lv_belnr_new = |TEST| && mv_belnr_test  ##NO_TEXT.  
  else.  
    lv_belnr_new = iv_belnr_new.  
  endif.  
  loop at it_acdoca into ls_acdoca.  
    lv_tabix = sy-tabix.  
    move-corresponding ls_acdoca to ls_print  ##ENH_OK.  
    ls_print-jvfunc = iv_jvfunc.  
    ls_print-belnr = lv_belnr_new.  
    if not it_acdoc_items_posted[] is initial.  
      clear: ls_acdoc_item_posted.  
      read table it_acdoc_items_posted into ls_acdoc_item_posted index lv_tabix.  
      ls_print-budat = ls_acdoc_item_posted-budat.  
      ls_print-bldat = ls_acdoc_item_posted-bldat.  
      ls_print-buzei = ls_acdoc_item_posted-buzei.  
      ls_print-bschl = ls_acdoc_item_posted-bschl.  
      ls_print-umskz = ls_acdoc_item_posted-umskz.  
      ls_print-recid = ls_acdoc_item_posted-recid.  
      ls_print-btype = ls_acdoc_item_posted-btype.  
      if ls_acdoc_item_posted-kunnr is not initial.  
        ls_print-racct = ls_acdoc_item_posted-kunnr.  
      elseif ls_acdoc_item_posted-lifnr is not initial.  
        ls_print-racct = ls_acdoc_item_posted-lifnr.  
      elseif ls_acdoc_item_posted-hkont is not initial.  
        ls_print-racct = ls_acdoc_item_posted-hkont.  
      else.  
        clear ls_print-racct.  
      endif.  
    else.  
      clear: ls_accit_posted.  
      read table it_accit_posted into ls_accit_posted index lv_tabix.  
      ls_print-budat = ls_accit_posted-budat.  
      ls_print-bldat = ls_accit_posted-bldat.  
      ls_print-buzei = ls_accit_posted-buzei.  
      ls_print-bschl = ls_accit_posted-bschl.  
      ls_print-umskz = ls_accit_posted-umskz.  
      ls_print-recid = ls_accit_posted-recid.
```

```

        ls_print-btype = ls_accit_posted-btype.
        if ls_accit_posted-kunnr is not initial.
            ls_print-racct = ls_accit_posted-kunnr.
        elseif ls_accit_posted-lifnr is not initial.
            ls_print-racct = ls_accit_posted-lifnr.
        elseif ls_accit_posted-hkont is not initial.
            ls_print-racct = ls_accit_posted-hkont.
        else.
            clear ls_print-racct.
        endif.
    endif.
*   Identify cost object for record
    if not ls_acdoca-rcntr is initial.
        lv_otype = 'C'.                " cost center
        lv_object = ls_acdoca-rcntr.
    elseif not ls_acdoca-aufnr is initial.
        lv_otype = 'O'.                " order
        lv_object = ls_acdoca-aufnr.
    elseif not ls_acdoca-ps_psp_pnr is initial.
        lv_otype = 'W'.                " WBS element
        select single posid
            from prps
            into lv_posid
            where pspnr = ls_acdoca-ps_psp_pnr.
        lv_object = lv_posid.
    elseif not ls_acdoca-nplnr is initial.
        lv_otype = 'N'.                " Network
        lv_object = ls_acdoca-nplnr.
    elseif not ls_acdoca-prctr is initial.
        lv_otype = 'P'.                " Profit Center
        lv_object = ls_acdoca-prctr.
    endif.
    ls_print-co_name = lv_object.
    ls_print-error = iv_posting_error.
    ls_print-error_text = iv_error_text.
    append_adjust_print_line( exporting
                                iv_jvfunc = iv_jvfunc
                                iv_intco  = iv_intco
                                is_print  = ls_print ).

endloop.
endmethod.

```

SAVE_CASH_CALL_INFO

Description: Save info about existing cash call amount

Inst. Method

Importing parameter

IS_ACDOCA_CHECK TYPE ACDOCA (Universal Journal Entry Line Items)

IV_JVFUNC TYPE JV_FUNC (JV Function)

IV_INTCO TYPE ABAP_BOOL

method save_cash_call_info.

data: ls_print type jva_ea_docprint.

* Add original line to print output table

```
move-corresponding is_acdoca_check to ls_print.
if ls_print-vptnr is initial.
  if is_acdoca_check-kunnr is not initial.
    ls_print-vptnr = is_acdoca_check-kunnr.
  elseif is_acdoca_check-lifnr is not initial.
    ls_print-vptnr = is_acdoca_check-lifnr.
  endif.
endif.
ls_print-is_original_data = abap_true.
ls_print-jvfunc = iv_jvfunc.
append_adjust_print_line( exporting
                          iv_jvfunc = iv_jvfunc
                          iv_intco  = iv_intco
                          is_print  = ls_print ).

endmethod.
```

SAVE_CHANGE_DOC_INFO

Description: Save the change doc info

Inst. Method

Importing parameter

IV_JVFUNC TYPE JV_FUNC (JV Function)

IS_ACDOCA TYPE ACDOCA

IV_BELNR_NEW TYPE ACDOCA-BELNR

IV_EGRUP_NEW TYPE ACDOCA-EGRUP

IV_ERROR_TEXT TYPE STRING

IV_POSTING_ERROR TYPE ABAP_BOOL

LT_ACDDOC_HEADER_POSTED TYPE FINST_ACDDOC_HEADER

LT_ACDDOC_ITEMS_POSTED TYPE FINST_ACDDOC_ITEM

method save_change_doc_info.

```
data: lv_belnr_new      type acdoca-belnr,
      ls_acdoc_header_posted type fins_acdoc_header,
      ls_acdoc_item_posted  type fins_acdoc_item,
      ls_print           type jva_ec_docprint,
      ls_color           type slis_specialcol_alv,
      lv_otype           type c,
      lv_object          type char24,
      lv_posid           type prps-posid,
      lv_rcntr           type acdoca-rcntr,
      lv_aufnr           type acdoca-aufnr,
      lv_ps_psp_pnr      type acdoca-ps_psp_pnr,
      lv_nplnr           type acdoca-nplnr,
      lv_nplnr_vorgn     type acdoca-nplnr_vorgn.
```

```
move-corresponding is_acdoca to ls_print ##ENH_OK.
```

```
ls_print-jvfunc = iv_jvfunc.
```

```
read table lt_acdoc_header_posted into ls_acdoc_header_posted index 1.
```

```
read table lt_acdoc_items_posted into ls_acdoc_item_posted index 1.
```

```
ls_print-budat = ls_acdoc_item_posted-budat.
```

```
ls_print-bldat = ls_acdoc_item_posted-bldat.
```

```
if iv_posting_error = 'X'.
```

```
  lv_belnr_new = 'ERROR'.
```

```
elseif ms_progpars-test = 'X'.
```

```
  lv_belnr_new = text-003.
```

```

else.
    lv_belnr_new = iv_belnr_new.
endif.
ls_print-belnr_corr = lv_belnr_new.
ls_print-buzei_corr = 1.
ls_print-vname_corr = is_acdoca-vname.
ls_print-egrup_corr = iv_egrup_new.
ls_print-etype_corr = is_acdoca-etype.
if ls_acdoc_item_posted-blart = 'K' or
    ls_acdoc_item_posted-blart = 'D'.
    if ls_acdoc_item_posted-kunnr is not initial.
        ls_print-racct = ls_acdoc_item_posted-kunnr.
    elseif ls_acdoc_item_posted-lifnr is not initial.
        ls_print-racct = ls_acdoc_item_posted-lifnr.
    elseif ls_acdoc_item_posted-hkont is not initial.
        ls_print-racct = ls_acdoc_item_posted-hkont.
    else.
        clear ls_print-racct.
    endif.
elseif ls_acdoc_item_posted-hkont is not initial.
    ls_print-racct = ls_acdoc_item_posted-hkont.
else.
    clear ls_print-racct.
endif.
lv_rcntr      = is_acdoca-rcntr.
lv_aufnr      = is_acdoca-aufnr.
lv_ps_psp_pnr = is_acdoca-ps_psp_pnr.
lv_nplnr      = is_acdoca-nplnr.
lv_nplnr_vorgn = is_acdoca-nplnr_vorgn.
* Identify the non-statistical cost object for the output
cl_jva_util=>determine_relevant_cost_object( exporting
                                             iv_accasty      = is_acdoca-accasty
                                             changing
                                             cv_rcntr        = lv_rcntr
                                             cv_aufnr         = lv_aufnr
                                             cv_ps_psp_pnr     = lv_ps_psp_pnr
                                             cv_nplnr         = lv_nplnr
                                             cv_nplnr_vorgn    = lv_nplnr_vorgn ).

if not lv_rcntr is initial.
    lv_otype = 'C'.                " cost center
    lv_object = lv_rcntr.
elseif not lv_aufnr is initial.
    lv_otype = 'O'.                " order
    lv_object = lv_aufnr.
elseif not lv_ps_psp_pnr is initial.
    lv_otype = 'W'.                " WBS element
    select single posid
        from prps
        into lv_posid
        where pspnr = lv_ps_psp_pnr.
    lv_object = lv_posid.
elseif not lv_nplnr is initial.
    lv_otype = 'N'.                " Network
    lv_object = lv_nplnr.

```

```
elseif not is_acdoca-prctr is initial.  
  lv_otype = 'P'. " Profit Center  
  lv_object = is_acdoca-prctr.  
endif.  
ls_print-co_name = lv_object.  
ls_print-error = iv_posting_error.  
ls_print-error_text = iv_error_text.  
* Add coloring information for ALV printing  
ls_color-fieldname = 'BELNR_CORR'.  
if iv_posting_error = 'X'.  
  ls_color-color-col = '6'. "Red background  
  append ls_color to ls_print-t_cell_color.  
else.  
  ls_color-color-col = '3'. "Col total (yellow)  
  append ls_color to ls_print-t_cell_color.  
endif.  
if iv_jvfunc = 'FACC'.  
  append ls_print to ms_ea_results-t_print_cc1.  
else.  
  append ls_print to ms_ea_results-t_print_ec.  
endif.  
endmethod.
```

SAVE_MESSAGE

Description: Save a message
Inst. Method

Importing parameter

```
IV_CLASS TYPE ANY  
IV_NUMBER TYPE ANY  
IV_TYPE TYPE ANY  
IV_VAR1 TYPE ANY OPTIONAL  
IV_VAR2 TYPE ANY OPTIONAL  
IV_VAR3 TYPE ANY OPTIONAL  
IV_VAR4 TYPE ANY OPTIONAL  
IV_MESSAGE_TEXT TYPE STRING OPTIONAL
```

```
method save_message.  
  data: ls_messages type t8jvt01,  
        lv_msgid type symsgid,  
        lv_msgno type symsgno,  
        lv_msgty type symsgty.  
  lv_msgid = iv_class.  
  lv_msgno = iv_number.  
  lv_msgty = iv_type.  
  mo_message_collector->add_message( iv_msgid = lv_msgid  
                                     iv_msgno = lv_msgno  
                                     iv_msgty = lv_msgty  
                                     iv_msgv1 = iv_var1  
                                     iv_msgv2 = iv_var2  
                                     iv_msgv3 = iv_var3  
                                     iv_msgv4 = iv_var4 ).  
* Set max error  
  set_total_error_flag( exporting
```

```

            iv_error = iv_type
            changing
            cv_total_error = ms_ea_results-max_error ).
ls_messages-msgid  = iv_class.
ls_messages-msgno  = iv_number.
ls_messages-status = iv_type.
ls_messages-var1   = iv_var1.
ls_messages-var2   = iv_var2.
ls_messages-var3   = iv_var3.
ls_messages-var4   = iv_var4.
if not iv_message_text is initial.
    ls_messages-text = iv_message_text.
else.
    message id lv_msgid type lv_msgty number lv_msgno
    with iv_var1 iv_var2 iv_var3 iv_var4
    into mv_message_text.
    ls_messages-text = mv_message_text.
endif.
collect ls_messages into ms_ea_results-t_messages.
endmethod.
```

SAVE_SY_MESSAGE

Description: Save a sy message
Inst. Method

```

method save_sy_message.
    if sy-msgid is initial.
        return.
    endif.
    save_message( iv_type   = sy-msgty
                  iv_class  = sy-msgid
                  iv_number = sy-msgno
                  iv_var1   = sy-msgv1
                  iv_var2   = sy-msgv2
                  iv_var3   = sy-msgv3
                  iv_var4   = sy-msgv4 ).
endmethod.
```

SCHEDMAN_CLOSE

Description: Close the schedule manager
Inst. Method

```

method schedman_close.
    data: lv_messages_balobject    type balobj_d value 'JVA',
          lv_messages_balsubobject type balsubobj value 'SCHEDMAN',
          lv_messages_id          type sy-uzeit,
          ls_message              type schedman_message,
          lv_aplstat              type smmain-aplstat.
    case ms_ea_results-max_error.
        when 'A'.
            lv_aplstat = 4.
        when 'E'.
            lv_aplstat = 4.
        when 'W'.

```

```
        lv_aplstat = 2.
    when others.
        lv_aplstat = 0.
    endcase.
    data(lt_spool) = mo_output_spool->get_spool_table( ).
*   Update and close the schedule manager log
    mo_output->kpep_moni_close_record( exporting
                                     is_key      = ms_progpars-s_schedman_key
                                     is_message = ls_message
                                     it_spool   = lt_spool
                                     changing
                                     cv_aplstat = lv_aplstat ).

    mo_output->commit_work( ).
endmethod.
```

SCHEDMAN_INITIALIZE

Description: Initialize the schedule manager

Inst. Method

```
method schedman_initialize.
    data: ls_detail type schedman_detail_user,
          lt_selkrit type schedman_selkrit_t,
          ls_selkrit type schedman_selkrit,
          ls_appl_jv type schedman_specific_jv.
*   Company code
    ls_selkrit = value #( structure = 'ACDOCA'
                          field    = 'BUKRS'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-bukrs
                          high     = ms_progpars-bukrs ).

    append ls_selkrit to lt_selkrit.
*   Venture
    ls_selkrit = value #( structure = 'ACDOCA'
                          field    = 'VNAME'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-vname
                          high     = ms_progpars-vname ).

    append ls_selkrit to lt_selkrit.
*   Year
    ls_selkrit = value #( structure = 'ACDOCA'
                          field    = 'GJAHR'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-year
                          high     = ms_progpars-year ).

    append ls_selkrit to lt_selkrit.
*   Period
    ls_selkrit = value #( structure = 'BKPF'
                          field    = 'MONAT'
```

```
        entry      = 1
        sign       = 'I'
        optio      = 'EQ'
        low        = ms_progpars-period
        high       = ms_progpars-period ).
    append ls_selkrit to lt_selkrit.
*   Old equity group
    ls_selkrit = value #( structure = 'ACDOCA'
                          field    = 'EGRUP'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-eqold
                          high     = ms_progpars-eqold ).
    append ls_selkrit to lt_selkrit.
*   New equity group
    ls_selkrit = value #( structure = 'ACDOCA'
                          field    = 'EGRUP'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-eqnew
                          high     = ms_progpars-eqnew ).
    append ls_selkrit to lt_selkrit.
*   From date
    ls_selkrit = value #( structure = 'SYST'
                          field    = 'DATUM'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-frdate
                          high     = ms_progpars-frdate ).
    append ls_selkrit to lt_selkrit.
*   To date
    ls_selkrit = value #( structure = 'SYST'
                          field    = 'DATUM'
                          entry    = 1
                          sign     = 'I'
                          optio    = 'EQ'
                          low      = ms_progpars-todate
                          high     = ms_progpars-todate ).
    append ls_selkrit to lt_selkrit.
*   Posting period selection
    loop at ms_progpars-t_budat into data(ls_budat).
        ls_selkrit = value #( structure = 'SYST'
                              field    = 'DATUM'
                              entry    = sy-tabix
                              sign     = ls_budat-sign
                              optio    = ls_budat-option
                              low      = ls_budat-low
                              high     = ls_budat-high ).
        append ls_selkrit to lt_selkrit.
    endloop.
*   Accounts
```

```
loop at ms_progpars-t_acct into data(ls_acct).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'RACCT'
                        entry      = sy-tabix
                        sign       = ls_acct-sign
                        optio      = ls_acct-option
                        low        = ls_acct-low
                        high       = ls_acct-high ).
  append ls_selkrit to lt_selkrit.
endloop.
* Cost center
loop at ms_progpars-t_cntr into data(ls_cntr).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'RCNTR'
                        entry      = sy-tabix
                        sign       = ls_cntr-sign
                        optio      = ls_cntr-option
                        low        = ls_cntr-low
                        high       = ls_cntr-high ).
  append ls_selkrit to lt_selkrit.
endloop.
* Order
loop at ms_progpars-t_ordnr into data(ls_ordnr).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'AUFNR'
                        entry      = sy-tabix
                        sign       = ls_ordnr-sign
                        optio      = ls_ordnr-option
                        low        = ls_ordnr-low
                        high       = ls_ordnr-high ).
  append ls_selkrit to lt_selkrit.
endloop.
* Project
loop at ms_progpars-t_projk into data(ls_projk).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'PS_PSP_PNR'
                        entry      = sy-tabix
                        sign       = ls_projk-sign
                        optio      = ls_projk-option
                        low        = ls_projk-low
                        high       = ls_projk-high ).
  append ls_selkrit to lt_selkrit.
endloop.
* Network
loop at ms_progpars-t_nplnr into data(ls_nplnr).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'NPLNR'
                        entry      = sy-tabix
                        sign       = ls_nplnr-sign
                        optio      = ls_nplnr-option
                        low        = ls_nplnr-low
                        high       = ls_nplnr-high ).
  append ls_selkrit to lt_selkrit.
endloop.
```

```
* Network activity
loop at ms_progpars-t_vornr into data(ls_vornr).
  ls_selkrit = value #( structure = 'ACDOCA'
                        field      = 'NPLNR_VORGN'
                        entry      = sy-tabix
                        sign       = ls_vornr-sign
                        optio      = ls_vornr-option
                        low        = ls_vornr-low
                        high       = ls_vornr-high ).
  append ls_selkrit to lt_selkrit.
endloop.
* Posting date
ls_selkrit = value #( structure = 'SYST'
                    field      = 'DATUM'
                    entry      = 1
                    sign       = 'I'
                    optio      = 'EQ'
                    low        = ms_progpars-budat
                    high       = ms_progpars-budat ).
append ls_selkrit to lt_selkrit.
* Text
ls_selkrit = value #( structure = 'BKPF'
                    field      = 'BKTXT'
                    entry      = 1
                    sign       = 'I'
                    optio      = 'EQ'
                    low        = ms_progpars-bktxt
                    high       = ms_progpars-bktxt ).
append ls_selkrit to lt_selkrit.
* Fill detail structure
ls_detail-tcode      = sy-tcode.
ls_detail-repid      = ms_progpars-repid_callback.
ls_detail-testflag   = ms_progpars-test.
ls_detail-function   = ''.
ls_detail-activity   = ''.
ls_detail-variante   = ''.
ls_detail-application = ''.
ls_detail-nr_of_objects = 0.
* Fill application data
ls_appl_jv-bukrs      = ms_progpars-bukrs.
ls_appl_jv-perio_from = ms_progpars-period.
ls_appl_jv-perio_to   = ms_progpars-period.
ls_appl_jv-gjahr      = ms_progpars-year.
ls_appl_jv-versn      = '000'.
ls_appl_jv-budat      = ms_progpars-budat.
* Initialize monitor recording
mo_output->kpep_moni_init_record(
  exporting
    is_detail = ls_detail
    it_selkrit = lt_selkrit
    is_appl   = ls_appl_jv
  importing
    es_key    = ms_progpars-s_schedman_key ).
endmethod.
```

SET_EVENT_PARAM

Description: Get the event parameters
Inst. Method

Importing parameter

CONTENSE TYPE ANY
NAME TYPE ANY

```
method set_event_param.  
  data: ls_t8jevp type t8jevp.  
  clear ls_t8jevp.  
  move-corresponding ms_progpars-s_t8jev to ls_t8jevp.  
  ls_t8jevp-param      = name.  
  ls_t8jevp-contense   = contense.  
*  Only update when not running in test mode  
  if ms_progpars-test <> abap_true.  
    mo_output->insert_t8jevp( ls_t8jevp ).  
  endif.  
endmethod.
```

SET_EVENT_PARAM_ACCOUNT

Description: Fill the account field
Inst. Method

```
method set_event_param_account.  
  data: ls_t8jevs type t8jevs.  
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.  
  ls_t8jevs-selpar = 'A'.  
  ls_t8jevs-seqn2 = 0.  
  loop at ms_progpars-t_acct into data(ls_acct).  
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.  
    move-corresponding ls_acct to ls_t8jevs.  
    ls_t8jevs-soption = ls_acct-option.  
*  Only update when not running in test mode  
    if ms_progpars-test <> abap_true.  
      mo_output->insert_t8jevs( ls_t8jevs ).  
    endif.  
  endloop.  
  if sy-subrc <> 0.  
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.  
*  Only update when not running in test mode  
    if ms_progpars-test <> abap_true.  
      mo_output->insert_t8jevs( ls_t8jevs ).  
    endif.  
  endif.  
endmethod.
```

SET_EVENT_PARAM_COST_CENTER

Description: Fill the cost center fields
Inst. Method

```
method set_event_param_cost_center.  
  data: ls_t8jevs type t8jevs.  
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.
```

```
ls_t8jevs-selpar = 'K'.
ls_t8jevs-seqn2 = 0.
loop at ms_progpars-t_cntr into data(ls_cntr).
  add 1 to ls_t8jevs-seqn2.
  move-corresponding ls_cntr to ls_t8jevs.
  ls_t8jevs-soption = ls_cntr-option.
*   Only update when not running in test mode
  if ms_progpars-test <> abap_true.
    mo_output->insert_t8jevs( ls_t8jevs ).
  endif.
endloop.
if sy-subrc <> 0.
  add 1 to ls_t8jevs-seqn2.
*   Only update when not running in test mode
  if ms_progpars-test <> abap_true.
    mo_output->insert_t8jevs( ls_t8jevs ).
  endif.
endif.
endmethod.
```

SET_EVENT_PARAM_ORDER

Description: Fill the order field

Inst. Method

```
method set_event_param_order.
  data: ls_t8jevs type t8jevs.
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.
  ls_t8jevs-selpar = '0'.
  ls_t8jevs-seqn2 = 0.
  loop at ms_progpars-t_ordnr into data(ls_ordnr).
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
    move-corresponding ls_ordnr to ls_t8jevs.
    ls_t8jevs-soption = ls_ordnr-option.
*   Only update when not running in test mode
    if ms_progpars-test <> abap_true.
      mo_output->insert_t8jevs( ls_t8jevs ).
    endif.
  endloop.
  if sy-subrc <> 0.
    ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
*   Only update when not running in test mode
    if ms_progpars-test <> abap_true.
      mo_output->insert_t8jevs( ls_t8jevs ).
    endif.
  endif.
endmethod.
```

SET_EVENT_PARAM_PROJECT

Description: Fille the project field

Inst. Method

```
method set_event_param_project.
  data: ls_t8jevs type t8jevs.
  move-corresponding ms_progpars-s_t8jev to ls_t8jevs.
```

```
ls_t8jevs-selpar = 'W'.
ls_t8jevs-seqn2 = 0.
loop at ms_progpars-t_projk into data(ls_projk).
  ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
  move-corresponding ls_projk to ls_t8jevs.
  ls_t8jevs-soption = ls_projk-option.
*   Only update when not running in test mode
  if ms_progpars-test <> abap_true.
    mo_output->insert_t8jevs( ls_t8jevs ).
  endif.
endloop.
if sy-subrc <> 0.
  ls_t8jevs-seqn2 = ls_t8jevs-seqn2 + 1.
*   Only update when not running in test mode
  if ms_progpars-test <> abap_true.
    mo_output->insert_t8jevs( ls_t8jevs ).
  endif.
endif.
endmethod.
```

SET_POSTING_INDICATORS

Description: Set posting key and indicators for FI doc line
Inst. Method

Importing parameter

```
VALUE(IV_JVFUNC) TYPE JV_FUNC  (JV Function)
VALUE(IS_ACDOCA) TYPE ACDOCA   (Universal Journal Entry Line Items)
VALUE(IV_JVACTIVITY) TYPE ACDOCA-JVACTIVITY  (JVA Activity (Joint Venture Accounting))
```

Changing parameter

```
CS_ACCIT TYPE ACCIT  (Accounting Interface: Item Information)
CV_FATAL_ERROR TYPE C
CV_ERROR_TEXT TYPE STRING
```

```
method set_posting_indicators.
  data: ls_t8j0g      type t8j0g,
        lv_fatal_error type abap_bool,
        lv_error_text type string.
  get_posting_rule( exporting
                    iv_bukrs      = is_acdoca-rbukrs
                    iv_jvfunc     = iv_jvfunc
                    iv_jvactivity = iv_jvactivity
                    iv_recid      = is_acdoca-recid
                    changing
                    cs_t8j0g      = ls_t8j0g
                    cv_fatal_error = lv_fatal_error
                    cv_error_text = lv_error_text ).
  if is_acdoca-wsl >= 0 and
     is_acdoca-hsl >= 0 and
     is_acdoca-ksl >= 0 and
     is_acdoca-osl >= 0 and
     is_acdoca-vsl >= 0 and
     is_acdoca-bsl >= 0 and
     is_acdoca-csl >= 0 and
     is_acdoca-dsl >= 0 and
```

```

    is_acdoca-esl >= 0 and
    is_acdoca-fsl >= 0 and
    is_acdoca-gsl >= 0.
    cs_accit-shkzg = 'S'.
else.
    cs_accit-shkzg = 'H'.
endif.
if cs_accit-shkzg = 'S'.
    cs_accit-bschl = ls_t8j0g-debpostkey.
    cs_accit-umskz = ls_t8j0g-debseind.
    cs_accit-btype = ls_t8j0g-debbillind.
    if not ls_t8j0g-debrecid is initial.
        cs_accit-recid = ls_t8j0g-debrecid.
    endif.
else.
    cs_accit-bschl = ls_t8j0g-crepostkey.
    cs_accit-umskz = ls_t8j0g-creseind.
    cs_accit-btype = ls_t8j0g-crebillind.
    if not ls_t8j0g-crerecid is initial.
        cs_accit-recid = ls_t8j0g-crerecid.
    endif.
endif.
if lv_fatal_error = 'X'.
    cv_fatal_error = 'X'.
    if cv_error_text is initial.
        cv_error_text = lv_error_text.
    endif.
endif.
endmethod.
```

SET_TOTAL_ERROR_FLAG

Description: Set the maximum error flag

Inst. Method

Importing parameter

IV_ERROR TYPE ANY

Changing parameter

CV_TOTAL_ERROR TYPE ANY

```

method set_total_error_flag.
    case iv_error.
        when 'A'.
            cv_total_error = 'A'.
        when 'E'.
            if cv_total_error <> 'A'.
                cv_total_error = 'E'.
            endif.
        when 'W'.
            if cv_total_error <> 'A' and
                cv_total_error <> 'E'.
                cv_total_error = 'W'.
            endif.
    endcase.
endmethod.
```

UPDATE_EVENT_TABLE
Description: Update the JVA event table
Inst. Method

```
method update_event_table.  
*   Update event table with success/failure indicator  
    if ms_ea_results-max_error = 'E' or  
        ms_ea_results-max_error = 'A'.  
        ms_progpars-s_t8jev-status = '3'.  "Failure  
    elseif ms_cb_results-vent_count_errors > 0.  
        ms_progpars-s_t8jev-status = '2'.  "Incomplete  
    else.  
        ms_progpars-s_t8jev-status = '1'.  "Complete  
    endif.  
*   Only update in productive run  
    if ms_progpars-test <> abap_true.  
        mo_output->update_t8jev( ms_progpars-s_t8jev ).  
    endif.  
endmethod.
```

Redefined Methods

Macros

```
*** use this source file for any macro definitions you need  
*** in the implementation part of the class
```

Overview

Attributes	1
Attributes	1
Private attribute	1
Intern. types	2
Private types	2
Methods	2
Private methods	2
ADD_ACCIT_LINE_CASHCALL	2
ADD_ACCIT_LINE_CORRECTION	4
ADD_ACCIT_LINE_SETTLEMENT	5
ADD_FIDOC_HEADER	5
ADD_GENERAL_INFORMATION	6
ADD_INFO	6
ADD_ITEM_TO_FIELDCATALOG	7
ADD_ITEM_TO_SELECT_TABLES	7
ADJUST_CASHCALL_EG	10
ADJUST_CASHCALL_EG_INTCO	11
ADJUST_CASHCALL_EQUITY_GROUP	12
ADJUST_CASHCALL_PARTNERS	12
ADJUST_CASHCALL_PARTNERS_INTCO	13
ADJUST_CASHCALL_PARTNER_SHARES	13
ADJUST_CUTBACK_RESULTS	14
ADJUST_EQUITY_GROUP	15
ADJUST_INTERCOMPANY_REVERSAL	16
APPEND_ADJUST_PRINT_LINE	16
CALC_CC_CORRECTION_AMOUNT	17
CHECK_ADJUSTMENT_DATE	17
CHECK_ADJUSTMENT_PERIOD	18
CHECK_AUTHORITY	20
CHECK_COMPANY_CODE	21
CHECK_EQUITY_GROUP	21
CHECK_FOR_PREVIOUS_CHANGES	23
CHECK_INTERCOMPANY_VENTURE	24
CHECK_LINE_ITEMS	25
CHECK_PARAMETERS	27
CHECK_POSTING_DATE	28
CHECK_RECID	29
CHECK_SETTLEMENT_ACCOUNT	30
CHECK_SHARES_CC1	30
CHECK_SHARES_CC1_INTCO	31
CHECK_SHARES_CC2	32
CHECK_SHARES_CC2_INTCO	33
CHECK_SHARES_INTCO_REVERSAL	35
CHECK_VENTURE	37
FILL_ACCCR	37
FILL_EVENT_TABLE	39
GET_BILLIND_RANGE_CASHCALL	40
GET_BILLIND_RANGE_CUTBACK	42
GET_BILLIND_RANGE_PAYMENTS	43

GET_DATA_CC1	43
GET_DATA_CC1_INTCO	45
GET_DATA_CC2	47
GET_DATA_CC2_INTCO	50
GET_DATA_EC	52
GET_DATA_INTCO	53
GET_FIELDS_FOR_ACDOCA_SELECTS	55
GET_INTCO_VENDOR	58
GET_MSGS_FROM_MSG_COLLECTOR	59
GET_PARTNER_SHARES	59
GET_POSTING_RULE	61
GET_POSTING_RULES	63
GET_RI_REBOOK_AND_REVERSE	63
GET_SETTINGS	64
INITIALIZE_MAIN_OBJECTS	65
MAKE_DATE_CLAUSE_FOR_SELECT	66
MAKE_DOC_INFO	67
POST_ADJUSTMENT_DOCUMENT	68
POST_CHANGE_DOCUMENT	69
POST_FI_DOC	72
PREPARE_ACCIT_LINE	74
PREPARE_CC_ADJUSTMENTS	75
PREPARE_CC_ADJUSTMENTS_INTCO	86
PREPARE_DIFF_SHARE_DATA	91
PREPARE_EQUITY_CHANGE	92
PREPARE_POSTINGS_INTCO	93
PRINT_RESULTS	93
RUN_ADJUSTMENTS	94
RUN_PROCESS	95
SAVE_ADJUSTMENT_DOC_INFO	95
SAVE_CASH_CALL_INFO	97
SAVE_CHANGE_DOC_INFO	98
SAVE_MESSAGE	100
SAVE_SY_MESSAGE	101
SCHEDMAN_CLOSE	101
SCHEDMAN_INITIALIZE	102
SET_EVENT_PARAM	106
SET_EVENT_PARAM_ACCOUNT	106
SET_EVENT_PARAM_COST_CENTER	106
SET_EVENT_PARAM_ORDER	107
SET_EVENT_PARAM_PROJECT	107
SET_POSTING_INDICATORS	108
SET_TOTAL_ERROR_FLAG	109
UPDATE_EVENT_TABLE	110
Redefined Methods	110
Macros	110