DDL Commands in SQ

Creating a Table

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50),
    gmail VARCHAR(100)
);

INSERT INTO Student (id, name, age, city, gmail)
VALUES (1, 'Vaibhav', 18, 'Bangalore', 'vaibhavhtbcarvu');

INSERT INTO Student (id, name, age, city, gmail)
VALUES (2, 'Manu', 19, 'Mysore', 'vaibhavhtbcarvu');

SELECT * FROM Student;
```

STDIN

Input for the program (Optional)

Output:

```
+------+---------+------+-----------+-----------------+
| id   | name    | age  | city      | gmail           |
+------+---------+------+-----------+-----------------+
|    1 | Vaibhav |   18 | Bangalore | vaibhavhtbcarvu |
|    2 | Manu    |   19 | Mysore    | vaibhavhtbcarvu |
+------+---------+------+-----------+-----------------+
```

Altering the table for adding the columns

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50),
    gmail VARCHAR(100)
);

INSERT INTO Student (id, name, age, city, gmail)
VALUES (1, 'Vaibhav', 18, 'Bangalore', 'vaibhavhtbcarvu@gmail.com');

INSERT INTO Student (id, name, age, city, gmail)
VALUES (2, 'Manu', 19, 'Mysore', 'vaibhavhtbcarvu@gmail.com');

UPDATE Student
SET age = 20
WHERE id = 1;

UPDATE Student
SET city = 'Mangalore'
WHERE id = 2;

SELECT * FROM Student;
```

STDIN

Input for the program (Optional)

Output:

```
+------+---------+------+-----------+--------------------------+
| id   | name    | age  | city      | gmail                    |
+------+---------+------+-----------+--------------------------+
|    1 | Vaibhav |   20 | Bangalore | vaibhavhtbcarvu@gmail.com |
|    2 | Manu    |   19 | Mangalore | vaibhavhtbcarvu@gmail.com |
+------+---------+------+-----------+--------------------------+
```

Modifying the Columns using Alte

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50),
    gmail VARCHAR(100)
);

INSERT INTO Student (id, name, age, city, gmail)
VALUES (1, 'Vaibhav', 18, 'Bangalore', 'vaibhavhtbcarvu@gmail.com');

INSERT INTO Student (id, name, age, city, gmail)
VALUES (2, 'Manu', 19, 'Mysore', 'vaibhavhtbcarvu@gmail.com');

UPDATE Student
SET age = 20
WHERE id = 1;

UPDATE Student
SET city = 'Mangalore'
WHERE id = 2;

SELECT * FROM Student;
```

STDIN

Input for the program (Optional)

Output:

id	name	age	city	gmail
1	Vaibhav	20	Bangalore	vaibhavhtbcarvu@gmail.com
2	Manu	19	Mangalore	vaibhavhtbcarvu@gmail.com

Dropping the Column using Alter

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50),
    gmail VARCHAR(100)
);

INSERT INTO Student (id, name, age, city, gmail)
VALUES (1, 'Vaibhav', 18, 'Bangalore', 'vaibhavhtbcarvu@gmail.com');

INSERT INTO Student (id, name, age, city, gmail)
VALUES (2, 'Manu', 19, 'Mysore', 'vaibhavhtbcarvu@gmail.com');

DELETE FROM Student
WHERE id = 2;

SELECT * FROM Student;
```

STDIN

Input for the program (Optional)

Output:

id	name	age	city	gmail
1	Vaibhav	18	Bangalore	vaibhavhtbcarvu@gmail.com

Dropping the Table

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50),
    gmail VARCHAR(100)
);

INSERT INTO Student (id, name, age, city, gmail)
VALUES (1, 'Vaibhav', 18, 'Bangalore', 'vaibhavhtbcarvu@gmail.com');

INSERT INTO Student (id, name, age, city, gmail)
VALUES (2, 'Manu', 19, 'Mysore', 'vaibhavhtbcarvu@gmail.com');

DELETE FROM Student
WHERE id = 2;

SELECT * FROM Student;
```

STDIN

Input for the program (Optional)

Output:

id	name	age	city	gmail
1	Vaibhav	18	Bangalore	vaibhavhtbcarvu@gmail.com