DML Commands

```sql
CREATE TABLE Vaibhav (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50)
);

INSERT INTO Vaibhav (id, name, age, city)
VALUES (1, 'Vaibhav', 18, 'Bangalore');

INSERT INTO Vaibhav (id, name, age, city)
VALUES (2, 'Manu', 19, 'Mysore');

SELECT * FROM Vaibhav:
```

STDIN

Input for the program (Optional)

Output:

```
+------+---------+------+-----------+
| id   | name    | age  | city      |
+------+---------+------+-----------+
|    1 | Vaibhav |   18 | Bangalore |
|    2 | Manu    |   19 | Mysore    |
+------+---------+------+-----------+
+------+---------+------+-----------+-------+-------+
```

Updating the Value

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50)
);

INSERT INTO Student (id, name, age, city)
VALUES (1, 'Vaibhav', 18, 'Bangalore');

INSERT INTO Student (id, name, age, city)
VALUES (2, 'Manu', 19, 'Mysore');

ALTER TABLE Student
ADD email VARCHAR(50);

ALTER TABLE Student
ADD phone VARCHAR(15);
```

```
|    2 | Manu    |   19 | Mysore    |
+------+---------+------+-----------+
+------+---------+------+-----------+-------+-------+
| id   | name    | age  | city      | email | phone |
+------+---------+------+-----------+-------+-------+
|    1 | Vaibhav |   18 | Bangalore | NULL  | NULL  |
|    2 | Manu    |   19 | Mysore    | NULL  | NULL  |
+------+---------+------+-----------+-------+-------+
```

Deleting the value

```sql
CREATE TABLE Student (
    id INT,
    name VARCHAR(50),
    age INT,
    city VARCHAR(50)
);

INSERT INTO Student (id, name, age, city)
VALUES (1, 'Vaibhav', 18, 'Bangalore');

INSERT INTO Student (id, name, age, city)
VALUES (2, 'Manu', 19, 'Mysore');

ALTER TABLE Student
MODIFY name VARCHAR(100);

ALTER TABLE Student
MODIFY age BIGINT;

SELECT * FROM Student;
```

Input for the program (Optional)

Output:

id	name	age	city
1	Vaibhav	18	Bangalore
2	Manu	19	Mysore