```java
package cie1;

import java.util.Scanner;
public class Student
{

    String name;
    String USN;
    int sem;
    public student()
    {
        Scanner in = new Scanner(System.in);
        System.out.println("Enter name of student");
        name = in.nextLine();
        System.out.println("Enter USN of student");
        USN = in.nextLine();
        System.out.println("Enter semester of student");
        sem = in.nextInt();

    }

}
```

```java
package cie1;
import java.util.Scanner;
public class Internals extends Student
{
    public double ciem[] = new double[3];
    public Internals()
    {
        Scanner in = new Scanner(System.in);
        System.out.println("Enter CIE marks");
        for(int i=0; i<5; i++)
        {
            System.out.println("Enter the cie marks for subject" + (i+1));
            ciem[i] = in.nextDouble();
        }
    }
}

package see1;
import java.util.Scanner;
{
    public double seem[] = new double[3];
    public externals()
    {
        Scanner in = new Scanner(System.in);
        System.out.println("Enter SEE marks");
        for(int i=0; i<5; i++)
        {
            System.out.println("Enter the see marks for subject" + (i+1));
            seem[i] = in.nextDouble();
        }
    }
}
```

```java
//Driver class
import cie1.*;
import sec.1.*;
import java.util.Scanner;
public class TotalMarks

{ public static void main (String args[])

{ int n;
  Scanner in = new Scanner (System.in);
  System.out.println ("Enter number of students ");
  n = in.nextInt();
  cie1.Internals C[] = new cie1.Internals [n];
  sec1.Externals S[] = new sec1.Externals[n];
  for(int i=0; i<n; i++)

  { System.out.println ("Details of Student "+(i+1));
    C[i] = new cie1.Internals();
    S[i] = new sec1.Externals();
    System.out.println (" Total marks in all 3 subjects of student "+(i+1));
    for (int j=0; j<5; j++)

    {
      System.out.println ("Total marks in subject "+(i+1)+": "+ (C[i].ciem[j]
               + S[i].seem[j])) ;

    }
  }
}
}
```