

Cryptography and Network Security (CS435/890BN)

Part Two
(Classic Encryption Techniques)


Symmetric Encryption

- or conventional / private-key / single-key
- sender and recipient share a common key
- all classical encryption algorithms are private-key
- and by far most widely used

Some Basic Terminology

- **plaintext** - original message
- **ciphertext** - coded message
- **cipher** - algorithm for transforming plaintext to ciphertext
- **key** - info used in cipher known only to sender/receiver
- **encipher (encrypt)** - converting plaintext to ciphertext
- **decipher (decrypt)** - recovering plaintext from ciphertext
- **cryptography** - study of encryption principles/methods
- **cryptanalysis (codebreaking)** - study of principles/methods of deciphering ciphertext *without* knowing key
- **cryptology** - field of both cryptography and cryptanalysis

Symmetric Cipher Model



Requirements

- two requirements for secure use of symmetric encryption:
 - a strong encryption algorithm
 - a secret key known only to sender / receiver
- mathematically have:
$$Y = E_K(X)$$
$$X = D_K(Y)$$
- assume encryption algorithm is known
- implies a secure channel to distribute key

Cryptanalysis

- objective to recover key not just message
- general approaches:
 - cryptanalytic attack
 - brute-force attack

Cryptanalytic Attacks

Type of Attack	Known to Cryptanalyst
Ciphertext Only	<ul style="list-style-type: none">■ Encryption algorithm■ Ciphertext
Known Plaintext	<ul style="list-style-type: none">■ Encryption algorithm■ Ciphertext■ One or more plaintext–ciphertext pairs formed with the secret key
Chosen Plaintext	<ul style="list-style-type: none">■ Encryption algorithm■ Ciphertext■ Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key
Chosen Ciphertext	<ul style="list-style-type: none">■ Encryption algorithm■ Ciphertext■ Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key
Chosen Text	<ul style="list-style-type: none">■ Encryption algorithm■ Ciphertext■ Plaintext message chosen by cryptanalyst, together with its corresponding ciphertext generated with the secret key■ Ciphertext chosen by cryptanalyst, together with its corresponding decrypted plaintext generated with the secret key

Brute Force Search

- always possible to simply try every key
- most basic attack, proportional to key size
- assume either know / recognise plaintext

Key Size (bits)	Number of Alternative Keys	Time required at 1 decryption/ μ s	Time required at 10^6 decryptions/ μ s
32	$2^{32} = 4.3 \times 10^9$	$2^{31} \mu\text{s} = 35.8 \text{ minutes}$	2.15 milliseconds
56	$2^{56} = 7.2 \times 10^{16}$	$2^{55} \mu\text{s} = 1142 \text{ years}$	10.01 hours
128	$2^{128} = 3.4 \times 10^{38}$	$2^{127} \mu\text{s} = 5.4 \times 10^{24} \text{ years}$	$5.4 \times 10^{18} \text{ years}$
168	$2^{168} = 3.7 \times 10^{50}$	$2^{167} \mu\text{s} = 5.9 \times 10^{36} \text{ years}$	$5.9 \times 10^{30} \text{ years}$
26 characters (permutation)	$26! = 4 \times 10^{26}$	$2 \times 10^{26} \mu\text{s} = 6.4 \times 10^{12} \text{ years}$	$6.4 \times 10^6 \text{ years}$

Classical Substitution Ciphers

- where letters of plaintext are replaced by other letters or by numbers or symbols
- or if plaintext is viewed as a sequence of bits, then substitution involves replacing plaintext bit patterns with ciphertext bit patterns

Caesar Cipher

- earliest known substitution cipher
- by Julius Caesar
- first attested use in military affairs
- replaces each letter by 3rd letter on
- example:

meet me after the toga party

PHHW PH DIWHU WKH WRJD SDUWB

Caesar Cipher

- can define transformation as:

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	A	B	C

- mathematically give each letter a number

a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

- then have Caesar cipher as:

$$c = E(p) = (p + k) \bmod (26)$$

$$p = D(c) = (c - k) \bmod (26)$$

Cryptanalysis of Caesar Cipher

- only have 26 possible ciphers
 - A maps to A,B,..Z
- could simply try each in turn
- a **brute force search**
- given ciphertext, just try all shifts of letters
- do need to recognize when have plaintext
- eg. break ciphertext "GCUA VQ DTGCM"

Monoalphabetic Cipher

- rather than just shifting the alphabet
- could shuffle (jumble) the letters arbitrarily
- each plaintext letter maps to a different random ciphertext letter
- hence key is 26 letters long

Plain: abcdefghijklmnopqrstuvwxyz

Cipher: DKVQFIBJWPESCXHTMYAUOLRGZN

Plaintext: ifwewishtoreplaceletters

Ciphertext: WIRFRWAJUHYFTSDVFSFUUFYA


Monoalphabetic Cipher Security

- now have a total of $26!$ keys
- with so many keys, might think is secure
- but would be **WRONG**
- problem is language characteristics

Language Redundancy and Cryptanalysis

- human languages are **redundant**
- eg "I cnduo't bveiee taht I culod aulacly
uesdtannrd waht I was rdnaieg"
- letters are not equally commonly used
 - in English E is by far the most common letter, followed by T,R,N,I,O,A,S
 - other letters like Z,J,K,Q,X are fairly rare
- have tables of single, double & triple letter frequencies for various languages

English Letter Frequencies



Use in Cryptanalysis

- key concept - monoalphabetic substitution
ciphers do not change relative letter frequencies
- discovered by Arabian scientists in 9th century
- calculate letter frequencies for ciphertext
- compare counts/plots against known values
- if caesar cipher look for common peaks/troughs
 - peaks at: A-E-I triple, NO pair, RST triple
 - troughs at: JK, X-Z
- for monoalphabetic must identify each letter
 - tables of common double/triple letters help

Example Cryptanalysis

- given ciphertext:

UZQSOVUOHXMOPVGPOZPEVSGZWSZOPFPESXUDBMETSXAIZ
VUEPHZHMDZSHZOWSFPAPPDTSVPQUZWYMXUZUHSX
EPYEPOPDZSZUFPOMBZWPFUPZHMDJUDTMOHMQ

- count relative letter frequencies (see text)
- guess P & Z are e and t
- guess ZW is th and hence ZWP is the
- proceeding with trial and error finally get:
it was disclosed yesterday that several informal but
direct contacts have been made with political
representatives of the viet cong in moscow

Playfair Cipher

- not even the large number of keys in a monoalphabetic cipher provides security
- one approach to improving security was to encrypt multiple letters
- the **Playfair Cipher** is an example
- invented by Charles Wheatstone in 1854, but named after his friend Baron Playfair

Multiletter Substitution Cipher (Hill Cipher)

- Substitute m successive plaintext letter with m ciphertext letters (e.g. m=3)
- encryption algorithm:

$$\begin{pmatrix} C_1 \\ C_2 \\ C_3 \end{pmatrix} = \begin{pmatrix} K_{11} & K_{12} & K_{13} \\ K_{21} & K_{22} & K_{23} \\ K_{31} & K_{32} & K_{33} \end{pmatrix} \begin{pmatrix} P_1 \\ P_2 \\ P_3 \end{pmatrix} \pmod{26}$$

where $K = \begin{pmatrix} K_{11} & K_{12} & K_{13} \\ K_{21} & K_{22} & K_{23} \\ K_{31} & K_{32} & K_{33} \end{pmatrix}$ is the key and $\det K \not\equiv 0 \pmod{26}$

- decryption algorithm:
- key space = 26^{m^2}

$$\begin{pmatrix} P_1 \\ P_2 \\ P_3 \end{pmatrix} = \begin{pmatrix} K_{11} & K_{12} & K_{13} \\ K_{21} & K_{22} & K_{23} \\ K_{31} & K_{32} & K_{33} \end{pmatrix}^{-1} \begin{pmatrix} C_1 \\ C_2 \\ C_3 \end{pmatrix} \pmod{26}$$

Hill Cipher

- example


$$K = \begin{pmatrix} 17 & 17 & 5 \\ 21 & 18 & 21 \\ 2 & 2 & 19 \end{pmatrix} \quad K^{-1} = \begin{pmatrix} 4 & 9 & 15 \\ 15 & 17 & 6 \\ 24 & 0 & 17 \end{pmatrix}$$

- It is easy to be broken by known plaintext attack by solve the following equation:

$$C_{m \times m} = K_{m \times m} * P_{m \times m}$$

- Case1: if P^{-1} exists, then $K_{m \times m} = C_{m \times m} * P_{m \times m}^{-1}$
- Case2: if P^{-1} not exist, then change P and C until P^{-1} found

Vernam Cipher and One-Time Pad



- Encryption: $c_i = p_i \oplus k_i$
- Decryption: $p_i = c_i \oplus k_i$

Classical Transposition Ciphers

- Hide the message by rearranging the letter order without altering actual letters used
- Row Transposition Cipher: write the message in a rectangle, row by row, and read the message off column by column but permute the order of the columns. The order of the columns becomes the key to the algorithm
- A one-time transposition cipher is easily recognized because it has the same letter frequencies as the original plaintext.

Row Transposition Cipher - Example

Key: 4 3 1 2 5 6 7

Plaintext: a t t a c k p
o s t p o n e
d u n t i l t
w o a m x y z

Ciphertext: TTNAAPTMTSUOAODWCOIXKNLYPETZ

Key: 4 3 1 2 5 6 7

Input: t t n a a p t
m t s u o a o
d w c o i x k
n l y p e t z


Output: NSCYAUOPTTWLTMDNAOIEPAXTTOKZ

Original: 01 02 03 04 05 06 07 08 09 10 11 12 13 14
15 16 17 18 19 20 21 22 23 24 25 26 27 28

After 1st transposition: 03 10 17 24 04 11 18 25 02 09 16 23 01 08
15 22 05 12 19 26 06 13 20 27 07 14 21 28

After 2nd transposition: 17 09 05 27 24 16 12 07 10 02 22 20 03 25
15 13 04 23 19 14 11 01 26 21 18 08 06 28

Rotor Machines



Steganography

3rd March

Dear George,

Greetings to all at Oxford. Many thanks for your letter and for the Summer examination package. All Entry Forms and Fees Forms should be ready for final despatch to the Syndicate by Friday 20th or at the very latest, I'm told, by the 21st. Admin has improved here, though there's room for improvement still; just give us all two or three more years and we'll really show you! Please don't let these wretched 16+ proposals destroy your basic O and A pattern. Certainly this sort of change, if implemented immediately, would bring chaos.

Sincerely yours.