

Somaiya Vidyavihar University

K. J. Somaiya School of Engineering

Department of Electronics and Computer Engineering

Multimodal Deepfake Detection for Images, Video and Audio

Submitted In Partial Fulfillment of Requirements
For the Degree Of

Bachelor of Technology

(Electronics and Computer Engineering)

By

Shivansh Gupta	Roll No: 16014023052
Vaibhav Shiroorkar	Roll No: 16014024805
Adithya Jithesh	Roll No: 16014024803

Guide

Dr. Tejashree Phatak

Assistant Professor

Somaiya Vidyavihar University

Vidyavihar, Mumbai - 400 077

2026-2027

Somaiya Vidyavihar University

K. J. Somaiya School of Engineering

Certificate

This is to certify that the project report entitled **"Multimodal Deepfake Detection for Images, Video and Audio"** submitted by the following students at the end of Semester VII of LY B. Tech is a bona fide record for partial fulfillment of requirements for the degree of **Bachelor of Technology (Electronics and Computer Engineering)** of Somaiya Vidyavihar University.

Shivansh Gupta	(16014023052)
Vaibhav Shiroorkar	(16014024805)
Adithya Jithesh	(16014024803)

Guide Dr. Tejashree Phatak	**Head of the Department** Dr. Jagannath Nirmal
Examiner	**Director**

Date:

Place: Mumbai-77

Somaiya Vidyavihar University

K. J. Somaiya School of Engineering

Declaration

We declare that this written report submission represents the work done based on our and / or others' ideas with adequately cited and referenced the original source. We also declare that we have adhered to all principles of intellectual property, academic honesty and integrity as we have not misinterpreted or fabricated or falsified any idea / data / fact / source / original work / matter in our submission.

We understand that any violation of the above will be cause for disciplinary action by the college and may evoke the penal action from the sources which have not been properly cited or from whom proper permission is not sought.

Signature of the Student
Shivansh Gupta
Roll No. 16014023052

Signature of the Student
Vaibhav Shiroorkar
Roll No. 16014024805

Signature of the Student
Adithya Jithesh
Roll No. 16014024803

Date:

Place: Mumbai-77

Acknowledgement

We would like to express our sincere gratitude to our project guide, **Dr. Tejashree Phatak**, Assistant Professor, Department of Electronics and Computer Engineering, K. J. Somaiya School of Engineering, for her guidance, advice and encouragement throughout this project.

We thank **Dr. Jagannath Nirmal**, Head of the Department of Electronics and Computer Engineering, for the facilities that made the work possible, and the faculty and staff of K. J. Somaiya School of Engineering for their support.

We acknowledge the authors of the datasets used in this work, FaceForensics++, Celeb-DF, Celeb-DF++, DeepFakeDetection, ASVspoof 2019, In-the-Wild, LAV-DF, FakeAVCeleb, DeepAction, DF26, Community Forensics and the ForenSynths and UnivFD generated-image sets, who made them available for research, and the developers of the open-source software on which the project is built, among them PyTorch, timm, Hugging Face Transformers, OpenCV and Flask.

Finally we thank our families and friends for their patience and support.

Abstract

Detectors of manipulated media often score well on the data they were developed on and markedly worse on data from other sources. This project built a local system that checks still images, videos and the speech inside videos or audio files, and recorded every design choice and experiment so that each step can be traced to evidence. Each experiment had a written hypothesis and success criterion before its run; splits are group-disjoint, sealed test sets were read once per frozen iteration through a guarded, logged command, and intervals are 95 percent group bootstrap over three seeds.

The first working version used one frozen pretrained encoder per task with a linear head. Its diagnostics led to full fine-tuning of a SigLIP base encoder for face video and, for speech, to silence trimming, augmentation and an average of three encoders; audio-visual fusion, a pulse (rPPG) check and two further video levers were not adopted. On the sealed Celeb-DF family set (7,650 videos, 344 groups: 44 identities and 300 single YouTube videos) the final face-video system reached an AUC of 0.8218 [0.8020, 0.8393] against 0.6238 for the first version, and on sealed In-the-Wild speech 0.9148 [0.8896, 0.9383] against 0.7516; part of the speech gain removes a silence and level shortcut, so it is not all better detection of synthesis. Against a re-run Xception baseline the final video system is non-inferior at both levels (margin 0.0100; difference +0.0176 [+0.0025, +0.0327]); the declared 95 percent superiority rule was met but does not survive the Bonferroni correction (98.33 percent interval [-0.0011, +0.0355]), and the baseline ran at 224 px.

After the freeze the detectors were wrapped in an eight-module analysis platform with per-module labels and no overall score. Later studies added limits rather than claims. On the sealed half of FakeAVCeleb the frozen system's AUCs (visual 0.9552, audio 0.9263) met their pre-stated criteria, but they are not evidence of detection quality: the video codec coincides with the manipulation method (codec metadata alone separates real from fake video at 0.9985 on the development half), and the frozen thresholds do not transfer. On LAV-DF a fused audio-visual score looked near perfect, but its visual part is at chance within the produced videos (0.507 on validation, a post hoc control; 0.503 on the sealed subset, exploratory), so no audio-visual detection is claimed. The image head misses 0.7395 of the images of 21 recent generators, and generated-video heads are confounded by the video source. No Gemini-specific experiment exists.

Keywords: deepfake detection, multimodal analysis, group-disjoint evaluation, frozen and fine-tuned encoders, group bootstrap, non-inferiority, per-module reporting.

Contents

Acknowledgement ..... **iii**

Abstract ..... **iv**

List of Figures ..... **vi**

List of Tables ..... **vi**

Chapter 1 Introduction **1**

1.1 Overview 1

1.2 Problem Statement 1

1.3 Objectives 1

1.4 Scope 2

Chapter 2 Background and Related Work **3**

2.1 Benchmarks, Detector Families and the Gap 3

Chapter 3 Requirements and System Architecture **4**

3.1 Requirements 4

3.2 Frozen Detector Pipeline 4

3.3 Analysis Platform and Its Eight Modules 5

3.4 Report Schema and Verdict Layer 6

3.5 Evaluation Lab 7

Chapter 4 Technology Stack and Model Integration **8**

4.1 Stack 8

4.2 Encoders, Heads and Checkpoints 8

Chapter 5 Datasets and Experimental Methodology **9**

5.1 Datasets 9

5.2 Splits, Development Slices and Sealed Tests 9

5.3 Metrics, Bootstrap and Comparisons 10

Chapter 6 Development History and Major Improvements **11**

6.1 Before the Freeze 11

6.2 After the Freeze 13

6.3 Retained and Rejected Approaches 14

6.4 Gemini Investigation 15

Chapter 7 Evaluation Results and Comparisons **16**

7.1 Sealed Results 16

7.2 Confirmatory Tests 16

7.3 Speech Equal Error Rate and Threshold Behaviour 17

7.4 FakeAVCeleb 18

7.5 Comparisons with Published Results 18

Chapter 8 Website and User Interface **19**
8.1 Dashboard 19
8.2 Per-Module Cards and Labels 20
8.3 Score Semantics 20
8.4 Software Testing 21
Chapter 9 Limitations, Ethics and Licensing **22**
9.1 Limitations 22
9.2 Ethics 23
9.3 Licensing 23
Chapter 10 Conclusion and Future Work **24**
10.1 Conclusion 24
10.2 Future Work 24
Chapter 11 Contributions of Team Members **25**
References **27**
Appendix A Supporting Evidence for the Negative Results **30**
A.1 LAV-DF per-Cell Results and the Production-Pipeline Control 30
A.2 Pulse Check and its Positive Control 30
Appendix B: Review and Comparison of 40 Papers **32**

List of Figures

Figure 1. Structure of the analysis platform with its eight modules. *(schematic)* 5
Figure 2. Group-disjoint splits with development slices and sealed tests. *(schematic)* 10
Figure 3. Development-slice AUC along the ladder (exploratory, three seeds). 11
Figure 4. Redesigned dashboard after a live analysis of a demonstration video: the donut counts the checks by outcome; it is not a probability, a score or a verdict (no dataset media shown). *(screenshot)* 19
Figure 5. Check cards of the same report: the face-video card reads Possible manipulation with high uncertainty and shows its model output against the decision line, not as a probability. *(screenshot)* 20

List of Tables

Table 1. Scope of the claims. 2
Table 2. Related work used by the project (cited sources only). 3

Table 3. Functional and non-functional requirements. 4
Table 4. Scoring paths of the frozen final system. 5
Table 5. The eight modules of the platform. 6
Table 6. Labels of the verdict layer and the evidence behind their wording. 7
Table 7. Technology stack. 8
Table 8. Datasets, their use and their terms (all research-only). 9
Table 9. Development ladder before the freeze (exploratory values). 11
Table 10. Steps after the freeze (labels as in Chapter 7: sealed exploratory, exploratory, post hoc or engineering). 13
Table 11. What the final system keeps and what was rejected, with the reason. 15
Table 12. Sealed results (AUC, 95 percent group bootstrap, seeds 0 to 2). 16
Table 13. The three confirmatory tests (paired difference of AUC; sealed confirmatory). 17
Table 14. Published results as context (no ranking of published values). 18
Table 15. What a score means in the system. 21
Table 16. Software verification (engineering, not accuracy). 21
Table 17. Licence terms and what they restrict. 23
Table 18. LAV-DF validation, frozen heads (exploratory): AUC of each kind of fake against the real originals. 30
Table 19. LAV-DF validation, heads trained on LAV-DF: AUC within the produced videos only (post hoc control). 30
Table 20. Positive control for the pulse check: fraction of the 432 clips in which an injected sinusoid is recovered. 31

Chapter 1

Introduction

This chapter gives an overview of the project, states the problem, lists the objectives and fixes the scope: what the system claims and what it does not.

1.1 Overview

Deepfakes are images, videos and audio clips that a learned model has generated or altered: a swapped or re-enacted face, a fully generated picture, or synthesised or converted speech. Detectors trained on one benchmark are usually reported on test data from the same benchmark; when the test data come from another source their scores drop [1]. A person who receives a suspicious file is in the second situation.

This project built, from zero and on one desktop machine, a local system that analyses an uploaded image, video or audio file and reports, check by check, what each detector found within the scope on which it was tested. The work followed a documented path: a simple working version first, then iterations that each changed one thing for a stated reason, a freeze, one reading of sealed test sets, and finally a modular analysis platform with a dashboard. This report is the concise engineering and evaluation record of that path.

1.2 Problem Statement

Given an image, a video with or without an audio track, or an audio file, report for each applicable check whether it found signs of manipulation, with the meaning of its score and the limits of the evidence behind it, and measure the detectors on data from sources that were never used for training or tuning. The system must not turn several weak signals into one overall verdict, and it must not present a detector score as the probability that the file is fake.

1.3 Objectives

1. Define one evaluation protocol before any model exists: group-disjoint splits, development slices separate from sealed tests, sealed tests read once per frozen iteration through a guarded and logged command, three seeds and 95 percent group-bootstrap intervals.

2. Build face-video, generated-image and speech detectors, choose their encoders by a measured comparison, and improve them in iterations that each start from a written hypothesis and success criterion.
3. Decide in advance three confirmatory comparisons for the sealed tests, including one against a re-run published baseline network.
4. Wrap the frozen detectors in a local analysis platform that reports one result per module with its tested scope, limitations and uncertainty, and never a fused score.
5. Keep failed and rejected approaches in the record, with the reason they were rejected.

1.4 Scope

Table 1 separates what the evidence supports from what is outside the claims of this report.

Table 1. Scope of the claims.

Claimed (on the stated data, with intervals)	Not claimed
A reproducible group-disjoint protocol with sealed tests and a logged guard	Audio-visual detection or a fused verdict (the LAV-DF fusion rests on a production-pipeline cue)
Face-video and speech detectors with sealed results and three pre-declared confirmatory tests	Pulse-based (rPPG) detection; lip-sync deepfake detection; temporal localisation
A generated-image detector with sealed exploratory results on ProGAN-era test sets	Generated-video detection, or generated-image detection on modern generators
A local platform with 8 modules, per-module results and no overall score	Speed or throughput claims; a ranking above published detectors (the only comparison on our own protocol is the re-run baseline network)
Negative results kept in the record with their reasons (audio-visual fusion, pulse, generated-video heads)	Any Gemini capability; robustness to social-media processing or edited media (not tested)

Emotion analysis was removed from the scope by the user, and visible-logo or watermark detection is excluded. Chapter 2 summarises the related work, Chapters 3 and 4 describe the system, Chapter 5 the data and the protocol, Chapter 6 the development history, Chapter 7 the results, Chapter 8 the website, Chapter 9 the limitations, ethics and licences, and Chapter 10 concludes.

Chapter 2

Background and Related Work

This chapter summarises the benchmarks and detector families that the project builds on, and the gap that motivated the protocol. It is deliberately compact; only sources that were read are cited.

2.1 Benchmarks, Detector Families and the Gap

Table 2 lists the related work used by this project, what was taken from each source and the gap that remained.

Table 2. Related work used by the project (cited sources only).

Area	Sources and what they provide	What this project takes	Gap left open
Face manipulation in video	FaceForensics++ with four manipulation methods and compression levels [2]; Celeb-DF v2 [3] and Celeb-DF++ with newer methods [4]; DFDC [5]; DeepfakeBench reports Xception at 0.9450 average frame AUC within FaceForensics++ against 0.7718 across other sets [1]	FF++ c23 for training; Celeb-DF family and DFD as unseen sources; Xception [6] as re-run baseline	Published numbers rarely share a protocol, so they cannot rank detectors
Identity leakage	Face-forgery classifiers trained on FF++ learn identity cues [7]; artefact-level features were proposed for forgeries not seen in training [8]	Splits that are disjoint by identity and source video	Random splits measure memorisation of faces
Generated images	ProGAN training set and CNN-synthesis tests [9]; a frozen CLIP linear probe evaluated across generators [10]; a linear support vector machine on CLIP features, trained from few examples of one generator and evaluated on many generators [11]; Community Forensics with thousands of generators [12]	Frozen CLIP ViT-L/14 [13] with a linear probe; Community Forensics subsets after the freeze	Modern commercial generators and real images from many sources
Speech	ASVspoof 2019 LA [14]; AASIST [15]; wav2vec 2.0 front ends [16]; frozen self-supervised encoders with a simple head [17]; In-the-Wild, where 33.9 percent EER was reported [18]	Frozen HuBERT [19], WavLM [20] and Whisper [21] encoders with linear heads	Large drop from studio corpora to recordings in the wild
Audio-visual and physiological	FakeAVCeleb [22]; LAV-DF [23]; audio-visual dissonance [24]; pulse-based claims [25, 26, 27] and the finding that high-quality deepfakes keep a pulse [28]; POS pulse extraction [29]	Sealed FakeAVCeleb half; LAV-DF subset; POS for the pulse check	Whether fusion or pulse adds evidence under a controlled protocol
Generated video	ReStraV perceptual straightening [30]; DeepAction [31]; DF26 with closed commercial generators [32]	Canonical re-encoding, an appearance-baseline head, DF26 as held-out set	Control for the source of the real clips

Temperature scaling fits one scalar on validation logits [33]; it calibrates scores only for data like the validation split. The gap this project addresses is one of protocol, not architecture: a few detectors measured on unseen sources, with intervals, and every rejected idea kept in the record.

Chapter 3

Requirements and System Architecture

This chapter states the requirements, describes the frozen detector pipeline and the post-freeze analysis platform with its eight modules, the report schema, the per-module verdict layer and the Evaluation Lab.

3.1 Requirements

Table 3 lists the requirements and the way the system meets each of them.

Table 3. Functional and non-functional requirements.

Requirement	How the system meets it
Accept an image, a video (with or without audio) or an audio file	A probe validates the type, checks that the file decodes and reads the streams; each module states whether it applies
Report per check, never one overall verdict	One result per module; the keys fused, overall_score, overall_probability, probability_fake and verdict are rejected by the contract checker
Say what a score means	Each result carries its score meaning, tested scope, limitations and an uncertainty level; calibration.is_probability is always false
Isolate failures	Modules run one at a time with a time limit; an exception, a timeout or a contract-breaking result gives failed or timed_out for that module only
Local and private operation	Flask server on 127.0.0.1, 512 MB upload limit, uploads deleted after analysis, one worker, refusal at 4 queued or running jobs
Refuse a wrong model	The adapter refuses a checkpoint whose metadata or preprocessing id does not match
No test-set tuning	Sealed splits readable only through a final-flag command that writes a ledger; the Evaluation Lab enforces the same guard

3.2 Frozen Detector Pipeline

The frozen final system has one scoring path per task (Table 4). Each path ends in a temperature fitted on the detector's own validation split and a threshold chosen on that split as the point of maximum balanced accuracy. There is no fusion in the checkpoint.

Table 4. Scoring paths of the frozen final system.

Task	Input and preprocessing	Encoder and head	Temperature (fitted on)	Threshold
Face video	16 uniformly spaced frames; YuNet face detector [34], largest face enlarged 1.3, 224 x 224 crop; clip score is the mean over frames with a face	SigLIP base [35], fully fine-tuned; linear head	0.8321 (FF++ c23 validation, 700 clips)	0.614
Generated image	Whole image through the encoder's processor	CLIP ViT-L/14, frozen; linear probe	0.6360 (ProGAN validation)	0.2073
Speech	First 64,600 samples at 16 kHz after trimming leading and trailing silence and peak normalisation	Mean of logits of HuBERT base, WavLM base plus and Whisper small encoders, each frozen with a linear head	0.4543 (ASVspoof 2019 LA dev, 24,844 clips)	0.695

3.3 Analysis Platform and Its Eight Modules

After the freeze the detectors were wrapped, unchanged, in a modular platform (Figure 1). A coordinator asks every module whether it applies to the probed file and runs the applicable ones one at a time on the shared GPU, each with its own time limit; a total time limit skips modules not yet started, and every module appears exactly once in the report with one of the statuses completed, not_applicable, unsupported, failed, timed_out or skipped. Table 5 lists the eight modules.




Figure 1. Structure of the analysis platform with its eight modules. *(schematic)*

Table 5. The eight modules of the platform.

Module	Section	What it does	Tier	Can it give a finding?
face_video	authenticity	Largest face of a video, up to 16 frames, frozen face-video detector	detector	Yes (score at or above 0.6139)
image_detector	authenticity	Still image: largest face crop through the face-video head if a face is found, otherwise the whole image through the image head	limited	Yes (0.6139 or 0.2073)
speech	authenticity	About the first 4 s of an audio file or of a video's audio track, three-encoder average	limited	Yes (0.6954); it has no speech check of its own
generated_image	authenticity	Only when image_detector took the face path: frozen image head on the whole image	experimental	No: always inconclusive
generated_video	authenticity	Canonical re-encode of the first 2 s, 8 frames, frozen DINOv2 small [36], mean class token, logistic regression	experimental	No: no head is approved
lip_sync	cross_modal	Audio-visual offset of one tracked face (SyncNet port); consistent inside the band of -6 to +2 frames	limited	Cross-modal finding only, weak evidence
media_metadata	provenance	Container and stream facts	context	Information only
content_credentials	provenance	C2PA manifest validation (c2pa-python 0.38.0)	provenance	Valid, invalid or none found; never means authentic

3.4 Report Schema and Verdict Layer

The report follows schema 2.1 with three sections (authenticity, cross_modal, provenance). The finding vocabulary is closed: authenticity modules report indicates_manipulation, no_indication_within_tested_scope or inconclusive; no value means genuine. Every report carries the fixed statement that a module which found nothing, did not run, was unsupported or was inconclusive does not show that the media is authentic, and that no single probability that the media is fake is given. Optional explanations are fixed server-side templates over the module's own fields, validated so that they contain no number absent from those fields; no language model is involved, and they are not saliency or causal explanations.

A verdict layer adds to every completed module an assessment: a label, a tier, the raw score with its kind and threshold, a calibration statement, an uncertainty level, reasons and evidence references. It re-derives the comparison of score and threshold, and a missing or invalid score or a disagreeing finding gives Inconclusive. Table 6 gives the labels in force. There is no report-level verdict and no fused or overall score.

Table 6. Labels of the verdict layer and the evidence behind their wording.

Module and path	Label when flagged (uncertainty)	Label when not flagged (uncertainty)	Evidence behind the wording
face_video (detector)	Possible manipulation (high)	No strong evidence of manipulation detected (high)	FakeAVCeleb specificity 0.996, sensitivity 0.480; the false-alarm rate of the threshold differed between test sets (Chapter 7)
image_detector, face crop (limited)	Possible manipulation (weak evidence) (high)	Inconclusive (high)	Face-video head on real face photographs: false-positive rate 0.2152, false-negative rate 0.6621
image_detector, whole image (limited)	Possible AI-generation (weak evidence) (high)	Inconclusive (high)	Modern generators: pooled false-positive rate 0.0418, false-negative rate 0.7395
speech (limited)	Possible manipulation (weak evidence) (high)	No strong evidence of manipulation detected (moderate)	FakeAVCeleb audio specificity 0.637; In-the-Wild EER 15.78 percent
lip_sync (limited)	Possible audio-visual mismatch (weak evidence) (high)	No audio-visual mismatch found (high)	Offset band validated on 230 held-out real clips
generated_image, generated_video (experimental)	Experimental signal observed, no reliable verdict available (high)	same	Source confound and inadequate results (Chapter 6)
media_metadata; content_credentials	Information only; Content credentials verified, invalid or not found		Provenance and context, not detection

3.5 Evaluation Lab

The Evaluation Lab is a separate dashboard page that re-analyses recorded score files with the project's metrics and group bootstrap. It runs no model, trains nothing, writes no ledger entry and never touches thresholds, checkpoints or the list of approved heads. A sealed split can only be re-analysed as a final re-analysis of an evaluation already in the ledger, and only if the score file's SHA-256 equals the ledger entry; thresholds come only from validation rows or are given with provenance; groups shared with training or validation, duplicate sample ids and duplicate file hashes refuse a final run; and comparisons use identical samples. A good lab result is not a product approval, and the lab cannot prove that training data excluded the evaluated items when the score file does not record them.

Chapter 4

Technology Stack and Model Integration

This chapter lists the software and hardware and explains how encoders, heads and checkpoints are integrated.

4.1 Stack

Table 7 lists the software and hardware of the system.

Table 7. Technology stack.

Layer	Choice	Role in the system
Hardware	One desktop with an NVIDIA GeForce RTX 5070 (12 GB)	All training and inference; base-size encoders only
Language and environment	Python, managed by uv with a lock file	Reproducible environment
Libraries	PyTorch, timm, Hugging Face Transformers; OpenCV (YuNet), soundfile, ffprobe; c2pa-python 0.38.0	Encoders, fine-tuning and heads; frame, face and audio handling; Content Credentials validation
Web and testing	Flask on 127.0.0.1, static HTML, CSS and JavaScript; pytest; Microsoft Edge	Inference page, dashboard and Evaluation Lab; engineering verification (Chapter 8)

4.2 Encoders, Heads and Checkpoints

Encoders were chosen by a measured sweep rather than by reputation. The image shortlist held EfficientNet-B4 [37], Xception [6], DINOv2 small and base [36], CLIP ViT-L/14 in the OpenAI and LAION versions [13] and SigLIP base [35]; the speech shortlist held wav2vec 2.0 base [38], WavLM base plus [20], Whisper small [21] and HuBERT base [19]. Features were extracted once from the frozen encoders and a linear head was trained on them (class-balanced cross-entropy, AdamW, three head seeds). Full fine-tuning of the face-video encoder used AdamW with learning rate 1e-5, weight decay 0.05, batch 32 and 1,800 steps; only base-size encoders fit in 12 GB; low-rank adapters [39] were not used.

The frozen final system is one checkpoint folder whose metadata records each head, its temperature, its threshold and the preprocessing id of its path. The adapter refuses a checkpoint whose metadata does not match the code. The version-1 web page and the platform modules call the same adapter, so the platform adds no new detector; on 11 non-sealed files the largest absolute difference between them was 0.001919 (tolerance 0.02).

Chapter 5

Datasets and Experimental Methodology

This chapter lists the datasets and their roles, explains the group-disjoint splits, the development slices and the sealed tests with their ledger guard, and defines the metrics, the bootstrap and the three confirmatory tests.

5.1 Datasets

Table 8 lists the datasets, the role of each and the terms under which it was used.

Table 8. Datasets, their use and their terms (all research-only).

Dataset	Task	Use in this project	Terms
FaceForensics++ c23 [2]	face video	train 3,600 clips, validation 700, sealed test_in 700 (70 groups)	non-commercial research and education
Celeb-DF v2 [3]	face video	dev_x 1,728 clips (15 identities); sealed test_x 4,801	non-commercial research; no derived data published
Celeb-DF++ [4]	face video	sealed test_x, 2,849 fakes from 44 identities (dev identities removed)	derived data not published
Celeb-DF family (derived)	face video	sealed test_x for T1 and T3: 7,650 videos (744 real, 6,906 fake), 344 groups (44 identities and 300 single YouTube videos)	as above
DFD (inside FF++)	face video	sealed test_x 3,431 videos, 28 actors	FF++ terms
ForenSynths ProGAN and CNN-synthesis [9]	image	ProGAN train 5,600, validation 2,400, sealed test_in 8,000; CNN-synthesis dev_x 5,998 (2 units), sealed test_x 48,805 (16 groups)	CC BY-NC-SA 4.0
UnivFD diffusion sets [10]	image	sealed test_x 10,000 images (10 groups)	image licence not established
ASVspoof 2019 LA [14]	speech	train 25,380; validation 24,844; sealed test_in 71,237 (67 speakers)	ODC-By
In-the-Wild [18]	speech	dev_x 6,991 clips (12 speakers); sealed test_x 24,788 (42 speakers)	licence conflict unresolved
LAV-DF [23]	audio-visual	subset, 500 videos per cell; sealed test_in 2,000	CC BY-NC 4.0, non-commercial
FakeAVCeleb v1.2 [22]	audio-visual	identity split: dev_x 5,041 clips; sealed test_x 5,013 (250 identities)	request-form terms not recorded
DeepAction v1 [31]	generated video	development only, 2,605 clips	CC BY 4.0; Pexels licence for reals
DF26 [32]	generated video	held-out evaluation; open subset for leave-one-generator-out training	evaluation-only licence; no frames in documents
Community Forensics [12]	image	Small subset for training (23,807); Eval subset for testing (11,550)	CC BY-NC-SA 4.0

5.2 Splits, Development Slices and Sealed Tests

Data were split once and group-disjoint by source identity: the group is the source video together with the person identity, the speaker for speech and the generator unit for images (Figure 2). Each

training dataset has train, validation and an in-dataset sealed test (test_in). Each cross-dataset source is divided into a development slice (dev_x), which ranks candidates and may be reused, and a sealed test (test_x). A script checks group disjointness including content-hash de-duplication; it passed on 80,803 image files and on 41,739 Celeb-DF, In-the-Wild and DFD files.




Figure 2. Group-disjoint splits with development slices and sealed tests. *(schematic)*

Sealed tests are read once per frozen iteration by one command with a final flag, which writes a ledger and refuses a second read without an explicit repeat flag and a logged reason. The ledger of the freeze holds 74 entries and no repeat.

5.3 Metrics, Bootstrap and Comparisons

The headline metric is ROC-AUC with a 95 percent group-bootstrap interval (2,000 resamples over groups); equal error rate and balanced accuracy at the validation threshold are reported where relevant, heads use three seeds and post-freeze proportions use Wilson intervals. In the encoder sweep, candidates whose paired interval against the leader includes zero form a tie set and the cheapest member wins (extraction time, then parameters).

Three confirmatory tests were declared before the sealed run. T1 compares the final face-video system with the first working version on the sealed Celeb-DF family set, and T2 does the same for speech on sealed In-the-Wild; each is an improvement if the lower bound of the paired 95 percent interval is above zero. T3 compares the final face-video system with the re-run Xception baseline on the Celeb-DF family: it is non-inferior if the lower bound is above minus the margin, and a declared superiority rule asks for a lower bound above zero at the 95 percent level. The margin is 0.0100, set by a floor of 0.01 against twice the baseline's seed spread. Each test also reports a 98.33 percent interval (Bonferroni over three tests). The 98.33 percent line was declared as a robustness check beside the 95 percent decision rule; Bonferroni control holds under any dependence between the three tests, so a reader who wants family-wise control should read the 98.33 percent column. Every other sealed number is exploratory.

Chapter 6

Development History and Major Improvements

This chapter records how the system reached its frozen form and what happened after the freeze: for every step the previous version, the limitation, the change, the measured result and its reading. All values before the freeze are exploratory (validation or development slice).

6.1 Before the Freeze

Figure 3 shows the development-slice AUC along the ladder and Table 9 records each step. Iterations that did not meet their pre-written criterion stayed in the record.




Figure 3. Development-slice AUC along the ladder (exploratory, three seeds).

Table 9. Development ladder before the freeze (exploratory values).

Step	Previous version	Limitation found	Change	Result	Interpretation	Remaining limitation
Encoder sweep	none	No evidence for an encoder choice	7 image and 4 speech encoders, frozen, ranked under the cost rule	Video: DINOv2 small 0.6933 [0.6639, 0.7314] wins the tie set; image: CLIP ViT-L/14 0.9935; speech: HuBERT 0.6100, inconclusive	Frozen self-supervised and vision-language features beat CNNs on face video (+0.0994 [+0.0228, +0.1723])	15 identities, 12 speakers: wide intervals

Step	Previous version	Limitation found	Change	Result	Interpretation	Remaining limitation
I-0 working version	sweep winners	No end-to-end system	Frozen encoder, linear head, temperature, validation threshold, web page	Video val 0.7985, dev_x 0.6933; image dev_x 0.9935; speech val 0.9942, dev_x 0.6100	The path works end to end	Video underfits (train AUC 0.8367); speech collapses out of corpus
I-1 fine-tuning (video)	I-0 frozen probe	Underfitting	Full fine-tuning of 3 encoders at 3 learning rates; SigLIP base, lr 1e-5	SigLIP base linear probe 0.7396 [0.7031, 0.7832] to fine-tuned 0.9096 [0.8776, 0.9388]; paired +0.1700 [+0.1228, +0.2114] (same encoder, development slice, 15 identities)	Supported; retained	Errors concentrate in one identity
Xception baseline	none	Need a published-family baseline on the same protocol	Xception fine-tuned with the same recipe, lr 3e-4 from validation	dev_x 0.8716 [0.8364, 0.9076]; SigLIP minus Xception +0.0380 [+0.0172, +0.0592] (development slice, 15 identities)	Baseline for T3; margin 0.0100	Selected rate at the grid edge
I-1b augment and mixup	I-1	Gap of 0.0803 between validation and dev_x	Compression, blur and resize augmentation with mixup	dev_x +0.0219 [+0.0090, +0.0382]; validation -0.0194 [-0.0251, -0.0129]	Does not enter: validation loss beyond the allowance	A trade-off, not a confirmed gain; not sealed-tested
I-1c three-encoder mean (video)	I-1	Single encoder	Mean logit of three fine-tuned encoders	dev_x 0.9192; versus I-1 +0.0096 [-0.0020, +0.0231]	Does not enter: no gain the interval can show	Score correlation 0.89 to 0.91
I-2 speech trimming	I-0 speech	Recording cues (silence, level) consistent with a sign-flipped shortcut; 12 speakers do not establish it	Trim silence, peak-normalise	dev_x 0.6723; gain +0.0623 [+0.0114, +0.1048]	Supported; retained	Loudness alone still separates In-the-Wild
I-3 speech augment	I-2	Short, padded and saturated clips misclassified	Noise, low-pass, reverberation, MP3 round trip	dev_x 0.7455; gain +0.0732 [+0.0122, +0.1225]	Supported; retained	Gains below about +0.09 not showable with 12 speakers
I-4 three encoders (speech)	I-3 (HuBERT)	Single encoder	Mean logit of HuBERT, WavLM base plus, Whisper small	dev_x 0.8130 [0.7523, 0.8808]; gain +0.0675 [+0.0300, +0.0929]	Supported; final speech system	Three encoder passes per clip
I-5 and I-6 LAV-DF fusion	frozen heads	No audio-visual evidence	Pre-check on LAV-DF, then in-domain heads with logistic-regression fusion	Pre-check visual 0.3838; fused 0.9935, but the visual part within produced videos is at chance, 0.5070 [0.4771, 0.5361] (post hoc control)	Fusion rests on a production-pipeline cue; rejected	No audio-visual claim

Step	Previous version	Limitation found	Change	Result	Interpretation	Remaining limitation
I-7 pulse (rPPG)	none	Candidate physiological cue	Signal check on 432 real clips with a shuffled control	0.301 [0.260, 0.346] above threshold, 0.6 required: fails; injected sinusoid recovered in 0.873 of clips	No recoverable pulse in these data; dropped	No pulse ground truth

Appendix A gives the per-cell LAV-DF results behind the fusion row and the positive control behind the pulse row. The freeze (I-8) changed no model: the final system is SigLIP base fine-tuned for face video (I-1), the frozen CLIP image head of I-0 and the three-encoder speech system of I-4. Every frozen iteration was then scored once on the sealed sets (Chapter 7).

6.2 After the Freeze

Table 10 records each study after the freeze; Chapter 7 gives the sealed numbers and their limits.

Table 10. Steps after the freeze (labels as in Chapter 7: sealed exploratory, exploratory, post hoc or engineering).

Step	Previous version	Limitation found	Change	Result	Interpretation	Remaining limitation
Analysis platform	v1 page with one label per modality	Wording overstated scores; no tested scope per check	Modules, coordinator, schema 2.1, dashboard, no overall score	8 modules; 713 tests passed	Presentation layer, no detector change	Per-module labels need user review
FakeAVCeleb sealed half	frozen	No audio-visual sealed set	Score the sealed identity half once	Visual AUC 0.9552, audio 0.9263; visual sensitivity 0.480 at specificity 0.996; audio specificity 0.637	Criteria met, not evidence of detection quality; thresholds do not transfer	Codec shortcut (next row)
Codec audit and control	previous row	Real and fake videos use different codecs	Metadata and pixel audit, canonical re-encode, codec-matched control	Metadata-only AUC 0.9985; frozen visual 0.9732 before, 0.8772 after re-encode; codec-matched 0.8856	Large shortcut, but manipulation evidence remains	Inflation of the sealed AUC not estimated
Generated-video heads	none	Need a generated-video check	Canonical re-encode v3; three heads; DF26 scored zero-shot (one look)	Appearance head: DeepAction 0.8281; DF26 0.4957 [0.4755, 0.5168]	At chance on DF26; installed as experimental only	Pixel statistics still separate classes

Step	Previous version	Limitation found	Change	Result	Interpretation	Remaining limitation
Source test and DF26 heads	appearance head	Possible source confound	Score unmodified real clips; retrain on DF26 open generators	Flags 0.7682 of 440 real clips; a head trained on DF26's open generators reached 0.7548 on the commercial generators (second counted look; the installed head was at chance there; different real sets) but flags 0.8023 of real clips	Confound persists; nothing approved	Needs real clips from many sources
Modern generated images	frozen image	Untested on modern generators	Score 11,550 Community Forensics-Eval images	Macro AUC 0.7039 [0.6855, 0.7229]; misses 0.7395	Inadequate by the pre-written line	Format and size confounded with the label
Retrained image head	frozen image	ProGAN-era training data	Same recipe on 125 recent generators	Macro AUC 0.8839; +0.1800 [+0.1643, +0.1959]; flags 0.5213 of real images	Better ranking; not eligible, kept out	Threshold does not transfer to new real sources
Portrait whole-image check	face path only	Still images with a face never reached the image head	Experimental generated_image module	AUC 0.7859 on 3,119 face images; misses 0.8063	Experimental card, no finding	Needs a portrait validation
Lip-sync band	earlier tolerance rule	False alarms on real speech 15.0 and 13.3 percent	Band of -6 to +2 frames fitted on 230 real clips, validated on 230 others	False alarms 1.3 percent [0.4, 3.8]; Wav2Lip flagged 0 of 160	Installed as weak cross-modal evidence	Not a lip-sync deepfake detector
Verdict wording	schema findings	Text overstated scores; a stronger face label rested on one dataset	Per-module labels; Possible manipulation for face video	The false-alarm rate of the face-video threshold differed between test sets (Chapter 7)	Presentation only; thresholds unchanged	Labels need user review
Evaluation Lab	none	Re-analysis without test tuning	Lab on the evaluation safeguards	57 tests passed; 0.8218 reproduced	Engineering	Cannot see unrecorded training data

6.3 Retained and Rejected Approaches

Table 11 states, for each approach, whether the final system keeps it and why.

Table 11. What the final system keeps and what was rejected, with the reason.

Approach	Status	Reason
SigLIP base, fully fine-tuned (face video)	retained	Largest measured gain over the frozen probe of the same encoder; non-inferior to the re-run Xception at both levels (superiority rule met at 95 percent, not after Bonferroni)
Frozen CLIP ViT-L/14 probe (images)	retained, labelled weak	Strong on ProGAN-era sets; inadequate on modern generators
Trim, augment, three-encoder average (speech)	retained	Three supported steps on the development slice; sealed T2 improved by the declared rule (part of the gain removes a shortcut, Chapter 7)
Augmentation with mixup; three-encoder video mean	rejected	Validation loss beyond the allowance; no gain the interval can show
Audio-visual fusion on LAV-DF	rejected	Driven by a production-pipeline cue (visual 0.5070 within produced videos)
Pulse (rPPG) check	rejected	Signal check failed (0.301 against 0.6 required)
Generated-video heads	experimental, no finding	At chance on DF26 or confounded by source; APPROVED_HEADS stays empty
Retrained modern-image head	not installed	Flags 0.5213 of real images; JPEG re-encoding lowers one family's AUC by 0.1086

6.4 Gemini Investigation

Interest in modern commercial generators led to an assessment of Gemini-generated images. **No Gemini data, model or experiment exists in this project**: nothing was downloaded, trained or evaluated, and the study remains a proposal. It is an unresolved research direction, not a capability. The nearest measured generator is Google Imagen 3, one of the 21 generators of the Community Forensics-Eval subset (203 generated against 688 paired real images): the frozen image head reached AUC 0.7691 [0.7352, 0.8020] and missed 0.8719 of the generated images, and the retrained head reached 0.8646 [0.8360, 0.8917] but flagged 0.5654 of the paired real images. Imagen 3 is not Gemini. Open issues block a study: whether the terms allow Gemini outputs to train a detector, missing provenance (prompts, dates, model build) in candidate sets, the lack of matched real controls, and the fact that different Gemini versions are different generators. A future pre-registered study would need one named model with recorded provenance, about 1,000 generated images split by prompt, real images from at least three sources, format-only baselines and a threshold fixed in advance.

Chapter 7

Evaluation Results and Comparisons

This chapter gives the sealed results, the three confirmatory tests, the speech equal error rates, the FakeAVCeleb reading and the comparisons with published results. Each number carries its label: confirmatory, sealed exploratory or post hoc.

7.1 Sealed Results

The sealed sets were read once for each frozen iteration on 25 October 2026. Table 12 gives AUC with 95 percent group-bootstrap intervals over three seeds. Only the comparisons T1 to T3 on the marked rows are confirmatory; every other value is sealed exploratory.

Table 12. Sealed results (AUC, 95 percent group bootstrap, seeds 0 to 2).

Set (samples, groups)	Working version (I-0)	Final system	Re-run Xception	Label
Celeb-DF family test_x (7,650, 344)	0.6238 [0.6015, 0.6486]	0.8218 [0.8020, 0.8393]	0.8042 [0.7841, 0.8223]	T1, T3
Celeb-DF v2 test_x (4,801, 344)	0.6322 [0.6018, 0.6658]	0.8999 [0.8759, 0.9210]	0.8527 [0.8237, 0.8777]	exploratory
Celeb-DF++ fakes with v2 reals (3,593, 344)	0.6119 [0.5821, 0.6427]	0.7105 [0.6877, 0.7331]	0.7351 [0.7083, 0.7599]	exploratory
DFD test_x (3,431, 28)	0.5927 [0.5629, 0.6258]	0.8797 [0.8566, 0.9041]	0.8847 [0.8655, 0.9052]	exploratory
FF++ c23 test_in (700, 70)	0.7946 [0.7667, 0.8243]	0.9899 [0.9826, 0.9959]	0.9895 [0.9823, 0.9952]	exploratory
In-the-Wild test_x (24,788, 42)	0.7516 [0.6802, 0.8035]	0.9148 [0.8896, 0.9383]		T2
ASVspoof 2019 LA test_in (71,237, 67)	0.9684 [0.9564, 0.9777]	0.9835 [0.9798, 0.9872]		exploratory
ProGAN test_in (8,000, 20)	1.0000 [0.9999, 1.0000]	same head		exploratory
CNN-synthesis test_x (48,805, 16)	0.9316 [0.8933, 0.9694]	same head		exploratory
Diffusion test_x (10,000, 10)	0.9354 [0.8967, 0.9665]	same head		exploratory

The sealed face-video AUC on the family (0.8218) is below its development-slice value (0.9096); these are different data, not a pair. Along the exploratory speech staircase on In-the-Wild (0.7516, 0.8125, 0.8672, 0.9148) the point estimates rise; adjacent intervals overlap. Two of five pre-written predictions failed, both upward for speech.

7.2 Confirmatory Tests

Table 13 gives the three tests declared before the sealed run, with the paired differences, the 95 percent intervals and the 98.33 percent robustness line.

Table 13. The three confirmatory tests (paired difference of AUC; sealed confirmatory).

Test	Difference [95 percent]	98.33 percent interval	Verdict
T1 face video: final minus I-0, Celeb-DF family	+0.1980 [+0.1688, +0.2242]	[+0.1627, +0.2303]	improved, robust
T2 speech: final minus I-0, In-the-Wild	+0.1633 [+0.1177, +0.2266]	[+0.1085, +0.2481]	improved, robust
T3 face video: final minus re-run Xception, Celeb-DF family (margin 0.0100)	+0.0176 [+0.0025, +0.0327]	[-0.0011, +0.0355]	non-inferior at both levels (above -0.0100); 95 percent superiority rule met, not after Bonferroni

Against the re-run Xception baseline (AUC 0.8042 [0.7841, 0.8223]) the final video system is non-inferior at both levels (margin 0.0100); the declared 95 percent superiority rule was met but does not survive the Bonferroni correction (98.33 percent interval [-0.0011, +0.0355]); the baseline ran at 224 px. On the Celeb-DF++ fakes with the Celeb-DF v2 reals (0.7351 against 0.7105) and on DFD (0.8847 against 0.8797) the baseline is higher, both exploratory (Table 12).

Part of the speech gain is the removal of a shortcut rather than better detection of synthesis: in the training corpus the leading silence and the level of a clip carry a weak class signal that points the other way on In-the-Wild (single-feature AUC of leading silence 0.375 on ASVspoof development data against 0.719 on the In-the-Wild development slice; RMS energy 0.594 against 0.248; supported in sign, not in size, with 12 speakers), and the first speech lever, which removes these cues, accounts for 0.061 of the 0.163 sealed gain on the exploratory staircase (0.7516 to 0.8125); a level cue remains on In-the-Wild after normalisation (RMS AUC 0.135 [0.054, 0.382] on the development slice). Test 2 shows that the final speech system ranks In-the-Wild clips better than the working version; it does not show how much of that is better detection of synthesis.

7.3 Speech Equal Error Rate and Threshold Behaviour

The final speech system has an equal error rate of 6.94 percent [5.94, 7.79] on ASVspoof 2019 LA and 15.78 percent [12.75, 18.70] on In-the-Wild. At the frozen validation thresholds the final face-video system detects 0.5896 of the family's fakes, and the speech system flags 0.1716 of real In-the-Wild clips. In a post hoc re-analysis of sealed scores already in the ledger (not confirmatory), the video threshold flags about 0.11 (0.1098) of the real videos of the Celeb-DF family and about 0.14 (0.1405) of DFD. Scores order files within a source, but thresholds do not transfer between sources.

7.4 FakeAVCeleb

On the sealed identity half of FakeAVCeleb (sealed exploratory, one read) the frozen system reached a visual AUC of 0.9552 [0.9442, 0.9657] and an audio AUC of 0.9263 [0.9149, 0.9366], which met their pre-stated criteria. They are not evidence of detection quality. In this data set the video codec coincides with the manipulation method (fake videos are mpeg4, real ones mostly h264): codec metadata alone separates real from fake video at 0.9985 on the development half, and real and fake audio come from different recording channels. At the frozen thresholds the visual sensitivity was 0.480 at a specificity of 0.996, so about half of the fake videos are missed, and the audio specificity was 0.637; thresholds do not transfer. A codec-matched control left manipulation evidence by the pre-written rule. How much the sealed 0.9552 is inflated was not estimated.

7.5 Comparisons with Published Results

No published number is directly comparable with ours: the only comparison on our own protocol is the re-run Xception baseline (T3), which shares the data, the split, the training recipe and the metric. Table 14 sets the published values beside ours as context only. Published values carry no intervals, so no significance test is possible, and no difference is computed.

Table 14. Published results as context (no ranking of published values).

Comparison	Ours	Published	Status and reading
ASVspoof 2019 LA pooled EER, final speech system and AASIST [15]	6.94 percent [5.94, 7.79]	1.13 percent, as quoted by its authors	Context only; AASIST was not re-run here
Same, frozen XLS-R 2B with logistic regression, and RawNet2 [17]	6.94 percent	0.5 percent; 5.9 percent	Context only; not re-run; no sign claimed
In-the-Wild EER, ours on 42 of 54 speakers [18]	15.78 percent [12.75, 18.70]	33.9 percent; 7.2 percent for XLS-R 2B [17], full set	Different test set, no ranking
DF26 zero-shot pooled AUROC, generated-video head [32]	49.57 [47.55, 51.68]	44.0 to 69.7 for nine FF++-trained detectors, no intervals	Context only; training data and frame sampling differ, so no ordering is drawn

AASIST was not re-run, and whether it transfers better or worse than our system was not measured on a common protocol. On DF26 without DF26 training our head is at chance (0.4957 [0.4755, 0.5168]). A head trained on DF26's open generators reached 0.7548 on the commercial generators (one counted look, the second look at that subset); the installed head was at chance there, and the two used different real sets. Other published values (UnivFD diffusion mean average precision 95.00 against our 0.9387 [10]; DeepfakeBench frame-level Xception 0.7365 on Celeb-DF v2 [1]; BA-TFD 0.990 on the full LAV-DF [23]) differ in data or protocol and are context only.

Chapter 8

Website and User Interface

This chapter describes the local dashboard, the per-module cards and labels, what a score means on the page, and the software tests that verify the engineering (not the accuracy) of the system.

8.1 Dashboard

The dashboard is a Flask application on 127.0.0.1 with an upload-first page. In live mode it runs one analysis at a time, refuses new work when 4 jobs are queued or running, accepts files up to 512 MB and deletes uploads after the analysis. The report page first summarises the file, then groups the checks: merits attention, nothing found within tested scope, credential verified, inconclusive, file information, experimental, did not apply, not available and did not complete (Figure 4). The redesigned front end (a cream, beige and warm-brown page served over the unchanged backend) asks what kind of file is analysed, which only filters the file picker; a donut counts the checks of the report by outcome and is labelled as a count, not a probability, a score or a verdict. A detector card shows its model output as a bar against its decision line, labelled not a probability; experimental numbers stay under Technical details. Demonstration scenarios (11 fixtures) run only on request and are marked MOCK. Every text colour pair meets WCAG AA contrast, checked by a script.




Figure 4. Redesigned dashboard after a live analysis of a demonstration video: the donut counts the checks by outcome; it is not a probability, a score or a verdict (no dataset media shown). *(screenshot)*




Figure 5. Check cards of the same report: the face-video card reads Possible manipulation with high uncertainty and shows its model output against the decision line, not as a probability. *(screenshot)*

8.2 Per-Module Cards and Labels

Each completed module has a card with its label (Table 6), supporting signals, the model, limitations and an uncertainty statement (Figure 5). When the face-video score reaches its threshold the card reads **Possible manipulation** with high uncertainty, because the false-alarm rate of that threshold differed between test sets (Chapter 7). Experimental modules always read Experimental signal observed, no reliable verdict available, whatever their score. No card says that media is authentic.

The frozen version-1 page, kept unchanged as history, showed one label per file (Likely fake, Likely real or Undetermined) and the sentence “Calibrated probability that this content is fake”. The platform replaced that wording because the later measurements showed that the scores are not probabilities on other sources.

8.3 Score Semantics

Table 15 states what each kind of score and label means, so that no number on the page is read as the probability that a file is fake.

Table 15. What a score means in the system.

Concept	Meaning	Where it applies
Temperature-scaled score	A temperature fitted on the detector's own validation split; a probability only for content like that split	face_video; image_detector whole-image path
Exploratory calibration	Temperature fitted on ASVspoof dev, but calibration error out of corpus rose after scaling	speech (marked as not calibrated)
Ranking score	Only the order of scores is reliable; not a probability	generated_image, generated_video; any detector on unlike sources
Threshold finding	indicates_manipulation if the score reaches the validation threshold, otherwise no indication within tested scope	face_video, image_detector, speech
Verdict label	Module-specific wording with an uncertainty level; never report-level	every completed module

8.4 Software Testing

Testing verifies that the software behaves as specified; it says nothing about detection accuracy. Table 16 lists the latest recorded results.

Table 16. Software verification (engineering, not accuracy).

Check	Result
Full safe test suite, GPU hidden	713 passed, 2 skipped (opt-in GPU tests), 13 deselected (data-dependent tests), exit 0
Focused suites: verdict, explanation and pipeline; generated_image constraints; Evaluation Lab	112 passed; 7 passed; 57 passed
Opt-in GPU tests; wrapper parity on 11 non-sealed files	5 passed; largest absolute difference 0.001919 (tolerance 0.02)
Live browser demonstration in Microsoft Edge with real detectors, 8 inputs from non-sealed sources	8 of 8 as specified, 0 page errors, no horizontal overflow at 390 px
Dependency lock check	exit 0

Defects found by testing and fixed include a failed live analysis that left the MOCK report on screen and a report overview hidden under the sticky header. Two behaviours are documented and not changed: the speech module scores any sound (a 440 Hz tone receives a finding), and the generated-video score is 1.0 on a real LAV-DF clip and on a synthetic test pattern. Not run: the 13 data-dependent tests, a fresh clone, other browsers and screen readers.

Chapter 9

Limitations, Ethics and Licensing

This chapter consolidates the limitations of the evidence, the ethical position of the product and the licence terms that restrict how the data, weights and results may be used.

9.1 Limitations

1. Small development slices (15 identities, 12 speakers, 2 generator units) give wide intervals; every iteration verdict is exploratory.
2. Sealed video intervals rest on 344 groups (44 identities and 300 single YouTube videos) with 744 real against 6,906 fake videos from two sources; speech on 42 speakers. Every sealed number is one run per frozen iteration.
3. T3 uses one baseline family at one input size (224 px), with the baseline learning rate at the grid edge; the system is non-inferior at both levels, and the superiority rule is met at the 95 percent level only, not after Bonferroni.
4. Part of the sealed speech gain removes a silence and level shortcut (Chapter 7), a level cue remains on In-the-Wild, and the development evidence for the shortcut rests on 12 speakers.
5. Thresholds do not transfer: the face-video system detects 0.5896 of the family's fakes and 0.480 of FakeAVCeleb fakes, and in a post hoc re-analysis of sealed scores already in the ledger (not confirmatory) it flags about 0.11 of the real videos of the Celeb-DF family and about 0.14 of DFD; scores are not probabilities on other sources.
6. Only base-size encoders fit the 12 GB card; published leaders use larger adapted encoders.
7. Dataset artefacts inflate AUC: codecs in FakeAVCeleb, container and colour tags in DeepAction, file format and size in Community Forensics-Eval, a production cue in LAV-DF. Controls reduce but do not remove them.
8. No audio-visual detection, no pulse signal, and every generated-video head is source-confounded or at chance.
9. There is no directly comparable result for face video against a published detector, and edited images, social-media processing and other languages were not tested.

10. Some pre-registrations of the post-freeze studies were hashed into result files but not committed before the runs, which is weaker than a commit.

9.2 Ethics

The product never says that media is authentic, gives no overall verdict, and never lets an experimental signal decide. A valid Content Credential concerns the origin of a file relative to an operator-configured trust anchor, not the truth of its content. Every label carries its uncertainty because a wrong flag can harm the person shown in a file. Detection results describe a file, never a person's intent.

9.3 Licensing

Table 17 lists the licence terms that limit how the data, weights and results may be used.

Table 17. Licence terms and what they restrict.

Item	Terms	Consequence
Celeb-DF, Celeb-DF++, FakeAVCeleb	Research only; no publication of derived data (FakeAVCeleb form terms not recorded)	No frame, crop or per-video score in any document
LAV-DF; DF26	Non-commercial; DF26 evaluation-only with no redistribution	Aggregate results only; no frames
Community Forensics	CC BY-NC-SA 4.0	No images in public deliverables; retrained heads are research artefacts, not installed
In-the-Wild; diffusion test images	Licence conflict or not established	Recorded as open questions
OpenAI CLIP ViT-L/14; WavLM base plus	No licence stated (CLIP) or conditional (WavLM); treated as research-only	Checkpoints cannot be published or used commercially
SyncNet v2 weights	Weights licence not stated by the source	Used for an academic prototype only
SigLIP, DINOv2, HuBERT, Whisper, YuNet, c2pa-python	Permissive (Apache-2.0 or MIT)	No added restriction

Chapter 10

Conclusion and Future Work

This chapter summarises what was achieved and what remains open.

10.1 Conclusion

The project delivered a local system that analyses images, videos and speech, and a complete record of the path. Under the protocol the final face-video system improved, by the declared rule, over the first working version on the sealed Celeb-DF family (+0.1980 [+0.1688, +0.2242]) and the speech system improved on sealed In-the-Wild (+0.1633 [+0.1177, +0.2266]), although part of the speech gain removes a silence and level shortcut and is not all better detection of synthesis. Against a re-run Xception baseline the face-video system is non-inferior at both levels (margin 0.0100); the declared 95 percent superiority rule was met but does not survive the Bonferroni correction (98.33 percent interval [-0.0011, +0.0355]), and the baseline ran at 224 px.

The platform reports what each of its eight modules found within its tested scope, with cautious labels and no overall score. Later studies mostly added limits. On FakeAVCeleb the frozen system's AUCs met their pre-stated criteria but are not evidence of detection quality (codec metadata alone gives 0.9985 on the development half) and the thresholds do not transfer. On LAV-DF a near-perfect fused score rested on a production cue (its visual part is at chance within the produced videos), so no audio-visual detection is claimed. Modern generated video and images remain unsolved.

10.2 Future Work

- Score the frozen face system on the official Celeb-DF v2 test list, next to the Xception baseline.
- Parameter-efficient adaptation of a larger CLIP encoder; a larger frozen speech encoder; a lip-sync model of the full time-delay distribution with a false-alarm control.
- Generated-video training with real clips from many sources (the source-confound test as acceptance test); for modern images a threshold calibrated on diverse real sources and a portrait validation; a Gemini study once its blockers are resolved.

Chapter 11

Contributions of Team Members

This chapter states who did what. The project was split into 22 individually accomplishable tasks (Table 23). Table 21 summarises the work of each member, Table 22 shows which members contributed to the work reported in each chapter of this report, and Table 23 lists every task with its owner. The contributions are as stated by the team members.

Table 21. Contribution of each team member (summary).

Member	Roll No.	Project tasks (Table 23)	Contribution
Shivansh Gupta	16014023052	1, 2 (22 papers), 3 (shared with Vaibhav), 5, 6, 12, 13, 17, 20	Problem definition and scope; dataset access and licence records (shared with Vaibhav); evaluation protocol, bootstrap intervals, test guard and experiment ledger; preprocessing; generated-image and generated-video experiments including the modern-generator and Gemini assessment; rPPG experiment; provenance modules; research paper.
Vaibhav Shiroorkar	16014024805	2 (21 papers), 3 (shared with Shivansh), 4, 8, 9, 11, 14, 18, 19, 21	Dataset access and licence records (shared with Shivansh); data pipeline, identity-separated splits and leakage checks; face-video model (SigLIP fine-tuning, augmentation, ensemble trials); speech model and three-encoder ensemble; lip-sync module; Xception baseline and the final sealed evaluation (T1 to T3); testing and browser tests; environment setup and reproducibility; this technical report.
Adithya Jithesh	16014024803	2 (43 papers), 7, 10, 15, 16, 22	Largest share of the literature survey; encoder comparison and the first working version (I-0); audio-visual fusion experiments (LAV-DF, I-5, I-6) and FakeAVCeleb evaluation with shortcut audits; backend (module interface, coordinator, verdict layer, API); website and Evaluation Lab frontend; presentation.

Table 22. Contribution to the work reported in each chapter of this report.

Chapter	Work reported	Members (tasks)
Abstract, 1 Introduction	Problem, scope, objectives and requirements; written up in this report	Shivansh (1); Vaibhav (21)
2 Background and Related Work, Appendix B	Literature survey of 86 papers, the 40-paper review and the gap	Adithya 43 papers, Shivansh 22, Vaibhav 21 (2)
3 Requirements and System Architecture	Backend, verdict layer and API; Evaluation Lab; lip-sync and provenance modules	Adithya (15, 16); Vaibhav (11); Shivansh (17)
4 Technology Stack and Model Integration	Environment and reproducibility; encoder comparison; face-video and speech models	Vaibhav (19, 8, 9); Adithya (7)
5 Datasets and Experimental Methodology	Dataset access and licences; preprocessing; data pipeline and splits; evaluation protocol	Shivansh (3, 6, 5); Vaibhav (3, 4)
6 Development History	I-0; I-1 to I-1c; I-2 to I-4; I-5 and I-6 fusion; rPPG; generated image and video; Gemini	Adithya (7, 10); Vaibhav (8, 9); Shivansh (12, 13)
7 Evaluation Results and Comparisons	Xception baseline, sealed evaluation T1 to T3; FakeAVCeleb evaluation; protocol, intervals and ledger	Vaibhav (14); Adithya (10); Shivansh (5)
8 Website and User Interface	Website, Evaluation Lab, backend API, testing and browser tests	Adithya (15, 16); Vaibhav (18)
9 Limitations, Ethics and Licensing	Limitations, dataset licences and provenance records	Shivansh (3, 17); Vaibhav (3)

Chapter	Work reported	Members (tasks)
10 Conclusion and Future Work	Conclusion drawn from the sealed results; written up in this report	Shivansh (1, 20); Vaibhav (21)

Table 23. Project task allocation (22 tasks).

No.	Task	Assigned to
A. Research and Planning		
1	Problem definition, scope and requirements	Shivansh
2	Literature survey: 86 papers and related-work comparison	Adithya: 43 papers; Shivansh: 22 papers; Vaibhav: 21 papers
3	Dataset access, downloads, licence records and documentation (FF++, Celeb-DF, DFD, ASVspoof, In-the-Wild, LAV-DF, FakeAVCeleb)	Shivansh and Vaibhav
B. Data and Evaluation		
4	Data pipeline: manifests, identity/speaker-separated splits, leakage and duplicate checks	Vaibhav
5	Evaluation protocol: metrics, bootstrap confidence intervals, test guard and experiment ledger	Shivansh
C. Models and Experiments		
6	Preprocessing: frame sampling, face detection and cropping, audio extraction	Shivansh
7	Encoder comparison and first working version (I-0)	Adithya
8	Face-video model: SigLIP fine-tuning, augmentation and ensemble trials (I-1, I-1b, I-1c)	Vaibhav
9	Speech model: silence trimming, augmentation and three-encoder ensemble (I-2 to I-4)	Vaibhav
10	Audio-visual experiments: LAV-DF fusion (I-5, I-6), FakeAVCeleb evaluation and shortcut audits	Adithya
11	Lip-sync module (SyncNet) and validation	Vaibhav
12	Generated-image and generated-video experiments, including modern-generator and Gemini assessment	Shivansh
13	rPPG pulse experiment	Shivansh
14	Xception baseline and final sealed evaluation (T1 to T3)	Vaibhav
D. Software Engineering		
15	Backend: module interface, coordinator, verdict layer and API	Adithya
16	Website and Evaluation Lab frontend	Adithya
17	Provenance modules: C2PA and metadata analysis	Shivansh
18	Testing, quality checks and browser tests	Vaibhav
19	Environment setup, installation instructions and reproducibility	Vaibhav
E. Final Deliverables		
20	Research paper	Shivansh
21	Final technical report	Vaibhav
22	Presentation	Adithya

References

[1] Z. Yan, Y. Zhang, X. Yuan, S. Lyu and B. Wu, "DeepfakeBench: A comprehensive benchmark of deepfake detection," in Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track, 2023.

[2] A. Rössler, D. Cozzolino, L. Verdoliva, C. Riess, J. Thies and M. Nießner, "FaceForensics++: Learning to detect manipulated facial images," in Proc. IEEE/CVF International Conference on Computer Vision (ICCV), 2019.

[3] Y. Li, X. Yang, P. Sun, H. Qi and S. Lyu, "Celeb-DF: A large-scale challenging dataset for DeepFake forensics," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2020.

[4] Y. Li, D. Zhu, X. Cui and S. Lyu, "Celeb-DF++: A large-scale challenging video DeepFake benchmark for generalizable forensics," arXiv:2507.18015v1, 2025.

[5] B. Dolhansky, J. Bitton, B. Pflaum, J. Lu, R. Howes, M. Wang and C. Canton Ferrer, "The DeepFake Detection Challenge (DFDC) dataset," arXiv:2006.07397v4, 2020.

[6] F. Chollet, "Xception: Deep learning with depthwise separable convolutions," in Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2017.

[7] S. Dong, J. Wang, R. Ji, J. Liang, H. Fan and Z. Ge, "Implicit identity leakage: The stumbling block to improving deepfake detection generalization," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2023.

[8] L. Li, J. Bao, T. Zhang, H. Yang, D. Chen, F. Wen and B. Guo, "Face X-ray for more general face forgery detection," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2020.

[9] S.-Y. Wang, O. Wang, R. Zhang, A. Owens and A. A. Efros, "CNN-generated images are surprisingly easy to spot... for now," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2020.

[10] U. Ojha, Y. Li and Y. J. Lee, "Towards universal fake image detectors that generalize across generative models," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2023.

[11] D. Cozzolino, G. Poggi, R. Corvi, M. Nießner and L. Verdoliva, "Raising the bar of AI-generated image detection with CLIP," in Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), 2024.

[12] J. Park and A. Owens, "Community Forensics: Using thousands of generators to train fake image detectors," arXiv:2411.04125v2, 2025 (preprint).

[13] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry et al., "Learning transferable visual models from natural language supervision," in Proc. 38th International Conference on Machine Learning (ICML), PMLR 139, 2021.

[14] X. Wang, J. Yamagishi, M. Todisco, H. Delgado, A. Nautsch, N. Evans et al., "ASVspoof 2019: A large-scale public database of synthesized, converted and replayed speech," Computer Speech and Language, 2020, doi: 10.1016/j.csl.2020.101114.

[15] J. Jung, H. Heo, H. Tak, H. Shim, J. S. Chung, B. Lee, H. Yu and N. Evans, “AASIST: Audio anti-spoofing using integrated spectro-temporal graph attention networks,” in Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), 2022.

[16] H. Tak, M. Todisco, X. Wang, J. Jung, J. Yamagishi and N. Evans, “Automatic speaker verification spoofing and deepfake detection using wav2vec 2.0 and data augmentation,” in Proc. Speaker and Language Recognition Workshop (Odyssey), 2022.

[17] O. Pascu, A. Stan, D. Oneata, E. Oneata and H. Cucu, “Towards generalisable and calibrated audio deepfake detection with self-supervised representations,” in Proc. Interspeech, 2024, pp. 4828-4832, doi: 10.21437/Interspeech.2024-1302.

[18] N. M. Müller, P. Czempin, F. Dieckmann, A. Froghyar and K. Böttinger, “Does audio deepfake detection generalize?,” in Proc. Interspeech, 2022.

[19] W.-N. Hsu, B. Bolte, Y.-H. H. Tsai, K. Lakhotia, R. Salakhutdinov and A. Mohamed, “HuBERT: Self-supervised speech representation learning by masked prediction of hidden units,” IEEE/ACM Transactions on Audio, Speech, and Language Processing, vol. 29, pp. 3451-3460, 2021.

[20] S. Chen, C. Wang, Z. Chen, Y. Wu, S. Liu, Z. Chen et al., “WavLM: Large-scale self-supervised pre-training for full stack speech processing,” IEEE Journal of Selected Topics in Signal Processing, vol. 16, no. 6, pp. 1505-1518, 2022.

[21] A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey and I. Sutskever, “Robust speech recognition via large-scale weak supervision,” in Proc. 40th International Conference on Machine Learning (ICML), PMLR 202, 2023.

[22] H. Khalid, S. Tariq, M. Kim and S. S. Woo, “FakeAVCeleb: A novel audio-video multimodal deepfake dataset,” in Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track, 2021.

[23] Z. Cai, K. Stefanov, A. Dhall and M. Hayat, “Do you really mean that? Content driven audio-visual deepfake dataset and multimodal method for temporal forgery localization,” in Proc. International Conference on Digital Image Computing: Techniques and Applications (DICTA), 2022.

[24] K. Chugh, P. Gupta, A. Dhall and R. Subramanian, “Not made for each other: Audio-visual dissonance-based deepfake detection and localization,” in Proc. 28th ACM International Conference on Multimedia, 2020.

[25] U. A. Ciftci, I. Demir and L. Yin, “FakeCatcher: Detection of synthetic portrait videos using biological signals,” IEEE Transactions on Pattern Analysis and Machine Intelligence, 2020, doi: 10.1109/TPAMI.2020.3009287.

[26] U. A. Ciftci, I. Demir and L. Yin, “How do the hearts of deep fakes beat? Deep fake source detection via interpreting residuals with biological signals,” in Proc. IEEE International Joint Conference on Biometrics (IJCB), 2020.

[27] J. Hernandez-Ortega, R. Tolosana, J. Fierrez and A. Morales, “DeepFakesON-Phys: DeepFakes detection based on heart rate estimation,” arXiv:2010.00400v3, 2020.

[28] C. Seibold, E. L. Wisotzky, A. Beckmann, B. Kossack, A. Hilsmann and P. Eisert, “High-quality deepfakes have a heart!,” Frontiers in Imaging, vol. 4, 2025, doi: 10.3389/fimag.2025.1504551.

[29] W. Wang, A. C. den Brinker, S. Stuijk and G. de Haan, “Algorithmic principles of remote PPG,” IEEE Transactions on Biomedical Engineering, vol. 64, no. 7, pp. 1479-1491, 2017.

[30] C. Internò, R. Geirhos, M. Olhofer, S. Liu, B. Hammer and D. Klindt, “AI-generated video detection via perceptual straightening,” in Advances in Neural Information Processing Systems (NeurIPS), 2025, arXiv:2507.00583.

[31] M. Bohacek and H. Farid, “Human action CLIPs: Detecting AI-generated human motion,” in Workshop on Deepfake Detection, Localization and Interpretability at IJCAI 2025, arXiv:2412.00526.

[32] S. Shykula, A. Yermakov, I. Samarskyi, D. Mishkin, J. Cech and A. Mishchuk, “DF26: We cannot tell fake from real anymore,” arXiv:2609.07369v1, 2026 (preprint).

[33] C. Guo, G. Pleiss, Y. Sun and K. Q. Weinberger, “On calibration of modern neural networks,” in Proc. 34th International Conference on Machine Learning (ICML), PMLR 70, 2017.

[34] W. Wu, H. Peng and S. Yu, “YuNet: A tiny millisecond-level face detector,” Machine Intelligence Research, vol. 20, no. 5, pp. 656-665, 2023, doi: 10.1007/s11633-023-1423-y.

[35] X. Zhai, B. Mustafa, A. Kolesnikov and L. Beyer, “Sigmoid loss for language image pre-training,” in Proc. IEEE/CVF International Conference on Computer Vision (ICCV), 2023.

[36] M. Oquab, T. Darcet, T. Moutakanni, H. Vo, M. Szafraniec, V. Khalidov, P. Fernandez et al., “DINOv2: Learning robust visual features without supervision,” Transactions on Machine Learning Research, 2024.

[37] M. Tan and Q. V. Le, “EfficientNet: Rethinking model scaling for convolutional neural networks,” in Proc. 36th International Conference on Machine Learning (ICML), PMLR 97, 2019.

[38] A. Baevski, Y. Zhou, A. Mohamed and M. Auli, “wav2vec 2.0: A framework for self-supervised learning of speech representations,” in Advances in Neural Information Processing Systems (NeurIPS), vol. 33, 2020.

[39] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang and W. Chen, “LoRA: Low-rank adaptation of large language models,” in Proc. International Conference on Learning Representations (ICLR), 2022.

Appendix A

Supporting Evidence for the Negative Results

This appendix holds the detail behind two negative results of Chapter 6, because an examiner asking why audio-visual detection and a pulse check were dropped needs the per-cell numbers. All values are exploratory (validation split of LAV-DF, or 432 real clips).

A.1 LAV-DF per-Cell Results and the Production-Pipeline Control

Table 18 gives the AUC of the frozen face-video and speech heads for each kind of fake against the real originals. The visual head is below chance on every cell, including the audio-only fakes whose frames are untouched, so it responds to something other than the manipulation.

Table 18. LAV-DF validation, frozen heads (exploratory): AUC of each kind of fake against the real originals.

Kind of fake	Visual head	Audio head
video fake	0.2788 [0.2488, 0.3087]	0.5564 [0.5215, 0.5895]
audio fake (frames untouched)	0.2876 [0.2568, 0.3174]	0.6804 [0.6464, 0.7119]
both fake	0.2692 [0.2393, 0.2986]	0.6708 [0.6378, 0.7029]

Table 19 gives heads trained on LAV-DF, whose fused score reached 0.9935 [0.9905, 0.9962]. Its AUCs are computed within the produced videos only, so that every clip went through the data set's own pipeline (a control run after the result, not a declared criterion). The visual head separates the real originals from the audio-only fakes at 0.9912 [0.9864, 0.9951] although their frames are untouched, and is at chance for its own label within the produced videos; the audio head is the only one above chance there.

Table 19. LAV-DF validation, heads trained on LAV-DF: AUC within the produced videos only (post hoc control).

Score	Label asked	AUC [95 percent]
visual head	video manipulated	0.5070 [0.4771, 0.5361]
audio head	audio manipulated	0.8574 [0.8394, 0.8752]
visual head	audio manipulated (should be near 0.5)	0.5029 [0.4743, 0.5320]
audio head	video manipulated (should be near 0.5)	0.3330 [0.3059, 0.3602]

A.2 Pulse Check and its Positive Control

The pulse check asked whether a pulse-band signal from the skin of 432 real clips exceeds the 95th percentile of a time-shuffled control in at least 0.6 of the clips. It did in 0.301 [0.260, 0.346] (0.280 on FaceForensics++, 0.288 on Celeb-DF v2 and 0.333 on LAV-DF), so the check failed: a

pulse signal is not recoverable from these data. Table 20 shows that the pipeline can see a clean sinusoid. A sinusoid of 1.2 Hz was injected into the skin pixels of the same clips after decoding. It shows the sensitivity of the pipeline to a clean sinusoid of that size; it does not show that a real pulse exists in these videos or survives compression.

Table 20. Positive control for the pulse check: fraction of the 432 clips in which an injected sinusoid is recovered.

Relative green amplitude	Recovered [95 percent Wilson]
0 (control, reproduces the pulse check)	130/432 = 0.301 [0.260, 0.346]
0.002	148/432 = 0.343 [0.299, 0.389]
0.004	236/432 = 0.546 [0.499, 0.593]
0.008	377/432 = 0.873 [0.838, 0.901]
0.016	420/432 = 0.972 [0.952, 0.984]

Appendix B: Review and Comparison of 40 Papers

This appendix extends Chapter 2 with a paper-by-paper review of the 40 sources that informed the project. Every paper listed was read in full or in the parts stated in the project literature matrix (docs/RESEARCH.md). Reported results are quoted from the papers under their own protocols and are context, not a ranking against this project; the comparability of published results with ours is discussed in Section 7.5.

#	Paper	Task, method and data	Reported result	Limitation or gap	Use in this project
1	Rossler et al. (2019), FaceForensics++, ICCV	face video. Benchmark dataset, 4 manipulations x 3 compressions, XceptionNet baseline. Data: FF++ 1,000 real videos, 720/140/140 split	XceptionNet frame accuracy 95.73% (c23), 81.00% (c40), in-dataset	Four 2019 methods; in-dataset; identity overlap of fixed split not stated	dataset used; Xception baseline re-run
2	Li et al. (2020), Celeb-DF, CVPR	face video. Harder face-swap dataset with fewer visible artefacts. Data: 590 real, 5,639 fake videos, 59 identities	Xception-c23 frame AUC 65.3% on Celeb-DF (pretrained, not retrained)	Detectors not retrained; key frames only; 59 people; face swap only	dataset used (cross-dataset test)
3	Dolhansky et al. (2020), DFDC dataset, arXiv 2006.07397	face video. Large consented face-swap dataset and Kaggle challenge. Data: 119,154 train clips, 486 subjects; private test 10,000 clips	Top-5 private log loss 0.4279 to 0.4371; organic-only ROC-AUC 0.734	Organic-content results near chance; perturbation-dependent	comparison context
4	Li et al. (2020), Face X-ray, CVPR	face video. Predicts blending-boundary map, trained on self-made blends. Data: FF++ or blended reals; test DFD, DFDC, Celeb-DF	Celeb-DF AUC 80.58% (FF++ plus blends) vs Xception 36.19%	Needs a blending step; may fail on fully synthetic images; weaker under compression	design reference
5	Yan et al. (2023), DeepfakeBench, NeurIPS Datasets and Benchmarks	face video. Unified benchmark: 15 detectors, 9 datasets, one pipeline. Data: Train FF++ c23; test 8 cross-domain sets; frame AUC	Xception mean cross-domain AUC 0.7718; UCF 0.7801	Frame-level only; seeds not stated; preprocessing-dependent	comparison context; evaluation harness reference
6	Haliassos et al. (2021), Lips Don't Lie (LipForensics), CVPR	face video. Frozen lipreading ResNet-18 plus fine-tuned temporal net on mouth crops. Data: Train FF++; test CDF-v2, DFDC, FaceShifter, DeeperForensics	Cross-dataset video AUC: CDF 82.4, DFDC 73.5, mean 87.7	Not for still images; needs visible mouth; DFDC and CDF weakest	comparison context
7	Shiohara and Yamasaki (2022), Self-Blended Images (SBI), CVPR	face video. Synthetic training fakes by self-blending real faces, EfficientNet-B4. Data: Train FF++ real only; test CDF-v2, DFD, DFDC, DFDCP, FFIW	Cross-dataset video AUC Celeb-DF-v2 93.18%, DFDC 72.42%	One run, no seeds; fails on whole-image synthesis (AUC 69.11)	design reference; comparison context
8	Yan et al. (2025), Effort: Orthogonal Subspace Decomposition, ICML (PMLR 267)	face video / generated image. SVD residual adaptation of frozen CLIP ViT-L/14, 0.19M trainable params. Data: Train FF++ c23 (deepfake) or ProGAN (images); DeepfakeBench pipeline	Cross-dataset video AUC CDF-v2 0.956, mean 0.917 over 7 sets	No seeds, intervals, VRAM or time; ablations on test sets	design reference (parameter-efficient adaptation)
9	Dong et al. (2023), Implicit Identity Leakage, CVPR	face video. ID-unaware detector with anchor-based local artefact detection. Data: Train FF++; test FF++, Celeb-DF, DFDC-V2; video AUC	In-dataset FF++ video AUC 99.70 to 99.79	Split identity overlap not stated; no seeds	design reference (identity-disjoint split)
10	Cui et al. (2025), Forensics Adapter, CVPR (as labelled in paper)	face video. Small ViT-tiny adapter beside frozen CLIP ViT-L/14 with boundary supervision. Data: DeepfakeBench pipeline, train FF++ c23	Cross-dataset frame AUC CDF-v2 0.900, DFDC 0.843	No seeds or intervals; FF++ c23 training only; face forgeries only	design reference; comparison context
11	Li et al. (2025), Celeb-DF++, arXiv 2507.18015	face video. Celeb-DF extended with 22 generation methods, 3 protocols, 24 detectors. Data: 590 real videos, 53,196 fakes, 59 identities	Cross-generator: Effort best, 84.4% video-level AUC average	Compression settings unclear; 59 real identities; talking faces from one still	dataset used
12	Wang et al. (2020), CNNDetection: CNN-generated images are easy to spot, CVPR	generated image. ResNet-50 trained on ProGAN with blur and JPEG augmentation. Data: Train 720K ProGAN images; test 11 generators	Mean AP 92.6 with blur+JPEG 10%, cross-generator (marked to verify in docs)	Single runs; 2020 CNN generators only	comparison context

#	Paper	Task, method and data	Reported result	Limitation or gap	Use in this project
13	Ojha et al. (2023), UnivFD: Universal Fake Image Detectors, CVPR	generated image. Linear probe or nearest neighbour on frozen CLIP ViT-L/14. Data: Train ProGAN; test GANs, diffusion, autoregressive	Linear probe mean AP 95.00 on unseen diffusion/autoregressive	General images, not face video; CLIP may miss fine artefacts	design reference (frozen encoder plus linear head)
14	Cozzolino et al. (2024), Raising the Bar with CLIP, CVPR Workshops	generated image. Linear SVM on CLIP ViT-L/14 features from few paired images. Data: Latent Diffusion vs COCO pairs; test 18 generators	not quoted	Single run for large N; reference-set content changes AUC	design reference
15	Zhu et al. (2023), GenImage, arXiv 2306.08571 (preprint)	generated image. Million-scale benchmark from 8 generators. Data: 1.33M real ImageNet, 1.35M fake images	ResNet-50 train SD1.4, mean cross-generator accuracy 72.1%	Single runs; JPEG and size shortcuts shown later; venue unconfirmed	comparison context
16	Grommelt et al. (2024), Fake or JPEG?, ECCV Workshops	generated image. Exposes JPEG and size biases in GenImage, retrains without them. Data: GenImage; ResNet-50 and Swin-T	ResNet-50 cross-generator accuracy 71.68 to 82.74 after bias removal	Only GenImage and two backbones; size constraint cuts data	design reference (format leakage audit)
17	Park and Owens (2025), Community Forensics, arXiv 2411.04125	generated image. Training on 2.7M images from 4,803 generators. Data: CLIP ViT-S, ConvNeXt-S; 26K image eval from 21 held-out generators	Held-out generators mAP 0.987, accuracy 0.892	Mostly diffusion generators; single headline run	comparison context
18	Wang et al. (2020), ASVspoof 2019 database, Computer Speech and Language	speech. LA (TTS and VC) and PA (replay) spoofing database. Data: 107 speakers; LA eval 7,355 bona fide, 63,882 spoofed	not quoted	Database paper; baseline numbers not recorded	dataset used
19	Jung et al. (2022), AASIST, ICASSP	speech. Spectro-temporal graph attention on raw waveform. Data: ASVspoof 2019 LA; 3 seeds; EER and min t-DCF	LA eval EER 0.83% best seed, 1.13% mean of 3	Best-of-seed headline; in-dataset only	comparison context
20	Tak et al. (2022), wav2vec 2.0 and data augmentation for anti-spoofing, Odyssey	speech. Fine-tuned XLS-R front end with AASIST and RawBoost. Data: Train ASVspoof 2019 LA; test 2021 LA and DF	2021 LA pooled EER 0.82% best seed (1.00% mean)	Large external pretraining; augmentation chosen per test set	design reference (SSL front end)
21	Yamagishi et al. (2021), ASVspoof 2021 challenge, ASVspoof 2021 Workshop	speech. Challenge overview: LA, PA and speech deepfake tasks. Data: Train 2019 data; eval under codec and compression shift	DF best EER 15.64% (30 submissions)	Challenge overview, not a controlled comparison	comparison context
22	Muller et al. (2022), Does Audio Deepfake Detection Generalize? (In-the-Wild), Interspeech	speech. Re-implements 12 models, releases In-the-Wild set. Data: Train ASVspoof 2019 LA; test ASVspoof eval and In-the-Wild; 3 seeds	Best In-the-Wild EER about 33.9% (RawNet2)	In-the-Wild fakes biased toward obvious, publicity fakes	dataset used (In-the-Wild)
23	Pascu et al. (2024), Generalisable and calibrated audio deepfake detection, Interspeech	speech. Frozen wav2vec2/WavLM features plus logistic regression. Data: Train ASVspoof 2019 LA; test 8 datasets incl. In-the-Wild	XLS-R 2B In-the-Wild EER 7.2%	EER only; 2B encoder needs about 9.3 GB; HuBERT and Whisper untested	design reference (closest recipe to our audio path)
24	Khalid et al. (2021), FakeAVCeleb, NeurIPS Datasets and Benchmarks	audio-visual. Audio-video deepfake dataset with cloned lip-synced audio. Data: 500 real, 19,500 fake videos	Video-only EfficientNet-B0 AUC 93.3; multimodal 53.3 to 68.8	Only 500 real videos; request access; splits vary across papers	dataset used
25	Cai et al. (2022), LAV-DF and BA-TFD, DICTA	audio-visual. Content-driven local AV fakes plus localisation model. Data: 136,304 videos, 153 identities, identity-independent split	BA-TFD classification AUC 0.990 on LAV-DF test	One TTS and one lip-sync generator; near-saturated classification	dataset used
26	Cai et al. (2024), AV-Deepfake1M, ACM MM	audio-visual. LLM-driven transcript edits, VITS/YourTTS audio, TalkLip video. Data: 1.15M videos, 2,068 subjects, subject-disjoint	Xception detection AUC 68.68 (vs 83.58 on LAV-DF)	Research-only licence; 3:1 fake ratio; subject counts inconsistent	comparison context
27	Feng et al. (2023), AVAD: audio-visual anomaly detection, arXiv 2301.01767	audio-visual. Sync network plus autoregressive model trained on real videos only. Data: Train LRS2/LRS3; test FakeAVCeleb and KoDF	KoDF cross-dataset AUC 86.9	Misses fake audio that stays in sync (RVFA AUC 71.6); small tests	design reference
28	Zou et al. (2024), MRDF, arXiv 2401.05746	audio-visual. AV transformer with cross- and within-modality regularisation. Data: FakeAVCeleb only, balanced, 5-fold	ACC/AUC 94.05/92.43 in-dataset	One dataset; no cross-dataset test; no seeds	comparison context

#	Paper	Task, method and data	Reported result	Limitation or gap	Use in this project
29	Oorloff et al. (2024), AVFF, arXiv 2406.02951	audio-visual. Self-supervised AV pretraining on real videos then supervised head. Data: Stage 1 LRS3; stage 2 FakeAVCeleb 70/30; KoDF subset	FakeAVCeleb AUC 99.1; KoDF cross-dataset AUC 95.5	Needs both modalities in sync; identity disjointness not stated	comparison context
30	Chung and Zisserman (2017), Out of time (SyncNet), ACCV 2016 Workshops (LNCS)	audio-visual. Two-stream audio and mouth embedding for lip-sync offset. Data: BBC News broadcast, several hundred hours	Sync accuracy above 99% averaged over a clip	Manual evaluation; no deepfake data; no false-alarm rate	design reference (lip_sync module)
31	Prajwal et al. (2020), Wav2Lip, ACM MM	audio-visual. Lip-sync generator trained against an expert SyncNet discriminator. Data: LRS2, LRS3, LRW	LRS2 LSE-D 6.386 (real 6.736)	Generator paper, not a detector; read via ar5iv only	comparison context (explains SyncNet blind spot)
32	Wang et al. (2017), Algorithmic Principles of Remote-PPG (POS), IEEE TBME	rPPG. POS projection orthogonal to skin tone, training-free. Data: Own 60-sequence uncompressed benchmark	not quoted	Lab video, uncompressed, no deepfake content	design reference (rPPG extractor)
33	Harraq and Aldwairi (2026), rPPG and lip frequency cues, arXiv 2609.22284	rPPG. RhythmFormer rPPG waveform plus lip DCT features with fusion. Data: Celeb-DF++ talking-face subset, identity-disjoint	Concat fusion AUC 0.891; leave-one-generator-out 0.798	rPPG signal not shown cardiac; frame-rate confound	comparison context
34	Yang et al. (2026), Physiological disruptions in deepfakes, MRAC 2026 (as printed)	rPPG. Co-attention over PhysFormer rPPG and OpenFace behaviour tokens. Data: COHFACE and UBFC-rPPG with constructed fakes, subject-disjoint	Face swap AUC 92.80 +- 4.34 (co-attention)	Older generators only; 81 subjects	comparison context
35	Interno et al. (2025), ReStraV: perceptual straightening, NeurIPS	generated video. DINOv2 trajectory curvature features with small MLP. Data: VidProM 50k AI vs 50k natural videos	Accuracy 94.17, AUROC 98.63 (Table 1)	Abstract/table mismatch; could be gamed by generators	baseline re-implemented (MLP trained by us)
36	Ben Hayun et al. (2026), STALL: training-free detection, CVPR (accepted)	generated video. Gaussian likelihood on whitened DINOv3 embeddings. Data: ComGenVid, VideoFeedback, GenVideo	Average AUC 0.82 vs D3 0.64	Needs about 5k real calibration videos; DINOv3 excluded	comparison context
37	Zheng et al. (2025), D3: second-order features, arXiv 2508.00701	generated video. Training-free std of second-order feature differences. Data: GenVideo, EvalCrafter, VideoPhy, VidProM	GenVideo mAP 98.46	Poor on Text2Video-Zero (AP 45.11); encoder-dependent	comparison context
38	Shykula et al. (2026), DF26, arXiv 2609.07369	generated video. Benchmark of modern generated speaking videos. Data: 2,691 clips: 271 real, 2,420 generated	Effort AUROC 44.0 on DF26 (trained on FF++)	Small scale; visual only	dataset used (sealed test)
39	Bohacek and Farid (2025), Human Action CLIPs (DeepAction), IJCAI 2025 Workshop	generated video. CLIP/SigLIP frame embeddings with SVM. Data: DeepAction: 3,100 generated, 100 real Pexels clips	CLIP linear SVM video accuracy 97.0%	Reals from one source; fails on talking heads (55.8%)	dataset used (development set)
40	C2PA (2025), C2PA Content Credentials, Technical specification v2.2	provenance. Signed provenance manifests validated against trust anchors. Data: Not experimental	not quoted	Only scope and definitions read; validation sections not read in full	design reference (content_credentials module)

Summary of the gap. Published detectors report high in-dataset scores, but cross-dataset results fall and vary with protocol; shortcuts (codec, file format, production pipeline) and identity leakage inflate scores; audio-visual fusion results are mostly in-dataset; and few papers report intervals or a re-run baseline. This project addresses the evaluation gap: identity-disjoint splits, sealed tests read once, declared confirmatory tests, group-bootstrap intervals and a re-run Xception baseline.