

WINGS MEDIAA

VOL. 02 — DEVELOPER HANDOFF

Build the system. Ship the feel.

Design tokens, motion specs, library setup, performance and accessibility budgets — everything a developer needs to take this from Figma to production.

Contents

01 — TECH STACK

The stack.

This stack is opinionated. Each choice is load-bearing for the bold-energetic motion direction. Substitutions are possible but require re-evaluation of the motion strategy.

LAYER	TOOL	WHY
Framework	Next.js 15 (App Router)	SSR/ISR for SEO; built-in Image/Font primitives; Vercel adjacency.
Smooth scroll	Lenis 1.x (lenis/react)	Universal inertial scroll; native sync with GSAP ScrollTrigger.
Animation	GSAP 3.12+ (Club bonus plugins)	ScrollTrigger, SplitText, Flip, CustomEase, Observer.
Component motion	Motion (Framer Motion) 11+	Layout animations, AnimatePresence, gestures.
3D / WebGL	Three.js + @react-three/fiber + @react-three/drei	Industry-standard; works in React tree.
State illustration	Rive	Lighter than Lottie; state-driven; interactive.
CMS	Sanity v3	Studio + Portable Text; live preview; structured content.
Forms	Resend + Edge functions	Email-first; no third-party widgets.
Hosting	Vercel	ISR; edge caching; preview deploys per PR.
Analytics	PostHog + Plausible	PostHog for funnels; Plausible for cookie-less marketing pages.
Type loading	next/font (self-hosted Pangram licenses)	Zero-FOUT; no CLS.

Install

```
# from project root
npx create-next-app@latest wings-mediaa --typescript --app --tailwind
cd wings-mediaa
npm i gsap lenis @react-three/fiber @react-three/drei three @rive-app/canvas \
  motion @sanity/client clsx
npm i -D @types/three
```

02 — DESIGN TOKENS

Tokens.

Tokens are the source of truth. Ship them as CSS variables on `:root` and re-export typed versions from `/lib/tokens.ts`. The same names are used in Figma, Tailwind, and the docs.

Color tokens

```
:root{
  --ink:          #0A0A0F;
  --ink-2:        #15151C;
  --bone:         #F4F4F1;
  --bone-2:       #E9E9E2;
  --crimson:      #FF3D2E;
  --crimson-2:    #FF5547;
  --lime:         #E6FF3C;
  --mute:         #8A8A95;
  --hair:         #1F1F26;          /* on dark */
  --hair-l:       #D7D7D2;          /* on light */
  --tint-glow:    rgba(255,61,46,.12);
  /* semantic */
  --success:      #E6FF3C;
  --warn:         #FF884F;
  --error:        #FF3D2E;
  --bg:           var(--ink);
  --fg:           var(--bone);
}
```

Type tokens (fluid)

```
:root{
  --t-xxl: clamp(64px, 9.2vw, 168px);
  --t-xl:  clamp(48px, 6vw, 112px);
  --t-l:   clamp(36px, 4.5vw, 72px);
  --t-m:   clamp(22px, 2vw, 28px);
  --t-body-l: clamp(18px, 1.4vw, 22px);
  --t-body: clamp(15px, 1.1vw, 18px);
  --t-cap: 14px;
  --t-mono: 13px;
}
```

Space scale (4px base)

```
--s-2:4px; --s-3:8px; --s-4:12px; --s-5:16px; --s-6:24px;
--s-7:40px; --s-8:64px; --s-9:96px; --s-10:160px;
```

Radius / border / blur

```
--r-2:8px; --r-3:14px; --r-4:18px; --r-pill:9999px;
--bw:1px;
--blur-glass: blur(12px) saturate(140%);
```

Tailwind extension

```
// tailwind.config.ts
extend: {
  colors: {
    ink: '#0A0A0F', 'ink-2': '#15151C', bone: '#F4F4F1', 'bone-2': '#E9E9E2',
    crimson: '#FF3D2E', lime: '#E6FF3C', mute: '#8A8A95'
  },
  fontFamily: {
    display: ['"PP Neue Montreal"', 'Inter', 'sans-serif'],
    body: ['"PP Neue Montreal"', 'Inter', 'sans-serif'],
    serif: ['"PP Editorial New"', '"Instrument Serif"', 'serif'],
    mono: ['"JetBrains Mono"', 'ui-monospace', 'monospace'],
  },
  fontSize: {
    'xxl': 'clamp(64px, 9.2vw, 168px)',
    'xl': 'clamp(48px, 6vw, 112px)',
    'l': 'clamp(36px, 4.5vw, 72px)',
  },
  transitionTimingFunction: {
    'out-expo': 'cubic-bezier(0.16, 1, 0.3, 1)',
    'out-quart': 'cubic-bezier(0.25, 1, 0.5, 1)',
    'overshoot': 'cubic-bezier(0.34, 1.56, 0.64, 1)',
    'slow-ease': 'cubic-bezier(0.65, 0, 0.35, 1)',
  }
}
```

03 — BREAKPOINTS & GRID

Layout system.

BREAKPOINT	RANGE	BEHAVIOR
sm	< 640px	Single column. Type clamps to mobile floor. Hero text becomes 4 lines.
md	640 – 1024	6-col grid. Section padding 60px. Marquee strips active.
lg	1024 – 1440	12-col grid. Section padding 96px. Full motion budget.
xl	1440 – 1920	12-col grid + max-width 1280 container. Full hero scale.
xxl	> 1920	Container capped at 1280. Wide canvases for hero only.

Grid

- 12 columns desktop, 6 mobile, 4 tiny mobile (<400px).
- Gutter: 24px desktop, 16px mobile.
- Section padding: 120–200px desktop vertical; 64–96px mobile.
- Container max-width 1280px on canvases; hero allowed 100vw.
- Broken-grid principle: navigation, footer and case index must obey strict grid; section interiors may break.

04 — MOTION SPECS

Motion tokens.

Every motion must use one of these named tokens. If a designer requests a value that does not appear here, document the deviation and add it to the system before shipping.

TOKEN	VALUES	WHERE IT IS USED
entrance	translateY(24–40px) + opacity 0→1600–900ms · out-expo · stagger 60ms	All section reveals, hero lines, card stagger entries.
hover-lift	scale 1.02–1.04 · 280ms · overshoot	Buttons, case tiles, metric blocks.
magnetic	translate * 0.18 of cursor offset · 120px radius	Primary CTAs, brand mark hover, case 'next' link.
mask-reveal	clip-path inset 100% 0 → 0 · 800ms · out-expo	Hero lines, image tile entries, section titles.
scrub-pin	ScrollTrigger pin + scrub:0.6 · 100–200vh	Service stack, numbers row, process steps.
marquee	translateX linear 60–100px/s · pause on hover	Client logo strip, services strip, footer ticker.
page-transition	color-flood w/ Crimson · 700ms in + 600ms out · slow-ease	Inter-route navigation.
cursor-lerp	lerp 0.16 · dot 8px · halo 36–80px	Global cursor system; respects reduced motion.
count-up	0 → target · 1.2s · out-quart	Metric blocks, numbers row.
idle-ambient	gradient drift 30s alternate · grain 4% · marquee strips 1–2 per page	All pages, always on.

Easing reference (paste into CustomEase)

```
// GSAP CustomEase definitions
CustomEase.create("outExpo",    "0.16, 1, 0.3, 1");
CustomEase.create("outQuart",   "0.25, 1, 0.5, 1");
CustomEase.create("overshoot",  "0.34, 1.56, 0.64, 1");
CustomEase.create("slowEase",   "0.65, 0, 0.35, 1");
```

Stagger reference

- Char-by-char (hero) — 20–40ms per char.
- Word stagger — 60–100ms per word.
- Section children — 60ms; max 8 items before grouping.

—Grid tile entry — 80–120ms diagonal; reset to 0 after viewport exit (do not retrigger).

05 — LIBRARY SETUP

Lenis + GSAP wiring.

This is the single most important integration. Lenis owns the scroll loop; GSAP/ScrollTrigger reads from it. Native scroll bypassed completely.

```
// app/providers/lenis-provider.tsx
'use client';
import { ReactLenis, useLenis } from 'lenis/react';
import { useEffect } from 'react';
import { gsap } from 'gsap';
import { ScrollTrigger } from 'gsap/ScrollTrigger';

gsap.registerPlugin(ScrollTrigger);

export default function LenisProvider({ children }: { children: React.ReactNode }) {
  return (
    <ReactLenis
      root
      options={{
        lerp: 0.1,
        smoothWheel: true,
        smoothTouch: false,
        syncTouch: false,
      }}
    >
      <ScrollRig>{children}</ScrollRig>
    </ReactLenis>
  );
}

function ScrollRig({ children }: { children: React.ReactNode }) {
  const lenis = useLenis(() => {
    ScrollTrigger.update();
  });
  useEffect(() => {
    gsap.ticker.add((t) => lenis?.raf(t * 1000));
    gsap.ticker.lagSmoothing(0);
    return () => { gsap.ticker.remove((t) => lenis?.raf(t * 1000)); };
  }, [lenis]);
  return <>{children}</>;
}
```

Wrap the app

```
// app/layout.tsx
import LenisProvider from '../providers/lenis-provider';
import Cursor from '@components/Cursor';
```

```
export default function RootLayout({ children }) {  
  return (  
    <html lang="en">  
      <body>  
        <LenisProvider>  
          <Cursor />  
          {children}  
        </LenisProvider>  
      </body>  
    </html>  
  );  
}
```

Reduced motion guard

```
// always bail to native scroll for prefers-reduced-motion  
const rm = typeof window === 'undefined'  
  && window.matchMedia('(prefers-reduced-motion: reduce)').matches;  
const lenisOpts = rm ? { autoRaf: false } : { lerp: 0.1, smoothWheel: true };
```

06 — CUSTOM CURSOR

Cursor component.

A two-element cursor (dot + halo) with five states. Pure CSS transforms updated by rAF; no React state per frame.

```
// components/Cursor.tsx
'use client';
import { useEffect, useRef, useState } from 'react';

type Mode = 'default' | 'link' | 'drag' | 'media' | 'hidden';

export default function Cursor() {
  const dot = useRef<HTMLDivElement>(null);
  const halo = useRef<HTMLDivElement>(null);
  const [mode, setMode] = useState<Mode>('default');

  useEffect(() => {
    const rm = window.matchMedia('(prefers-reduced-motion: reduce)').matches;
    const touch = window.matchMedia('(hover: none)').matches;
    if (rm || touch) { setMode('hidden'); return; }

    let mx = 0, my = 0, hx = 0, hy = 0;
    const onMove = (e: MouseEvent) => { mx = e.clientX; my = e.clientY;
      if (dot.current) dot.current.style.transform = `translate3d(${mx - 4}px, ${my - 4}px, 0)`;
    };
    let raf = 0;
    const loop = () => {
      hx += (mx - hx) * 0.16; hy += (my - hy) * 0.16;
      if (halo.current) halo.current.style.transform = `translate3d(${hx - 21}px, ${hy - 21}px, 0)`;
      raf = requestAnimationFrame(loop);
    };
    raf = requestAnimationFrame(loop);
    window.addEventListener('mousemove', onMove);

    const onOver = (e: MouseEvent) => {
      const t = e.target as HTMLElement;
      if (t.closest('[data-cur="drag"]')) setMode('drag');
      else if (t.closest('[data-cur="media"]')) setMode('media');
      else if (t.closest('a, button, [data-cur="link"]')) setMode('link');
      else setMode('default');
    };
    document.addEventListener('mouseover', onOver);

    return () => {
      cancelAnimationFrame(raf);
      window.removeEventListener('mousemove', onMove);
      document.removeEventListener('mouseover', onOver);
    };
  }, []);
}
```

```

    };
  }, []);

  if (mode === 'hidden') return null;
  return (
    <
      <div ref={dot} className={`cur-dot ${mode}`} aria-hidden />
      <div ref={halo} className={`cur-halo ${mode}`} aria-hidden />
    </>
  );
}

```

Cursor states

STATE	TRIGGER	APPEARANCE
default	global	dot 8px + halo 36px · mix-blend-mode difference
link	hover a/button/[data-cur=link]	halo grows to 56–80px · accent border · label inside
media	hover [data-cur=media] case tile	halo becomes 80×80 mini-preview
drag	hover [data-cur=drag] carousel	halo becomes horizontal pill with ◀ DRAG ▶
hidden	touch / reduced-motion	cursor removed, focus rings amplified

07 — PATTERNS

Reference implementations.

Hero — kinetic statement

```
// components/HeroStatement.tsx
'use client';
import { useEffect, useRef } from 'react';
import { gsap } from 'gsap';
import { SplitText } from 'gsap/SplitText';

gsap.registerPlugin(SplitText);

export default function HeroStatement() {
  const ref = useRef<HTMLHeadingElement>(null);
  useEffect(() => {
    if (!ref.current) return;
    const split = new SplitText(ref.current, { type: 'lines,words', linesClass:
'line', wordsClass: 'word' });
    gsap.from(split.words, {
      yPercent: 110,
      duration: 1.1,
      ease: 'cubic-bezier(0.16, 1, 0.3, 1)',
      stagger: 0.06,
      delay: 0.2,
    });
    return () => split.revert();
  }, []);
  return (
    <h1 ref={ref} className="font-display font-extrabold text-xxl leading-[.92]
tracking-[-0.04em]">
      We make brands <em className="font-serif text-crimson italic">move</em>
<br/>
      in feeds, in funnels, on screen.
    </h1>
  );
}
```

Magnetic button

```
// components/Magnetic.tsx
'use client';
import { useRef } from 'react';

export default function Magnetic({ children, radius = 120, coeff = 0.22 }: {
  children: React.ReactNode; radius?: number; coeff?: number;
}) {
  const ref = useRef<HTMLDivElement>(null);
  const onMove = (e: React.MouseEvent) => {
    const el = ref.current; if (!el) return;
    const r = el.getBoundingClientRect();
```

```

    const dx = e.clientX - (r.left + r.width / 2);
    const dy = e.clientY - (r.top + r.height / 2);
    if (Math.hypot(dx, dy) < radius)
      el.style.transform = `translate3d(${dx * coeff}px, ${dy * coeff}px, 0)`;
  };
  const onLeave = () => { if (ref.current) ref.current.style.transform =
'translate3d(0,0,0)'; };
  return <div ref={ref} onMouseMove={onMove} onMouseLeave={onLeave}
    style={{ transition: 'transform .35s cubic-bezier(0.25, 1, 0.5, 1)',
display:'inline-block' }}>
    {children}
  </div>;
}

```

Pin & scrub section

```

// components/PinScrub.tsx
'use client';
import { useEffect, useRef } from 'react';
import { gsap } from 'gsap';
import { ScrollTrigger } from 'gsap/ScrollTrigger';

export default function PinScrub({ children }: { children: React.ReactNode }) {
  const wrap = useRef<HTMLDivElement>(null);
  useEffect(() => {
    if (!wrap.current) return;
    const ctx = gsap.context(() => {
      const inner = wrap.current!.querySelector('[data-inner]') as HTMLElement;
      gsap.to(inner, {
        xPercent: -50, ease: 'none',
        scrollTrigger: {
          trigger: wrap.current, start: 'top top', end: '+=200%',
          pin: true, scrub: 0.6, anticipatePin: 1
        }
      });
    });
    return () => ctx.revert();
  }, [wrap]);
  return <section ref={wrap}><div data-inner
className="flex">{children}</div></section>;
}

```

Page transition — color flood

```

// app/template.tsx (App Router transition wrapper)
'use client';
import { motion, AnimatePresence } from 'motion/react';
import { usePathname } from 'next/navigation';

export default function Template({ children }: { children: React.ReactNode }) {
  const pathname = usePathname();
  return (
    <AnimatePresence mode="wait">
      <motion.div key={pathname}>

```

```

      {children}
      <motion.div
        initial={{ scaleY: 1 }} animate={{ scaleY: 0 }}
        exit={{ scaleY: 1 }}
        transition={{ duration: 0.7, ease: [0.65, 0, 0.35, 1] }}
        style={{ position: 'fixed', inset: 0, transformOrigin: 'top',
          background: 'var(--crimson)', zIndex: 100, pointerEvents: 'none'
        }}
      />
    </motion.div>
  </AnimatePresence>
);
}

```

Count-up metric

```

// components/CountUp.tsx
'use client';
import { useEffect, useRef, useState } from 'react';

export default function CountUp({ to, suffix = '' }: { to: number; suffix?: string }) {
  const ref = useRef<HTMLSpanElement>(null);
  const [v, setV] = useState(0);
  useEffect(() => {
    const io = new IntersectionObserver([(e)] => {
      if (!e.isIntersecting) return;
      const start = performance.now();
      const dur = 1200;
      const tick = (t: number) => {
        const p = Math.min((t - start) / dur, 1);
        const ease = 1 - Math.pow(1 - p, 4);
        setV(+(to * ease).toFixed(1));
        if (p < 1) requestAnimationFrame(tick);
      };
      requestAnimationFrame(tick);
      io.disconnect();
    }, { threshold: 0.4 });
    if (ref.current) io.observe(ref.current);
    return () => io.disconnect();
  }, [to]);
  return <span ref={ref} className="tabular-nums">{v}{suffix}</span>;
}

```

08 — PROJECT STRUCTURE

Folder layout.

```
wings-mediaa/
├── app/
│   ├── (site)/
│   │   ├── page.tsx                # Homepage
│   │   ├── work/page.tsx          # Work index
│   │   ├── work/[slug]/page.tsx   # Case study
│   │   ├── services/[slug]/page.tsx
│   │   ├── about/page.tsx
│   │   ├── insights/page.tsx
│   │   └── contact/page.tsx
│   ├── providers/
│   │   └── lenis-provider.tsx
│   ├── layout.tsx
│   └── template.tsx                # Page transition wrapper
├── components/
│   ├── Cursor.tsx
│   ├── Magnetic.tsx
│   ├── HeroStatement.tsx
│   ├── Marquee.tsx
│   ├── CaseTile.tsx
│   ├── Metric.tsx
│   ├── PinScrub.tsx
│   ├── Nav.tsx
│   ├── Footer.tsx
│   └── webgl/HeroScene.tsx        # r3f canvas, dynamic-imported
├── lib/
│   ├── tokens.ts                  # typed token exports
│   ├── sanity.ts
│   └── utils.ts
├── studio/                        # Sanity studio
│   └── schemas/ ...
├── public/
│   └── fonts/                      # self-hosted PP Neue Montreal, PP Editorial
├── New
│   └── images/
├── styles/
│   └── globals.css                # tokens, base reset, grain layer
└── tailwind.config.ts
```

Conventions

- All client-side animation components must include 'use client' and prefers-reduced-motion guards.
- WebGL components must be dynamic-imported with `ssr: false` and a static poster fallback.
- Token names are stable and shared across Figma, CSS variables, and Tailwind.
- Use `clsx` for conditional class names; no nested-ternary class strings.

—Naming convention: PascalCase for components; kebab-case for files when not components.

09 — PERFORMANCE

Budgets.

METRIC	BUDGET	NOTES
LCP	< 2.0s on 4G mid-range mobile	Inline critical CSS; hero text first paint.
CLS	< 0.05	Reserve space for media; next/image with explicit dimensions.
INP	< 200ms with motion engine running	Throttle scroll handlers; avoid layout-thrash.
TBT	< 200ms	Defer non-critical scripts; dynamic-import 3D scenes.
JS bundle (homepage)	< 220KB gzipped	Code-split per route; tree-shake GSAP plugins.
Media (non-3D pages)	< 1.5MB total	AVIF first; JPG fallback; loading=lazy below the fold.
Media (hero 3D pages)	< 2.5MB total	Draco-compressed glTF; ktx2 textures.

Image pipeline

- AVIF + JPG fallback via next/image.
- Hero media: loading=eager, fetchpriority=high, decoded above the fold.
- Below-the-fold: loading=lazy.
- Video: poster image must match first frame exactly to prevent shift.
- All case-study video: H.264 + AV1 at < 1.5Mbps avg; muted+autoplay+playsinline.

Fonts

- Self-host PP Neue Montreal + PP Editorial New under valid Pangram Pangram license.
- Subset to Latin; preload display weights only; use font-display: swap with size-adjust to prevent CLS.
- Mono and free fallbacks via next/font.

10 — ACCESSIBILITY

WCAG 2.2 AA — non-negotiable.

AREA	REQUIREMENT
Reduced motion	All entrance + parallax + cursor systems honor prefers-reduced-motion. Fall back to a 1-frame opacity transition.
Keyboard	Every interactive surface reachable; visible focus ring (2px crimson outline + 2px ink offset).
Color contrast	Min 4.5:1 for body, 3:1 for large text. Crimson on Ink passes large text only — never use as small body.
Cursor	Custom cursor is decoration. Native cursor remains for users who disable it. Touch and reduced-motion always hide it.
Skip link	Visually hidden 'Skip to content' surfaces on first tab.
Form labels	Every input has an associated <label>; placeholder is decorative.
Alt text	Every has a meaningful alt; decorative imagery uses alt="" (empty).
Live regions	Toast/success states announce via aria-live=polite.
Heading order	H1 once per page; no skipped levels.
Video	Captions for any case-study film with dialogue.

Test gates

- axe-core CI run on every PR; zero violations gate merge.
- Manual keyboard pass on homepage, work index, case study, contact.
- Lighthouse a11y score >= 95 on every page.
- Quarterly screen-reader walkthrough (NVDA + VoiceOver).

11 — CONTENT MODEL

Sanity schemas.

Three core types: Case, Service, Insight. Plus singletons for Homepage, About, Contact, SiteSettings.

Case schema (excerpt)

```
// studio/schemas/case.ts
export default {
  name: 'case', title: 'Case study', type: 'document',
  fields: [
    { name: 'slug', type: 'slug' },
    { name: 'title', type: 'string' },
    { name: 'client', type: 'string' },
    { name: 'year', type: 'number' },
    { name: 'verticals', type: 'array', of: [{ type: 'string' }] },
    { name: 'services', type: 'array', of: [{ type: 'reference', to: [{ type: 'service' }] }] }
  ],
  { name: 'cover',
    type: 'object', fields: [
      { name: 'kind', type: 'string', options: { list: ['video', 'still', '3d'] } },
      { name: 'asset', type: 'file' },
      { name: 'poster', type: 'image' },
      { name: 'accent', type: 'string', description: 'Hex used as the case accent for transition flood' },
    ] },
    { name: 'summary', type: 'text' },
    { name: 'metrics', type: 'array', of: [{ type: 'object', fields: [
      { name: 'value', type: 'string' }, { name: 'label', type: 'string' }
    ] } ] },
    { name: 'sections', type: 'array', of: [ /* poster | gallery | quote | scroll-scrub | embed */ ] },
    { name: 'credits', type: 'array', of: [{ type: 'object', fields: [
      { name: 'role', type: 'string' }, { name: 'name', type: 'string' }
    ] } ] },
    { name: 'next', type: 'reference', to: [{ type: 'case' }] },
  ],
}
```

Homepage singleton

```
{
  hero: { line1, line2, line3, italicWord },
  proofBar: { logos: [{ image, name }] },
  selectedWork: [ref to case x4-6],
  numbers: [{ value, label } x3],
  services: [ref to service x5],
  process: [{ n, label, blurb } x4],
  voices: [{ quote, name, role, company, portrait } x2],
}
```

```
cta: { heading, primary:{label,href}, secondary:{label,href} },
}
```

12 — DEPLOY & OPS

Pipeline.

- Vercel project linked to main branch; PR preview deploys on every push.
- Sanity Studio deployed under /studio path with separate auth.
- Image CDN: Vercel; transformations through next/image.
- Edge function for /api/contact (Resend SMTP).
- ISR revalidate: 60s on case studies; 0 on homepage in launch week, raise to 60s post-launch.
- OG image: generated per case via @vercel/og at /work/[slug]/opengraph-image.tsx.
- Monitoring: Vercel Web Vitals + PostHog session replay (sampling 10%).

Pre-launch checklist

- Lighthouse all green (perf/a11y/SEO/best-practices) on homepage, work, case, contact.
- axe-core clean.
- Manual keyboard pass.
- Mobile (iOS Safari + Android Chrome) device farm pass.
- Cursor hidden on touch and reduced-motion confirmed.
- 404 page in Lime + working.
- Sitemap + robots.txt.
- OG previews tested on WhatsApp, Slack, LinkedIn, X.
- Schema.org Organization + WebSite + BreadcrumbList present.
- hello@wingsmediaa.com receiving and CC routing live.
- Calendly / Cal.com booking link tested end-to-end.

13 — SIGN-OFF

Definition of done.

A feature is done when all of the following are true:

- Component matches Figma spec at every breakpoint.
- Motion uses only named tokens from §04.
- Keyboard and screen-reader pass.
- Reduced-motion fallback verified.
- Lighthouse on the page hosting the component is in budget.
- PR includes a 5-second screen recording of the interaction.
- Reviewed by one designer and one engineer before merge.

This document is v1.0. Any deviation from the system must be proposed in a single-issue PR titled SYSTEM CHANGE: <name>, accompanied by a Figma frame and a rationale paragraph. Without that, the system stays as it is.