ascolite

TECHNICAL DATASHEET

FIXOBOND® TILE LOCK

HIGHLY POLYMERIZED ADMIXTURE FOR TILING ON WET FLOOR SCREED



ZERO WASTAGE

STRONG BONDING

NON-SHRINK



www.ascolite.in | info@ascolite.in

FOR INQUIRY

VERSION 1

PRODUCT DESCRIPTION

FIXOBOND® TILE LOCK is a special green strength buildup powder additive to be mixed with ordinary portland cement and directly used as wet on wet slurry based adhesive to fix tiles on the floor for indoor & outdoor applications.

INDEX

KEY FEATURES 1

TECHNICAL INFORMATION 1

APPLICATION COMPATIBILITY 1

APPLICATION METHOD 1

PACKAGING 2

DOSAGE 2

SHELF LIFE 2

HEALTH & SAFETY GUIDELINES 2

TOOLS & ACCESSORIES 3

DISCLAIMER 3

Version: 03 (April 2024)

KEY FEATURES

- Non-shrink
- Self-curing
- Extended open time
- Strong bonding
- High adjustment time
- Cost effective
- Superior workability
- Improves screed strength
- Nil VOC (Volatile Organic Compounds)
- Compatible with both grey & white ordinary portland cement

TECHNICAL INFORMATION

APPLICATION PROPERTIES

PROPERTY: TEST METHOD	TYPICAL VALUES
Appearance	White powder
Bulk density	720 kg/m^3
Dry mix mixing ratio (Powder : Cement)	3 : 500 (by weight)
Water demand for the powder & cement mix @ 27 ± 2°C	50 ± 2% by weight
Pot life of mix @ 27 ± 2°C	25 – 30 minutes
Open time @ 27 ± 2°C	20 – 25 minutes
Adjustment time @ 27 ± 2°C	20 – 25 minutes
Floor grouting @ 27 ± 2°C	72 hours
Light foot traffic @ 27 ± 2°C	24 hours
Tensile adhesion strength dry condition @ 28 days	0.5 N/mm^2
Shear adhesion strength dry condition @ 28 days	1 N/mm^2
Application temperature (Substrate & laying material)	+5°C to +35°C
Final bed thickness	1 mm – 2 mm

APPLICATION COMPATIBILITY

AREAS OF APPLICATION

- Tiling for internal & external floors.
- Tiling for dry & moist areas.
- Residential & industrial applications.

SUITABLE SUBSTRATE

- Freshly laid **ASCOSCREED RM** or **ASCOSCREED** and sand (as per site availability).
- Wet cement & sand machan with a ratio not exceeding 1 : 8 (Cement : Sand).

SUITABLE LAYING MATERIAL

- Ceramic tiles, vitrified tiles, porcelain & natural stones.

APPLICATION METHOD

SUBSTRATE PREPARATION

- Prepare screed for laying tiles using **ASCOSCREED RM** or **ASCOSCREED** and sand (as per site availability). Cement/sand machan can also be used for preparing the surface. The concrete substrate should be fully cured for 28 days before laying the screed. Ensure to provide expansion joints during laying of the screed.
- Lay the screed onto the substrate; while laying the screed, ensure the surface undulations are minimized and the screed is levelled.
- Ensure that the screed is still wet enough and free from all sorts of containments like debris, dust, etc., before applying **FIXOBOND® TILE LOCK** slurry adhesive.

Version: 03 (April 2024)

MIXING



- Dry mix 300 grams **FIXOBOND® TILE LOCK** powder thoroughly in 50 kg ordinary portland cement.



- Add 50 ± 2% water by weight of the dry mix and mix the material using slow speed (< 300 RPM) mechanical mixer to homogenize it thoroughly. If weight mixing isn't an option, volume mixing can be done instantly with **FIXOBOND® TILE LOCK** in a clean vessel or container. Mix 25 - 26 litres of clean water with 50.30 kg of **FIXOBOND® TILE LOCK** & cement mix to achieve slump-free slurry consistency.



- Remix the prepared slurry adhesive of **FIXOBOND® TILE LOCK** occasionally to maintain the smooth consistency.
- **FIXOBOND® TILE LOCK** slurry adhesive is now ready for application.

APPLICATION

- **FIXOBOND® TILE LOCK** slurry adhesive is specifically formulated for wet-on-wet application of tile/stone installation over freshly applied screed. Since it is wet on wet application, don't use this slurry adhesive on the screed which has already begun to set or is already cured.
- Pour the **FIXOBOND® TILE LOCK** slurry adhesive over freshly applied **ASCOSCREED RM** or **ASCOSCREED** and sand (as per site availability). Spread the slurry evenly using a notched trowel (3 mm) to form a bed thickness of approximately 2 mm. This slurry adhesive can also be applied over cement/sand machan while it is still fresh.
- Place the tile/stone onto the wet slurry and lightly hammer the tile/stone with a rubber mallet and check the level using a spirit level to fix the tile/stone firmly over the wet screed.
- Fix the tile/stone within 20 minutes after the slurry is spread on the wet screed.
- Don't use this slurry adhesive on the screed which has already begun to set or is already cured.
- The slurry adhesive is to be used for floor applications only.

POST APPLICATION PROCEDURE

- While the slurry adhesive is still wet, use a damp sponge or cloth to remove any excess adhesive from the tile joints and the tile face.
- After use, immediately wash and clean all tools with warm soapy water.
- Give the installation at least 24 hours to dry completely before starting the grouting process or using the tiled areas.

PACKAGING



- 300 grams

DOSAGE

- 300 grams for 50 kg of cement.

SHELF LIFE



- **FIXOBOND® TILE LOCK,** when unopened, can be stored above the floor in a cool dry place for a duration of up to 12 months.

HEALTH & SAFETY GUIDELINES



- Take preventive measures to keep children away from this product.
- Use of safety goggles, nose mask and hand gloves are recommended to protect eyes, skin and mouth while in use.

Version: 03 (April 2024)

- Minimize prolonged skin exposure and refrain from inhaling the dust. If contact occurs, rinse the affected area with warm water and soap.
- In case, of eye contact, thoroughly wash the eyes and seek medical advice.
- For additional details, please consult the Material Safety Data Sheet.

TOOLS & ACCESSORIES

TILLING TOOLS


ROLLER


BUCKET


NOTCHED TROWEL


HAMMER & CHISEL


BRUSH


WIRE BRUSH


MIXER


RUBBER MALLET


TILE VIBRATOR


SUCTION CUP


SPIRIT LEVEL


PLUMB BOB

TILLING ACCESSORIES


TILE SPACER


TILE WEDGE WITH CLIP

GROUTING TOOLS


GROUT SPREADER


SPONGE


PUTTY KNIFE

SCREEDING TOOLS


BUCKET


PLAIN TROWEL


FINISHING TROWEL


WIRE BRUSH


MIXER


BRUSH


RAFFTER


NOTCHED TROWEL


SPIRIT LEVEL

DISCLAIMER:

This technical data sheet supersedes all previous versions from the immediate effect. The company guarantees its products against any manufacturing defects. The user should determine the product's usability for its intended use. Since the company has no control over site conditions and the installation procedures, the company would not be responsible under any circumstances for any loss, damage or liability from incorrect usage. For the products on which the company is offering a warranty, please refer to the warranty document to know the entire terms and conditions. The same can be availed on request or from the company website. All orders are accepted subject to our prevailing terms of sales and delivery. While the technical details & recommendations contained in this document and the related details given by the representatives of the company correspond to the best of our knowledge & experience, all the above information must in any case be considered as merely indicative and subject to confirmation. Our company maintains an active research and development policy, allowing us to continuously enhance our products. As a result, we reserve the right to revise this information at any time without prior notice. For optimal results, we recommend this product be installed by a qualified professional. By using this product, users acknowledge and agree to the terms and conditions outlined in this disclaimer.