

# CS 4530: Fundamentals of Software Engineering

## Module 2.2: Test-Driven Development

---

Adeel Bhutta, Mitch Wand, Rob Simmons  
Khoury College of Computer Sciences

# Learning Goals for this Lesson

---

- At the end of this lesson, you should be prepared to
  - Explain the basics of Test-Driven Development
  - Explain the connection between conditions of satisfaction and testable behaviors
  - Begin developing simple applications using TypeScript and Vitest

# Non-Goals for this Lesson

---

- This is *\*not\** a tutorial for Typescript or for Vitest
- We will show you simple examples, but you will need to go through the tutorials to learn the details.


# Part 3: Test-Driven Development



PEOPLE



PROCESSES



PROGRAMS

PLANNING



ORGANIZING



IMPLEMENTING



Requirements Analysis

User Stories

Testing Conditions of Satisfaction

# Review: User Stories

- As a College Administrator, I want to keep track of students, the courses they have taken, and the grades they received in those courses, so that I can advise them on their studies.

*As a <role>  
I want <capability>  
so that I can <get some benefit>*



# Review: Conditions of Satisfaction

---

- We will build a secure web application backed by a persistent database that allows an authenticated administrator to:
  - Add a new student to the database
  - Add a new student with the same name as an existing student.
  - Retrieve the transcript for a student
  - Delete a student from the database
  - Add a new grade for an existing student
  - Find out the grade that a student got in a course that they took


# Test Driven Development (TDD)

---

- Puts test specification as the critical design activity
  - Understands that deployment comes when the system passes testing
- The act of defining tests requires a deep understanding of the problem
- Clearly defines what success means
  - No more guesswork as to what “complete” means

# The TDD Cycle

---






# CoS are ultimately about the user

---


We will build a secure web application backed by a persistent database that allows an authenticated administrator to add a new student to the database



# CoS are ultimately about the user

---

We will build a secure web application backed by a persistent database that allows an authenticated administrator to add a new student to the database



The addStudent service function should add a student to the database

# Analyzing CoS to get testable behaviors

---

```
import {
  StudentID,
  Student,
  Course,
  CourseGrade,
  Transcript,
} from './types.ts';
export interface TranscriptService {
  addStudent(studentName: string): StudentID;
  getTranscript(id: StudentID): Transcript;
  deleteStudent(id: StudentID): void; // hmm, what to do about errors??
  addGrade(id: StudentID, course: Course, courseGrade: CourseGrade): void;
  getGrade(id: StudentID, course: Course): CourseGrade;
  nameToIDs(studentName: string): StudentID[];
}
```

# Analyzing CoS to get testable behaviors

---

CoS: The user can...

- ...add a new student to the database
- ...add a new student with the same name as an existing student
- ...retrieve the transcript for a student

Testable behaviors:

- addStudent should add a student to the database and return their ID
- addStudent should return an ID distinct from any ID in the database
- addStudent should permit adding a student with the same name as an existing student
- getTranscript, given the ID of a student, should return the student's transcript.
- getTranscript, given an ID that is not the ID of any student, should ...????...

# The tiniest introduction to Vitest

---

```
import {  
  StudentID,  
  Student,  
  Course,  
  CourseGrade,  
  Transcript,  
} from './types.ts';  
  
export interface TranscriptService {  
  addStudent(studentName: string): StudentID;  
  getTranscript(id: StudentID): Transcript; // throws error if ID invalid  
  deleteStudent(id: StudentID): void; // throws error if ID invalid  
  addGrade(id: StudentID, course: Course, courseGrade: CourseGrade): void;  
  getGrade(id: StudentID, course: Course): CourseGrade;  
  nameToIDs(studentName: string): StudentID[];  
}
```

# The tiniest introduction to Vitest

---

```
// types.ts - types for the transcript service
export type StudentID = number;
export type Student = { studentID: number; studentName: StudentName };
export type Course = string;
export type CourseGrade = { course: Course; grade: number };
export type Transcript = { student: Student; grades: CourseGrade[] };
export type StudentName = string;
```

# The tiniest introduction to Vitest

---

```
// types.spec.ts
import { describe, expect, it } from 'vitest';
import { type Student } from './types.ts';

const alvin: Student = { studentID: 37, studentName: 'Alvin' };
const bryn: Student = { studentID: 38, studentName: 'Bronwyn' };

describe('the Student type', () => {
  it('should allow extraction of id', () => {
    expect(alvin.studentID).toEqual(37);
    expect(bryn.studentID).toEqual(38);
  });
  it('should allow extraction of name', () => {
    expect(alvin.studentName).toEqual('Alvin');
    expect(bryn.studentName).toEqual('Jazzhands'); // will fail
  });
});
```

# The tiniest introduction to Vitest

---

```
% npx vitest --run src/types.spec.ts
```

```
RUN v4.0.16 /Users/rjsimmon/r/transcript-server
```

```
> src/types.spec.ts (2 tests | 1 failed) 4ms
> the Student type (2)
  ✓ should allow extraction of id 1ms
  × should allow extraction of name 3ms
```

---

## Failed Tests 1

```
FAIL src/types.spec.ts > the Student type > should allow extraction of name
AssertionError: expected 'Bronwyn' to deeply equal 'Jazzhands'
```

```
Expected: "Jazzhands"
```

```
Received: "Bronwyn"
```

```
> src/types.spec.ts:13:30
11|   it('should allow extraction of name', () => {
12|     expect(alvin.studentName).toEqual('Alvin');
13|     expect(bryn.studentName).toEqual('Jazzhands'); // will fail
   |                                     ^
14|   });
15| });
```

```
Test Files 1 failed (1)
```

```
Tests 1 failed | 1 passed (2)
```




# Turning testable behaviors into Vitest tests

---

```
// transcript.service.spec.ts
import { beforeEach, describe, expect, it } from 'vitest';
import { TranscriptDB, type TranscriptService } from './transcript.service.ts';
```

```
let db: TranscriptService;
beforeEach(() => {
  db = new TranscriptDB();
});
```



Start each test with a new empty database

```
describe('addStudent', () => {
  it('should add a student to the database and return their id', () => {
    expect(db.nameToIDs('blair')).toStrictEqual([]);
    const id1 = db.addStudent('blair');
    expect(db.nameToIDs('blair')).toStrictEqual([id1]);
  });
});
```

# Turning testable behaviors into Vitest tests

---

```
describe('addStudent', () => {  
  it('should add a student to the database and return their id', () => {  
  
    expect(db.nameToIds('blair')).toStrictEqual([]);  
  
    const id1 = db.addStudent('blair');  
  
    expect(db.nameToIds('blair')).toStrictEqual([id1]);  
  
  });  
});
```



Assemble (and verify)

Act

Assess

# Turning testable behaviors into Vitest tests

---

```
describe('addStudent', () => {  
  it('should return an ID distinct from any ID in the database', () => {  
    // we'll add 3 students and check to see that their IDs are all different.  
    const id1 = db.addStudent('blair');  
    const id2 = db.addStudent('corey');  
    const id3 = db.addStudent('del');  
    expect(id1).not.toEqual(id2);  
    expect(id1).not.toEqual(id3);  
    expect(id2).not.toEqual(id3);  
  });  
});
```

# Turning testable behaviors into Vitest tests

---

```
describe('addStudent', () => {  
  it('should permit adding a student w/ same name as an existing student', () => {  
    const id1 = db.addStudent('blair');  
    const id2 = db.addStudent('blair');  
    expect(id1).not.toEqual(id2);  
  });  
});
```

# Turning testable behaviors into Vitest tests

---

```
describe('addStudent', () => {  
  it('should permit adding a student w/ same name as an existing student', () => {  
    const id1 = db.addStudent('blair');  
    const id2 = db.addStudent('blair');  
    expect(id1).not.toEqual(id2);  
  });  
});
```

# Turning testable behaviors into Vitest tests

---

```
describe('getTranscript', () => {  
  it('should permit adding a student w/ same name as an existing student', () => {  
    const id1 = db.addStudent('blair');  
    expect(db.getTranscript(id1)).not.toBeNull();  
  });  
  
  it('should permit adding a student w/ same name as an existing student', () => {  
    // in an empty database, all IDs are bad :)  
    // Note: the expression you expect to throw  
    // must be wrapped in a (() => ...)  
    expect(() => db.getTranscript(1)).toThrowError();  
  });  
});
```

# A quick word about cleanup

Start each test with a new empty database

```
let db: TranscriptService;  
beforeEach(() => {  
  db = new TranscriptDB();  
});
```

OR

Create one database at the very start

```
let db: TranscriptService;  
beforeAll(() => {  
  db = new TranscriptDB();  
});
```

```
beforeEach(() => {  
  db.clear([]);  
});
```


Start every test with the database cleared out

- Use `afterEach()` if needed.

## ...now TDD lets us implement addStudent!

---

Implementing the TranscriptDB according to the TranscriptService spec will let us turn our testable behaviors into fully executable tests.





# Review

---

It's the end of the lesson, so you should be prepared to:

- Explain the basics of Test-Driven Development
- Explain the connection between conditions of satisfaction and testable behaviors
- Begin developing simple applications using TypeScript and Vitest