

Back To Practice

Q1

Save

Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

Input Format

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Example 1

Sample Input 1

```
3
0 5 2
1 3 1
2 2 3
```

Sample Output 1

```
Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
```

Select Language: C (GCC 9.2.0)

```
1 #include <stdio.h>
2 int main(){
3     int n;
4     printf("Enter number of processes: \n");
5     scanf("%d", &n);
6     int AT[n], BT[n], PR[n];
7     int CT[n], TAT[n], WT[n];
8     int visited[n];
9     for(int i = 0; i < n; i++){
10         printf("Enter AT, BT and Priority for P%d: \n", i + 1);
11         scanf("%d %d %d", &AT[i], &BT[i], &PR[i]);
12         visited[i] = 0;
13     }
14     int completed = 0, time = 0;
15     float totalTAT = 0, totalWT = 0;
16     while(completed < n){
17         int highestPriority = 100000;
18         int index = -1;
19         for(int i = 0; i < n; i++){
20             if(AT[i] <= time && visited[i] == 0){
21                 if(PR[i] < highestPriority){
22                     highestPriority = PR[i];
23                     index = i;
24                 }
25             }
26         }
27         if(index == -1){
28             time++;
29         }
30         else{
31             time += BT[index];
32             CT[index] = time;
33             TAT[index] = CT[index] - AT[index];
34             WT[index] = TAT[index] - BT[index];
35             totalTAT += TAT[index];
36             totalWT += WT[index];
37             visited[index] = 1;
38             completed++;
39         }
40     }
41     printf("\nAverage Turnaround Time = %.2f\n", totalTAT / n);
42     printf("Average Waiting Time = %.2f\n", totalWT / n);
43 }
```

Test Cases 2

Custom Test Case

Run Sample Cases

Run All Cases

Back To Practice

< Q1 >

Save

Non-Preemptive Priority Scheduling algorithm

Write a C program to implement the Non-Preemptive Priority Scheduling algorithm. The program should accept number of processes their Arrival Time (AT), Burst Time (BT), and Priority for each process. The process with the highest priority (lowest numerical value) must be executed first among those that have arrived. Calculate the Average Waiting Time and Average Turnaround Time.

Input Format

The first line contains an integer representing the number of processes.

The next lines contain three integers for each process, where

- The first integer denotes the Arrival Time (AT)
- The second integer denotes the Burst Time (BT)
- The third integer denotes the Priority of the process.

A lower numerical value indicates a higher priority.

Output Format

Input :

```
3
0 5 2
1 3 1
2 2 3
```

Expected Output :

```
Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33
```

Output :

```
Enter number of processes:
Enter AT, BT and Priority for P1:
Enter AT, BT and Priority for P2:
Enter AT, BT and Priority for P3:

Average Turnaround Time = 6.67
Average Waiting Time = 3.33
```

Sample Test Case

> Test Case - 1

Power & Battery

Energy saver is on