

Rajalakshmi Engineering College

Name: SRIVAISHNAVI N

Email: 241501217@rajalakshmi.edu.in

Roll no: 241501217

Phone: 8946071284

Branch: REC

Department: I AI & ML FC

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: *X*; Value: *Y*" where *X* represents the contact's name and *Y* represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX_CONTACTS 50
```

```
#define MAX_LEN 15
```

```

int main() {
    int n;
    char names[MAX_CONTACTS][MAX_LEN];
    char numbers[MAX_CONTACTS][MAX_LEN];

    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%s %s", names[i], numbers[i]);
    }

    char key[MAX_LEN];
    scanf("%s", key);

    int found = 0;
    int index_to_remove = -1;
    for (int i = 0; i < n; i++) {
        if (strcmp(names[i], key) == 0) {
            found = 1;
            index_to_remove = i;
            break;
        }
    }

    if (found) {
        printf("The given key is removed!\n");
        for (int i = index_to_remove; i < n - 1; i++) {
            strcpy(names[i], names[i + 1]);
            strcpy(numbers[i], numbers[i + 1]);
        }
        n--;
    } else {
        printf("The given key is not found!\n");
    }

    for (int i = 0; i < n; i++) {
        printf("Key: %s; Value: %s\n", names[i], numbers[i]);
    }

    return 0;
}

```

Status : Correct

Marks : 10/10