

Python MCQ Questions and Answers

1. What is the default separator (sep) used in the print() function?

- A) \n (newline)
- B) "" (empty string)
- C) " " (single space)
- D) "," (comma)

Answer: C

2. Which argument determines what is printed at the very end of a print() statement?

- A) sep
- B) end
- C) final
- D) stop

Answer: B

3. What is the output of print("A", "B", sep="->", end="!")?

- A) A B-> !
- B) A->B!
- C) AB->!
- D) A->B-> !

Answer: B

4. How do you print a double newline using only the end parameter?

- A) end="\n\n"
- B) end="2n"
- C) end="\n" * 2
- D) sep="\n\n"

Answer: A

5. What is the correct syntax for an f-string?

- A) f("Value: {x}")
- B) f"Value: {x}"
- C) str(f"Value: x")
- D) "{f}Value: {x}"

Answer: B

6. What do the curly braces {} do inside an f-string?

- A) Create a dictionary
- B) Start a code block

- C) Act as a placeholder to evaluate variables
- D) Print literal braces to the screen

Answer: C

7. What is the result of "{} is {}".format("Python", "fun")?

- A) {Python} is {fun}
- B) Python is fun
- C) fun is Python
- D) Python fun

Answer: B

8. How do you format a float to exactly 2 decimal places in an f-string?

- A) f"{val:.2f}"
- B) f"{val.2f}"
- C) f"{val:2}"
- D) f"{round(val, 2)}"

Answer: A

9. What data type does the input() function return by default?

- A) int
- B) float
- C) str (string)
- D) None

Answer: C

10. How do you correctly convert a user's input into an integer?

- A) x = int(input())
- B) x = input(int)
- C) x = input().int()
- D) int x = input()

Answer: A

11. What happens if you run int(input()) and the user types 25.7?

- A) It returns 25
- B) It returns 26
- C) It raises a ValueError
- D) It raises a TypeError

Answer: C

12. If a user inputs "A B C", what does input().split() return?

- A) "ABC"
- B) ["A", "B", "C"]
- C) ("A", "B", "C")
- D) ["A B C"]

Answer: B

13. What is the purpose of the map() function when taking input?

- A) To create a map or dictionary
- B) To apply a function (like int) to all parts of the input
- C) To sort the input data
- D) To remove extra spaces

Answer: B

14. How do you take two integers from one line of input?

- A) a, b = int(input().split())
- B) a, b = map(int, input().split())
- C) a, b = input().split().map(int)
- D) a, b = map(input().split(), int)

Answer: B

15. What is the result of m1, m2 = map(float, ["10", "20"])?

- A) m1=10.0, m2=20.0
- B) m1="10", m2="20"
- C) m1=10, m2=20
- D) It causes an error

Answer: A

16. What happens if you set sep=None in a print() statement?

- A) No space is used
- B) The default single space is used
- C) It raises an error
- D) It prints the word "None"

Answer: B

17. What is the output of print("Hi", end=" ") followed by print("Anil")?

- A) Hi\nAnil
- B) Hi Anil
- C) HiAnil
- D) Anil Hi

Answer: B

18. What is the length of the list returned by "1,2,3,4".split(",")?

- A) 1
- B) 4
- C) 7
- D) 3

Answer: B

19. Which escape sequence represents a tab?

- A) \t
- B) \b
- C) \n
- D) \r

Answer: A

20. Which code will cause a TypeError?

- A) print("Score: " + "10")
- B) print("Score:", 10)
- C) print("Score: " + 10)
- D) print(f"Score: {10}")

Answer: C