

Experiment 6: Shell Loops

Name: Vaishnavi Kumari Roll No.: 590029048 Date: 23-09-2025

Aim:

- To understand and implement shell loops (for, while, until) in Bash.
- To practice loop control constructs (break, continue) and loop-based file processing.

Requirements

- A Linux system with bash shell.
- A text editor (nano, vim) and permission to create and execute shell scripts.

Theory

Loops allow repeated execution of commands until a condition is met. Common loop constructs in Bash include **for** (iterate over items), **while** (repeat while condition true), and **until** (repeat until condition becomes true). Loop control statements like **break** and **continue** change the flow inside loops. Loops are essential for automating repetitive tasks such as processing multiple files, generating sequences, and collecting user input.

Procedure & Observations

Exercise 1: Simple for loop

Task Statement:

Write a for loop that prints numbers 1 to 5.

Command(s):

```
for i in 1 2 3 4 5; do
    echo "Number: $i"
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.1.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ ./exp6.1.sh
Number: 1
Number: 2
Number: 3
Number: 4
Number: 5
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.2.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ ./exp6.2.sh
Count: 1
Count: 2
Count: 3
Count: 4
Count: 5
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.3.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ ./exp6.3.sh
Count: 1
Count: 2
Count: 3
Count: 4
Count: 5
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.4.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ ./exp6.4.sh
Number: 1
Number: 2
Number: 4
Number: 5
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.5.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ ./exp6.5.sh
Hello
World
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux/exp6$ vim exp6.6.sh
```

Exercise 2: for loop over files

Task Statement:

Process all .txt files in a directory and count lines in each.

Command(s):

```
for f in *.txt; do
    echo "File: $f - Lines: $(wc -l < "$f")"
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task1.sh
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task1.sh
File: backup_file.txt - Lines: 0
File: backup_original.txt - Lines: 0
File: file.txt - Lines: 0
File: link.txt - Lines: 1
File: link1.txt - Lines: 0
wc: 'standard input': Is a directory
File: logfile.txt - Lines: 0
File: orig.txt - Lines: 1
File: original.txt - Lines: 0
File: sym.txt - Lines: 0
vaishnavii29@DESKTOP-BSKS7E4: /mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Exercise 3: C-style for loop

Task Statement:

Use arithmetic C-style loop for numeric iteration.

Command(s):

```
for ((i=0;i<5;i++)); do
    echo "i=$i"
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task2.sh
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task2.sh
i=0
i=1
i=2
i=3
i=4
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Exercise 4: while loop and reading input

Task Statement:

Write a while loop that reads lines from a file or from user input.

Command(s):

```
# Read from file
while read -r line; do
    echo "Line: $line"
done < sample.txt

# Read from user with exit condition
while true; do
    read -p "Enter a number (0 to exit): " n
    if [[ $n -eq 0 ]]; then
        echo "Exiting..."; break
    fi
    echo "You entered: $n"
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task3.sh
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task3.sh
./exp6.task3.sh: line 3: sample.txt: No such file or directory
Enter a number (0 to exit): 1
You entered: 1
Enter a number (0 to exit): 0
Exiting...
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Exercise 5: until loop

Task Statement:

Use an until loop to run until a condition becomes true.

Command(s):

```
count=1
until [ $count -gt 5 ]; do
    echo "count=$count"
    ((count++))
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task4.sh
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task4.sh
count=1
count=2
count=3
count=4
count=5
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Exercise 6: break and continue

Task Statement:

Demonstrate break and continue inside a loop.

Command(s):

```
for i in {1..10}; do
    if [[ $i -eq 5 ]]; then
        echo "Reached 5, breaking"; break
    fi
    if (( i % 2 == 0 )); then
        echo "Skipping even $i"; continue
    fi
    echo "Processing $i"
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task5.sh
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task5.sh
Processing 1
Skipping even 2
Processing 3
Skipping even 4
Reached 5, breaking
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Exercise 7: Nested loops

Task Statement:

Create nested loops to generate a multiplication table.

Command(s):

```
for i in {1..3}; do
  for j in {1..3}; do
    echo -n "${i*j}) "
  done
done
echo
done
```

Output:

```
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ vim exp6.task6.s
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ ./exp6.task6.sh
1 2 3
2 4 6
3 6 9
vaishnavii29@DESKTOP-BSKS7E4:/mnt/c/Users/DELL/Desktop/New folder/linux$ |
```

Result

- Implemented for, while, and until loops and used loop control statements.
- Practiced reading input, processing files, and nested iteration.

Challenges Faced & Learning Outcomes

- Challenge 1: Handling spaces and special characters when iterating filenames — learned to use quotes and read -r.
- Challenge 2: Remembering arithmetic syntax in Bash — used (()) and expr where needed.

Learning:

- Loops are powerful for automation in shell scripting. Correct quoting and use of control constructs prevent common bugs.

Conclusion

The lab demonstrated practical loop constructs in Bash for automating repetitive tasks and processing data efficiently.