# EXPERIMENT-2



# AIM: To convert the ER diagram of an Indian E-commerce platform into Relational Schema, create MySQL tables with Primary Key, Foreign Key Not Null, Unique. On delete CASCADE and ON DELETE SET NULL constraints, insert sample data, and demonstrate referential integrity notations.

# RELATIONAL SCHEMA:

**Student**
- Student ID
- Student Name
- Email (UNIQUE)
- Dept. ID

**Department**
- Dept. ID
- Dept. Name

**Course**
- Course ID
- Course Name
- Credits

**Enrollment**
- Enroll ID
- Student ID
- Course ID

# SOURCE CODE (My SQL) :-

```
CREATE DATABASE college DB;
Use college DB;
CREATE TABLE DEPARTMENT (
  Dept. ID INT PRIMARY KEY,
  Dept. Name VARCHAR (50) NOT Null UNIQUE
  );

CREATE TABLE Student C
    Student ID INT PRIMARY KEY,
    Student Name VARCHAR (50) NOT NULL,
    Email VARCHAR(100) UNIQUE,
    Dept. ID INT,
    FOREIGN KEY (Dept.ID)
    REFERENCE Department (Dept. ID)
    ON DELETE SET NULL
);
    CREATE TABLE Course(
        Course ID INT PRIMARY KEY,
        Course Name VARCHAR (50) NOT NULL,
        Credits INT NOT NULL
);

    CREATE TABLE Enrollment (
     Enroll ID INT Primary Key
     Student ID INT,
     Course ID INT

    ON DELETE CASCADE
    FOREIGN KEY (course ID)
    REFRENCES Course ( Course ID)
    ON DELETE CASCADE
);
```

# Output :-

Department

| Dept. ID | Dept. Name |
|---|---|
| 1 | CSE |
| 2 | AI ML |

Student

| ID | Name | Email | Dept. ID |
|---|---|---|---|
| 101 | Rahul | rahul12@gmail.com | 1 |
| 102 | Vansh | vansh@gmail.com | 2 |

26 08 24

Course

| ID | Name | Credits |
|---|---|---|
| 101 | DBMS | 4 |
| 102 | operating Systems | 4 |

Enrollment

| Enroll ID | Student ID | Course ID |
|---|---|---|
| 1 | 101 | 201 |
| 2 | 102 | 202 |