1. COMMIT Program

‹/› SQL

```sql
CREATE DATABASE BankDB;
USE BankDB;

CREATE TABLE Account (
    Account_ID INT PRIMARY KEY,
    Name VARCHAR(50),
    Balance INT
);

INSERT INTO Account VALUES (101, 'Rahul', 10000);
INSERT INTO Account VALUES (102, 'Priya', 15000);

COMMIT;

SELECT * FROM Account;
```

COMMIT permanently saves the changes.

2. ROLLBACK Program

‹/› SQL

```sql
CREATE DATABASE BankDB2;
USE BankDB2;

CREATE TABLE Account (
    Account_ID INT PRIMARY KEY,
    Name VARCHAR(50),
    Balance INT
);

INSERT INTO Account VALUES (101, 'Rahul', 10000);
INSERT INTO Account VALUES (102, 'Priya', 15000);

COMMIT;

START TRANSACTION;

UPDATE Account
SET Balance = Balance - 2000
WHERE Account_ID = 101;

ROLLBACK;

SELECT * FROM Account;
```

ROLLBACK cancels the changes made after the transaction started.

3. SAVEPOINT Program

‹/› SQL

```sql
CREATE DATABASE BankDB3;
USE BankDB3;

CREATE TABLE Account (
    Account_ID INT PRIMARY KEY,
    Name VARCHAR(50),
    Balance INT
);

INSERT INTO Account VALUES (101, 'Rahul', 10000);
INSERT INTO Account VALUES (102, 'Priya', 15000);

COMMIT;

START TRANSACTION;

UPDATE Account
SET Balance = Balance - 2000
WHERE Account_ID = 101;

SAVEPOINT sp1;

UPDATE Account
SET Balance = Balance + 2000
WHERE Account_ID = 102;

COMMIT;
```



SAVEPOINT creates a point inside a transaction to which you can later roll back.

4. ROLLBACK TO SAVEPOINT Program

SQL

```sql
CREATE DATABASE BankDB4;
USE BankDB4;

CREATE TABLE Account (
    Account_ID INT PRIMARY KEY,
    Name VARCHAR(50),
    Balance INT
);

INSERT INTO Account VALUES (101, 'Rahul', 10000);
INSERT INTO Account VALUES (102, 'Priya', 15000);

COMMIT;

START TRANSACTION;

UPDATE Account
SET Balance = Balance - 2000
WHERE Account_ID = 101;

SAVEPOINT sp1;

UPDATE Account
SET Balance = Balance + 5000
WHERE Account_ID = 102;

ROLLBACK TO SAVEPOINT sp1;
```

```
COMMIT;

SELECT * FROM Account;
```

Here, the **₹5000 change is cancelled**, but Rahul's ₹2000 change remains.

5. RELEASE SAVEPOINT Program

‹/› SQL

```sql
CREATE DATABASE BankDB5;
USE BankDB5;

CREATE TABLE Account (
    Account_ID INT PRIMARY KEY,
    Name VARCHAR(50),
    Balance INT
);

INSERT INTO Account VALUES (101, 'Rahul', 10000);
INSERT INTO Account VALUES (102, 'Priya', 15000);

COMMIT;

START TRANSACTION;

UPDATE Account
SET Balance = Balance - 2000
WHERE Account_ID = 101;

SAVEPOINT sp1;

UPDATE Account
SET Balance = Balance + 2000
WHERE Account_ID = 102;

RELEASE SAVEPOINT sp1;
```

```
COMMIT;

SELECT * FROM Account;
```

RELEASE SAVEPOINT removes the savepoint because it is no longer needed.