Exp – 4

Vaishnav s

1BM18CS121

VAISHNAV S
1BM18CS121

Experiment -4.

Question : Demonstrate Static IP Setting.

Aim : Static IP Setting.

Topology :



Procedure :

1) Connect the PCS & routers as shown above.
2) Set IP & default gateways for both PC
3) Configure Router 0 & router 2 Static IPS;
   & for Router 1 set IP router.
4) Ping one PC from other to check connection

Vaishnav S

CLI Commands.

Router.

1) enable.
2) config t
3) interface fastethernet 0/0.
4) ip address 10.0.0.10 255.0.0.0
5) ip route 0.0.0.0 0.0.0.0 20.0.0.2
6) show ip rot.
7) no shut.

Observation:

1) The Packets from Sender to receiver is passed through Router in between.
2) Even through the dest set the route specifically. The default route allocated for sending data.

Vaishnav.S

SCREEN SHOTS:

```
Router>enable
Router#congif t
              ^
% Invalid input detected at '^' marker.

Router#config t
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#ip route 0.0.0.0 0.0.0.0 20.0.0.2
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is 20.0.0.2 to network 0.0.0.0

C    10.0.0.0/8 is directly connected, FastEthernet0/0
C    20.0.0.0/8 is directly connected, Serial2/0
S*   0.0.0.0/0 [1/0] via 20.0.0.2

Router#
```

Ctrl+F6 to exit CLI focus

```
Router(config-if)#
Router(config-if)#ip route 0.0.0.0 0.0.0.0 30.0.0.1
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is 30.0.0.1 to network 0.0.0.0

C    30.0.0.0/8 is directly connected, Serial2/0
C    40.0.0.0/8 is directly connected, FastEthernet0/0
S*   0.0.0.0/0 [1/0] via 30.0.0.1

Router#
```

TOPOLOGY:


```
Router(config-if)#
Router(config-if)#ip route 0.0.0.0 0.0.0.0 30.0.0.1
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console
show ip route
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

Gateway of last resort is 30.0.0.1 to network 0.0.0.0

C    30.0.0.0/8 is directly connected, Serial2/0
C    40.0.0.0/8 is directly connected, FastEthernet0/0
S*   0.0.0.0/0 [1/0] via 30.0.0.1

Router#
```

RESULT:


Se2/0
30.0.0.2
Router-PT
Router
Fa0/0
40.0.0.10
Fa0
PC-PT
PC1
40.0.0.1
PC0
Physical
Config
Desktop
Programming
Attributes
Command Prompt
X
Request timed out.
Request timed out.
Request timed out.
Request timed out.
Ping statistics for 40.0.0.1:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
C:\>ping 40.0.0.1
Pinging 40.0.0.1 with 32 bytes of data:
Request timed out.
Reply from 40.0.0.1: bytes=32 time=2ms TTL=125
Reply from 40.0.0.1: bytes=32 time=9ms TTL=125
Reply from 40.0.0.1: bytes=32 time=15ms TTL=125
Ping statistics for 40.0.0.1:
Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
Minimum = 2ms, Maximum = 15ms, Average = 8ms
C:\>
Top