Instruction/feature support across the fleet
(derived entirely from black-box #UD-vs-executes behavior, no cpuid read)
AVX2 (vpaddd ymm)
BMI1 (andn)
BMI2 (pext)
FMA (vfmadd132ps)
RDRAND
RDSEED
AES-NI, scalar (aesenc)
PCLMULQDQ, scalar
AES-NI, vectorized (vaesenc)
VPCLMULQDQ, vectorized
SHA-NI (sha256rnds2)
GFNI
CLFLUSHOPT-class
AVX-512F (vaddps zmm)
AVX-512 VNNI
AVX-512 BITALG
PKU (rdpkru)
UMIP-restricted (sldt)
WAITPKG (umwait)
UD OK OK OK OK OK
UD OK OK OK OK OK
UD OK OK OK OK OK
UD OK OK OK OK OK
UD OK OK OK OK OK
UD UD OK OK OK OK
OK OK OK OK OK OK
OK OK OK OK OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
UD UD OK OK OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
UD UD UD UD OK OK
ok ok ok ok GP GP
UD UD UD UD UD UD
z420
Sandy Bridge-EP
2012
imac
Haswell
2013
fuzzarch
Kaby Lake-R
2017
d153-system
Coffee Lake
2019
lily
Tiger Lake
2020
debian
Tiger Lake
2020
present / executes
ambiguous (or: UMIP-restricted)
absent (#UD)