

Pocket Smart AI

Test with Real-World Budget Input Across Domains

Team Member Assignment – Pushra N

1. Topic

Testing with real-world budget inputs across different domains.

Epic: Testing & Validation

2. Project Overview

Pocket Smart AI is an AI-powered application that can work with user-provided budget information. This task focuses on testing realistic budget inputs from different domains such as food, travel, education, shopping, healthcare, and household expenses. Domain-based testing divides input values into valid, invalid, boundary, and special cases so that the system can handle real-world inputs reliably.

3. Objective

To test Pocket Smart AI using realistic budget values across multiple domains and verify that valid inputs are processed correctly, invalid inputs are rejected properly, and boundary or unusual values do not cause incorrect results or application failures.

4. Work Steps

- 1 Identify the budget input fields and define acceptable ranges for each domain.
- 2 Create realistic test data for food, travel, education, shopping, healthcare, and household budgets.
- 3 Divide the inputs into valid, invalid, boundary, zero, negative, blank, and unusually large values.
- 4 Test normal budget values and verify that the generated result matches the expected behavior.
- 5 Test boundary values such as the minimum, maximum, and values immediately around each limit.
- 6 Test invalid inputs such as negative amounts, text, special characters, blank values, and incorrect formats.
- 7 Record defects found during testing and verify the application's error messages and handling.
- 8 Retest corrected cases and confirm that the complete budget workflow works across all domains.

5. Real-World Budget Test Domains

Food: ■500, ■2,000, ■10,000; test ■0, negative values, and very large values.

Travel: ■3,000, ■15,000, ■1,00,000; test values below and above the accepted range.

Education: ■1,000, ■25,000, ■2,00,000; test boundary and invalid formats.

Shopping: ■500, ■5,000, ■50,000; test zero, negative, blank, and text inputs.

Healthcare: ■1,000, ■10,000, ■1,00,000; test realistic and extreme amounts.

Household: ■2,000, ■10,000, ■50,000; test valid ranges and invalid entries.

6. Expected Test Outcome

The application should correctly accept valid budget inputs, identify invalid or out-of-range values, handle boundary cases safely, and provide clear responses without crashing. Testing should also confirm that the same validation principles work consistently across different real-world budget domains.

7. Team Member

Name: Pushra N

Role: Member

Topic: Test with Real-World Budget Input Across Domains

Epic: Testing & Validation