

Employee Name : - PravinKumar RajaSahayam
Employee Id : - 11946
Day - 4

MYSQL : -

```
mysql> create database mysqlday4;  
Query OK, 1 row affected (0.01 sec)
```

```
mysql> use mysqlday4;  
Database changed
```

```
mysql> create table tbl_employee1 (  
    -> eid int(5),  
    -> ename varchar(10),  
    -> esalary int(15),  
    -> edeptno int(56)  
    -> );  
Query OK, 0 rows affected, 3 warnings (0.04 sec)
```

```
mysql> show tables;  
+-----+  
| Tables_in_mysqlday4 |  
+-----+  
| tbl_employee1      |  
+-----+  
1 row in set (0.01 sec)
```

```
mysql> desc tbl_employee1;  
+-----+-----+-----+-----+-----+-----+  
| Field | Type      | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| eid   | int       | YES  |     | NULL    |       |  
| ename | varchar(10) | YES  |     | NULL    |       |  
| esalary | int       | YES  |     | NULL    |       |  
| edeptno | int       | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
4 rows in set (0.00 sec)
```

```
mysql> insert into tbl_employee1 values (101,'Pravins',1000,10);  
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee1 values(102,'Pravins',2000,20);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee1 values(103,'Pravins',3000,30);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee1 values(104,'Pravins',4000,404);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee1 values(105,'Pravins',5000,550);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> select * from tbl_employee1;
```

eid	ename	esalary	edeptno
101	Pravins	1000	10
102	Pravins	2000	20
103	Pravins	3000	30
104	Pravins	4000	404
105	Pravins	5000	550

5 rows in set (0.00 sec)

```
mysql> select edeptno , count(*) from tbl_employee1 group by edeptno;
```

edeptno	count(*)
10	1
20	1
30	1
404	1
550	1

5 rows in set (0.00 sec)

```
mysql> select edeptno , count(*) from tbl_employee1 group by edeptno having min(esalary = 3000);
```

edeptno	count(*)
30	1

1 row in set (0.00 sec)

```
mysql> select ename from tbl_employee1;
```

```
+-----+  
| ename |  
+-----+  
| Pravins |  
| Pravins |  
| Pravins |  
| Pravins |  
| Pravins |  
+-----+
```

5 rows in set (0.00 sec)

```
mysql> select upper(ename) from tbl_employee1;
```

```
+-----+  
| upper(ename) |  
+-----+  
| PRAVINS      |  
| PRAVINS      |  
| PRAVINS      |  
| PRAVINS      |  
| PRAVINS      |  
+-----+
```

5 rows in set (0.00 sec)

```
mysql> select lower(ename) from tbl_employee1;
```

```
+-----+  
| lower(ename) |  
+-----+  
| pravins      |  
| pravins      |  
| pravins      |  
| pravins      |  
| pravins      |  
+-----+
```

5 rows in set (0.00 sec)

```
mysql> create view myview as select * from tbl_employee1 where edeptno = 10 ;  
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> show tables;
```

```
+-----+  
| Tables_in_mysql |  
+-----+
```

```
| myview      |
| tbl_employee1 |
+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from myview;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | 1000 | 10 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> desc myview;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| eid | int | YES | | NULL | |
| ename | varchar(10) | YES | | NULL | |
| esalary | int | YES | | NULL | |
| edeptno | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> update myview set esalary = 73000 where eid = 101;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1 Changed: 1 Warnings: 0
```

```
mysql> select * from myview;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | 73000 | 10 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee1;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | 73000 | 10 |
| 102 | Pravins | 2000 | 20 |
| 103 | Pravins | 3000 | 30 |
| 104 | Pravins | 4000 | 404 |
```

```
| 105 | Pravins | 5000 | 550 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
mysql> update tbl_employee1 set esalary = null where edeptno = 10;
Query OK, 1 row affected (0.00 sec)
Rows matched: 1 Changed: 1 Warnings: 0
```

```
mysql> select * from myview;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | NULL | 10 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee1;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | NULL | 10 |
| 102 | Pravins | 2000 | 20 |
| 103 | Pravins | 3000 | 30 |
| 104 | Pravins | 4000 | 404 |
| 105 | Pravins | 5000 | 550 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
mysql> desc tbl_employee1;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| eid | int | YES | | NULL | |
| ename | varchar(10) | YES | | NULL | |
| esalary | int | YES | | NULL | |
| edeptno | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee1;
+-----+-----+-----+-----+
| eid | ename | esalary | edeptno |
+-----+-----+-----+-----+
| 101 | Pravins | NULL | 10 |
```

102	Pravins	2000	20
103	Pravins	3000	30
104	Pravins	4000	404
105	Pravins	5000	550

+-----+-----+-----+-----+

5 rows in set (0.00 sec)

mysql> desc myview;

+-----+-----+-----+-----+-----+-----+

Field	Type	Null	Key	Default	Extra
eid	int	YES		NULL	
ename	varchar(10)	YES		NULL	
esalary	int	YES		NULL	
edeptno	int	YES		NULL	

+-----+-----+-----+-----+-----+

4 rows in set (0.00 sec)

mysql> select * from tbl_employee1;

+-----+-----+-----+-----+

eid	ename	esalary	edeptno
101	Pravins	NULL	10
102	Pravins	2000	20
103	Pravins	3000	30
104	Pravins	4000	404
105	Pravins	5000	550

+-----+-----+-----+-----+

5 rows in set (0.00 sec)

mysql> create table tbl_customers (

-> customer_code int(5),

-> customer_name varchar(13),

-> customer_area varchar(19)

->);

Query OK, 0 rows affected, 1 warning (0.03 sec)

mysql> select * from tbl_customers;

Empty set (0.00 sec)

mysql> desc tbl_customers;

+-----+-----+-----+-----+-----+-----+

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

+-----+-----+-----+-----+-----+

customer_code	int	YES	NULL
customer_name	varchar(13)	YES	NULL
customer_area	varchar(19)	YES	NULL

+-----+-----+-----+-----+

3 rows in set (0.00 sec)

mysql> show tables;

+-----+

Tables_in_mysql

+-----+

myview

tbl_customers

tbl_employee1

+-----+

3 rows in set (0.00 sec)

mysql> alter table tbl_customers modify customer_code varchar(16);

Query OK, 0 rows affected (0.07 sec)

Records: 0 Duplicates: 0 Warnings: 0

mysql> insert into tbl_customers values ('C101','customer1','chennai');

Query OK, 1 row affected (0.01 sec)

mysql> insert into tbl_customers values ('C102','customer2','chennai');

Query OK, 1 row affected (0.01 sec)

mysql> insert into tbl_customers values ('C103','customer3','chennai');

Query OK, 1 row affected (0.02 sec)

mysql> insert into tbl_customers values ('C104','customer4','Bangalore');

Query OK, 1 row affected (0.01 sec)

mysql> insert into tbl_customers values ('C105','customer5','Bangalore');

Query OK, 1 row affected (0.01 sec)

mysql> select * from tbl_customers;

+-----+-----+-----+

customer_code	customer_name	customer_area
---------------	---------------	---------------

+-----+-----+-----+

C101	customer1	chennai
------	-----------	---------

C102	customer2	chennai
------	-----------	---------

C103	customer3	chennai
------	-----------	---------

C104	customer4	Bangalore
------	-----------	-----------

C105	customer5	Bangalore
------	-----------	-----------

```
+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
mysql> create table tbl_agents (
  -> agent_code varchar(16),
  -> agent_name varchar(16),
  -> working_area varchar(16)
  -> );
```

Query OK, 0 rows affected (0.05 sec)

```
mysql> select * from tbl_agents;
Empty set (0.00 sec)
```

```
mysql> desc tbl_agents;
```

```
+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+
| agent_code | varchar(16) | YES  |     | NULL    |       |
| agent_name | varchar(16) | YES  |     | NULL    |       |
| working_area | varchar(16) | YES  |     | NULL    |       |
+-----+-----+-----+-----+
```

3 rows in set (0.00 sec)

```
mysql> show tables;
```

```
+-----+
| Tables_in_mysql |
+-----+
| myview          |
| tbl_agents      |
| tbl_customers   |
| tbl_employee1   |
+-----+
```

4 rows in set (0.00 sec)

```
mysql> insert into tbl_agents values ('A101','agent1','chennai');
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into tbl_agents values ( 'A102','agent2','chennai');
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_agents values ('A103','agent3','Bangalore');
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into tbl_agents values ('A104','agent4','Bangalore');
```


Query OK, 1 row affected (0.01 sec)

```
mysql> select * from tbl_agents;
```

agent_code	agent_name	working_area
A101	agent1	chennai
A102	agent2	chennai
A103	agent3	Bangalore
A104	agent4	Bangalore

4 rows in set (0.00 sec)

```
mysql> select tbl_agents.agent_name,tbl_agents.agent_code,tbl_customers.customer_name  
from tbl_agents,tbl_customers where tbl_agents.working_area = tbl_customers.customer_area ;
```

agent_name	agent_code	customer_name
agent2	A102	customer1
agent1	A101	customer1
agent2	A102	customer2
agent1	A101	customer2
agent2	A102	customer3
agent1	A101	customer3
agent4	A104	customer4
agent3	A103	customer4
agent4	A104	customer5
agent3	A103	customer5

10 rows in set (0.01 sec)

```
mysql> select a.agent_name,a.agent_code,c.customer_name from tbl_agents a,tbl_customers  
c where a.working_area = c.customer_area;
```

agent_name	agent_code	customer_name
agent2	A102	customer1
agent1	A101	customer1
agent2	A102	customer2
agent1	A101	customer2
agent2	A102	customer3
agent1	A101	customer3
agent4	A104	customer4
agent3	A103	customer4

agent4	A104	customer5
agent3	A103	customer5

10 rows in set (0.00 sec)

```
mysql> select a.agent_name,a.agent_code,c.customer_name from tbl_agents a join
tbl_customers c on a.working_area = c.customer_area;
```

agent_name	agent_code	customer_name
agent2	A102	customer1
agent1	A101	customer1
agent2	A102	customer2
agent1	A101	customer2
agent2	A102	customer3
agent1	A101	customer3
agent4	A104	customer4
agent3	A103	customer4
agent4	A104	customer5
agent3	A103	customer5

10 rows in set (0.00 sec)

```
mysql> select a.agent_name,a.agent_code,c.customer_name from tbl_agents a inner join
tbl_customers c on a.working_area = c.customer_area;
```

agent_name	agent_code	customer_name
agent2	A102	customer1
agent1	A101	customer1
agent2	A102	customer2
agent1	A101	customer2
agent2	A102	customer3
agent1	A101	customer3
agent4	A104	customer4
agent3	A103	customer4
agent4	A104	customer5
agent3	A103	customer5

10 rows in set (0.00 sec)

```
mysql> insert into tbl_agents values ('A150','agent5','Kolkata');
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_customers values ('C106','customer6','Delhi');
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from tbl_agents;
```

```
+-----+-----+-----+
| agent_code | agent_name | working_area |
+-----+-----+-----+
| A101      | agent1     | chennai      |
| A102      | agent2     | chennai      |
| A103      | agent3     | Bangalore    |
| A104      | agent4     | Bangalore    |
| A150      | agent5     | Kolkata      |
+-----+-----+-----+
```

5 rows in set (0.00 sec)

```
mysql> select * from tbl_customers;
```

```
+-----+-----+-----+
| customer_code | customer_name | customer_area |
+-----+-----+-----+
| C101          | customer1     | chennai       |
| C102          | customer2     | chennai       |
| C103          | customer3     | chennai       |
| C104          | customer4     | Bangalore     |
| C105          | customer5     | Bangalore     |
| C106          | customer6     | Delhi         |
+-----+-----+-----+
```

6 rows in set (0.00 sec)

```
mysql> select * from tbl_agents a left outer join tbl_customers c on a.working_area =
c.customer_area;
```

```
+-----+-----+-----+-----+-----+-----+
| agent_code | agent_name | working_area | customer_code | customer_name | customer_area |
+-----+-----+-----+-----+-----+-----+
| A101      | agent1     | chennai      | C103          | customer3     | chennai       |
| A101      | agent1     | chennai      | C102          | customer2     | chennai       |
| A101      | agent1     | chennai      | C101          | customer1     | chennai       |
| A102      | agent2     | chennai      | C103          | customer3     | chennai       |
| A102      | agent2     | chennai      | C102          | customer2     | chennai       |
| A102      | agent2     | chennai      | C101          | customer1     | chennai       |
| A103      | agent3     | Bangalore    | C105          | customer5     | Bangalore     |
| A103      | agent3     | Bangalore    | C104          | customer4     | Bangalore     |
| A104      | agent4     | Bangalore    | C105          | customer5     | Bangalore     |
| A104      | agent4     | Bangalore    | C104          | customer4     | Bangalore     |
+-----+-----+-----+-----+-----+-----+
```

A150	agent5	Kolkata	NULL	NULL	NULL	
------	--------	---------	------	------	------	--

11 rows in set (0.00 sec)

```
mysql> select * from tbl_agents a right outer join tbl_customers c on a.working_area = c.customer_area;
```

agent_code	agent_name	working_area	customer_code	customer_name	customer_area
A102	agent2	chennai	C101	customer1	chennai
A101	agent1	chennai	C101	customer1	chennai
A102	agent2	chennai	C102	customer2	chennai
A101	agent1	chennai	C102	customer2	chennai
A102	agent2	chennai	C103	customer3	chennai
A101	agent1	chennai	C103	customer3	chennai
A104	agent4	Bangalore	C104	customer4	Bangalore
A103	agent3	Bangalore	C104	customer4	Bangalore
A104	agent4	Bangalore	C105	customer5	Bangalore
A103	agent3	Bangalore	C105	customer5	Bangalore
NULL	NULL	NULL	C106	customer6	Delhi

11 rows in set (0.00 sec)

```
mysql> select * from tbl_agents cross join tbl_customers;
```

agent_code	agent_name	working_area	customer_code	customer_name	customer_area
A150	agent5	Kolkata	C101	customer1	chennai
A104	agent4	Bangalore	C101	customer1	chennai
A103	agent3	Bangalore	C101	customer1	chennai
A102	agent2	chennai	C101	customer1	chennai
A101	agent1	chennai	C101	customer1	chennai
A150	agent5	Kolkata	C102	customer2	chennai
A104	agent4	Bangalore	C102	customer2	chennai
A103	agent3	Bangalore	C102	customer2	chennai
A102	agent2	chennai	C102	customer2	chennai
A101	agent1	chennai	C102	customer2	chennai
A150	agent5	Kolkata	C103	customer3	chennai
A104	agent4	Bangalore	C103	customer3	chennai
A103	agent3	Bangalore	C103	customer3	chennai
A102	agent2	chennai	C103	customer3	chennai
A101	agent1	chennai	C103	customer3	chennai

A150	agent5	Kolkata	C104	customer4	Bangalore	
A104	agent4	Bangalore	C104	customer4	Bangalore	
A103	agent3	Bangalore	C104	customer4	Bangalore	
A102	agent2	chennai	C104	customer4	Bangalore	
A101	agent1	chennai	C104	customer4	Bangalore	
A150	agent5	Kolkata	C105	customer5	Bangalore	
A104	agent4	Bangalore	C105	customer5	Bangalore	
A103	agent3	Bangalore	C105	customer5	Bangalore	
A102	agent2	chennai	C105	customer5	Bangalore	
A101	agent1	chennai	C105	customer5	Bangalore	
A150	agent5	Kolkata	C106	customer6	Delhi	
A104	agent4	Bangalore	C106	customer6	Delhi	
A103	agent3	Bangalore	C106	customer6	Delhi	
A102	agent2	chennai	C106	customer6	Delhi	
A101	agent1	chennai	C106	customer6	Delhi	

```
+-----+-----+-----+-----+-----+-----+
```

30 rows in set (0.00 sec)

mysql>