

```
mysql> use mydb;
```

```
Database changed
```

```
mysql> show tables;
```

```
+-----+
| Tables_in_mydb |
+-----+
| tbl_1           |
| tbl_countries  |
| tbl_dup_countries |
| tbl_job_history |
| tbl_jobs        |
+-----+
5 rows in set (0.02 sec)
```

```
mysql> desc tbl_1;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| name  | varchar(10)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
1 row in set (0.01 sec)
```

```
mysql> create table tbl_Employee (eid int(5),ename varchar(20),esal
int(5));
```

```
Query OK, 0 rows affected, 2 warnings (0.05 sec)
```

```
mysql> desc tbl_Employee;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| eid   | int           | YES  |     | NULL    |       |
| ename | varchar(20)   | YES  |     | NULL    |       |
| esal  | int           | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> insert into tbl_Employee values(101,"Domnic",2000);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into tbl_Employee values(102,"Mahesh",2010);
```

```
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from tbl_Employee;
```

```
+-----+-----+-----+-----+-----+-----+
```

eid	ename	esal
101	Domnic	2000
102	Mahesh	2010

2 rows in set (0.00 sec)

```
mysql> insert into tbl_Employee values(103,null,4010);
```

Query OK, 1 row affected (0.02 sec)

```
mysql> insert into tbl_Employee (eid,ename) values(102,"dev");
```

Query OK, 1 row affected (0.01 sec)

```
mysql> select * from tbl_employee;
```

eid	ename	esal
101	Domnic	2000
102	Mahesh	2010
103	NULL	4010
102	dev	NULL

4 rows in set (0.00 sec)

```
mysql> select eid,ename,esal from tbl_employee;
```

eid	ename	esal
101	Domnic	2000
102	Mahesh	2010
103	NULL	4010
102	dev	NULL

4 rows in set (0.00 sec)

```
mysql> select eid from tbl_employee;
```

eid
101
102
103
102

4 rows in set (0.00 sec)

```
mysql> select * from tbl_employee where esal>2000;
```

```
+-----+-----+-----+
| eid   | ename   | esal   |
+-----+-----+-----+
| 102   | Mahesh  | 2010   |
| 103   | NULL    | 4010   |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee where esal=2010;
```

```
+-----+-----+-----+
| eid   | ename   | esal   |
+-----+-----+-----+
| 102   | Mahesh  | 2010   |
+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename!='mahesh';
```

```
+-----+-----+-----+
| eid   | ename   | esal   |
+-----+-----+-----+
| 101   | Domnic  | 2000   |
| 102   | dev     | NULL   |
+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename is null;
```

```
+-----+-----+-----+
| eid   | ename   | esal   |
+-----+-----+-----+
| 103   | NULL    | 4010   |
+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename is not null;
```

```
+-----+-----+-----+
| eid   | ename   | esal   |
+-----+-----+-----+
| 101   | Domnic  | 2000   |
| 102   | Mahesh  | 2010   |
| 102   | dev     | NULL   |
+-----+-----+-----+
3 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename is not null and  
esal=2000;
```

```
+-----+-----+-----+  
| eid  | ename  | esal |  
+-----+-----+-----+  
| 101  | Domnic | 2000 |  
+-----+-----+-----+  
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename is null or esal=null;
```

```
+-----+-----+-----+  
| eid  | ename  | esal |  
+-----+-----+-----+  
| 103  | NULL   | 4010 |  
+-----+-----+-----+  
1 row in set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename is null and esal=null;  
Empty set (0.00 sec)
```

```
mysql> select * from tbl_employee where eid in(101,103,106);
```

```
+-----+-----+-----+  
| eid  | ename  | esal |  
+-----+-----+-----+  
| 101  | Domnic | 2000 |  
| 103  | NULL   | 4010 |  
+-----+-----+-----+  
2 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee where eid not in(101,103,106);
```

```
+-----+-----+-----+  
| eid  | ename  | esal |  
+-----+-----+-----+  
| 102  | Mahesh | 2010 |  
| 102  | dev    | NULL  |  
+-----+-----+-----+  
2 rows in set (0.00 sec)
```

```
mysql> select * from tbl_employee where esal between 2000 and 4000;
```

```
+-----+-----+-----+  
| eid  | ename  | esal |  
+-----+-----+-----+  
| 101  | Domnic | 2000 |  
| 102  | Mahesh | 2010 |  
+-----+-----+-----+
```

2 rows in set (0.00 sec)

```
mysql> select * from tbl_employee where esal not between 2000 and 4000;
```

eid	ename	esal
103	NULL	4010

1 row in set (0.00 sec)

```
mysql> select * from tbl_employee where esal between 4000 and 2000;
Empty set (0.00 sec)
```

```
mysql> select * from tbl_employee where ename like 'd%';
```

eid	ename	esal
101	Domnic	2000
102	dev	NULL

2 rows in set (0.00 sec)

```
mysql> select * from tbl_employee where ename like '_a%';
```

eid	ename	esal
102	Mahesh	2010

1 row in set (0.00 sec)

```
mysql> select * from tbl_employee where ename like '%v';
```

eid	ename	esal
102	dev	NULL

1 row in set (0.00 sec)

```
mysql> select * from tbl_employee where ename like '%e%';
```

eid	ename	esal
102	Mahesh	2010
102	dev	NULL

```
+-----+-----+-----+
2 rows in set (0.00 sec)
```

```
mysql> insert into tbl_employee values(105,"Purush",1200);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee values(125,"Shiva",5200);
Query OK, 1 row affected (0.01 sec)
```

```
mysql> insert into tbl_employee values(525,"Aravind",3900);
Query OK, 1 row affected (0.02 sec)
```

```
mysql> select * from tbl_employee;
```

```
+-----+-----+-----+
| eid  | ename  | esal |
+-----+-----+-----+
| 101  | Domnic | 2000 |
| 102  | Mahesh | 2010 |
| 103  | NULL   | 4010 |
| 102  | dev    | NULL |
| 105  | Purush | 1200 |
| 125  | Shiva  | 5200 |
| 525  | Aravind | 3900 |
+-----+-----+-----+
7 rows in set (0.00 sec)
```

```
mysql> commit;
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> update tbl_employee set esal=0;
Query OK, 7 rows affected (0.01 sec)
Rows matched: 7  Changed: 7  Warnings: 0
```

```
mysql> select * from tbl_employee;
```

```
+-----+-----+-----+
| eid  | ename  | esal |
+-----+-----+-----+
| 101  | Domnic | 0     |
| 102  | Mahesh | 0     |
| 103  | NULL   | 0     |
| 102  | dev    | 0     |
| 105  | Purush | 0     |
| 125  | Shiva  | 0     |
| 525  | Aravind | 0     |
```

```
+-----+-----+-----+
7 rows in set (0.00 sec)
```

mysql> rollback;

Query OK, 0 rows affected (0.00 sec)

mysql> select * from tbl_employee;

```
+-----+-----+-----+
| eid  | ename  | esal |
+-----+-----+-----+
| 101  | Domnic | 0    |
| 102  | Mahesh | 0    |
| 103  | NULL   | 0    |
| 102  | dev    | 0    |
| 105  | Purush | 0    |
| 125  | Shiva  | 0    |
| 525  | Aravind | 0    |
+-----+-----+-----+
7 rows in set (0.00 sec)
```

mysql> select @@autocommit from dual;

```
+-----+
| @@autocommit |
+-----+
| 1            |
+-----+
1 row in set (0.00 sec)
```

mysql> set autocommit=0;

Query OK, 0 rows affected (0.00 sec)

mysql> select @@autocommit from dual;

```
+-----+
| @@autocommit |
+-----+
| 0            |
+-----+
1 row in set (0.00 sec)
```

mysql> update tbl_employee set esal=1000 where eid=101;

Query OK, 0 rows affected (0.00 sec)

Rows matched: 1 Changed: 0 Warnings: 0

mysql> select * from tbl_employee;

```
+-----+-----+-----+
```

eid	ename	esal
101	Domnic	1000
102	Mahesh	1000
103	NULL	1000
102	dev	1000
105	Purush	1000
125	Shiva	1000
525	Aravind	1000

7 rows in set (0.00 sec)

mysql> rollback;

Query OK, 0 rows affected (0.00 sec)

mysql> select * from tbl_employee;

eid	ename	esal
101	Domnic	0
102	Mahesh	0
103	NULL	0
102	dev	0
105	Purush	0
125	Shiva	0
525	Aravind	0

7 rows in set (0.00 sec)

mysql> update tbl_employee set esal=2000;

Query OK, 7 rows affected (0.00 sec)

Rows matched: 7 Changed: 7 Warnings: 0

mysql> select * from tbl_employee;

eid	ename	esal
101	Domnic	2000
102	Mahesh	2000
103	NULL	2000
102	dev	2000
105	Purush	2000
125	Shiva	2000
525	Aravind	2000

7 rows in set (0.00 sec)

mysql> commit;

Query OK, 0 rows affected (0.00 sec)

mysql> rollback;

Query OK, 0 rows affected (0.00 sec)

mysql> select * from tbl_employee;

```
+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 101   | Domnic  | 2000  |
| 102   | Mahesh  | 2000  |
| 103   | NULL    | 2000  |
| 102   | dev     | 2000  |
| 105   | Purush  | 2000  |
| 125   | Shiva   | 2000  |
| 525   | Aravind | 2000  |
+-----+-----+-----+
7 rows in set (0.00 sec)
```

**mysql> update tbl_employee set ename=null,esal=0 where eid
in(101,103,100);**

Query OK, 2 rows affected (0.00 sec)

Rows matched: 2 Changed: 2 Warnings: 0

mysql> select * from tbl_employee;

```
+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 101   | NULL    | 0      |
| 102   | Mahesh  | 2000  |
| 103   | NULL    | 0      |
| 102   | dev     | 2000  |
| 105   | Purush  | 2000  |
| 125   | Shiva   | 2000  |
| 525   | Aravind | 2000  |
+-----+-----+-----+
7 rows in set (0.00 sec)
```

mysql> rollback;

Query OK, 0 rows affected (0.00 sec)

mysql> select * from tbl_employee;

```

+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 101   | Domnic  | 2000  |
| 102   | Mahesh  | 2000  |
| 103   | NULL    | 2000  |
| 102   | dev     | 2000  |
| 105   | Purush  | 2000  |
| 125   | Shiva   | 2000  |
| 525   | Aravind | 2000  |
+-----+-----+-----+
7 rows in set (0.00 sec)

```

```

mysql> delete from tbl_employee where eid=102;
Query OK, 2 rows affected (0.00 sec)

```

```

mysql> select * from tbl_employee;
+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 101   | Domnic  | 2000  |
| 103   | NULL    | 2000  |
| 105   | Purush  | 2000  |
| 125   | Shiva   | 2000  |
| 525   | Aravind | 2000  |
+-----+-----+-----+
5 rows in set (0.00 sec)

```

```

mysql> select * from tbl_employee order by eid;
+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 101   | Domnic  | 2000  |
| 103   | NULL    | 2000  |
| 105   | Purush  | 2000  |
| 125   | Shiva   | 2000  |
| 525   | Aravind | 2000  |
+-----+-----+-----+
5 rows in set (0.00 sec)

```

```

mysql> select * from tbl_employee order by eid desc;
+-----+-----+-----+
| eid   | ename   | esal  |
+-----+-----+-----+
| 525   | Aravind | 2000  |

```

	125		Shiva		2000	
	105		Purush		2000	
	103		NULL		2000	
	101		Domnic		2000	

+-----+-----+-----+

5 rows in set (0.00 sec)