

**Employee Name: Jeban Ignesh.J**

**Employee ID: 11963.**

### MySQL Create Table [20 exercises with solution]

1. Write a SQL statement to create a simple table of countries including columns country\_id, country\_name and region\_id.

```
mysql> create table tbl_countries(country_id int(5),country_name varchar(20),region_id int(5));
Query OK, 0 rows affected, 2 warnings (0.03 sec)

mysql> desc tbl_countries;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | int           | YES  |     | NULL    |       |
| country_name | varchar(20)   | YES  |     | NULL    |       |
| region_id  | int           | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

2. Write a SQL statement to create a simple table of countries including columns country\_id, country\_name and region\_id which already exist.

```
mysql> create table tbl_countries(country_id int(5),country_name varchar(20),regio_id int(5));
ERROR 1050 (42S01): Table 'tbl_countries' already exists
mysql>
```

3) Write a SQL statement to create the structure of a table dup\_countries similar to countries.

```
mysql> create table tbl_dup_countries like tbl_countries;
Query OK, 0 rows affected (0.02 sec)

mysql> show tables;
+-----+
| Tables_in_lab_1 |
+-----+
| tbl_countries    |
| tbl_dup_countries |
+-----+
2 rows in set (0.00 sec)
```

4) Write a SQL statement to create a duplicate copy of countries table including structure and data by name dup\_countries.

```
mysql> create table tbl_dup_countries as select * from tbl_countries;
ERROR 1050 (42S01): Table 'tbl_dup_countries' already exists
mysql>
```

5) Write a SQL statement to create a table where countries set a constraint NULL.

```
mysql> alter table tbl_countries modify country_id int(5) NOT NULL;
Query OK, 0 rows affected, 1 warning (0.03 sec)
Records: 0 Duplicates: 0 Warnings: 1

mysql> alter table tbl_countries modify country_name varchar(20) NOT NULL;
Query OK, 0 rows affected (0.03 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> alter table tbl_countries modify region_id int(5) NOT NULL;
Query OK, 0 rows affected, 1 warning (0.03 sec)
Records: 0 Duplicates: 0 Warnings: 1

mysql> desc tbl_countries;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | int       | NO   |     | NULL    |       |
| country_name | varchar(20) | NO   |     | NULL    |       |
| region_id  | int       | NO   |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql>
```

6. Write a SQL statement to create a table named jobs including columns job\_id, job\_title, min\_salary, max\_salary and check whether the max\_salary amount exceeding the upper limit 25000.

```
mysql> create table tbl_jobs (job_id int, job_title varchar(20), min_salary int,max_salary int check(max_salary<=25000));
Query OK, 0 rows affected (0.03 sec)

mysql> desc tbl_jobs;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| job_id     | int       | YES  |     | NULL    |       |
| job_title  | varchar(20) | YES  |     | NULL    |       |
| min_salary | int       | YES  |     | NULL    |       |
| max_salary | int       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

7. Write a SQL statement to create a table named countries including columns country\_id, country\_name and region\_id and make sure that no countries except Italy, India and China will be entered in the table.

```
mysql> create table countries (COUNTRY_ID varchar(2),country_name varchar(30),check(country_name in('Italy','India','China')),region_id decimal(10,0));
Query OK, 0 rows affected (0.03 sec)

mysql> desc countries;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| COUNTRY_ID | varchar(2)    | YES  |     | NULL    |       |
| country_name | varchar(30)   | YES  |     | NULL    |       |
| region_id   | decimal(10,0) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

8. Write a SQL statement to create a table named job\_histry including columns employee\_id, start\_date, end\_date, job\_id and department\_id and make sure that the value against column end\_date will be entered at the time of insertion to the format like '--/--/----'.

```
mysql> create table job_histry(Employee_id decimal(6,0) not null,Start_Date date not null,End_Date date not null check(End_Date Like '--/--/----'),Job_Id varchar(10) not null,Department_Id decimal(4,0) not null);
Query OK, 0 rows affected (0.01 sec)

mysql> desc job_histry;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| Employee_id | decimal(6,0)  | NO   |     | NULL    |       |
| Start_Date  | date          | NO   |     | NULL    |       |
| End_Date    | date          | NO   |     | NULL    |       |
| Job_Id      | varchar(10)   | NO   |     | NULL    |       |
| Department_Id | decimal(4,0) | NO   |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

9. Write a SQL statement to create a table named countries including columns country\_id,country\_name and region\_id and make sure that no duplicate data against column country\_id will be allowed at the time of insertion.

```
mysql> create table countries1 (country_id varchar(2) not null,country_name varchar(30) not null,region_id decimal(10,0) not null, unique(country_id));
Query OK, 0 rows affected (0.01 sec)

mysql> desc countries1;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | varchar(2)    | NO   | PRI | NULL    |       |
| country_name | varchar(30)   | NO   |     | NULL    |       |
| region_id   | decimal(10,0) | NO   |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

10. Write a SQL statement to create a table named jobs including columns job\_id, job\_title, min\_salary and max\_salary, and make sure that, the default value for job\_title is blank and min\_salary is 8000 and max\_salary is NULL will

be entered automatically at the time of insertion if no value assigned for the specified columns.

```
mysql> create table if not exists jobs (job_id varchar(10) not null unique, job_title varchar(30) not null default ' ', min_salary decimal(6,0) default 8000, max_salary decimal(6,0) default null);
Query OK, 0 rows affected (0.02 sec)

mysql> desc jobs;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| job_id | varchar(10) | NO | PRI | NULL | |
| job_title | varchar(30) | NO | | 8000 | |
| min_salary | decimal(6,0) | YES | | NULL | |
| max_salary | decimal(6,0) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

11. Write a SQL statement to create a table named countries including columns country\_id, country\_name and region\_id and make sure that the country\_id column will be a key field which will not contain any duplicate data at the time of insertion.

```
mysql> create table countries2(country_id varchar(2) not null, country_name varchar(30) not null, region_id decimal(6,0) not null, unique(country_id));
Query OK, 0 rows affected (0.02 sec)

mysql> desc countries2;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | varchar(2) | NO | PRI | NULL | |
| country_name | varchar(30) | NO | | NULL | |
| region_id | decimal(6,0) | NO | | NULL | |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

12. Write a SQL statement to create a table countries including columns country\_id, country\_name and region\_id and make sure that the column country\_id will be unique and store an auto incremented value.

```
mysql> create table countries3(country_id integer not null unique auto_increment primary key, country_name varchar(40) not null, region_id decimal(10,0) not null);
Query OK, 0 rows affected (0.02 sec)

mysql> desc countries3;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | int | NO | PRI | NULL | auto_increment |
| country_name | varchar(40) | NO | | NULL | |
| region_id | decimal(10,0) | NO | | NULL | |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

13. Write a SQL statement to create a table countries including columns country\_id, country\_name and region\_id and make sure that the combination of columns country\_id and region\_id will be unique.

```
mysql> create table countries4 (country_id varchar(2) not null, country_name varchar(30) not null, region_id decimal(10,0) not null, unique (country_id, region_id));
Query OK, 0 rows affected (0.02 sec)

mysql> desc countries4;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| country_id | varchar(2) | NO | PRI | NULL | |
| country_name | varchar(30) | NO | | NULL | |
| region_id | decimal(10,0) | NO | PRI | NULL | |
+-----+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)
```

14. Write a SQL statement to create a table job\_history including columns employee\_id, start\_date, end\_date, job\_id and department\_id and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion and the foreign key column job\_id contain only those values which are exists in the jobs table.

```
mysql> create table jobs1(job_id varchar(10) not null unique,job_title varchar(35) not null default'',min_salary decimal(6,0) default 8000,max_salary decimal(6,0)default null);
Query OK, 0 rows affected (0.01 sec)

mysql> create table job_history1 (employee_id decimal(6,0) not null primary key,start_date date not null, end_date date not null, job_id varchar(10) not null, department_id decimal(4,0) default null, foreign key (job_id) references jobs1(job_id));
Query OK, 0 rows affected (0.02 sec)

mysql> desc job_history1;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| employee_id | decimal(6,0) | NO | PRI | NULL | |
| start_date | date | NO | | NULL | |
| end_date | date | NO | | NULL | |
| job_id | varchar(10) | NO | MUL | NULL | |
| department_id | decimal(4,0) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> desc jobs1;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| job_id | varchar(10) | NO | PRI | NULL | |
| job_title | varchar(35) | NO | | | |
| min_salary | decimal(6,0) | YES | | 8000 | |
| max_salary | decimal(6,0) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

15. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, email, phone\_number hire\_date, job\_id, salary, commission, manager\_id and department\_id and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion and the foreign key columns combined by department\_id and manager\_id columns contain only those unique combination values, which combinations are exists in the departments table.

```
mysql> create table departments (department_id decimal(4,0)not null primary key, department_name decimal(10,0) not null, manager_id decimal(6,0)not null default 0,location_id decimal(4,0) null default null);
Query OK, 0 rows affected (0.02 sec)

mysql> desc departments;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| department_id | decimal(4,0) | NO | PRI | NULL | |
| department_name | decimal(10,0) | NO | | NULL | |
| manager_id | decimal(6,0) | NO | | 0 | |
| location_id | decimal(4,0) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE IF NOT EXISTS employees (
->  EMPLOYEE_ID decimal(6,0) NOT NULL PRIMARY KEY,
->  FIRST_NAME varchar(20) DEFAULT NULL,
->  LAST_NAME varchar(25) NOT NULL,
->  EMAIL varchar(25) NOT NULL,
->  PHONE_NUMBER varchar(20) DEFAULT NULL,
->  HIRE_DATE date NOT NULL,
->  JOB_ID varchar(10) NOT NULL,
->  SALARY decimal(8,2) DEFAULT NULL,
->  COMMISSION_PCT decimal(2,2) DEFAULT NULL,
->  MANAGER_ID decimal(6,0) DEFAULT NULL,
->  DEPARTMENT_ID decimal(4,0) DEFAULT NULL,
->  FOREIGN KEY(DEPARTMENT_ID,MANAGER_ID)
->  REFERENCES tbl_departments(DEPARTMENT_ID,MANAGER_ID)
-> )ENGINE=InnoDB;
Query OK, 0 rows affected (0.03 sec)
```

16. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, email, phone\_number hire\_date, job\_id, salary, commission, manager\_id and department\_id and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion, and the foreign key column department\_id, reference by the column department\_id of departments table, can contain only those values which are exists in the departments table and another foreign key column job\_id, referenced by the column job\_id of jobs table, can contain only those values which are exists in the jobs table. The InnoDB Engine have been used to create the tables.

"A foreign key constraint is not required merely to join two tables. For storage engines other than InnoDB, it is possible when defining a column to use a REFERENCES tbl\_name(col\_name) clause, which has no actual effect, and serves only as a memo or comment to you that the column which you are currently defining is intended to refer to a column in another table." - Reference dev.mysql.com

Assume that the structure of two tables departments and jobs.

Field	Type	Null	Key	Default	Extra
DEPARTMENT_ID	decimal(4,0)	NO	PRI	0	
DEPARTMENT_NAME	varchar(30)	NO		NULL	
MANAGER_ID	decimal(6,0)	YES		NULL	
LOCATION_ID	decimal(4,0)	YES		NULL	

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

JOB_ID	varchar(10)	NO	PRI		
JOB_TITLE	varchar(35)	NO		NULL	
MIN_SALARY	decimal(6,0)	YES		NULL	
MAX_SALARY	decimal(6,0)	YES		NULL	

+-----+-----+-----+-----+-----+-----+

```
mysql> create table departments (
  -> department_id decimal(4,0) NOT NULL PRIMARY KEY default '0',
  -> department_name varchar(30) NOT NULL,
  -> manager_id decimal(6,0) default NULL,
  -> location_id decimal(4,0) default NULL
  -> );
Query OK, 0 rows affected (0.03 sec)

mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
+-----+
1 row in set (0.00 sec)
```

```
mysql> create table jobs (
  -> job_id varchar(10) NOT NULL PRIMARY KEY,
  -> job_title varchar(35) NOT NULL,
  -> min_salary decimal(6,0) default NULL,
  -> max_salary decimal(6,0) default NULL
  -> );
Query OK, 0 rows affected (0.03 sec)

mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
| jobs          |
+-----+
2 rows in set (0.00 sec)

mysql> desc jobs;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| job_id | varchar(10) | NO | PRI | NULL | |
| job_title | varchar(35) | NO | | NULL | |
| min_salary | decimal(6,0) | YES | | NULL | |
| max_salary | decimal(6,0) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE IF NOT EXISTS employees (
  -> EMPLOYEE_ID decimal(9,0) NOT NULL PRIMARY KEY,
  -> FIRST_NAME varchar(20) DEFAULT NULL,
  -> LAST_NAME varchar(25) NOT NULL,
  -> EMAIL varchar(25) NOT NULL,
  -> PHONE_NUMBER varchar(20) DEFAULT NULL,
  -> HIRE_DATE date NOT NULL,
  -> JOB_ID varchar(10) NOT NULL,
  -> SALARY decimal(8,2) DEFAULT NULL,
  -> COMMISSION_PCT decimal(2,2) DEFAULT NULL,
  -> MANAGER_ID decimal(9,0) DEFAULT NULL,
  -> DEPARTMENT_ID decimal(4,0) DEFAULT NULL,
  -> FOREIGN KEY(DEPARTMENT_ID)
  -> REFERENCES departments(DEPARTMENT_ID),
  -> FOREIGN KEY(JOB_ID)
  -> REFERENCES jobs(JOB_ID)
  -> )ENGINE=InnoDB;
Query OK, 0 rows affected (0.03 sec)

mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs          |
+-----+
3 rows in set (0.00 sec)
```

```
mysql> desc employees;
```

Field	Type	Null	Key	Default	Extra
EMPLOYEE_ID	decimal(6,0)	NO	PRI	NULL	
FIRST_NAME	varchar(20)	YES		NULL	
LAST_NAME	varchar(25)	NO		NULL	
EMAIL	varchar(25)	NO		NULL	
PHONE_NUMBER	varchar(20)	YES		NULL	
HIRE_DATE	date	NO		NULL	
JOB_ID	varchar(10)	NO	MUL	NULL	
SALARY	decimal(8,2)	YES		NULL	
COMMISSION_PCT	decimal(2,2)	YES		NULL	
MANAGER_ID	decimal(6,0)	YES		NULL	
DEPARTMENT_ID	decimal(4,0)	YES	MUL	NULL	

```
11 rows in set (0.00 sec)
```

17. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, job\_id, salary and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion, and the foreign key column job\_id, referenced by the column job\_id of jobs table, can contain only those values which are exists in the jobs table. The InnoDB Engine have been used to create the tables. The specialty of the statement is that, The ON UPDATE CASCADE action allows you to perform cross-table update and ON DELETE RESTRICT action reject the deletion. The default action is ON DELETE RESTRICT.

Assume that the structure of the table jobs and InnoDB Engine have been used to create the table jobs.

```
CREATE TABLE IF NOT EXISTS jobs (
JOB_ID integer NOT NULL UNIQUE PRIMARY KEY,
JOB_TITLE varchar(35) NOT NULL DEFAULT '',
MIN_SALARY decimal(6,0) DEFAULT 8000,
MAX_SALARY decimal(6,0) DEFAULT NULL
)ENGINE=InnoDB;
```

```
+-----+-----+-----+-----+-----+
| Field  | Type    | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| JOB_ID | int(11) | NO   | PRI | NULL    |       |
| JOB_TITLE | varchar(35) | NO   |     |         |       |
| MIN_SALARY | decimal(6,0) | YES  |     | 8000    |       |
| MAX_SALARY | decimal(6,0) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```



```
mysql> create table tbl_jobs (
  -> job_id integer NOT NULL UNIQUE PRIMARY KEY,
  -> job_title varchar(35) NOT NULL default ' ',
  -> min_salary decimal(6,0) default 8000,
  -> max_salary decimal(6,0) default NULL
  -> )ENGINE=InnoDB;
```

Query OK, 0 rows affected (0.02 sec)

```
mysql> show tables;
```

```
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs          |
| tbl_jobs      |
+-----+
```

4 rows in set (0.00 sec)

```
mysql> desc tbl_jobs;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| job_id     | int           | NO   | PRI | NULL    |       |
| job_title  | varchar(35)   | NO   |     |         |       |
| min_salary | decimal(6,0)  | YES  |     | 8000    |       |
| max_salary | decimal(6,0)  | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
```

4 rows in set (0.00 sec)

```
mysql> CREATE TABLE IF NOT EXISTS tbl_employees (
  -> EMPLOYEE_ID decimal(6,0) NOT NULL PRIMARY KEY,
  -> FIRST_NAME varchar(20) DEFAULT NULL,
  -> LAST_NAME varchar(25) NOT NULL,
  -> EMAIL varchar(25) NOT NULL,
  -> PHONE_NUMBER varchar(20) DEFAULT NULL,
  -> HIRE_DATE date NOT NULL,
  -> JOB_ID varchar(10) NOT NULL,
  -> SALARY decimal(8,2) DEFAULT NULL,
  -> COMMISSION_PCT decimal(2,2) DEFAULT NULL,
  -> MANAGER_ID decimal(6,0) DEFAULT NULL,
  -> DEPARTMENT_ID decimal(4,0) DEFAULT NULL,
  -> FOREIGN KEY(DEPARTMENT_ID)
  -> REFERENCES departments(DEPARTMENT_ID),
  -> FOREIGN KEY(JOB_ID)
  -> REFERENCES jobs(JOB_ID)
  -> )ENGINE=InnoDB;
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs          |
| tbl_employees |
| tbl_jobs      |
+-----+
5 rows in set (0.00 sec)
```

```
mysql> desc tbl_employees;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| EMPLOYEE_ID | decimal(6,0)  | NO   | PRI | NULL    |       |
| FIRST_NAME  | varchar(20)   | YES  |     | NULL    |       |
| LAST_NAME   | varchar(25)   | NO   |     | NULL    |       |
| EMAIL       | varchar(25)   | NO   |     | NULL    |       |
| PHONE_NUMBER | varchar(20)   | YES  |     | NULL    |       |
| HIRE_DATE   | date          | NO   |     | NULL    |       |
| JOB_ID      | varchar(10)   | NO   | MUL | NULL    |       |
| SALARY      | decimal(8,2)  | YES  |     | NULL    |       |
| COMMISSION_PCT | decimal(2,2)  | YES  |     | NULL    |       |
| MANAGER_ID  | decimal(6,0)  | YES  |     | NULL    |       |
| DEPARTMENT_ID | decimal(4,0)  | YES  | MUL | NULL    |       |
+-----+-----+-----+-----+-----+-----+
11 rows in set (0.00 sec)
```

18. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, job\_id, salary and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion, and the foreign key column job\_id, referenced by the column job\_id of jobs table, can contain only those values which are exists in the jobs table. The InnoDB Engine have been used to create the tables. The

specialty of the statement is that, The ON DELETE CASCADE that lets you allow to delete records in the employees(child) table that refer to a record in the jobs(parent) table when the record in the parent table is deleted and the ON UPDATE RESTRICT actions reject any updates.

Assume that the structure of the table jobs and InnoDB Engine have been used to create the table jobs.

```
CREATE TABLE IF NOT EXISTS jobs (  
  JOB_ID integer NOT NULL UNIQUE PRIMARY KEY,  
  JOB_TITLE varchar(35) NOT NULL DEFAULT '',  
  MIN_SALARY decimal(6,0) DEFAULT 8000,  
  MAX_SALARY decimal(6,0) DEFAULT NULL  
)ENGINE=InnoDB;
```

Field	Type	Null	Key	Default	Extra
JOB_ID	int(11)	NO	PRI	NULL	
JOB_TITLE	varchar(35)	NO			
MIN_SALARY	decimal(6,0)	YES		8000	
MAX_SALARY	decimal(6,0)	YES		NULL	

```
mysql> create table tbl_jobas (  
-> job_id int(11) NOT NULL UNIQUE PRIMARY KEY,  
-> job_title varchar(35) NOT NULL default ' ',  
-> min_salary decimal(6,0) default '8000' ,  
-> max_salary decimal(6,0) default NULL  
-> )ENGINE=InnoDB;
```

Query OK, 0 rows affected, 1 warning (0.05 sec)

```
mysql> show tables;
```

```
+-----+  
| Tables_in_sal |  
+-----+  
| departments  |  
| employees    |  
| jobs         |  
| tbl_employees|  
| tbl_jobas    |  
| tbl_jobs     |  
+-----+
```

6 rows in set (0.00 sec)

```
mysql> desc tbl_jobas;
```

```
+-----+-----+-----+-----+-----+-----+  
| Field      | Type          | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| job_id     | int           | NO   | PRI | NULL    |       |  
| job_title  | varchar(35)   | NO   |     |         |       |  
| min_salary | decimal(6,0)  | YES  |     | 8000    |       |  
| max_salary | decimal(6,0)  | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+
```

4 rows in set (0.00 sec)

```

mysql> CREATE TABLE IF NOT EXISTS tbl_employeesa (
-> EMPLOYEE_ID decimal(6,0) NOT NULL PRIMARY KEY
-> FIRST_NAME varchar(20) DEFAULT NULL,
-> LAST_NAME varchar(25) NOT NULL,
-> JOB_ID INTEGER NOT NULL,
-> SALARY decimal(8,2) DEFAULT NULL,
-> FOREIGN KEY(JOB_ID)
-> REFERENCES tbl_jobs(JOB_ID)
-> ON DELETE CASCADE ON UPDATE RESTRICT
-> )ENGINE=InnoDB;
Query OK, 0 rows affected (0.02 sec)

mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs           |
| tbl_employees |
| tbl_employeesa |
| tbl_employees |
| tbl_jobas     |
| tbl_jobs      |
+-----+
8 rows in set (0.00 sec)

```

19. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, job\_id, salary and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion, and the foreign key column job\_id, referenced by the column job\_id of jobs table, can contain only those values which are exists in the jobs table. The InnoDB Engine have been used to create the tables. The specialty of the statement is that, The ON DELETE SET NULL action will set the foreign key column values in the child table(employees) to NULL when the record in the parent table(jobs) is deleted, with a condition that the foreign key column in the child table must accept NULL values and the ON UPDATE SET NULL action resets the values in the rows in the child table(employees) to NULL values when the rows in the parent table(jobs) are updated.

Assume that the structure of two table jobs and InnoDB Engine have been used to create the table jobs.

```
CREATE TABLE IF NOT EXISTS jobs (
```

```
JOB_ID integer NOT NULL UNIQUE PRIMARY KEY,  
JOB_TITLE varchar(35) NOT NULL DEFAULT '',  
MIN_SALARY decimal(6,0) DEFAULT 8000,  
MAX_SALARY decimal(6,0) DEFAULT NULL  
)ENGINE=InnoDB;
```

Field	Type	Null	Key	Default	Extra
JOB_ID	int(11)	NO	PRI	NULL	
JOB_TITLE	varchar(35)	NO			
MIN_SALARY	decimal(6,0)	YES		8000	
MAX_SALARY	decimal(6,0)	YES		NULL	

```
mysql> create table tbl_jobase (
  -> job_id integer NOT NULL UNIQUE PRIMARY KEY,
  -> job_title varchar(35) NOT NULL default ' ',
  -> min_salary decimal(6,0) default '8000',
  -> max_salary decimal(6,0) default NULL
  -> )ENGINE=InnoDB;
```

Query OK, 0 rows affected (0.03 sec)

```
mysql> show tables;
```

```
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs          |
| tbl_employeess|
| tbl_employeessa|
| tbl_employees |
| tbl_jobas     |
| tbl_jobase    |
| tbl_jobs      |
+-----+
```

9 rows in set (0.00 sec)

```
mysql> desc tbl_jobase;
```

Field	Type	Null	Key	Default	Extra
job_id	int	NO	PRI	NULL	
job_title	varchar(35)	NO			
min_salary	decimal(6,0)	YES		8000	
max_salary	decimal(6,0)	YES		NULL	

4 rows in set (0.00 sec)

```
mysql> CREATE TABLE IF NOT EXISTS employees (  
-> EMPLOYEE_ID decimal(6,0) NOT NULL PRIMARY KEY,  
-> FIRST_NAME varchar(20) DEFAULT NULL,  
-> LAST_NAME varchar(25) NOT NULL,  
-> JOB_ID INTEGER,  
-> SALARY decimal(8,2) DEFAULT NULL,  
-> FOREIGN KEY(JOB_ID)  
-> REFERENCES jobs(JOB_ID)  
-> ON DELETE SET NULL  
-> ON UPDATE SET NULL  
-> )ENGINE=InnoDB;
```

Query OK, 0 rows affected, 1 warning (0.01 sec)

```
mysql> show tables;
```

Tables_in_sal
departments
employees
jobs
tbl_employeess
tbl_employeessa
tbl_employees
tbl_jobas
tbl_jobase
tbl_jobs

9 rows in set (0.00 sec)



```
mysql> desc employees;
```

Field	Type	Null	Key	Default	Extra
EMPLOYEE_ID	decimal(6,0)	NO	PRI	NULL	
FIRST_NAME	varchar(20)	YES		NULL	
LAST_NAME	varchar(25)	NO		NULL	
EMAIL	varchar(25)	NO		NULL	
PHONE_NUMBER	varchar(20)	YES		NULL	
HIRE_DATE	date	NO		NULL	
JOB_ID	varchar(10)	NO	MUL	NULL	
SALARY	decimal(8,2)	YES		NULL	
COMMISSION_PCT	decimal(2,2)	YES		NULL	
MANAGER_ID	decimal(6,0)	YES		NULL	
DEPARTMENT_ID	decimal(4,0)	YES	MUL	NULL	

```
11 rows in set (0.00 sec)
```

20. Write a SQL statement to create a table employees including columns employee\_id, first\_name, last\_name, job\_id, salary and make sure that, the employee\_id column does not contain any duplicate value at the time of insertion, and the foreign key column job\_id, referenced by the column job\_id of jobs table, can contain only those values which are exists in the jobs table. The InnoDB Engine have been used to create the tables. The specialty of the statement is that, The ON DELETE NO ACTION and the ON UPDATE NO ACTION actions will reject the deletion and any updates.

Assume that the structure of two table jobs and InnoDB Engine have been used to create the table jobs.

```
CREATE TABLE IF NOT EXISTS jobs (
JOB_ID integer NOT NULL UNIQUE PRIMARY KEY,
JOB_TITLE varchar(35) NOT NULL DEFAULT '',
MIN_SALARY decimal(6,0) DEFAULT 8000,
MAX_SALARY decimal(6,0) DEFAULT NULL
)ENGINE=InnoDB;
```

```
+-----+-----+-----+-----+-----+
| Field  | Type   | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| JOB_ID | int(11) | NO   | PRI | NULL    |      |
| JOB_TITLE | varchar(35) | NO   |     |         |      |
```

MIN_SALARY	decimal(6,0)	YES	8000	
MAX_SALARY	decimal(6,0)	YES	NULL	

+-----+-----+-----+-----+-----+

```
mysql> create table tbl_jonds (
  -> job_id integer NOT NULL UNIQUE PRIMARY KEY,
  -> job_title varchar(35) NOT NULL default ' ',
  -> min_salary decimal(6,0) default '8000' ,
  -> max_salary decimal(6,0) default NULL
  -> )ENGINE=InnoDB;
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> show tables;
+-----+
| Tables_in_sal |
+-----+
| departments   |
| employees     |
| jobs          |
| tbl_employees |
| tbl_employeesa|
| tbl_employees |
| tbl_jobas     |
| tbl_jobbase   |
| tbl_jobs      |
| tbl_jonds     |
+-----+
10 rows in set (0.00 sec)
```

```
mysql> CREATE TABLE IF NOT EXISTS employees (  
-> EMPLOYEE_ID decimal(6,0) NOT NULL PRIMARY KEY,  
-> FIRST_NAME varchar(20) DEFAULT NULL,  
-> LAST_NAME varchar(25) NOT NULL,  
-> JOB_ID INTEGER NOT NULL,  
-> SALARY decimal(8,2) DEFAULT NULL,  
-> FOREIGN KEY(JOB_ID)  
-> REFERENCES jobs(JOB_ID)  
-> ON DELETE NO ACTION  
-> ON UPDATE NO ACTION  
-> )ENGINE=InnoDB;
```

Query OK, 0 rows affected, 1 warning (0.00 sec)

```
mysql> show tables;
```

```
+-----+  
| Tables_in_sal |  
+-----+  
| departments  |  
| employees    |  
| jobs         |  
| tbl_employees|  
| tbl_employeesa|  
| tbl_employees|  
| tbl_jobas    |  
| tbl_jobase   |  
| tbl_jobs     |  
| tbl_jonds    |  
+-----+
```

10 rows in set (0.00 sec)