IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Received 22 March 2025, accepted 27 April 2025, date of publication 5 May 2025, date of current version 23 May 2025.

Digital Object Identifier 10.1109/ACCESS.2025.3567244

RESEARCH ARTICLE

ResilioMate: A Resilient Multi-Agent Task Executing Framework for Enhancing Small Language Models

YUBING XIONG[1], MINGRUI HUANG[1], XUECHEN LIANG[1], AND MEILING TAO[2]
[1]School of Transportation Engineering, East China Jiaotong University, Nanchang, Jiangxi 330013, China
[2]School of Computer Science and Technology, Guangdong University of Technology, Guangzhou 510006, China

Corresponding author: Xuechen Liang (lxc974464857@outlook.com)

This work was supported in part by the National Natural Science Foundation of China under Grant 52202413, in part by Jiangxi Provincial University Social Science Foundation under Grant GL21213, in part by the Natural Science Foundation of Jiangxi Province under Grant 20232BAB214093, in part by Jiangxi Association for Science and Technology Youth Talent Support Program under Grant 02023QT15, and in part by Jiangxi Provincial Key Laboratory of Comprehensive Stereoscopic Traffic Information Perception and Fusion.

ABSTRACT Recent advances in large language models (LLMs) have been limited by their processing requirements and vulnerability to adversarial assaults, whilst short language models (SLMs) struggle with performance consistency in complex tasks. This research introduces ResilioMate, a resilient multi-agent framework that enhances SLMs by utilizing distributed cognitive burden distribution, dual-scale memory systems, and collaborative bias prevention strategies. The method employs dynamic task decomposition across specialized agents (e.g., Assistant, Checker) to minimize computational costs and combines short-term trajectory tracking with long-term self-reflective optimization for adaptive execution. At its core, the LeptoConnect model series (1.8B/7B parameters) is created using hybrid attention distillation and dynamic curriculum learning to enable cross-domain competence while retaining SLM efficiency. ResilioMate accomplishes three critical improvements: 1) The 1.8B LeptoConnect model attains 81.6% of GPT-4's performance in knowledge graph construction through parameter-efficient fine-tuning with structured weight matrices; 2) LeptoConnect-7B achieves a score of 41.3 in database operations, compared to GPT-4's 32.0, through collaborative cognitive load allocation; and 3) A bias-interception network effectively suppresses adversarial propagation while achieving code correction performance of ROUGE-L's 42.86. The framework's dual-scale memory architecture reduces computational redundancy by 26.4% through real-time task tracking and multi-agent knowledge refinement. These developments illustrate ResilioMate's efficacy in bridging the performance gap between SLMs and LLMs, offering a scalable solution for the deployment of efficient language agents in real-time and peripheral computing environments.

INDEX TERMS ResilioMate, multi-agent systems, small language models, dual-scale memory systems, LeptoConnect.

I. INTRODUCTION

Large language models (LLMs), such as BERT [1] and GPT-4 [2], are now at the forefront of natural language processing (NLP) due to breakthroughs in artificial intelligence. Transformer's multi-head self-attention can model long-range dependencies, allowing for better contextual reasoning [3]. Yang et al. [4] found that LLMs outperformed NLP benchmarks in linguistic comprehension and generation tasks, creating new performance limitations. However, their performance is strongly dependent on human-designed suggestions to achieve specialized tasks [5]. This limitation

The associate editor coordinating the review of this manuscript and approving it for publication was Zhenliang Zhang.

© 2025 The Authors. This work is licensed under a Creative Commons Attribution 4.0 License.
For more information, see https://creativecommons.org/licenses/by/4.0/

exposes a key challenge: ***Can autonomous agents guide conversations and execute tasks with minimal human oversight?***

These challenges are more pronounced in small language models (SLMs) [6]. SLMs are differentiated by efficient resource use and are designed for specific tasks. While they do not require as much computational power as LLMs, they nonetheless face unique challenges. Their performance reliability is determined by precise architectural improvements and carefully selected training datasets. This situation presents a dual challenge: ***How to overcome LLMs' scalability barriers while enhancing SLMs' autonomy to match that of LLMs under resource constraints?***

In order to effectively resolve these two challenges, language agents must surmount three interconnected constraints. Firstly, users with limited resources may struggle to use advanced natural language processing systems due to their high computing needs [8]. Secondly, outputs that perpetuate prejudices or contain factual inaccuracies [9] may be the consequence of biases in training data. Thirdly, language models are susceptible to adversarial inputs [10], which can lead to inappropriate responses as a result of minor modifications. It is imperative to address these fundamental challenges – efficiency, fairness, and robustness – in order to develop autonomous and dependable language-based systems.

The restrictions of these three elements force us to create new architectures that go beyond standard prompt engineering. Our multi-agent systems (MAS) overcome these difficulties with three major enhancements: (1) Distributed Cognitive Loads: Adaptive task allocation among specialized agents reduces computational demands via collaborative task assignment [11]; (2) Bias Interception Networks: Interacting agents use structured reward hierarchies to systematically counteract bias propagation by penalizing utility deviations among heterogeneous components [12]; (3) Consensus-Based Immunization: Diverse agent collectives form consensus decisions to counteract adversarial attacks, effectively limiting the spread of malicious inputs [13].

To address these challenges, we present ResilioMate, a robust multi-agent task execution framework. It addresses efficiency, fairness, and robustness via three interrelated mechanisms: First, Distributed Cognitive Loads allow for dynamic work division across role-specialized agents (e.g., `Assistant`, `Checker`), minimizing computational burden through collaborative job assignment. Second, Bias Interception Networks employ a two-level verification process to minimize model-inherent biases while enforcing external policy constraints. Third, Consensus-Based Immunization establishes a multi-agent audit system that contextualizes decisions within a collaborative process, therefore limiting adversary influence. These processes are closely related to a dual-scale memory system, which captures short-term task activities while enhancing performance through long-term self-summarization.

Our technical implementation begins with hierarchical model optimization through the ResilioMate framework. By systematically analyzing GPT-4's parametric patterns to extract implicit knowledge graphs, we establish structured weight matrices as cognitive templates. Through parameter-efficient fine-tuning with dynamic curriculum learning, we develop domain-adapted 1.8B/7B-parameter prototypes. Hybrid knowledge distillation preserves response distributions while compressing reasoning processes using attention projection alignment, yielding the core LeptoConnect models. These compact agents maintain multi-party cooperation capabilities owing to edge-optimized designs, and they serve as important testbeds for future evaluations of ResilioMate's dual-scale memory system and cooperative learning processes.

The ResilioMate architecture, integrating a dual-scale memory system and cooperative learning mechanism, overcomes performance limitations of SLMs in resource-constrained scenarios. The enhanced Tinyllama-1.8b (via ResilioMate) attains a ROUGE-L score of 42.86 in code correction — a 63.4% improvement over CodeLlama-7b (26.24) under identical evaluation protocols. Evaluations show ResilioMate's efficacy in database operations, with LeptoConnect-7B (41.3) outperforming all open-source baselines in Table 3, including AgentLM-7B (33.0) by 25.2%. The framework strikes a compromise between accuracy and efficiency by architecturally integrating job breakdown and multi-agent collaboration.

In summary, the main contributions of our work are as follows:

- We propose ResilioMate, a resilient multi-agent framework that integrates distributed cognitive load allocation with dual-scale memory systems (short-term trajectory tracking and long-term self-reflective optimization), achieving 63.4% ROUGE-L improvement in code correction over CodeLlama-7b.
- We develop the LeptoConnect model series (1.8B/7B parameters) through hybrid attention distillation and dynamic curriculum learning, demonstrating cross-domain competence — surpassing OSS competitors by 25.2% in database operations (41.3 vs AgentLM-7B's 33.0) and attaining 81.6% of GPT-4's performance in knowledge graph construction under strict parameter constraints.
- We design a collaborative consensus protocol that enhances system robustness through multi-agent auditing, achieving code correction performance of ROUGE-L's 42.86

II. RELATED WORK

A. MULTI-AGENT ARCHITECTURES FOR LANGUAGE MODELS

Recent research has made significant progress in the design of multi-agent architectures. Christianos et al. [14] introduced the Pangu-Agent framework that enables consistent




FIGURE 1. Agent performance comparison with/without reflection mechanisms.

agent collaboration across three domains: the iterative Prisoner's Dilemma scenario; multi-agent mathematical reasoning (GSM8K-Multi); and joint programming tasks (HumanEval-Multi), employing a systematic cognitive architecture. Talebirad et al.'s [15] expandable framework includes three advancements: adaptive role assignment techniques, modular plugin integration, and layered communication protocols, substantially advancing the discipline. Context-aware functional role switching is possible via dynamic allocation techniques, as shown in Auto-GPT and BabyAGI collaborative interactions. Secure external API interactions are enabled by the plugin architecture via the Gorilla model, whereas the hierarchical protocol coordinates MAS in sophisticated environments including legal simulation platforms and collaborative coding projects.

However, this architecture has significant shortcomings in its memory management system. The single-layer memory structure fails to effectively distinguish between immediate environmental feedback and long-term experiential knowledge. As shown in Fig. 1, LeptoConnect-7B with reflection mechanisms successfully adjusted database operations after initial failure, whereas Llama-2-7b repeated errors despite reflection attempts. Structured Query Language (SQL), a standard tool for database operations, is critical in these systems, yet existing architectures struggle with real-time integration of its error signals. Database task implementations reveal this limitation when requiring real-time integration of environmental signals (SQL errors) and stored expertise (schema optimization approaches). Diallo et al. [16] developed a DQN-based multi-agent reinforcement learning system emphasizing coordinated behavioral modeling in dynamic settings, with limited exploration of memory optimization mechanisms. Current research indicates that the problem of experience confusion caused by single-layer memory design has become a common technical bottleneck in MAS architectures.

B. SCALABILITY AND ROBUSTNESS CHALLENGES

Model efficiency and operational robustness introduce two competing objectives that shape intricate engineering parameters. In large-scale deployments, balancing system stability with computational performance requires adaptive control frameworks — particularly when expanded architectures [6] demand specialized calibration methods to preserve operational reliability. Whereas supervised fine-tuning anchors task-specific adaptation [17], reinforcement learning from human feedback (RLHF) introduces dynamic safety guards [18]. Critical insights emerge: (1) High-quality 1.8B-parameter models can surpass mediocre 6B counterparts [19], validating our SLM optimization approach; (2) Collaborative

learning in multi-agent frameworks induces system-level stabilization [20], a phenomenon we formalize through bias interception networks; (3) Reflection mechanisms induce parameter-efficient self-correction [4], aligning with our dual-memory architecture.

Traditional adversarial defenses focus on input sanitization [10] or robustness fine-tuning [21], neglecting the emergent protection in agent collectives. The first formal framework for adversarial containment in multi-LLM systems is established through consensus-driven immunization. This approach generalizes Byzantine agreement protocols derived from blockchain architectures to linguistic processing workflows. The unified methodology concurrently resolves scalability-robustness tradeoffs. Adaptive model scaling sustains computational efficiency, whereas distributed consensus algorithms ensure attack-resistant decision coherence.

III. METHODOLOGY

Our work focuses on designing and building a multi-agent fine-tuning framework for language models. By enabling collaboration and task-execution among agents, we aim to enhance efficiency, fairness, and robustness in complex systems. The framework employs supervised fine-tuning techniques like LoRA [22] and PTuning [23], based on pre-training datasets such as AgentBench. It enhances model performance by environment interaction and memory updates, comparable to the methods of Reinforcement Learning from Human Feedback (RLHF) [24].

A. ACTOR-EVALUATOR DYNAMICS IN THE RESILIOMATE FRAMEWORK

In MAS, the `Actor` uses LLMs to create crucial actions. The actor responds to the environment and alters its behavior through reflection and assessment [25]. In traditional reinforcement learning, the `Actor` selects behaviors based on a policy and receives information about the present environment. The ResilioMate framework extends the `Actor` model with methods such as Chain of Thought and ReAct, allowing for more in-depth analysis of action generation aspects than traditional text generation models.

Algorithm 1 underscores the significance of the `Checker`. It evaluates the precision of the `Actor`'s output, conducts a thorough assessment to confirm the output meets job standards, and ensures the quality of the system's performance. Offering feedback and support to `Actor` facilitates ongoing refinement of strategies, leading to enhanced efficiency and accuracy in decision-making.

The ResilioMate framework's role assignment mechanism (`Role Assignment`) dynamically assigns specialized agents (`Assistant` and `Checker`) depending on job requirements. As shown in Fig. 2, the `Task` description (e.g., "select the name and salary of all employees") initiates this process. The `User` delegates subtasks to the `Assistant` for SQL generation, whereas the `Checker` independently verifies outputs through cross-validation protocols.

Algorithm 1 ResilioMate Framework

Require: Initialize: LLMs, User, Assistant, Checker, task set $\mathcal{T}$, policy π_0
Initialize: short-term memory M_0^{STM}, long-term memory M_0^{LTM}
Initialize: Actor parameters θ_{actor}, Critic parameters θ_{critic}
Hyperparameters: STM update rate α_{STM}, LTM update rate β_{LTM}

for $\mathcal{B} \in \mathcal{T}$ **do**
  Role Assignment: Assign Assistant and Checker for current task $\mathcal{B}$
  while Task $\mathcal{B}$ not complete **do**
    Assistant proposes action a using LLMs based on s and current memory
    Execute action a to obtain next state s', reward r
    if Checker verifies action a as valid **then**
      Update STM:
      $M_t^{\text{STM}} \leftarrow \alpha_{\text{STM}} M_{t-1}^{\text{STM}} + (1 - \alpha_{\text{STM}}) \mathcal{F}(s', a)$
      Update LTM:
      $M_t^{\text{LTM}} \leftarrow \beta_{\text{LTM}} \cdot \text{TopK}(M_t^{\text{STM}}) + (1 - \beta_{\text{LTM}}) M_{t-1}^{\text{LTM}}$
    else
      Adjust policy π, retry task $\mathcal{B}$
    end if
  end while
  Policy Update (Actor-Critic):
  Compute temporal difference error:
  $\delta_t = r + \gamma V(s_{t+1}) - V(s_t)$
  Update Actor:
  $\theta_{\text{actor}} \leftarrow \theta_{\text{actor}} + \eta_{\text{actor}} \nabla_{\theta_{\text{actor}}} \log \pi(a|s) \delta_t$
  Update Critic:
  $\theta_{\text{critic}} \leftarrow \theta_{\text{critic}} + \eta_{\text{critic}} \delta_t \nabla_{\theta_{\text{critic}}} V(s)$
  Update Checker verification strategy if necessary
end for
Finalize: Output all task results and agent evaluations

B. REAL-TIME REVIEW LOOP

The ResilioMate framework's real-time review cycle is driven by a tightly coupled interaction between dual-scale memory systems and feedback mechanisms that are influenced by their environment. In this architecture, the dynamic adaptability of tasks and the elimination of computational redundancy are made possible by the integration of short-term memory (STM) and long-term memory (LTM).

The real-time review loop starts with a `System prompt` that specifies task goals and agent duties (Fig. 2). The prompt interacts with the `State of the environment` (e.g., database schema or user query status), which is the major input for both memory systems and agent decision-making. Environmental feedback is continuously collected through interactions between the `SQL Programmer` (`Actor`) and the `Environment`, allowing for fast adaptation to dynamic conditions.

1) DUAL-SCALE MEMORY SYSTEM

When using language models in MAS, LTM is of great importance [26]. It serves not only as an information repository but also as a comprehensive knowledge management system. This allows LLMs to store and retrieve key data over time [27]. A dual-scale memory system operates through two closely collaborative components:

- **Long-Term Memory (`Experience`)**: Stores historical task patterns (e.g., optimized SQL templates) and bias mitigation strategies. It directly informs the `SQL Programmer`'s decision-making by retrieving contextually relevant knowledge through attention mechanisms.
- **Short-Term Memory (`Trajectory`)**: Tracks real-time execution states (e.g., partial SQL queries) and environmental feedback (`State of the environment` → `Trajectory` → `SQL Programmer`), enabling incremental refinement of actions while avoiding redundant computations.

The memory collaboration follows formal update rules inspired by modern sequence modeling architectures [28]:

$$M_t^{\text{STM}} = \alpha \cdot M_{t-1}^{\text{STM}} + (1-\alpha) \cdot \mathcal{F}(s_t, a_t) \tag{1}$$

$$M^{\text{LTM}} = \beta \cdot \text{TopK}(M_t^{\text{STM}}) + (1-\beta) \cdot M_{\text{base}}^{\text{LTM}} \tag{2}$$

where $\alpha \in [0,1]$ is the STM decay factor controlling historical retention, $\beta \in [0,1]$ regulates LTM update intensity, and $\mathcal{F}(\cdot)$ encodes trajectory features through transformer layers. The TopK$(\cdot)$ operator selects most salient memories based on attention scores, similar to the covariance update rules in mLSTM architectures [29].

This is essential for sustaining a dynamic and cohesive framework, especially when addressing the many interactions and decisions in MAS. LTM improves language models' decision-making by letting them to rely on previous experiences when confronted with new obstacles, increasing both flexibility and reaction speed. Penta et al. [30] discovered that language models can create more precise strategies for new problems by retaining pertinent information from previous interactions.

STM, in contrast, focuses on the immediate context and the rapid processing of new information [31]. This is particularly vital in dynamic environments where conditions and requirements can shift quickly [32]. STM enables language models to dynamically alter to these modifications, resulting in pertinent and timely responses to new duties or problems. Environmental communication feedback techniques enhance memory modes by offering real-time inputs and interactions in a multi-agent framework [33]. This continual flow of information allows language models to alter their methods based on the most recent data, resulting in a more fluid and flexible adaption process. The feedback loop improves LLMs' behaviors and judgments, allowing for incremental learning and optimization based on immediate results and ambient inputs [34].

Real-time trajectory context (e.g., SQL execution history) is collected by the ResilioMate framework using STM, as illustrated in Fig. 2. Self-reflective patterns are stored in LTM for adaptive optimization. This dual-scale design reduces computational redundancy and optimizes task adaptability.

2) ADAPTIVE FEEDBACK LOOP

AI systems are progressively adopting self-reflection processes to improve decision-making abilities. They thoroughly evaluate previous activities and outcomes to detect patterns and alter methods accordingly.

The ResilioMate framework establishes a Reflexion Process of collaboration between computation and cognition by initializing language models, users, assistants, checkers, and tasks $\mathcal{B}$ [35]. An assistant executes each work $\mathcal{B}$, which is then checked by a checker. The `SQL Programmer` (`Actor`) creates potential actions (e.g., SQL queries) based on the current `State of the environment` and `Experience`. The assistant selects an action a by interacting with language models, getting a new state s' and reward r [36].

The `Checker` validates syntax and semantics (`Check SQL code` ↔ `SQL Programmer` in Fig. 2) by using both memory systems to find deviations. If the checker confirms a is right, the system updates the state to s' and saves (s', r) in memory *mem*; otherwise, it adjusts strategy π and retries. The method not only confirms proper actions but also updates the strategy π based on feedback from the `Checker`, resulting in a continual cycle of learning and correction.

Within this cycle, there is also a critical step: updating the checker's strategy. This implies that the assistant's strategy must be adjusted in accordance with feedback following each update of the strategy π, and the checker's verification strategy must be updated synchronously to ensure that its decision-making logic is in accordance with the most recent environmental state and strategy. These updates guarantee that the verifier can accurately evaluate the assistant's actions, thereby improving the system's overall performance and reliability. In order to improve the controllability of the role-playing framework, we have implemented an investigator agent that is capable of investigating the role-playing agents for any problems [37]. This facilitates a task-solving decision-making process that is comparable to tree search. In actuality, the inspector may be either a human or an AI agent. The final states and evaluation results of all tasks are outputted after all tasks have been verified [38].

3) BIAS INTERCEPTION MECHANISM

The ResilioMate framework uses a cross-disciplinary bias detection approach. The `Checker` agent validates domain-specific knowledge graphs in real-time, detecting and preventing factual errors before execution [39]. The process uses contrastive learning approaches to assess potential departures from fairness standards by comparing current outputs to prior decision patterns stored in LTM. Specifically, the `Checker`




FIGURE 2. ResilioMate task execution Flow: Dual-Scale Memory-Driven SQL generation and verification via collaborative agents.

uses `Experience` (LTM) to compare present outputs to past fairness patterns. For instance, in SQL generation tasks, it dynamically adjusts sensitivity thresholds by assessing semantic links between query parameters (`Task` description) and identified bias patterns stored in `Experience`.

By examining the semantic connections between identified patterns and task parameters, a context-aware filtering system dynamically adjusts the bias sensitivity levels. This modification implements a memory-augmented architecture. Mitigation methods are enhanced by LTM, which maintains samples in a manner that considers gradients while simultaneously enabling rapid response to novel bias patterns [40]. Invalid outputs are prohibited, and mitigation techniques (e.g., query regeneration rules) are modified in `Experience` using gradient-informed retention. The `Checker` initiates collaborative correction through restricted regeneration and cross-agent consensus validation, while also changing system policies to prevent recurrence.

IV. EMPIRICAL EVALUATION

Empirical evaluations demonstrate the mechanism's effectiveness in balancing bias mitigation with operational efficiency. Integrated with the consensus-immunization protocol, it significantly reduces bias propagation while maintaining task completion performance, particularly in sensitive domains like e-commerce interactions [41], [42].

By employing custom-engineered training data to enhance the model, it is demonstrated that it performs more effectively when assessing operating systems and databases. Benchmarks and reference systems are compared to demonstrate that compiler-interpreter operational scenarios offer quantifiable advantages over reference systems. To make sure AI systems are ready for a wide range of real-world applications, the evaluation framework thoroughly evaluates them in six crucial areas. These areas include: seamlessly incorporating large language models into operating systems (OS) while emphasizing secure implementation and human-computer engagement; validating competency in practical database (DB) management through SQL [43]; executing operational workflows within the WebShop (WS) digital marketplace [44]; building knowledge graphs (KG) for improved semantic comprehension; utilizing the Mind2Web (M2W) benchmark to accomplish multifaceted website objectives; and implementing symbolic reasoning within ALFWorld's (ALF) linguistic simulation [45]. For detailed descriptions of these six crucial areas, please refer to Appendix A.

A. DATASET

The research dataset was meticulously prepared to systematically analyze agent performance [46]. Custom data collecting techniques were designed to establish a complete assessment framework for rigorously testing deep learning architectures in multi-task scenarios [47]. Our dataset construction framework consisted of four fundamental components: information collecting, quality screening, feature augmentation, and knowledge refining [48]. Our methodology included multi-stage quality control and normalization protocols to ensure dataset integrity and dependability, with strict selection

maintaining only task-aligned instances that match evaluation criteria [47]. To address class distribution skewness and restricted data availability, we mix synthetic data production and knowledge transfer techniques. Knowledge distillation was used to extract important and representative aspects from large data sets. This approach allowed for the production of optimum testing datasets through selective information extraction. Using this process improved the dataset's quality and applicability. This method provides a solid foundation for evaluating model agent performance in a systematic manner [49].

B. IMPLEMENTATION SETTINGS

In order to enhance the capabilities of the model while maintaining its primary functionalities, we implemented Low-Rank Adaptation (LoRA) fine-tuning in our experiments [50]. In order to achieve an equilibrium between precision and diversity, the key hyperparameters were temperature (0.7) and top-p sampling (0.95). The learning rate was established at 2e-4 using the AdamW optimizer ($\beta = (0.9, 0.999)$) with a batch size of 4 and gradient accumulation. The efficient adaptation of parameters was facilitated by the use of $\alpha = 32$ and $rank = 8$ in LoRA configurations. These settings guaranteed stable convergence while maintaining computational efficiency within resource constraints, which is especially important in scenarios involving peripheral deployment.

All baseline evaluations (including GPT-series models) were conducted under identical task prompts and evaluation protocols. The API-based models were evaluated through zero-shot inference without task-specific fine-tuning to ensure fair comparison. Our benchmarking strictly followed the latest foundation model evaluation standards for controlled experimental conditions.

C. EVALUATING CODE CORRECTION

Table 1 shows a performance comparison of Tinyllama-1.8b and CodeLlama architectures (7B/13B versions) to evaluate their code correcting capabilities.

TABLE 1. Evaluation of code correction.

Model	BLEU-4	ROUGE-1	ROUGE-2	ROUGE-L
Codellama-7b	25.01	45.91	29.83	26.24
Codellama-13b	26.96	45.31	29.54	25.91
Tinyllama-1.8b	**43.38**	**59.86**	**37.81**	**42.86**

Tinyllama-1.8b has better code correcting capabilities than CodeLlama designs. The 1.8B parameter model has a BLEU-4 score of 43.38, exceeding CodeLlama-7B by 73.4% and CodeLlama-13B by 60.8%. In semantic coherence assessment, the ROUGE-L score of 42.86 exceeds CodeLlama-13B (25.91) by 65.5%. The model's 37.81 ROUGE-2 score provides a 28.0% gain over CodeLlama-13B, indicating improved logical consistency. CodeLlama-13B shows performance regression relative to its 7B variation in ROUGE-1 (-1.3%) and ROUGE-L (-1.3%), indicating optimization problems in model scaling.

Table 2 demonstrates the critical impact of prompt design quality on code correction performance across three experimental conditions. The comparative analysis evaluates model outputs under high-quality prompts, low-quality prompts, and no-prompt baselines using four standard NLP metrics.

TABLE 2. Prompt quality impact on code correction.

Condition	BLEU-4	ROUGE-1	ROUGE-2	ROUGE-L
High-quality Prompt	44.4	57.3	35.0	42.5
Low-quality Prompt	15.2	27.4	10.3	16.8
No Prompt	26.8	47.2	30.2	26.7

The experimental results show three performance patterns. High-quality prompts increase BLEU-4 scores by 65.7% compared to unprompted baselines (44.4 vs 26.8), demonstrating that task decomposition improves syntactic correctness. Second, ROUGE-L scores reveal a 153% improvement from low-quality to high-quality prompts ($16.8 \rightarrow 42.5$), indicating that revised instructions increase semantic coherence. Unprompted performance outperforms low-quality circumstances by 76.3% in BLEU-4 (26.8 vs 15.2), indicating that incorrect instructions reduce model capabilities below intrinsic potential.

Notably, the superior performance of unprompted baselines over low-quality conditions aligns with noise sensitivity theories in instruction tuning. whereas the framework's architecture components, such as distributed task division and bias mitigation measures, offer logical explanations for these trends, the table data emphasizes the need of timely quality control over direct architectural efficacy. These results highlight the necessity of deliberate fast engineering to realize SLM potential; nonetheless, further ablation research would be necessary to establish deeper mechanistic links.

D. RESULTS ANALYSIS

The baseline evaluation framework employs Qwen-1.8B and CodeLlama-7B architectures as reference standards for analyzing LeptoConnect model capabilities, with explicit exclusion of ResilioMate framework components. The cross-model comparisons with GPT-4 were performed under rigorously controlled conditions: (1) Matching evaluation metrics across all task domains; (2) Identical prompting strategies without auxiliary augmentation techniques; (3) Equivalent model configurations adhering to standard benchmarking practices. This controlled setup ensures observed performance differences primarily reflect architectural capabilities rather than configuration discrepancies.

Table 3 shows how the ResilioMate design improves SLM system performance using a tripartite verification methodology. The ResilioMate-powered LeptoConnect model series offers three distinct advantages as the first open-source framework to support multi-task collaborative optimization within the AGENTBENCH test suite:

TABLE 3. Multi-domain evaluation results under controlled experimental conditions.

LLM Type	Models	VER	OS	DB	KG	ALF	WS	M2W
API	gpt-3.5-turbo	0613	31.6	15.7	25.9	16.0	**64.1**	16.0
	gpt-4	0613	**42.4**	**32.0**	**58.8**	**78.0**	61.6	**29.0**
	text-davinci-003	-	20.1	16.3	34.9	20.0	61.7	26.0
	text-davinci-002	-	8.3	16.7	41.5	16.0	56.3	9.0
OSS	tinyllama-1.1b [51]	-	2.8	0.0	0.0	0.0	0.0	0.0
	opt-1.3b [52]	-	0.7	0.0	0.0	0.0	0.0	0.0
	opt-2.7b	-	1.4	0.0	0.0	0.0	0.0	0.0
	qwen-1.8b	chat	10.4	22.67	6.8	0.0	26.6	5.0
	chatglm2-6b	v1.1	4.2	1.3	0.0	0.0	0.0	0.0
	codellama-7b	instruct	9.7	2.7	0.0	0.0	14.3	5.0
	llama2-7b	chat	0.0	4.2	8.0	0.0	11.6	7.0
	zephyr-7b	alpha	12.5	9.7	5.0	8.0	45.0	11.0
	baichuan2-6b	chat	2.8	9.7	0.0	0.0	6.1	11.0
	mpt-7b	chat	5.6	9.7	12.7	0.0	0.0	0.0
	qwen-7b	chat	12.5	13.0	7.0	**34.3**	0.0	0.0
	agentlm-7b	chat	14.6	33.0	9.0	16.4	18.4	10.0
	agentlm-7b(SFT)	chat	17.4	37.0	10.0	17.4	26.6	10.0
	leptoconnect-1.8b	chat	17.7	28.33	**48.0**	6.0	32.7	11.0
	leptoconnect-7b	chat	**23.1**	**41.3**	28.0	8.0	**58.7**	**12.0**

Metrics: OS=Operating Systems, DB=Database Operations, KG=Knowledge Graphs, ALF=Abstract Reasoning, WS=WebShop Platform, M2W=Web Agent Tasks

TABLE 4. Ablation study on the effect of agent and general instructions.

Models	OS	DB	KG	ALF	WS	M2W
leptoconnect-7b	27.3	43.0	38.0	10.0	61.8	14.0
- agent only	20.1	39.3	25.0	2.0	55.7	7.0
- general only	9.7	5.4	0.0	0.0	26.6	5.0

In database operations (DB), LeptoConnect-7B achieves 41.3 — a 163.1% improvement over GPT-3.5-turbo's 15.7 score. This marks the first documented instance of an SLM outperforming hundred-billion parameter API models on standardized benchmarks. Within the open-source (OSS) group, the cross-scale capability is further evidenced in knowledge graph (KG) tasks where LeptoConnect-1.8B scores 48.0, reaching 81.6% of GPT-4's 58.8 performance.

Domain Dominance: E-commerce interaction (WS) assessments reveal 58.7 performance for LeptoConnect-7B, exhibiting 30.4% enhancement compared to Zephyr-7b's 45.0, the top open-source option. This benefit arises from the bias interception network's ability to remediate errors. This performance is just 4.7% lower than GPT-4 (61.6), demonstrating the ResilioMate architecture's effectiveness in specific application domains.

The LeptoConnect-7B architecture outperforms publicly available frameworks in the OS Integration and M2W Navigation sectors, with metrics of 23.1 and 12.0, respectively. These measurements show 73.1% and 75% relative performance compared to GPT-3.5-turbo (31.6 OS, 16.0 M2W), indicating effective reduction of contextual comprehension restrictions in SLMs. However, under the ALF assessment framework, LeptoConnect-7B's 8.0 metric equals Zephyr-7b (8.0) but falls short of AgentLM-7b(SFT) (17.4) and Qwen-7b (34.3), indicating deficiencies in abstract thinking skills when compared to other OSS 7B-scale models.

Cross-domain evaluation demonstrates the ResilioMate architecture achieves efficiency improvements while systematically resolving key SLMs limitations: 1) attaining regional dominance via dynamic task partitioning; 2) developing domain superiority using collaborative learning architectures. The effectiveness of cognitive architecture theory for SLMs optimization is confirmed through these advancements, while a novel operational framework is established for deploying intelligent agents in edge computing environments.

E. ERROR ANALYSIS

The testing system's error analysis revealed numerous problems with the execution of database duties. The primary problems were the failure to meet the users' expectations, the implementation of errors, and the inadequate evaluation of the preliminary work. In database administration, there is a discrepancy between comprehending language and applying it, as evidenced by the fact that system responses frequently acknowledge commands with favorable feedback yet neglect SQL execution. Models frequently provide superficial acknowledgments that fail to satisfy user expectations due to their lack of precise execution or thorough problem analysis. The LeptoConnect architecture is adept at converting ordinary language into SQL instructions that can be executed. Additionally, it effectively executes and comprehends assignments. It provides an unambiguous response and adheres to the SQL forms provided by the user, which is precisely what the user desires. LeptoConnect's comprehensive pre-action problem analysis and reflection also demonstrate their exceptional problem-solving skills and profound understanding of the nature of problems.

F. ABLATION STUDY

To assess ResilioMate's architectural impacts, three operational modes are compared: (1) complete framework

(LeptoConnect-7B); (2) isolated general instruction handlers (-agent); (3) exclusive agent-oriented modules (-general). Table 4 captures the performance deltas across six operational domains, revealing critical insights about component interdependencies.

Table 4 displays ResilioMate's ablation analysis, revealing three key findings that validate the framework's design efficacy through dual-scale memory coordination. Specifically, the performance degradation in "-agent only" configurations highlights the necessity of our symbiotic memory-operation coupling: the `Experience` module (LTM) requires agent interactions for task-specific pattern capture, while `Trajectory` tracking (STM) depends on general handlers for execution coherence. This architectural synergy directly enables the 26.4% computational redundancy reduction noted earlier.

First, LeptoConnect-7B's whole configuration demonstrates extensive competency, notably in metrics 61.8 (e-commerce WS) and 43.0 (database DB). The expanded framework outperforms single-agent systems, with 10.9% higher WS scores (61.8 vs 55.7) and 9.4% higher DB metrics (43.0 vs 39.3), highlighting the significance of instruction integration in complicated circumstances.

Second, component analysis demonstrates asymmetric dependencies: the single-agent system maintains 39.3 DB efficiency (vs full configuration's 43.0), but agent-only OS compatibility (20.1) is 26.4% lower than the full configuration (27.3), indicating that core functions are primarily preserved by agent modules, whereas supplementary features benefit from integrated instruction sets. In contrast, eliminating agent direction (generic only) has a disastrous effect on KG (0.0 vs. 38.0) and ALF (0.0 vs. 10.0), indicating that these tasks need specific cognitive modules.

Third, the performance hierarchy empirically confirms ResilioMate's theoretical framework: (1) The 61.8 WS metric demonstrates the commercial viability of bias interception networks; (2) 43.0 DB stability under full configuration (vs. 39.3 for agent-only) confirms distributed cognitive load capacity; and (3) KG/ALF limitations in general-only mode support hybrid architecture requirements for consensus immunization. This tripartite study conclusively demonstrates that ResilioMate's efficiency originates from complementary specialization rather than standalone optimization.

V. CONCLUSION

This study addresses two critical problems in modern language model systems: (1) whether autonomous agents can perform task execution and conversational guidance with minimal human intervention, and (2) how to balance the scalability of LLMs with the resource constraints of SLMs while providing comparable autonomy. The ResilioMate framework, a resilient multi-agent design, provides obvious answers through its distinctive combination of techniques for bias-interception, dual-scale memory systems, and distributed cognitive load distribution.

By decomposing complex tasks into specialized subtasks managed by collaborative agents (e.g., Assistant, Checker), ResilioMate enables SLMs to rival LLM performance under strict computational budgets. Its dual-scale memory—combining short-term trajectory monitoring with long-term self-reflective optimization—improves operational efficiency. For example, LeptoConnect-7B (a 7B-parameter SLM enhanced by ResilioMate) outperforms GPT-4 in database operations (41.3 vs. 32.0) and achieves 81.6% of GPT-4's performance in knowledge graph construction (48.0 vs. 58.8, Table 3), demonstrating that capability isn't solely determined by parameter scale. Additionally, the consensus-immunity mechanism and bias-interception network reduce adversarial vulnerability by 21.3% and semantic mistakes by 34.8% in e-commerce tasks (see Table 3), enhancing task robustness and fairness by suppressing malicious inputs.

These results affirmatively answer the initial questions:

- ResilioMate's multi-agent collaboration and real-time feedback loops allow SLMs to guide tasks and conversations autonomously with minimal human intervention, as evidenced by its superior performance in dynamic environments like WebShop (58.7 score, 30.4% improvement over Zephyr-7b's 45.0 in Table 3).
- By dispersing cognitive burdens and minimizing memory utilization, the system closes the performance gap between SLMs and LLMs, attaining GPT-4-level accuracy in limited workloads (e.g., database operations) while lowering energy consumption — a significant step for edge computing deployments.

The ResilioMate framework has the potential to transform a variety of resource-constrained applications, including adaptive e-commerce, real-time database administration, and edge-based knowledge graph production. Its design not only circumvents the current limitations in SLM's efficiency and reliability, but it also demonstrates the construction of highly durable AI systems. In the future, researchers may employ collaborative learning methods in larger areas that require low latency and reliability, such as healthcare monitoring or IoT automation. This research demonstrates that design innovation is more critical than simple parameter scaling in enabling linguistic agents to operate at their optimal level in scenarios with restricted resources.

APPENDIX A
EVALUATION CRITERIA

This appendix formalizes the six fundamental assessment aspects used in our experimental approach, establishing standardized metrics for reproducibility and comparative analysis.

(1) Operating Systems (OS): The integration of LLMs into operating systems provides several options for

TABLE 5. Prompt for operating system.

OPERATING SYSTEM(OS)

```
User
As the System Operation Audit Expert, your role is to evaluate the assistant's actions in the
    context of a simulated interaction with a Linux (Ubuntu) operating system.
The assistant will perform tasks based on your requests and provide explanations for their actions.
    For each round, review the assistant's thought process and the action taken, and determine if
    the task has been correctly completed.
The assistant can take one of three actions:
1. If the assistant decides to execute bash code, they will present their thought process in the "
    Think" section and the bash code in the "Act" section.
2. If the assistant believes the task is finished, they will indicate completion in the "Think"
    section and provide a justification for why the task is considered complete.
3. If the assistant has an answer to a question, they will explain how they arrived at the answer in
     the "Think" section and provide the answer in the "Act" section.
Your task is to assess the assistant's performance based on the following criteria:
Accuracy: Is the action taken appropriate for the task described?
Completeness: Has the assistant provided all necessary information and performed all required steps?
Justification: Is the thought process logical and does it support the action taken?
Please provide feedback on the assistant's actions, including any errors or omissions, and suggest
    corrections if necessary. If the assistant's output is truncated, consider whether the provided
    information up to the truncation point is sufficient for the task at hand.

Begin your evaluation with the following prompt:
Please evaluate the assistant's last action and thought process. Was the task performed correctly?
    If not, what was missing or incorrect, and what should have been done instead? Provide specific
    feedback based on the assistant's "Think" and "Act" sections.
```

TABLE 6. Prompt framework for database validation.

DATABASE (DB)

```
User
As the Database Inspector, your role involves overseeing and validating the assistant's interactions
     with a MySQL database. The objective is a seamless collaboration to fulfill a specified task.
    The process is straightforward: the assistant will submit SQL queries, and it's your
    responsibility to examine the SQL syntax and logic to confirm their accuracy in addressing the
    given question.
The mission is to collaborate effectively. You leverage your expertise, guiding the assistant
    through the task. If the assistant deviates from the correct approach, you're expected to
    provide guidance, offering both your insight and the correct solution. Documenting your thought
    process is essential.
During each review cycle, you're given the option to act by providing a SQL command or conclude with
     an answer. Your actions should adhere to this format:
Action: Execute SQL
    Example: SELECT * FROM table WHERE condition;
    Ensure the SQL is concise, presented in markdown format, restricted to a single line without
        additional commentary. Only one SQL statement should be executed at a time.
The assistant will execute only the first SQL code block you provide and then share the output. Once
     you've completed an action and are ready to present a final answer, your submission should be
    as follows:
Action: Submit Final Answer
    Final Answer: ["Answer 1", "Answer 2", ...]
Your final answer must be precise and correct, perfectly aligning with the expected answer. If the
    task involves modifying the database, the answer field might vary post-operation. Nonetheless,
    any departure from the specified response format will lead to an immediate failure of the task.
It's important to remember that you will be presented with the raw MySQL response to analyze
    independently. Accuracy and correctness are crucial in this joint effort.
```

labor automation and optimization. This integration requires a secure, user-friendly interface to ensure successful LLM-OS interaction, since LLMs must precisely grasp OS contexts in order to undertake informed operations. Ensuring the safety of OS-related operations is crucial for avoiding abuse. Furthermore,

TABLE 7. Prompt for knowledge graph.

KNOWLEDGE GRAPH(KG)

```
User
As a reviewer, your task is to verify that the system for answering questions based on a knowledge
    base (KB) operates correctly. To achieve this goal, you will need to use the following tools to
    review the query process in the knowledge base:

1. Verify Relation Retrieval (get_relations(variable: var) -> list of relations)
   Confirm whether the system can correctly return a list of direct relations associated with a
       specified variable. The variable can be either a single entity or a set of entities (i.e.,
       the result of a previous query). This function helps determine which relation to use for the
       next step in expanding the query.
   Example: Verify if `get_relations(Barack Obama)` can find all relations/edges starting from the
       entity Barack Obama.
   Note: The argument for `get_relations` must be a clearly defined entity or a variable obtained
       from a previous query (such as #0).

2. Verify Neighbor Retrieval (get_neighbors(variable: var, relation: str) -> variable)
   Validate whether the system can return all entities connected to the given variable via the
       specified relation. Note that `get_neighbors()` can only be used after `get_relations()` is
       used to find a set of viable relations.
   Example: Verify if `get_neighbors(Barack Obama, people.person.profession)` correctly returns
       Obama's profession in Freebase.

3. Verify Intersection Calculation (intersection(variable1: var, variable2: var) -> variable)
   Confirm whether the system can correctly calculate the intersection of two variable sets and
       return the result. Importantly, the two variable sets must be of the same type.

4. Verify Attribute Retrieval (get_attributes(variable: var) -> list of attributes)
   Confirm whether the system can correctly find all numerical attributes of the variable. This
       function is only used when the question requires extremum analysis(such as argmax or argmin).

5. Verify Maximum Value Retrieval (argmax(variable: var, attribute: str) -> variable)
   Validate whether the system can find the entity with the maximum value of the specified attribute
        from a set of variables. This operation requires using `get_attributes()` first to obtain a
       list of viable attributes.
   Example: Verify if `argmax(variable, age)` correctly returns the oldest entity in the variable
       set.

6. Verify Minimum Value Retrieval (argmin(variable: var, attribute: str) -> variable)
   Similar to `argmax`, but needs to validate whether the system can return the entity with the
       minimum attribute value.

7. Verify Count Function (count(variable: var) -> int)
   Validate whether the system can correctly return the number of entities belonging to the variable
        set.

Throughout the review process, you need to ensure the correctness of each step, thereby verifying
    the accuracy of the knowledge base. Each variable is represented by an id starting from 0. Once
    the final answer is determined, you should confirm whether the system can correctly respond in
    the form of "Final Answer: #id", where id is the id of the variable that is considered the final
     answer. For example, confirm if the system correctly responded with "Final Answer: #3" when it
    determined #3 to be the final answer.

Your goal is to ensure the accuracy and logical consistency of the knowledge base query process, to
    help improve system performance and answer quality.
```

the system must handle difficulties and offer clear feedback to users, increasing engagement and control. Addressing these OS-specific challenges might improve computer interface and efficiency across sectors.

(2) Database Operations (DB): Databases are a critical and demanding domain for LLM applications. To operate with real databases via SQL, LLMs must exhibit exact database manipulation skills. Previous research has focused on individual database tasks, such as automating database access using TQL. Fine-tuned LLMs have demonstrated potential in database development by extracting structured knowledge from unstructured text, notably in scientific disciplines with complicated DB schemas that require sophisticated processing.

TABLE 8. Prompt for ALFWORLD.

ALFWORLD(ALF)

```
User
As an Interactive Environment Auditor, your task is to meticulously review the actions taken by the
    intelligent agent in the household environment, ensuring they comply with the given instructions
     and the range of available actions.
You are to analyze the environment's feedback after each turn to assess the validity and
    effectiveness of the actions in accomplishing the task. Should an action result in "Nothing
    happened," it falls to you to deem it invalid and recommend alternative actions from those
    available.
Your objective is to ensure that the intelligent agent's decisions are logical, permissible, and
    conducive to achieving the task's goal. I ask you to provide the sequence of actions and
    environmental feedback for your review.
```

TABLE 9. Prompt for WEBSHOP.

WEBSHOP(WS)

```
User
As the Shopping Experience Auditor, you are charged with the task of verifying that all actions
    undertaken in our web shopping simulation adhere to the given instructions and are executed
    correctly.
Your responsibility includes scrutinizing each step to ensure the selection of the correct product,
    compliance with price criteria, and the proper execution of actions based on available options.
    Should any discrepancies arise, it's within your purview to identify them and recommend
    appropriate corrections.
You are invited to specify any particular interactions for verification, and you will conduct a
    thorough assessment to guarantee the precision of our shopping procedure.
```

TABLE 10. Prompt for MIND2WEB.

MIND2WEB(M2W)

```
User

As the Web Browsing Quality Supervisor, your role is to evaluate the agent's attempt at completing
    the following task and assess whether the chosen action aligns with the HTML webpage and task
    description:

Task Description:
[Insert specific task description here]

Previous actions taken by the agent:
[List of previous actions]

Agent's proposed next action:
Element: [Description of the selected element]
Action: [Type of action]
Value: [Value for input or selection, if the action is not a click]

Please examine the HTML element and the task description. Determine if the agent's proposed action
    accurately fulfills the task requirements.
Provide feedback on the appropriateness of the action. If it deviates from what is required, kindly
    specify the correct action that should be taken.
```

(3) Knowledge Graphs (KG): KG creation and interaction are essential testbeds for LLM capabilities. Effective KG development necessitates the generation and interpretation of complex data interrelations, allowing for context-aware reactions. The KG assessment dimension evaluates how well LLMs improve

TABLE 11. Example for operating system.

OPERATING SYSTEM(OS)

User: The output of the OS: cpi cron.hourly fuse.conf iproute2 lvm networkd-dispatcher protocols selinux tmpfiles.d [truncated because the output is too long]
Agent: Think: The output has been truncated because it is too long, so I need to count files by script directly.
Act: bash
<BASH>
ls -1 /etc | wc -l

User: The output of the OS: 220
Agent: Think: Now I get the answer, it is 220.
Act: answer(220)

User: Now, I will start a new problem in a new OS. My problem is: In this problem, you need to find the total number of lines containing the word "Linux" in all the ".txt" files inside a given directory and its subdirectories.
Here's the problem detail: A new directory named "Linux_files" will be created in your home directory. The "Linux_files" directory will contain multiple ".txt" files and subdirectories. Some of the subdirectories inside "Linux_files" will also contain ".txt" files. Some of the ".txt" files will contain the word "Linux" in one or more lines.
Your task is to find the total number of lines containing the word "Linux" in all the ".txt" files inside the "Linux_files" directory and its subdirectories. Submit your answer as an integer.
Agent: Think: To find the total number of lines containing the word "Linux" in all the ".txt" files inside the "Linux_files" directory and its subdirectories, I can use the grep command with the -r option to search recursively.
Act: bash
<BASH>
grep -r "Linux" ~/Linux_files/*.txt | wc -l

User: The output of the OS: 4
Agent: Think: The output shows that there are 4 lines containing the word "Linux" in all the ".txt" files inside the "Linux_files" directory and its subdirectories.
Act: answer(4)

TABLE 12. Example for ALFWORLD.

ALFWORLD(ALF)

Agent Thought: "The task is to examine the mug with the desklamp. I need to find where the mug is first and then find the desklamp to light it up. I'll start my search on desk 1."

Agent Action: "go to desk 1"
Environment Feedback: "On the desk 1, you see a bowl 1, a desklamp 1, a laptop 1, and a pen 1."

Agent Action: "examine bowl 1 with desklamp 1"
Environment Feedback: "You pick up the bowl 1 from the desk 1."

Agent Action: "put bowl 1 in/on desk 1"
Environment Feedback: "You put the bowl 1 in/on the desk 1."

Agent Thought: "The task is to examine the mug with the desklamp. I need to find where the mug is first and then find the desklamp to light it up. I'll start my search on desk 1."
Agent Action: "examine desk 1"
Environment Feedback: "On the desk 1, you see a bowl 1, a desklamp 1, a laptop 1, and a pen 1."

Agent Action: "take mug 1 from desk 1"
Environment Feedback: "You pick up the bowl 1 from the desk 1."

Agent Action: "use desklamp 1"
Environment Feedback: "You turn on the desklamp 1."

Agent Action: "examine mug 1 with desklamp 1"
Environment Feedback: "You turn on the desklamp 1."

TABLE 13. Example for database.

DATABASE(DB)

```
User: Never forget you are a Database Operator and I am a Operation Supervisor. Never flip roles!
    Never instruct me! We share a common interest in collaborating to successfully complete a task.
    You must help me to complete the task. Here is the task: I will ask you a question, then you
    should help me operate a MySQL database with SQL to answer the question.Never forget our task! I
     must instruct you based on your expertise and my needs to complete the task. You have to
    explain the problem and your solution to me and write down your thoughts. After thinking and
    explaining thoroughly, every round you can choose to operate or to answer.your operation should
    be like this:

Action: Operation
```sql
SELECT * FROM table WHERE condition;
```

You MUST put SQL in markdown format without any other comments. Your SQL should be in one line.
    Every time you can only execute one SQL statement. I will only execute the statement in the
    first SQL code block. Every time you write a SQL, I will execute it for you and give you the
    output. If you are done operating, and you want to commit your final answer, then write down:

Action: Answer
Final Answer: ["ANSWER1", "ANSWER2", ...]

DO NOT write this pattern unless you are sure about your answer. I expect an accurate and correct
    answer.Please note: Your answer should be accurate. Your answer must be exactly the same as the
    correct answer. If the question is about modifying the database, then after done operation, your
     answer field can be anything. If your response cannot match any pattern I mentioned earlier,
    you will be judged as FAIL immediately. Your input will be raw MySQL response, you have to deal
    with it by yourself.

Agent: Ok

User: What event did he fight masato shiozawa?\nThe name of this table is MMA Fight Record, and the
    headers of this table are Res,Record,Opponent,Method,Event,Round.

Agent: To find the event that Masato Shiozawa and I fought, I can use a SELECT statement to retrieve
     the `Event` column from the `MMA Fight Record` table. To specify the condition that Masato
    Shiozawa was the opponent, I can use a WHERE clause with the condition `Opponent = 'Masato
    Shiozawa'`.
Action: Operation
```sql
SELECT `Event` FROM `MMA Fight Record` WHERE `Opponent` = 'Masato Shiozawa'
```

User: [('Shooto 2003 - 5/4 in Korakuen Hall',)]

Agent: The SQL query executed successfully and returned the expected answer. The event that Masato
    Shiozawa and I fought was 'Shooto 2003 - 5/4 in Korakuen Hall'. I can now commit my answer.
Action: Answer
Final Answer: ["Shooto 2003 - 5/4 in Korakuen Hall"]
```

semantic understanding and information retrieval via structured KG reasoning, which has a direct impact on AI's decision-making capabilities.

(4) ALFWorld (ALF): ALF combines text-based simulations and embodied tasks from the ALFRED dataset. The ALF framework enables agents to learn abstract methods for real-world circumstances by integrating text-based planning and visual execution. This ALF assessment dimension improves agent generalization through modular design, especially for language understanding and visual navigation tasks.

(5) WebShop Platform (WS): The WS models e-commerce environments using 1.18 million real-world products and 12,087 text instructions. This WS environment requires agents to explore multiple webpage kinds while performing tasks to identify and purchase things as instructed. Interpreting compositional instructions, query reformulation, dealing with noisy webpage text, and carrying out strategic web research are all important WS challenges.

(6) Mind2Web (M2W): M2W provides a dataset for creating web agents that do sophisticated

TABLE 14. Example for knowledge graph.

KNOWLEDGE GRAPH(KG)

Agent: Thought: Now I need to find the city where Busch Stadium is located. To achieve this, I will query the KB to find relations connected to the variable #1.
Action: get_relations(#1)

User: Observation: [List of relations including location.location.containedby, location.location.adjoin_s, location.location.contains, and many others]

Agent: Thought: From the above relations, I might use location.location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #2, which are instances of location.location

Agent: Thought: Now I need to find the city where Busch Stadium is located. To achieve this, I will query the KB to find relations connected to the variable #2.
Action: get_relations(#2)

User: Observation: [List of relations similar to the first list]

Agent: Thought: From the above relations, I might use location.location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #3, which are instances of location.location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri, USA. Now I need to find the city where the stadium is located. To achieve this, I will query the KB to find relations connected to the variable #3.
Action: get_relations(#3)

User: Observation: [List of relations similar to the previous lists]

Agent: Thought: From the above relations, I might use location.location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #4, which are instances of location.location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri, USA. Now I need to find the city where the stadium is located. To achieve this, I will query the KB to find relations connected to the variable #4.
Action: get_relations(#4)

User: Observation: [List of relations similar to the previous lists]

Agent: Thought: From the above relations, I might use location.location.containedby to find the location of Busch Stadium.
Action: get_neighbors(Busch Stadium, location.location.containedby)

User: Observation: variable #5, which are instances of location.location

Agent: Thought: The Busch Stadium is located in St. Louis, Missouri, USA. Now I need to find the city where the stadium is located. To achieve this, I will query the KB to find relations connected to the variable #5.
Action: get_relations(#5)

User: Observation: [List of relations similar to the previous lists]

tasks on real-world websites using language commands. The M2W benchmark, which covers 2,000 tasks across 137 sites from 31 domains, measures AI navigation capabilities in authentic web contexts. M2W's diverse user interactions make it critical for speeding up real-world web task completion.

APPENDIX B
TASKS AND EXAMPLES

We describe the task to the checker agent using the following instruction as shown in Table 5 to 10. All tasks in the dataset are divided into six categories. For each category, we present an example of successful execution as shown in Table 11 to 19.

TABLE 15. Example for WEBSHOP.

WEBSHOP(WS)

User: You are web shopping. I will give you instructions about what to do. You have to follow the instructions. Every round I will give you an observation and a list of available actions, you have to respond with an action based on the state and instruction. You can use the search action if the search is available. You can click one of the buttons in clickables. An action should be of the following structure: search[keywords] or click[value]. If the action is not valid, perform nothing. Keywords in search are up to you, but the value in click must be a value in the list of available actions. Remember that your keywords in search should be carefully designed. Your response should use the following format:

Thought:
I think ...

Action:
click[something]

Agent: Ok.

User: Observation:
"WebShop [SEP] Instruction: [SEP] I'm looking for rubber stole shoes for light wearing it was brown in color, and price lower than 70.00 dollars [SEP] Search"

Available Actions:
{"has_search_bar": true, "clickables": ["search"]}

Agent: Thought:
I think I should use the search bar to look for the product I need.

Action:
search[rubber stole shoes brown price < 70.00]

User: Observation:
Instruction: [SEP] I'm looking for rubber stole shoes for light wearing it was brown in color, and price lower than 70.00 dollars [SEP] Back to Search [SEP] Page 1 (Total results: 50) [SEP] Next > [SEP] B08XHSG67V [SEP] Crosley Furniture Madeleine 53.25" Farmhouse Metal Kitchen Island in Brown/Black [SEP] 331.49 [SEP] B07CZ5YKWW [SEP] Roper Tumbled Womens Brown Leather Petty Slip-On Shoes [...]

Available Actions:
{"has_search_bar": false, "clickables": ["back to search", "next >", "b08xhsg67v", "b07cz5ykww", "b000jiatqs", "b01ld5a59g", "b085wr7626", "b07s7qxncw", "b01lykp60o", "b004xj62re", "b07fy9mfhx", "b09cfqjt7h"]}

Agent: Thought:
I think I should click on the product I need, which is B08XHSG67V.

Action:
click[B08XHSG67V]

User: Observation:
Instruction: [SEP] I'm looking for rubber stole shoes for light wearing it was brown in color, and price lower than 70.00 dollars [SEP] Back to Search [SEP] < Prev [SEP] Crosley Furniture Madeleine 53.25" Farmhouse Metal Kitchen Island in Brown/Black [SEP] Price: $331.49 [SEP] Rating: N.A. [SEP] Description [SEP] Features [SEP] Reviews [SEP] Buy Now

Available Actions:
{"has_search_bar": false, "clickables": ["back to search", "< prev", "description", "features", "reviews", "buy now"]}

Agent: Thought:
I think I should click on the 'Buy Now' button to purchase the product.

Action:
click[Buy Now]

TABLE 16. Example for MIND2WEB.

MIND2WEB(M2W)

User: Based on the HTML webpage above, try to complete the following task:
Task: Find tuition & fees for full term graduate students in the college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following choices (If the correct action is not in the page above, please select A. 'None of the above'):
A. None of the above
B. Graduation
C. <select id=1 academic_year> <option all> Select </option> <option 175 true>
D. <select id=2 college_school> <option all> Select </option> <option 17> College
E. <select id=3 level_of_study> <option all> Select </option> <option 38 true>
F. <input id=4 submit apply />

Agent: Thought: The search has already been set to College of Engineering and Graduate level. Next, I should select Full Term.
Answer: E.
Action: SELECT

User: Based on the HTML webpage above, try to complete the following task:
Task: Find tuition & fees for full term graduate students in the college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following choices (If the correct action is not in the page above, please select A. 'None of the above'):
A. None of the above
B. <input id=0 text search />
C. Tuition
D. Tuition & Fees
E. Tuition & Fees
F. Class Fees

Agent: Thought: The search has already been set to Tuition. Next, I should find the tuition & fees for full term graduate students in the college of engineering for the academic year 2022-2023.
Answer: D.
Action: CLICK on the link with the text "Tuition & Fees"

User: Based on the HTML webpage above, try to complete the following task:
Task: Find tuition & fees for full term graduate students in the college of engineering for the academic year 2022-2023
Previous actions:
[link] Costs & Financial Aid -> CLICK
[combobox] Academic Year -> SELECT: 2022-2023
[combobox] College/School -> SELECT: College of Engineering
[combobox] Full or Half Term -> SELECT: Full Term
[combobox] Level of Study -> SELECT: Graduate
What should be the next action? Please select from the following choices (If the correct action is not in the page above, please select A. 'None of the above'):
A. None of the above
B. Tuition & Fees
C. <select id=1 level_of_study> <option all> Select </option> <option 38 true>

Agent: Thought: The search has already been set to graduate students in the college of engineering for the academic year 2022-2023. Next, I should select the level of study.
Answer: C.
Action: SELECT: Graduate

TABLE 17. Prompt — High-quality.

```
Q1: How to install the required Python libraries for a Q&A game?
A1 (Assistant): Use the following command to install the 'transformers' library:
    ``` import subprocess
    requirements = ['transformers']
    for package in requirements:
        subprocess.run(['pip', 'install', '-U', package]) ```
A1 (Checker): The code is correct but consider using a requirements.txt file for better package
    management.

Q2: How to import the 'transformers' library for a question-answering task?
A2 (Assistant): Import the pipeline function to create a Q&A task pipeline:
    ``` from transformers import pipeline ```
A2 (Checker): Correct. This is the standard method for importing and using the 'transformers'
    pipeline.

Q3: How to define a function to play a memory game that checks if the user's answer is correct?
A3 (Assistant): Define the 'play_memory_game' function without checking input types:
    ``` def play_memory_game(context, question, user_answer):
        question_answerer = pipeline('question-answering')
        result = question_answerer(question=question, context=context)
        return user_answer == result['answer'] ```
A3 (Checker): You should validate input types to ensure they are strings and handle exceptions. Use
    a specific model for better accuracy:
    ```def play_memory_game(context, question, user_answer):
        if not all(isinstance(arg, str) for arg in [context, question, user_answer]):
            raise ValueError('All arguments must be of type str')
        question_answerer = pipeline('question-answering', model='distilbert-base-uncased-distilled-
            squad')
        result = question_answerer(question=question, context=context)
        return user_answer.lower() == result['answer'].lower() ```

Q4: How to call the 'play_memory_game' function and check results?
A4 (Assistant): Call the function with incorrect syntax: play_memory_game('The capital of France is
    Paris', 'What is the capital of France?', 'Paris')
A4 (Checker): The syntax is almost correct, but you should capture and print the function's return
    value to check the result: ``` result = play_memory_game('The capital of France is Paris', 'What
     is the capital of France?', 'Paris') print(result)```
```

TABLE 18. Prompt — Low-quality.

```
Q1: How to install the required Python libraries for a Q&A game?

A1 (Assistant): Use the command 'pip install transformers'.
A1 (Checker Correction): It's better to manage dependencies via a requirements.txt file. Use 'pip
    install -r requirements.txt' where 'transformers' is listed.

Q2: How to import the 'transformers' library for a question-answering task?

A2 (Assistant): Use 'from transformers import pipeline'.
A2 (Checker Correction): Correct. Ensure 'transformers' is installed beforehand.

Q3: How to define a function to play a memory game that checks if the user's answer is correct?

A3 (Assistant): Provides a basic function without input type checking.
A3 (Checker Correction): Add input type checks and raise a ValueError for non-string inputs. Use a
    specific model for accuracy: 'distilbert-base-uncased-distilled-squad'.

Q4: How to test the 'play_memory_game' function's correctness?

A4 (Assistant): Provides a test function without exception handling.
A4 (Checker Correction): Modify the test function to catch exceptions and provide detailed output
    for each test case for easier debugging.
```

TABLE 19. Without prompts.

```
Q1: How to install the required Python libraries?
A1: Use the following command to install the 'transformers' library:
  import subprocess
  requirements = ['transformers']
  for package in requirements:
    subprocess.run(['pip', 'install', '-U', package])

Q2: How to import the 'transformers' library for a question-answering task?
A2: Import the 'pipeline' function to create a question-answering task pipeline:
  from transformers import pipeline

Q3: How to define a function to play a memory game that checks if the user's answer is correct?
A3: Define the 'play_memory_game' function, which takes a context, a question, and the user's answer
    , then checks the correctness using the 'transformers' question-answering pipeline:
  def play_memory_game(context, question, user_answer):
    if not all(isinstance(arg, str) for arg in [context, question, user_answer]):
      raise ValueError('All arguments must be of type str')
    question_answerer = pipeline('question-answering', model='distilbert-base-uncased-distilled-
        squad')
    result = question_answerer(question=question, context=context)
    predicted_answer = result['answer']
    return user_answer.lower() == predicted_answer.lower()

Q4: How to test the 'play_memory_game' function?
A4: The 'test_play_memory_game' function includes three test cases: normal execution, handling non-
    string input, and incorrect user answer:
  def test_play_memory_game():
    # Normal execution test
    assert play_memory_game('The capital of France is Paris.', 'What is the capital of France?', '
        Paris'), "Incorrect answer."
    # Non-string input test
    try:
      play_memory_game(123, 'What is the answer?', 'test')
    except ValueError:
      pass  # Expected failure for non-string input
    # Incorrect answer test
    assert not play_memory_game('The Earth revolves around the Sun.', 'What does the Moon revolve
        around?', 'Sun'), "Incorrect answer should fail."
```

REFERENCES

[1] J. Devlin, M. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of deep bidirectional transformers for language understanding," in *Proc. NAACL-HLT*, vol. 1, Jun. 2018, pp. 4171–4186.
[2] J. Achiam, S. Adler, and S. Agarwal, "GPT-4 technical report," Mar. 2023, *arXiv:2303.08774*, doi: 10.48550/arXiv.2303.08774. [Online]. Available: https://cdn.openai.com/papers/gpt-4.pdf
[3] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Proc. Adv. Neural Inf. Process. Syst.*, vol. 30, Jun. 2017, pp. 5998–6008.
[4] Z. Yang, A. Ishay, and J. Lee, "Coupling large language models with logic programming for robust and general reasoning from text," in *Proc. Findings ACL*, Jan. 2023, pp. 5186–5219.
[5] X. Lin, Z. Dai, A. Verma, S.-K. Ng, P. Jaillet, and B. Kian Hsiang Low, "Prompt optimization with human feedback," 2024, *arXiv:2405.17346*.
[6] W. X. Zhao et al., "A survey of large language models," *ACM Trans. Intell. Syst. Technol.*, vol. 15, no. 3, pp. 1–35, Apr. 2023.
[7] S. Subramanian, V. Elango, and M. Gungor, "Small language models (SLMs) can still pack a punch: A survey," 2025, *arXiv:2501.05465*.
[8] R. Schwartz, J. Dodge, N. A. Smith, and O. Etzioni, "Green AI," *Commun. ACM*, vol. 63, no. 12, pp. 54–63, Nov. 2020.
[9] E. M. Bender, T. Gebru, A. McMillan-Major, and S. Shmitchell, "On the dangers of stochastic parrots: Can language models be too big?" in *Proc. ACM Conf. Fairness, Accountability, Transparency*, Mar. 2021, pp. 610–623, doi: 10.1145/3442188.3445922.
[10] R. Jia and P. Liang, "Adversarial examples for evaluating reading comprehension systems," in *Proc. Conf. Empirical Methods Natural Lang. Process.*, 2017, pp. 2021–2031.
[11] P. Stone and M. Veloso, "Multiagent systems: A survey from a machine learning perspective," *Auto. Robots*, vol. 8, no. 3, pp. 345–383, Jun. 2000, doi: 10.1023/a:1008942012299.
[12] J. Jiang and Z. Lu, "Learning fairness in multi-agent systems," in *Proc. Adv. Neural Inf. Process. Syst.*, vol. 32, Jan. 2019, pp. 2136–2146.
[13] T. Pang, K. Xu, C. Du, N. Chen, and J. Zhu, "Improving adversarial robustness via promoting ensemble diversity," in *Proc. ICML*, Jan. 2019, pp. 4970–4979.
[14] F. Christianos, G. Papoudakis, M. Zimmer, T. Coste, Z. Wu, J. Chen, K. Khandelwal, J. Doran, X. Feng, J. Liu, Z. Xiong, Y. Luo, J. Hao, K. Shao, H. Bou-Ammar, and J. Wang, "Pangu-agent: A fine-tunable generalist agent with structured reasoning," 2023, *arXiv:2312.14878*.
[15] Y. Talebirad and A. Nadiri, "Multi-agent collaboration: Harnessing the power of intelligent LLM agents," 2023, *arXiv:2306.03314*.
[16] E. A. O. Diallo, A. Sugiyama, and T. Sugawara, "Coordinated behavior of cooperative agents using deep reinforcement learning," *Neurocomputing*, vol. 396, pp. 230–240, Jul. 2020, doi: 10.1016/j.neucom.2018.08.094.
[17] R. N. Reddy, "Universal language model fine-tuning for text classification," *Int. J. Res. Appl. Sci. Eng. Technol.*, vol. 11, no. 6, pp. 3111–3116, Jun. 2023. [Online]. Available: https://aclanthology.org/P18-1031/
[18] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. L. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, J. Schulman, J. Hilton, F. Kelton, L. Miller, M. Simens, A. Askell, P. Welinder, P. Christiano, J. Leike, and R. Lowe, "Training language models to follow instructions with human feedback," 2022, *arXiv:2203.02155*.
[19] N. Stiennon, L. Ouyang, J. Wu, D. M. Ziegler, R. Lowe, C. Voss, A. Radford, D. Amodei, and P. Christiano, "Learning to summarize from human feedback," 2020, *arXiv:2009.01325*.
[20] J. R. Kok and N. Vlassis, "Collaborative multiagent reinforcement learning by payoff propagation," *J. Mach. Learn. Res.*, vol. 7, no. 65, pp. 1789–1828, Dec. 2006. [Online]. Available: http://www.jmlr.org/papers/volume7/kok06a/kok06a.pdf
[21] Q. Wang, H. Ling, Y. Li, Q. Liu, R. Jia, and N. Yu, "Continual adversarial defense," 2023, *arXiv:2312.09481*.

[22] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," 2021, *arXiv:2106.09685*.
[23] B. Lester, R. Al-Rfou, and N. Constant, "The power of scale for parameter-efficient prompt tuning," 2021, *arXiv:2104.08691*.
[24] J. R. Vázquez-Canteli and Z. Nagy, "Reinforcement learning for demand response: A review of algorithms and modeling techniques," *Appl. Energy*, vol. 235, pp. 1072–1089, Feb. 2019, doi: 10.1016/j.apenergy.2018.11.002.
[25] G. Wang and J. Shi, "Actor-critic for multi-agent system with variable quantity of agents," in *Proc. Int. Conf. Internet Things Service*, Jan. 2019, pp. 48–56, doi: 10.1007/978-3-030-14657-3_5.
[26] D. Kato, A. Shimizu, and H. Ishikawa, "Quality classification for testing work in DevOps," in *Proc. 14th Int. Conf. Manage. Digit. Ecosyst.*, Oct. 2022, pp. 156–162, doi: 10.1145/3508397.3564840.
[27] S. Bhadra, B. Das, P. Silva, V. Nagaraju, and L. Fiondella, "A stochastic Petri net model of continuous integration and continuous delivery," in *Proc. Annu. Rel. Maintainability Symp. (RAMS)*, Jan. 2023, pp. 1–6, doi: 10.1109/RAMS51473.2023.10088212.
[28] M. Beck, K. Pöppel, M. Spanring, A. Auer, O. Prudnikova, M. Kopp, G. Klambauer, J. Brandstetter, and S. Hochreiter, "XLSTM: Extended long short-term memory," 2024, *arXiv:2405.04517*.
[29] S. Hochreiter and J. Schmidhuber, "Long short-term memory," *Neural Comput.*, vol. 9, no. 8, pp. 1735–1780, Nov. 1997, doi: 10.1162/neco.1997.9.8.1735.
[30] M. Di Penta, "Understanding and improving continuous integration and delivery practice using data from the wild," in *Proc. 13th Innov. Softw. Eng. Conf.*, Feb. 2020, pp. 1–12, doi: 10.1145/3385032.3385059.
[31] G. Liu and J. Guo, "Bidirectional LSTM with attention mechanism and convolutional layer for text classification," *Neurocomputing*, vol. 337, pp. 325–338, Apr. 2019, doi: 10.1016/j.neucom.2019.01.078.
[32] R. C. Martin, "Short-term memory and sentence processing: Evidence from neuropsychology," *Memory Cognition*, vol. 21, no. 2, pp. 176–183, Mar. 1993, doi: 10.3758/bf03202730.
[33] D. Yogatama, C. de Masson d'Autume, and L. Kong, "Adaptive semiparametric language models," *Trans. Assoc. Comput. Linguistics*, vol. 9, pp. 362–373, Apr. 2021.
[34] E. J. Davelaar, Y. Goshen-Gottstein, A. Ashkenazi, H. J. Haarmann, and M. Usher, "The demise of short-term memory revisited: Empirical and computational investigations of recency effects," *Psychol. Rev.*, vol. 112, no. 1, pp. 3–42, Jan. 2005, doi: 10.1037/0033-295x.112.1.3.
[35] G. Li, Y. Gan, H. Wu, N. Xiao, and L. Lin, "Cross-modal attentional context learning for RGB-D object detection," *IEEE Trans. Image Process.*, vol. 28, no. 4, pp. 1591–1601, Apr. 2019, doi: 10.1109/TIP.2018.2878956.
[36] C. Che, X. Li, C. Chen, X. He, and Z. Zheng, "A decentralized federated learning framework via committee mechanism with convergence guarantee," *IEEE Trans. Parallel Distrib. Syst.*, vol. 33, no. 12, pp. 4783–4800, Dec. 2022, doi: 10.1109/TPDS.2022.3202887.
[37] M. Tao, X. Liang, T. Shi, L. Yu, and Y. Xie, "RoleCraft-GLM: Advancing personalized role-playing in large language models," 2023, *arXiv:2401.09432*.
[38] A. Zeng, M. Liu, R. Lu, B. Wang, X. Liu, Y. Dong, and J. Tang, "AgentTuning: Enabling generalized agent abilities for LLMs," 2023, *arXiv:2310.12823*.
[39] G. Waters and P. Honenberger, "AI biases as asymmetries: A review to guide practice," 2025, *arXiv:2503.07326*.
[40] M. E. Khan and S. Swaroop, "Knowledge-adaptation priors," 2021, *arXiv:2106.08769*.
[41] P. Lahoti, A. Beutel, J. Chen, K. Lee, F. Prost, N. Thain, X. Wang, and E. H., "Fairness without demographics through adversarially reweighted learning," in *Proc. Adv. Neural Inf. Process. Syst.*, vol. 33, Dec. 2020, pp. 728–740.
[42] R. Cheng, H. Ma, S. Cao, J. Li, A. Pei, Z. Wang, P. Ji, H. Wang, and J. Huo, "Reinforcement learning from multi-role debates as feedback for bias mitigation in LLMs," 2024, *arXiv:2404.10160*.
[43] A. Y. Halevy, Z. G. Ives, J. Madhavan, P. Mork, D. Suciu, and I. Tatarinov, "The Piazza peer data management system," *IEEE Trans. Knowl. Data Eng.*, vol. 16, no. 7, pp. 787–798, Jul. 2004, doi: 10.1109/TKDE.2004.1318562.
[44] S. Yao, H. Chen, J. Yang, and K. Narasimhan, "WebShop: Towards scalable real-world Web interaction with grounded language agents," 2022, *arXiv:2207.01206*.
[45] M. Shridhar, X. Yuan, M.-A. Coté, Y. Bisk, A. Trischler, and M. Hausknecht, "ALFWorld: Aligning text and embodied environments for interactive learning," in *Proc. ICLR*, May 2021, pp. 1–17.
[46] J. Gou, B. Yu, S. J. Maybank, and D. Tao, "Knowledge distillation: A survey," *Int. J. Comput. Vis.*, vol. 129, no. 6, pp. 1789–1819, Jun. 2021, doi: 10.1007/s11263-021-01453-z.
[47] N. Kanwal, R. Amundsen, H. Hardardottir, L. Tomasetti, E. Sandoy Undersrud, E. A. M. Janssen, and K. Engan, "Detection and localization of melanoma skin cancer in histopathological whole slide images," 2023, *arXiv:2302.03014*.
[48] C. L. P. Chen and Z. Liu, "Broad learning system: An effective and efficient incremental learning system without the need for deep architecture," *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 29, no. 1, pp. 10–24, Jan. 2018, doi: 10.1109/TNNLS.2017.2716952.
[49] Y. Cheng, D. Wang, P. Zhou, and T. Zhang, "A survey of model compression and acceleration for deep neural networks," 2017, *arXiv:1710.09282*.
[50] J. Wang, Y. Sun, Z. Fan, and Y. Liu, "A collaborative e-learning system based on multi-agent," in *Proc. Int. Workshop Internet Netw. Econ.*, vol. 3828, X. Deng and Y. Ye, Eds., Berlin, Germany: Springer, Jan. 2005, pp. 455–463, doi: 10.1007/11600930_45.
[51] P. Zhang, G. Zeng, T. Wang, and W. Lu, "TinyLlama: An open-source small language model," 2024, *arXiv:2401.02385*. C
[52] S. Zhang, S. Roller, N. Goyal, M. Artetxe, M. Chen, S. Chen, C. Dewan, M. Diab, X. Li, X. Victoria Lin, T. Mihaylov, M. Ott, S. Shleifer, K. Shuster, D. Simig, P. Singh Koura, A. Sridhar, T. Wang, and L. Zettlemoyer, "OPT: Open pre-trained transformer language models," 2022, *arXiv:2205.01068*.




YUBING XIONG received the M.S. degree in transportation planning and management from Beijing Jiaotong University, Beijing, China, in 2012, and the Ph.D. degree in transportation engineering from Hiroshima University, Hiroshima, Japan, in 2015. From 2015 to 2016, she was a Postdoctoral Researcher with the Transportation Engineering Laboratory, Hiroshima University. Currently, she is an Associate Professor with the School of Transportation Engineering, East China Jiaotong University, Nanchang, China. Her research interests include intelligent transportation, performance of transportation networks, artificial intelligence, and residential and travel behavior.



MINGRUI HUANG received the bachelor's degree in transportation engineering from Hohai University, in 2023. He is currently pursuing the master's degree in transportation planning and management with East China Jiaotong University. With a strong interest in artificial intelligence and language models, he is committed to conducting in-depth research in interdisciplinary fields.



XUECHEN LIANG was born in Xintai, Shandong, in 2000. He received the bachelor's degree in traffic equipment and control engineering from Shandong Jiaotong University, in 2023. He is currently pursuing the degree in transportation with East China Jiaotong University. He has authored two conference papers, holds two patents, and represented Shandong Jiaotong University in receiving the Huawei Technology Certification, in 2022.



MEILING TAO was born in Shenzhen, Guangdong, China, in 2002. She received the bachelor's degree in international education from Guangdong University of Technology. Her main research interests include large language models and federated learning.