

The Multi-State Constraint Kalman Filter

Or, how we learned to stop worrying and love the null space

Valentin Peretroukhin and Lee Clement


AER1513 Course Project



Institute for Aerospace Studies
UNIVERSITY OF TORONTO

Problem: Vision-aided Inertial Navigation

Goal: Use an IMU with a monocular camera to estimate motion *without a map*.



Algorithm: MSCKF

Idea: Traditional pairwise landmark triangulation ignores correlations with observations at other states, so use a hybrid batch/recursive filter

Batch component: Track each feature until it goes out of view, then compute its position from *all available measurements*.


Recursive component: Use landmark position and all of its measurements (with null space trick) *to constrain motion*.

Advantages over plain EKF:


- **Sliding window of poses** allows each constraint to affect multiples states
- **Computational complexity is linear** in number of landmarks instead of cubic for plain EKF SLAM.

Algorithm: MSCKF


Each set of observations for a given feature (i.e. a 'feature track') adds a motion constraint.



Dataset: Starry Night (Assignment 3)



- ✓ Perfect data association
- ✓ Ground truth for landmark positions
- ✓ Pre-integrated IMU measurements



Planned Analysis: MSCKF

We will **investigate** MSCKF parameters:

1. Feature track length
2. Maximum window size

We will **compare**:

MSCKF *vs.* Sliding Window
Batch Estimation



State Estimation Street Fight

Proof of Progress

<ul style="list-style-type: none">augmentState.mcalcF.mcalcG.mcalcGNPosEst.mcalcHoj.mcalcJ.mcalcResidual.mcalcTH.mdataset3.matMSCKF.mMSCKF.m~propagateImuState.mpropagateMsckfCovar.mupdateState.m	<pre>74 75 76 77 78 - 79 80 81 - 82 83 84 85 86 87 - 88 - 89 - 90 - 91 - 92 93 94 - 95 - 96 - 97 - 98 99 - 100 - 101 - 102 - 103</pre>	<pre>%=====STATE PROPAGATION===== %Propagate state and covariance msckfState = propagateMsckfCovar(msckfState, measuremen %Add camera pose to msckfState msckfState = augmentState(msckfState, camera); %=====FEATURE TRACKING===== % Add observations to the feature tracks, or initiali % If an observation is -1, add the track to featureTr featureTracksToResidualize = {}; for featureId = 1:20 meas_k = measurements{state_k}.y(:, featureId); if ismember(featureId, trackedFeatureIds) if meas_k(1,1) == -1 %Add to residualize queue and remove from %struct featureTracksToResidualize{end+1} = featur featureTracks = featureTracks(trackedFeat trackedFeatureIds(trackedFeatureIds == fe else %Append observation and increase k2 featureTracks{trackedFeatureIds == featur featureTracks{trackedFeatureIds == featur end else %Track new feature</pre>
---	--	---



Thanks!

